



FCC/ISED - TEST REPORT

Report Number

: **709502400725-00A**Date of Issue: August 22, 2025

Model

: M-RC02, M-RC03, C-RC01, M-RC01, M/C-RC01

Product Type

: Remote Control

Applicant

: Tempo Manufacturing LLC.

Address

100 Yalujiang Road, Rudong Economic Development Zone
226400 Nantong City, Jiangsu Province PEOPLE'S REPUBLIC
: OF CHINA

Production Facility

: Phaeton Manufacturing LLC.

Address

No. 69, Jinshajiang Road, Rudong Economic Development Zone
: 226400 Nantong PEOPLE'S REPUBLIC OF CHINA

Test Result

: Positive NegativeTotal pages including
Appendices: 24

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.

1 Table of Contents

1	Table of Contents	2
2	Report Modification Record	3
3	Details about the Test Laboratory	3
4	Description of the Equipment Under Test	4
5	Summary of Test Standards	5
6	Summary of Test Results	6
7	General Remarks	7
8	Systems test configuration	8
9	Test Setups	9
10	Test Methodology	11
10.1	Conducted Emission	11
10.2	The Field strength of Emissions	12
10.3	20dB Bandwidth Measurement	18
10.4	99% Bandwidth Measurement	19
10.5	Deactivation Time	20
11	Test Equipment List	21
12	System Measurement Uncertainty	22
13	Photographs of Test Set-ups	23
14	Photographs of EUT	24



2 Report Modification Record

Alterations and additions to this report will be issued to the holders of each copy in the form of a complete document.

Issue	Description of Change	Date of Issue
709502400725-00A	First Issue	08/22/2025

3 Details about the Test Laboratory

Details about the Test Laboratory

Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
No.16 Lane, 1951 Du Hui Road,
Shanghai 201108,
P.R. China

Telephone: +86 21 6141 0123

Fax: +86 21 6140 8600

FCC Registration No.: 820234

FCC Designation Number: CN1183

ISED CAB identifier CN0101

IC Registration No.: 31668



4 Description of the Equipment Under Test

Product:	Remote Control
Model no./HVIN:	M-RC02, M-RC03, C-RC01, M-RC01, M/C-RC01
PMN:	P-type shell remote control: M-RC02; A-type shell remote control: M-RC03; Adsorption type shell remote control: C-RC01; Watch style shell remote control: M-RC01; Melon seed style shell remote control: M/C-RC01
FCC ID:	2BL2STPKSKCTSTCSC
IC:	33277-TPKSCTSCTS
Rating:	DC 3V
RF Transmission Frequency:	433.92 MHz
No. of Operated Channel:	1
Modulation:	ASK
Hardware Version:	HT-D35-433YK-V1
Software Version:	HS16F1200 SOP8/CHK:9634-0116
Antenna Type:	PCB Antenna
Description of the EUT:	The Equipment Under Test (EUT) is a Remote Control with SRD function. We tested it and listed the worst data in this report.
Test sample no.:	SHA-751784-2

The sample's mentioned in this report is/are submitted/ supplied/ manufactured by client. The laboratory therefore assumes no responsibility for accuracy of information on the brand name, model number, origin of manufacture, consignment, antenna gain or any information supplied.



5 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2023 Edition	RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators
RSS-Gen Issue 5 April 2018 + Amendment 1 March 2019 + Amendment 2 February 2021	General Requirements for Compliance of Radio Apparatus
RSS-210 Issue 11 June 25, 2024	RSS-210 — License-exempt Radio Apparatus: Category I Equipment

All the test methods were according to ANSI C63.10-2020.



6 Summary of Test Results

Technical Requirements					
FCC Part 15.231 Subpart C, RSS-210 Issue 11					
Test Condition			Pages	Test Site	Test Result
§15.207	RSS-GEN A8.8	Conducted emission AC power port	11	Shield room	Not Applicable See note 1
§15.205, §15.209, 15.35 (c)§15.231(b)	RSS-210 A.1.3 RSS-GEN 8.9	The Field strength of Emissions	12-17	3m chamber	Pass
§15.231(c)	RSS-210 A.1.4	20dB and 99% Bandwidth Measurement	18-19	Shield room	Pass
§15.231(a)(1)	RSS-210 A.1.2(a)	Deactivation Time	20	Shield room	Pass
§15.203	RSS-Gen 6.8	Antenna requirement	See note 2		

Note 1: N/A=Not Applicable. Conducted emission is not apply for battery operated device.

Note 2: The EUT uses a PCB Antenna, which gain is 2.0dBi for 433.908MHz SRD. In accordance to §15.203 and RSS-Gen 5, It is considered sufficiently to comply with the provisions of this section.



7 General Remarks

Remarks

According to client's declaration, the models M-RC02, M-RC03, C-RC01, M-RC01 and M/C-RC01 are identical except for different appearance size and shape. So we chose the model M/C-RC01 to perform full tests.

This submittal(s) (test report) is intended for FCC ID: 2BL2STPKSKCTSTCSC, IC: 33277-TPKSCTSCTS complies with Section 15.205, 15.207, 15.209, 15.231 of the FCC Part 15, Subpart C Rules and RSS-Gen Issue 5 A1:2019+ A2:2021 and RSS-210 issue 11 June 25, 2024.

SUMMARY:

All tests according to the regulations cited on page 5 were

- Performed

- Not Performed

The Equipment Under Test

- Fulfills the general approval requirements.

- Does not fulfill the general approval requirements.

Sample Received Date: March 05, 2024

Testing Start Date: April 29, 2024

Testing End Date: May 10, 2024

-TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch

Reviewed by:

Prepared by:

Tested by:

Jiaxi XU



Yong.ZHANG

Jiaxi XU
Review Engineer

Yong ZHANG
Project Engineer

Guochengjie

Chengjie GUO
Test Engineer




8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
--	--	--	--


9 Test Setups

9.1 AC Power Line Conducted Emission test setups




9.2 Radiated test setups


9kHz ~ 30MHz Test Setup:



30MHz ~ 1GHz Test Setup:



Above 1GHz Test Setup:



9.3 Conducted RF test setups



10 Test Methodology

10.1 Conducted Emission

Test Method

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. Both sides of AC line were checked for maximum conducted interference.
6. The frequency range from 150 kHz to 30 MHz was searched.
7. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

Limit

According to §15.207 and RSS-GEN Issue 5 8.8, conducted emissions limit as below:

Frequency MHz	QP Limit dB μ V	AV Limit dB μ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

*Decreasing linearly with logarithm of the frequency.

Note: Conducted emission is not apply for battery operated device.

10.2 The Field strength of Emissions

Test Method

- 1: The EUT was place on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2: The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
- 3: The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4: For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 5: Use the following spectrum analyzer settings According to C63.10:
 - 9kHz -150kHz
RBW = 200Hz, VBW = 1kHz for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.
 - 150kHz - 30MHz
RBW = 10 kHz, VBW = 30 kHz for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.
 - 30MHz - 1GHz
RBW = 100 kHz, VBW = 300 kHz for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.
 - For Above 1GHz
RBW = 1MHz, VBW \geq 3RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.



Limit

1. FCC Limit: In addition to the provisions of § 15.205, the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Fundamental frequency (MHz)	Field Strength of Fundamental (Microvolts /meter)	Field Strength of spurious emissions ((Microvolts /meter)
40.66-40.70	2,250	225
70-130	1,250	125
130-174	1,250 to 3,750 *	125 to 375 *
174-260	3,750	375
260-470	3,750 to 12, 500*	375 to 1,250*
Above 470	12,500	1,250

*Linear interpolation with frequency

(a) The above field strength limits are specified at a distance of 3 meters. The tighter limits apply at the band edges.

(b) Intentional radiators operating under the provisions of this section shall demonstrate compliance with the limits on the field strength of emissions, as shown in the above table, based on the average value of the measured emissions. As an alternative, compliance with the limits in the above table may be based on the use of measurement instrumentation with a CISPR quasi-peak detector. The specific method of measurement employed shall be specified in the application for equipment authorization. If average emission measurements are employed, the provisions in § 15.35 for averaging pulsed emissions and for limiting peak emissions apply. Further, compliance with the provisions of § 15.205 shall be demonstrated using the measurement instrumentation specified in that section.

(c) The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in § 15.209, whichever limit permits a higher field strength.

Limits for 15.209 Radiated emission limits

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3



2. ISED Limit:

(a) The field strength of emissions from momentarily operated intentional radiators shall not exceed the limits in table A1, based on the average value of the measured emissions. The requirements of the “Pulsed Operation” section of RSS-Gen apply for averaging pulsed emissions and limiting peak emissions. Alternatively, compliance with the limits in table A1 may be based on the use of a CISPR quasi-peak detector.

(b) Unwanted emissions shall be 10 times below the fundamental emissions field strength limits in table A1 or comply with the limits specified in RSS-Gen, whichever is less stringent.

Table A1: Permissible field strength limits for momentarily operated devices

Fundamental frequency (MHz)	Field Strength of Fundamental (Microvolts /meter @ 3m)	Field Strength of spurious emissions ((Microvolts /meter @ 3m)
70-130	1,250	125
130-174	1,250 to 3,750 *	125 to 375 *
174-260	3,750	375
260-470	3,750 to 12, 500*	375 to 1,250*
Above 470	12,500	1,250

*Linear interpolation with frequency

General field strength limits at frequencies below 30 MHz

Frequency	Magnetic field strength (H-Field) (μ A/m)	Measurement distance (meters)
9 – 490 kHz*	6.37/F (F in kHz)	300
490 – 1705 kHz	63.7/F (F in kHz)	30
1.705-30.0 MHz	0.08	30

*The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

Note 1: Limit $3m(dB\mu V/m) = Limit\ 300m(dB\mu V/m) + 40\log(300m/3m)$ (Below 30MHz)

Note 2: Limit $3m(dB\mu V/m) = Limit\ 30m(dB\mu V/m) + 40\log(30m/3m)$ (Below 30MHz)

Note 3: $dB\mu V/m = 20\log(\mu V/m)$, $dB\mu A/m = 20\log(\mu A/m)$



Field strength of Emissions

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

Radiated Emission									
Value	Emissions Frequency MHz	E-Field Polarity	PK Emission dB μ V/m	Corr.	Average Factor dB	AV Emission dB μ V/m	Limit dB μ V/m	Margin	Emission Type
Below 1GHz									
PK	433.908	H	64.75	26.14	/	/	100.83	36.05	Fundamental
AV	433.908	H	64.75	/	-8.14	56.61	80.83	24.19	Fundamental
PK	433.908	V	72.19	26.14	/	/	100.83	28.61	Fundamental
AV	433.908	V	72.19	/	-8.14	64.05	80.83	16.75	Fundamental
PK	867.837	H	55.41	24.94	/	/	100.83	45.39	Spurious
AV	867.837	H	55.41	/	-8.14	47.27	80.83	33.53	Spurious
PK	867.837	V	65.41	24.94	/	/	100.83	35.39	Spurious
AV	867.837	V	65.41	/	-8.14	57.27	80.83	23.53	Spurious
Above 1GHz									
PK	1301.765*	H	50.98	-15.2	/	/	74.00	23.02	Restricted band
AV	1301.765*	H	50.98	/	-8.14	42.84	54.00	11.16	Restricted band
PK	1735.765	H	47.24	-13.3	/	/	80.83	33.59	Spurious
AV	1735.765	H	47.24	/	-8.14	39.1	60.83	13.59	Spurious
PK	2169.546	H	52.90	-11.0	/	/	80.83	27.93	Spurious
AV	2169.546	H	52.90	/	-8.14	44.76	60.83	7.93	Spurious
PK	2603.109	H	41.39	-10.8	/	/	80.83	39.44	Spurious
AV	2603.109	H	41.39	/	-8.14	33.25	60.83	19.44	Spurious
PK	3037.328	H	39.48	-6.4	/	/	80.83	41.35	Spurious
AV	3037.328	H	39.48	/	-8.14	31.34	60.83	21.35	Spurious
PK	3905.437*	H	41.66	-4.9	/	/	74.00	32.34	Restricted band
AV	3905.437*	H	41.66	/	-8.14	33.52	54.00	20.48	Restricted band
PK	1301.765*	V	55.75	-15.2	/	/	74.00	18.25	Restricted band
AV	1301.765*	V	55.75	/	-8.14	47.61	54.00	6.39	Restricted band
PK	1735.546	V	53.11	-13.3	/	/	80.83	27.72	Spurious
AV	1735.546	V	53.11	/	-8.14	44.97	60.83	7.72	Spurious
PK	2169.437	V	55.75	-11.0	/	/	80.83	25.08	Spurious
AV	2169.437	V	55.75	/	-8.14	47.61	60.83	5.08	Spurious
PK	2603.218	V	52.35	-10.8	/	/	80.83	28.48	Spurious
AV	2603.218	V	52.35	/	-8.14	44.21	60.83	8.48	Spurious
PK	3037.546	V	48.88	-6.4	/	/	80.83	31.95	Spurious
AV	3037.546	V	48.88	/	-8.14	40.74	60.83	11.95	Spurious


Remark:

- 1: AV Emission Level= PK Emission Level+20log(dutycycle)
- 2: Data of measurement within this frequency range shown "/" in the table above means the reading of emissions are attenuated more than 20db below the permissible limits or the field strength is too small to be measured.
- 3: "*" means the emission(s) appear within the restrict bands shall follow the requirement of section 15.205.
- 4: Level= Reading Level + Correction Factor


Correction Factor = Antenna Factor + Cable Loss- Amplifier Gain
(The Reading Level is recorded by software which is not shown in the sheet)

Duty Cycle = $1.014\text{ms} \times 13 + 0.4348\text{ms} \times 12 / 44.348\text{ ms} = 39.14\%$.


Duty Cycle Factor = $20\log(\text{Duty Cycle}) = -8.14$.



Date: 10.MAY.2024 14:34:54



Date: 10.MAY.2024 14:35:11



Date: 10.MAY.2024 14:35:31

10.3 20dB Bandwidth Measurement

Test Method

1. The EUT was placed on 0.8m height table, the RF output of EUT was connected to the test receiver by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously. Use the following test receiver settings:
RBW = 1% to 5% of the OBW, VBW \geq 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
3. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth. Record the results.


Limit

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70MHz and below 900MHz. For devices operating above 900MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20dB down from the modulated carrier.

The limit for the EUT = $0.25\% * 433.92 \text{ MHz} = 1084.8 \text{ kHz}$

Test Result

Channel	20dB Bandwidth (KHz)	Limit (KHz)	Result
1	6.99	≤ 1084.8	Pass



10.4 99% Bandwidth Measurement

Test Method

1. The EUT was placed on 0.8m height table, the RF output of EUT was connected to the test receiver by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
Use the following test receiver settings:
RBW = 1% to 5% of the OBW, VBW \geq 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
3. Allow the trace to stabilize. Use the 99 % power bandwidth function of the instrument. Record the results.

Limit


The occupied bandwidth of momentarily operated devices shall be less than or equal to 0.25% of the centre frequency for devices operating between 70 MHz and 900 MHz. For devices operating above 900 MHz, the occupied bandwidth shall be less than or equal to 0.5% of the centre frequency.

The limit for the EUT = 0.25% * 433.92 MHz = 1084.8 kHz

Test Result

Channel	99% bandwidth (kHz)	Limit (kHz)	Result
1	45.58	\leq 1084.8	Pass

99% bandwidth





10.5 Deactivation Time

Test Method

1. The EUT was placed on 0.8m height table, the RF output of EUT was connected to the test receiver by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT in transmitting mode.
3. Set center frequency of spectrum analyzer=operating frequency.
4. Set the spectrum analyzer as $RBW \geq OBW$, $VBW \geq RBW$, Span=0Hz, detector=peak.
5. Repeat above procedures until all frequency measured was complete.


Limit

According to FCC Part 15.231 (a) and RSS-210 A.1.2(a), the transmitter shall be complied the following requirements:

- (1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.
- (2) A transmitter activated automatically shall cease transmission within 5 seconds after activation.
- (3) Periodic transmissions at regular predetermined intervals are not permitted. However, polling or supervision transmissions, including data, to determine system integrity of transmitters used in security or safety applications are allowed if the total duration of transmissions does not exceed more than two seconds per hour for each transmitter. There is no limit on the number of individual transmissions, provided the total transmission time does not exceed two seconds per hour.

Test Result

Channel	Frequency	Deactivation Time	Limit	Result
1	433.92MHz	121.74ms	≤5s	Pass



Date: 10.MAY.2024 14:28:57



11 Test Equipment List

List of Test Instruments

Test Site1

RF Conductive Test

Description	Manufacturer	Model no.	Serial no.	Calibration Date	Calibration Due
Signal and spectrum analyzer	R&S	FSV40	S1503003-YQ-EMC	2023-8-01	2024-7-31

Conducted Emission

Description	Model no.	Manufacturer	Equipment ID.	Calibration Date	Calibration Due
EMI test receiver	ESR3	R&S	S1503001-YQ-EMC	2023-8-01	2024-7-31
2-Line V-network	ENV216	R & S	S1503103-YQ-EMC	2023-8-01	2024-7-31

Radiated Emission Test

USED	Equipment Name	Model	Manufacturer	Equipment ID.	Calibration Date	Calibration Due
<input checked="" type="checkbox"/>	EMI test receiver	ESR3	R&S	S1503109-YQ-EMC	2023-8-01	2024-7-31
<input checked="" type="checkbox"/>	Trilog super broadband test antenna	SCHWARZBECK	VULB9168	S1808296-YQ-EMC	2023-8-30	2024-8-29
<input checked="" type="checkbox"/>	Double-ridged waveguide horn antenna	HF907	R&S	S1503009-YQ-EMC	2024-4-14	2025-4-13
<input checked="" type="checkbox"/>	Pre-amplifier	HPAP-9K0130	Shenzhen HzEMC	S2110423b-YQ-EMC	2023-8-01	2024-7-31
<input checked="" type="checkbox"/>	Signal and spectrum analyzer	FSV40	R&S	S1503003-YQ-EMC	2023-8-01	2024-7-31
<input checked="" type="checkbox"/>	Loop antenna	HFH2-Z2	R&S	S1503013-YQ-EMC	2023-6-15	2024-6-14

Measurement Software Information

Test Item	Software	Manufacturer	Version
RE	EMC 32	Rohde & Schwarz	V10.50.40
CE	EMC 32	Rohde & Schwarz	V9.15.03

12 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty

Items	Extended Uncertainty
Conducted Disturbance at Mains Terminals	150kHz to 30MHz, LISN, 3.16dB
Radiated Disturbance	9kHz to 30MHz, 3.52dB 30MHz to 1GHz, 5.03dB (Horizontal) 5.12dB (Vertical) 1GHz to 18GHz, 5.49dB 18GHz to 40GHz, 5.63dB
Carrier power conducted measurement	50MHz~18GHz, 1.238dB
Spurious Emission Conducted Measurement	9kHz ~40GHz, 1.224dB

Measurement Uncertainty Decision Rule:

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115: 2023, clause 4.3.3.



13 Photographs of Test Set-ups

Refer to the < Test Setup photos >.



14 Photographs of EUT

Refer to the < External Photos > & < Internal Photos >.

-----End of Test Report-----