





RF TEST REPORT

Report Reference No.....	MAX25050231P01-R09RF
FCC ID.....	2BL3Q-FD104
Compiled by (position+printed name+signature)...	Engineer/ Cindy Zheng 
Supervised by (position+printed name+signature)...	Manager/Haley Wen 
Approved by (position+printed name+signature)...	RF Manager/ Vivian Jiang 
Date of issue.....	June 21, 2025
Testing Laboratory Name	MAXLAB Testing Co.,Ltd.
Address.....	1/F, Building B, Xinshidai GR Park, Shiyan Street, Bao'an District, Shenzhen, Guangdong, 518052, People's Republic of China
Applicant's name.....	SHENZHEN MINGSHIDA COMMUNICATION TECHNOLOGY CO.,LTD
Address.....	Building D, No. 4 Longshan Industrial Zone, Nanwan Street, Longgang District, Shenzhen
Test specification.....	FCC Part 15.231 KDB 447498 D01 V06 ANSI C95.1-2019 FCC §1.1310
MAXLAB Testing Co.,Ltd. All rights reserved.	
This publication may be reproduced in whole or in part for non-commercial purposes as long as the MAXLAB Testing Co.,Ltd. is acknowledged as copyright owner and source of the material. MAXLAB Testing Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	
Test item description.....	Car keys
Trade Mark.....	N/A
Manufacturer.....	SHENZHEN MINGSHIDA COMMUNICATION TECHNOLOGY CO.,LTD
Model/Type reference.....	2BL3Q-FD104
Listed Models	N/A
Ratings.....	DC 3V From Battery
Modulation	ASK
Frequency.....	315MHz
Result.....	PASS

RF Exposure Evaluation

1. The corresponding SAR Exclusion Threshold condition, listed below:

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [V_f(\text{GHz})] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, 16 where

$\geq f(\text{GHz})$ is the RF channel transmit frequency in GHz

\geq Power and distance are rounded to the nearest mW and mm before calculation

\geq The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is $<$ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

2) At 100 MHz to 6 GHz and for test separation distances $>$ 50 mm, the SAR test exclusion threshold is determined according to the following:

a) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm):($f(\text{MHz})/1500$)] mW, at 100MHz to 1500 MHz

b) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm)-10] mW at $>$ 1500 MHz and \leq 6 GHz

3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion.

a) The threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by $[1+\log(100/f(\text{MHz}))]$ for test separation distances $>$ 50 mm and $<$ 200 mm.

b) The threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by /2 for test separation distances \leq 50 mm.

c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.

2. CLASSIFICATION

The antenna of this product, under normal use condition, is at less than 20cm away from the body of the user. So, this device is classified as Portable Device.

EUT Specification

Antenna type:	PCB Antenna
Antenna gain (Max)	2.1 dBi
Evaluation applied	<input type="checkbox"/> MPE Evaluation <input checked="" type="checkbox"/> SAR Evaluation

3. SAR TEST EXCLUSION THRESHOLDS

The measured conducted PK Power

Mode	Frequency(MHz)	Field strength(dBuV/m@3)	EIRP (dBm)
TX	315	65.81	-34.15

Note:

$$\text{EIRP} = \text{E}_{\text{Meas}} + 20 \log(\text{d}_{\text{Meas}}) - 109.5$$

EIRP is the equivalent isotropically radiated power, in dBm

E_{Meas} is the field strength of the emission at the measurement distance, in dBuV/m

d_{Meas} is the measurement distance, in m

$$\text{EIRP} = \text{E} + 20 \log(\text{d}) - 109.5$$

The tuned conducted PK Power (declared by client)

Mode	Frequency(MHz)	Target Power (dBm)	Tolerance \pm (dBm)
TX	315	-34	1

Frequency (MHz)	Minimum Separation distance (mm)	RF Output power		Result	Limit for 1-g SAR	Verdict
		(dBm)	(mW)			
315	5	-33	0.0005	0.000056	3.0	Exempt from SAR

Conclusion

Therefore this device complies with FCC's RF radiation exposure limits for general population without SAR evaluation.