



MAXLAB Testing Co.,Ltd.

FCC ID: 2BL3Q-HN101

## RF Exposure Evaluation

1. The corresponding SAR Exclusion Threshold condition, listed below:

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [f(\text{GHz})] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- >  $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- > Power and distance are rounded to the nearest mW and mm before calculation
- > The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

2) At 100 MHz to 6 GHz and for test separation distances  $> 50$  mm, the SAR test exclusion threshold is determined according to the following:

a) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm)  $\cdot$  ( $f(\text{MHz})/150$ )] mW, at 100 MHz to 1500 MHz

b) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm)  $\cdot$  10] mW at  $> 1500$  MHz and  $\leq 6$  GHz

3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion.

a) The threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by  $[1 + \log(100/f(\text{MHz}))]$  for test separation distances  $> 50$  mm and  $< 200$  mm.

b) The threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by  $/2$  for test separation distances  $\leq 50$  mm.

c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.

## 2. CLASSIFICATION

The antenna of this product, under normal use condition, is at less than 20cm away from the body of the user. So, this device is classified as Portable Device.

## EUT Specification

|                    |                                                                                               |
|--------------------|-----------------------------------------------------------------------------------------------|
| FCC ID             | 2BL3Q-HN101                                                                                   |
| PRODUCT:           | Car keys                                                                                      |
| MODEL NO.:         | HN101                                                                                         |
| STANDARDS:         | FCC Part 15.231<br>KDB 447498 D01 V06<br>ANSI C95.1- 1999<br>FCC §1.1310                      |
| Antenna type:      | PCB antenna                                                                                   |
| Antenna gain (Max) | 2.1dBi                                                                                        |
| Evaluation applied | <input type="checkbox"/> MPE Evaluation<br><input checked="" type="checkbox"/> SAR Evaluation |



**MAXLAB Testing Co.,Ltd.**

**FCC ID: 2BL3Q-HN101**

### 3. SAR TEST EXCLUSION THRESHOLDS

The measured conducted PK Power

| Mode | Frequency(MHz) | Field strength(dBuV/m@3) | EIRP (dBm) |
|------|----------------|--------------------------|------------|
| TX   | 433.92         | 65.08                    | -30.08     |

Note:

$$\text{EIRP} = E_{\text{Meas}} + 20\log(d_{\text{Meas}}) - 104.7$$

EIRP is the equivalent isotropically radiated power, in dBm

$E_{\text{Meas}}$  is the field strength of the emission at the measurement distance, in dBuV/m

$d_{\text{Meas}}$  is the measurement distance, in m

$$\text{EIRP} = E + 20\log(d) - 104.7$$

The tuned conducted PK Power (declared by client)

| Mode | Frequency(MHz) | Target Power (dBm) | Tolerance $\pm$ (dBm) |
|------|----------------|--------------------|-----------------------|
| TX   | 433.92         | -30                | 1                     |

| Frequency (MHz) | Minimum Separation distance (mm) | RF Output power |         | Result   | Limit for 1-g SAR | Verdict         |
|-----------------|----------------------------------|-----------------|---------|----------|-------------------|-----------------|
|                 |                                  | (dBm)           | (mW)    |          |                   |                 |
| 433.92          | 5                                | -29             | 0.00126 | 0.000269 | 3.0               | Exempt from SAR |

### Conclusion

Therefore this device complies with FCC's RF radiation exposure limits for general population without SAR evaluation.