



## RF Exposure Evaluation

### Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>,  $P_{out}$  = output power to antenna in mW;

$G$  = gain of antenna in linear scale,  $\pi = 3.1416$ ;

$r$  = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance  $r$  where the MPE limit is reached.

### Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



## Test Result of RF Exposure Evaluation

### Tune-up Power

BT EDR					
Modulation Type	Frequency (MHz)	Output Power to antenna (dBm)	Output Power to antenna (mW)	Tune-up Power(dBm) ±1	Max mun Tune-up Power(dBm)
GFSK	2402	3.76	2.377	3	4
2.4G WIFI					
802.11b	2412	14.02	25.23	14	15
5G WIFI					
802.11n (HT20)	5240	15.14	21.677	15	16
5.8G WIFI					
802.11ac (VHT80)	5775	14.98	23.768	14	15

Frequency (MHz)	Max Output power to antenna (dBm)	Max Output power to antenna (mW)	Power Density at R=20cm (mW/cm2)	Limit (mW/cm2)	Result
BT EDR					
GFSK	HOP	4	2.512	0.00090	1.0 PASS
2.4G WIFI					
802.11b	2412	15	31.623	0.01132	1.0 PASS
5.1G WIFI					
802.11n (HT20)	5240	16	39.811	0.01428	1.0 PASS
5.8G WIFI					
802.11ac (VHT80)	5775	15	31.623	0.01386	1.0 PASS

Remark: antenna gain=EDR/2.4G:2.55dBi/ 5G:2.56dBi/3.43dBi

So a SAR test is not required