



Diagram illustrating the back view of the device with labeled components:

- Charging Pin
- Charging Pin Head
- Stainless Steel Tube
- Backing
- Switching
- Tempo
- Tempo

- Step 2**
- Enable Bluetooth on your smart device and remove the probe from the booster.



Diagram of the probe display with numbered callouts:

- 1: Connected
- 2: Disconnected
- 3: Probe meat temperature
- 4: Probe battery level
- 5: Buzzer icon
- 6: Setting
- 7: On/Off icon
- 8: Temperature
- 9: Booster battery level
- 10: 10 Spikes icon

- 1 Icon of successful connection between cell phone APP and base: not shown in disconnection, always lit in connection.
- 2 Mobile APP and box disconnect icon: not displayed in the connection, disconnection is always lit.
- 3 Probe meat temperature display area, “—” is displayed when the probe is not connected.
- 4 Probe battery power display area, blue battery flashing means the device at the same time every 30 seconds to send a “drip” reminder (the probe needs to be charged in time). When the probe is charging in the base, the icon shows 0, 1, 2 and 3 dots sequentially.
- 5 Buzzer icon: when there is a temperature alarm task (after setting the temperature) the icon is always on and the user is always on, when the target temperature is reached the buzzer alarms and the icon blinks.

1. Probe pairing: press **+** at the same time for 3s, the temperature, ambient temperature area display **→** flashing, enter pairing mode, the device is automatically paired to connect the nearby probe.
2. Temperature Alarm Setting: Press setup key to enter the alarm temperature setting, press **+** key to set the temperature (the upper limit of temperature is 100°C), press setup key again to complete the setting (no operation for 15 seconds will cancel the alarm), when the temperature reaches the target temperature, it will trigger the temperature alarm, press any key to cancel the alarm when it is alarmed. Put the probe into the device, you can cancel the alarm task manually.
3. Protective alarm: when the oven temperature reaches 300°C or meat temperature reaches 100°C, the protective alarm will be triggered, press any key to cancel the alarm, or the alarm will be canceled automatically when the temperature returns to normal.
4. Automatic shutdown: no operation for 30 seconds, the screen will go out automatically, press any key, the screen will light up for 30 seconds.

Temperature Range:	
Internal Temperature	-20~100°C
Ambient Temperature	0~309°C
Sensor Type	NTC
Transmission Range	18m (59ft)
Battery Life:	
Probe	Up to 40h
Power:	
Booster	3.7V (Built-in lithium rechargeable battery)
Probe	2.4V (Built-in lithium rechargeable battery)
Dimension:	
LCD Display	1.4*1.4 In
Booster	0.95 In* 2.43 In* 7.5 In

Federal Communications Commission (FCC) Statement.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide Reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Warning: Changes or modifications made to this device not expressly approved by **ANHUI UNI ELECTRONIC TECHNOLOGY CO., LTD** may void the FCC authorization to operate this device.

Note: The manufacturer is not responsible for any radio or TV interference caused by unauthorized modifications to this equipment. Such modifications could void the user's authority to operate the equipment.

RF exposure statement:

This device complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. The device is installed and operated without restriction.