

TEST REPORT

Applicant: Shantou Hongxing Toys Industry Co., Ltd

Address of Applicant: Yangdong Industrial Zone, Dongwan Village, Lianxia Town,
Chenghai District, Shantou City, China

Manufacturer/Factory: Shantou Hongxing Toys Industry Co., Ltd

**Address of
Manufacturer/Factory:** Yangdong Industrial Zone, Dongwan Village, Lianxia Town,
Chenghai District, Shantou City, China

Equipment Under Test (EUT)

Product Name: Remote control car

Model No.: See section 5.1

FCC ID: 2BLCP93300

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.249

Date of sample receipt: September 23, 2024

Date of Test: September 24, 2024-October 09, 2024

Date of report issued: October 09, 2024

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Luo


Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	October 09, 2024	Original

Prepared By:




Date:

October 09, 2024

Project Engineer

Check By:



Date:

October 09, 2024

Reviewer

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
4.1 MEASUREMENT UNCERTAINTY	4
5 GENERAL INFORMATION.....	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	7
5.3 DESCRIPTION OF SUPPORT UNITS	7
5.4 DEVIATION FROM STANDARDS.....	7
5.5 ABNORMALITIES FROM STANDARD CONDITIONS.....	7
5.6 TEST FACILITY.....	7
5.7 TEST LOCATION	7
5.8 ADDITIONAL INSTRUCTIONS.....	7
6 TEST INSTRUMENTS LIST	8
7 TEST RESULTS AND MEASUREMENT DATA.....	10
7.1 ANTENNA REQUIREMENT	10
7.2 RADIATED EMISSION METHOD	11
7.2.1 Field Strength of The Fundamental Signal	13
7.2.2 Spurious emissions.....	14
7.2.3 Bandedge emissions.....	22
7.3 20dB OCCUPY BANDWIDTH	26
8 TEST SETUP PHOTO.....	28
9 EUT CONSTRUCTIONAL DETAILS	28

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	N/A
Field strength of the fundamental signal	15.249 (a)	Pass
Spurious emissions	15.249 (a) (d)/15.209	Pass
Band edge	15.249 (d)/15.205	Pass
20dB Occupied Bandwidth	15.215 (c)	Pass

Remarks:

1. Test according to ANSI C63.10:2013.
2. Pass: The EUT complies with the essential requirements in the standard.

4.1 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	RF conducted power	$\pm 0.75\text{dB}$
5	RF power density	$\pm 3\text{dB}$
6	Conducted Spurious emissions	$\pm 2.58\text{dB}$
7	AC Power Line Conducted Emission	$\pm 3.44\text{dB}$ (0.15MHz ~ 30MHz)
8	Radiated Spurious emission test	$\pm 3.1\text{dB}$ (9kHz-30MHz)
		$\pm 3.8039\text{dB}$ (30MHz-200MHz)
		$\pm 3.9679\text{dB}$ (200MHz-1GHz)
		$\pm 4.29\text{dB}$ (1GHz-18GHz)
		$\pm 3.30\text{dB}$ (18GHz-40GHz)
9	Temperature test	$\pm 1^\circ\text{C}$
10	Humidity test	$\pm 3\%$
11	Time	$\pm 3\%$

5 General Information

5.1 General Description of EUT

Product Name:	Remote control car
Model No.:	93300, 93301, 93302, 93303, 93304, 93305, 93306, 93307, 93308, 93309, 93310, 93311, 93312, 93313, 93314, 93315, 93316, 93317, 93318, 93319, 93320, 93210, 93211, 93212, 93213, 93214, 93215, 93216, 93217, 93218, 93219, 93220, 93221, 93222, 93223, 93224, 93225, 93226, 93227, 93228, 93229, 93110, 93111, 93112, 93113, 93114, 93115, 93116, 93117, 93118, 93119, 93120, D93300, D93301, D93302, D93303, D93304, D93305, D93306, D93307, D93308, D93309, D93310, D93311, D93312, D93313, D93314, D93315, D93316, D93317, D93318, D93319, 93200, 93201, 93202, 93203, 93204, 93205, 93206, 93207, 93208, 93209, D93225, D93226, 93227, 93228, 93229, D93217, D93218, D93219, D93227, D93228, D93229, 93114S, 93210S, 93205S, 93208S, 93230-1, 93230-2, 93230-3, 93230-4, 93230-5, 93230-6, 93230-7, 93230-8, 93230-9, 93230-10, 93230-11, 93231
Test Model No.:	93300
Remark: All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are appearance, color and model name for commercial purpose.	
Serial No.:	N/A
Test sample(s) ID:	GTS2024090192-1
Sample(s) Status	Engineered sample
Operation Frequency:	2405MHz~2475MHz
Channel Numbers:	71
Modulation Type:	GFSK
Antenna Type:	Wire Antenna
Antenna gain:	0dBi(declare by applicant)
Power supply:	DC 3V(2*1.5V Size“AA” Battery)

Remark:

1. Antenna gain information provided by the customer
2. The relevant information of the sample is provided by the entrusting company, and the laboratory is not responsible for its authenticity.

Operation Frequency each of channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2405	19	2423	37	2441	55	2459
2	2406	20	2424	38	2442	56	2460
3	2407	21	2425	39	2443	57	2461
4	2408	22	2426	40	2444	58	2462
5	2409	23	2427	41	2445	59	2463
6	2410	24	2428	42	2446	60	2464
7	2411	25	2429	43	2447	61	2465
8	2412	26	2430	44	2448	62	2466
9	2413	27	2431	45	2449	63	2467
10	2414	28	2432	46	2450	64	2468
11	2415	29	2433	47	2451	65	2469
12	2416	30	2434	48	2452	66	2470
13	2417	31	2435	49	2453	67	2471
14	2418	32	2436	50	2454	68	2472
15	2419	33	2437	51	2455	69	2473
16	2420	34	2438	52	2456	70	2474
17	2421	35	2439	53	2457	71	2475
18	2422	36	2440	54	2458		

The test frequencies are below:

Channel	Frequency
The lowest channel	2405MHz
The middle channel	2440MHz
The Highest channel	2475MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
Remark: New battery is used during all test.	

Per-test mode.

We have verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report (Only show the worst case:Y axis) and defined as follows:

Axis	X	Y	Z
Field Strength(dBuV/m)	88.51	89.66	87.24

5.3 Description of Support Units

None.

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC—Registration No.: 381383**

Designation Number: CN5029

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files.

- **ISED—Registration No.: 9079A**

CAB identifier: CN0091

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of ISED for radio equipment testing

- **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

5.7 Test Location

All tests were performed at:
Global United Technology Services Co., Ltd. Address: No. 123- 128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960

5.8 Additional Instructions

Test Software	Special test command provided by manufacturer
Power level setup	Default

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Jun. 22, 2024	Jun. 21, 2027
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Apr. 11, 2024	Apr. 10, 2025
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9168	GTS640	Mar. 19, 2023	Mar. 18, 2025
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	Apr. 17, 2023	Apr. 16, 2025
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	Apr. 11, 2024	Apr. 10, 2025
8	Loop Antenna	ZHINAN	ZN30900A	GTS534	Nov. 13, 2023	Nov.12, 2024
9	Broadband Preamplifier	SCHWARZBECK	BBV9718	GTS535	Apr. 11, 2024	Apr. 10, 2025
10	Amplifier(1GHz-26.5GHz)	HP	8449B	GTS601	Apr. 11, 2024	Apr. 10, 2025
11	Horn Antenna (18-26.5GHz)	/	UG-598A/U	GTS664	Oct. 29, 2023	Oct. 28, 2024
12	Horn Antenna (26.5-40GHz)	A.H Systems	SAS-573	GTS665	Oct. 29, 2023	Oct. 28, 2024
13	FSV·Signal Analyzer (10Hz-40GHz)	Keysight	FSV-40-N	GTS666	Mar. 12, 2024	Mar. 11, 2025
14	Amplifier	/	LNA-1000-30S	GTS650	Apr. 11, 2024	Apr. 10, 2025
15	CDNE M2+M3-16A	HCT	30MHz-300MHz	GTS692	Nov. 08, 2023	Nov. 07, 2024
16	Wideband Amplifier	/	WDA-01004000-15P35	GTS602	Apr. 11, 2024	Apr. 10, 2025
17	Thermo meter	JINCHUANG	GSP-8A	GTS643	Apr. 18, 2024	Apr. 17, 2025
18	RE cable 1	GTS	N/A	GTS675	Jul. 02, 2024	Jul. 01, 2025
19	RE cable 2	GTS	N/A	GTS676	Jul. 02, 2024	Jul. 01, 2025
20	RE cable 3	GTS	N/A	GTS677	Jul. 02, 2024	Jul. 01, 2025
21	RE cable 4	GTS	N/A	GTS678	Jul. 02, 2024	Jul. 01, 2025
22	RE cable 5	GTS	N/A	GTS679	Jul. 02, 2024	Jul. 01, 2025
23	RE cable 6	GTS	N/A	GTS680	Jul. 02, 2024	Jul. 01, 2025
24	RE cable 7	GTS	N/A	GTS681	Jul. 05, 2024	Jul. 04, 2025
25	RE cable 8	GTS	N/A	GTS682	Jul. 05, 2024	Jul. 04, 2025

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	Apr. 13, 2024	Apr. 12, 2025
2	EMI Test Receiver	R&S	ESCI 7	GTS552	Apr. 13, 2024	Apr. 12, 2025
3	PSA Series Spectrum Analyzer	Agilent	E4440A	GTS536	Apr. 13, 2024	Apr. 12, 2025
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	Apr. 13, 2024	Apr. 12, 2025
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	Apr. 13, 2024	Apr. 12, 2025
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	Apr. 13, 2024	Apr. 12, 2025
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	Apr. 13, 2024	Apr. 12, 2025
8	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	Apr. 13, 2024	Apr. 12, 2025
9	Thermo meter	JINCHUANG	GSP-8A	GTS641	Apr. 18, 2024	Apr. 17, 2025


General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	KUMAO	SF132	GTS647	Apr. 18, 2024	Apr. 17, 2025



7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
EUT Antenna:	
The antenna is wire antenna, reference to the appendix II for details.	

7.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	9kHz-150kHz	Quasi-peak	200Hz	300Hz	Quasi-peak Value
	150kHz-30MHz	Quasi-peak	9kHz	10kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit: (Field strength of the fundamental signal)	Frequency		Limit (dBuV/m @3m)		Remark
	2400MHz-2483.5MHz		94.00		Average Value
			114.00		Peak Value
Limit: (Spurious Emissions)	Frequency		Limit (uV/m)		Remark
	0.009MHz-0.490MHz		2400/F(kHz) @300m		Quasi-peak Value
	0.490MHz-1.705MHz		24000/F(kHz) @30m		Quasi-peak Value
	1.705MHz-30.0MHz		30 @30m		Quasi-peak Value
	30MHz-88MHz		100 @3m		Quasi-peak Value
	88MHz-216MHz		150 @3m		Quasi-peak Value
	216MHz-960MHz		200 @3m		Quasi-peak Value
	960MHz-1GHz		500 @3m		Quasi-peak Value
	Above 1GHz		500 @3m		Average Value
5000 @3m			Peak Value		
Limit: (band edge)	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.				
Test setup:	For radiated emissions from 9kHz to 30MHz				
					
	For radiated emissions from 30MHz to1GHz				

	 For radiated emissions above 1GHz 						
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.						
Test Instruments:	Refer to section 6.0 for details						
Test mode:	Refer to section 5.2 for details						
Test environment:	<table><tr><td>Temp.:</td><td>25 °C</td><td>Humid.:</td><td>52%</td><td>Press.:</td><td>1012mbar</td></tr></table>	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar		
Test voltage:	DC 3V						
Test results:	Pass						

Measurement data:

7.2.1 Field Strength of The Fundamental Signal

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2405.00	93.24	27.43	4.57	38.56	86.68	114.00	-27.32	Vertical
2405.00	92.31	27.43	4.57	38.56	85.75	114.00	-28.25	Horizontal
2440.00	96.12	27.55	4.56	38.57	89.66	114.00	-24.34	Vertical
2440.00	92.65	27.55	4.56	38.57	86.19	114.00	-27.81	Horizontal
2475.00	95.83	27.64	4.55	38.58	89.44	114.00	-24.56	Vertical
2475.00	92.41	27.64	4.55	38.58	86.02	114.00	-27.98	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2405.00	81.92	27.43	4.57	38.56	75.36	94.00	-18.64	Vertical
2405.00	80.99	27.43	4.57	38.56	74.43	94.00	-19.57	Horizontal
2440.00	84.80	27.55	4.56	38.57	78.34	94.00	-15.66	Vertical
2440.00	81.33	27.55	4.56	38.57	74.87	94.00	-19.13	Horizontal
2475.00	84.51	27.64	4.55	38.58	78.12	94.00	-15.88	Vertical
2475.00	81.09	27.64	4.55	38.58	74.70	94.00	-19.30	Horizontal

Note: For fundamental frequency , RBW>20dB BW, VBW>=RBW, PK detector for PK value, RMS detector for AV value


7.2.2 Spurious emissions

■ Below 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o), the test result no need to reported.


■ Below 1GHz

Pre-scan all test modes, found worst case at 2405MHz, and so only show the test result of it
Horizontal



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
31.620	37.45	12.50	1.13	32.30	18.78	40.00	-21.22	QP
39.576	33.20	14.32	1.25	32.30	16.47	40.00	-23.53	QP
78.139	34.06	9.99	1.65	32.41	13.29	40.00	-26.71	QP
141.826	28.68	13.88	2.39	32.46	12.49	43.50	-31.01	QP
345.595	25.39	13.51	3.65	32.28	10.27	46.00	-35.73	QP
734.491	24.87	20.99	5.22	31.34	19.74	46.00	-26.26	QP


Vertical



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
31.180	44.92	12.50	1.12	32.30	26.24	40.00	-13.76	QP
49.533	35.42	12.69	1.38	32.30	17.19	40.00	-22.81	QP
76.512	38.90	10.15	1.65	32.41	18.29	40.00	-21.71	QP
167.824	33.75	13.62	2.62	32.43	17.56	43.50	-25.94	QP
317.701	27.58	12.81	3.51	32.29	11.61	46.00	-34.39	QP
627.274	24.98	19.65	4.76	31.73	17.66	46.00	-28.34	QP


■ Above 1GHz

Test channel:	Lowest	Polarization:	Horizontal
---------------	--------	---------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4810.000	51.23	32.02	6.01	38.54	50.72	74.00	-23.28	Peak
7215.000	43.04	36.23	7.93	39.15	48.05	74.00	-25.95	Peak
9620.000	37.39	38.20	14.60	40.22	49.97	74.00	-24.03	Peak

Test channel:	Lowest	Polarization:	Vertical
---------------	--------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4810.000	49.81	32.02	6.01	38.54	49.30	74.00	-24.70	Peak
7215.000	43.09	36.23	7.93	39.15	48.10	74.00	-25.90	Peak
9620.000	37.35	38.20	14.60	40.22	49.93	74.00	-24.07	Peak

Test channel:	Middle	Polarization:	Horizontal
---------------	--------	---------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4880.000	51.10	32.10	6.03	38.52	50.71	74.00	-23.29	Peak
7320.000	43.39	36.30	8.04	39.22	48.51	74.00	-25.49	Peak
9760.000	39.92	38.20	11.35	40.25	49.22	74.00	-24.78	Peak

Test channel:	Middle	Polarization:	Vertical
---------------	--------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4880.000	40.22	32.10	6.03	38.52	39.83	74.00	-34.17	Peak
7320.000	41.95	36.30	8.04	39.22	47.07	74.00	-26.93	Peak
9760.000	39.95	38.20	11.35	40.25	49.25	74.00	-24.75	Peak

Test channel:	Highest	Polarization:	Horizontal
---------------	---------	---------------	------------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4950.000	50.72	32.20	6.05	38.51	50.46	74.00	-23.54	Peak
7425.000	41.38	36.30	8.14	39.30	46.52	74.00	-27.48	Peak
9900.000	41.54	38.20	10.70	40.28	50.16	74.00	-23.84	Peak

Test channel:	Highest	Polarization:	Vertical
---------------	---------	---------------	----------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4950.000	39.36	32.20	6.05	38.51	39.10	74.00	-34.90	Peak
7425.000	43.27	36.30	8.14	39.30	48.41	74.00	-25.59	Peak
9900.000	41.50	38.20	10.70	40.28	50.12	74.00	-23.88	Peak


Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. For above 18GHz, no emission found.
4. If the average limit is met when using a Peak detector, the EUT shall be deemed to meet both peak and average limits. And measurement with the average detector is unnecessary.

7.2.3 Bandedge emissions


All of the restriction bands were tested, and only the data of worst case was exhibited.

Test channel:	Lowest	Polarization:	Horizontal
---------------	--------	---------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	34.17	27.00	4.13	39.14	26.16	54.00	-27.84	Average
2310.000	47.03	27.00	4.13	39.14	39.02	74.00	-34.98	Peak
2390.000	42.78	27.08	4.17	39.34	34.69	54.00	-19.31	Average
2390.000	54.84	27.08	4.17	39.34	46.75	74.00	-27.25	Peak
2400.000	52.77	27.10	4.18	39.36	44.69	54.00	-9.31	Average
2400.000	62.76	27.10	4.18	39.36	54.68	74.00	-19.32	Peak

Test channel:	Lowest	Polarization:	Vertical
---------------	--------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	32.36	27.00	4.13	39.14	24.35	54.00	-29.65	Average
2310.000	45.52	27.00	4.13	39.14	37.51	74.00	-36.49	Peak
2390.000	42.55	27.08	4.17	39.34	34.46	54.00	-19.54	Average
2390.000	54.26	27.08	4.17	39.34	46.17	74.00	-27.83	Peak
2400.000	53.48	27.10	4.18	39.36	45.40	54.00	-8.60	Average
2400.000	65.37	27.10	4.18	39.36	57.29	74.00	-16.71	Peak

Test channel:	Highest	Polarization:	Horizontal
---------------	---------	---------------	------------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	46.43	27.27	4.08	39.56	38.22	54.00	-15.78	Average
2483.500	57.33	27.27	4.08	39.56	49.12	74.00	-24.88	Peak
2500.000	35.63	27.30	4.06	39.60	27.39	54.00	-26.61	Average
2500.000	49.59	27.30	4.06	39.60	41.35	74.00	-32.65	Peak

Test channel:	Highest	Polarization:	Vertical
---------------	---------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	50.72	27.27	4.08	39.56	42.51	54.00	-11.49	Average
2483.500	61.95	27.27	4.08	39.56	53.74	74.00	-20.26	Peak
2500.000	37.75	27.30	4.06	39.60	29.51	54.00	-24.49	Average
2500.000	51.83	27.30	4.06	39.60	43.59	74.00	-30.41	Peak

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- For above 18GHz, no emission found


7.3 20dB Occupy Bandwidth

Test Requirement:	FCC Part15 C Section 15.249/15.215
Test Method:	ANSI C63.10:2013
Limit:	Operation Frequency range 2400MHz~2483.5MHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data

Test channel	20dB bandwidth(MHz)	Result
Lowest	1.224	Pass
Middle	1.234	Pass
Highest	1.242	Pass


Test plot as follows:



Lowest channel



Middle channel



Highest channel

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----