



FCC Test Report

Report No: FCS202509240H01

Issued for

Applicant:	GUANGDONG GOLDEN MONKEY TECHNOLOGY CO.,LTD
Address:	Industrial Park No. 4 Tangxia Road, Shizheng Town, Pingyuan County, Meizhou City, Guangdong Province, China
Product Name:	DIY AMBIENT TABLE LAMP
Brand Name:	N/A
Model Name:	GM-0709A-1
Series Model:	GM-0709A-2, GM-0709B-1, GM-0709B-2
FCC ID:	2BLF5-GM-0709A-1
Test Standard:	FCC 47CFR §2.1091
Issued By: Flux Compliance Service Laboratory Add: Room 105 Floor Bao hao Technology Building 1 NO.15 Gong ye West Road Hi-Tech Industrial, Song shan lake Dongguan Tel: 769-27280901 Fax:769-27280901 http://www.FCS-lab.com	

**TEST RESULT CERTIFICATION**

Applicant's Name.....: GUANGDONG GOLDEN MONKEY TECHNOLOGY CO.,LTD
Address: Industrial Park No. 4 Tangxia Road, Shizheng Town, Pingyuan
County, Meizhou City, Guangdong Province, China
Manufacture's Name.....: GUANGDONG GOLDEN MONKEY TECHNOLOGY CO.,LTD
Address: Industrial Park No. 4 Tangxia Road, Shizheng Town, Pingyuan
County, Meizhou City, Guangdong Province, China

Product Description

Product Name.....: DIY AMBIENT TABLE LAMP
Brand Name: N/A
Model Name: GM-0709A-1
Series Model.....: GM-0709A-2, GM-0709B-1, GM-0709B-2
Test Standards.....: FCC 47CFR §2.1091
447498 D01 Interim General RF Exposure Guidance v06

This device described above has been tested by Flux Compliance Service Laboratory, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of Flux Compliance Service Laboratory, this document may be altered or revised by Flux Compliance Service Laboratory, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests : Sept. 12, 2025 ~ Sept. 18, 2025

Date of Issue.....: Sept. 18, 2025

Test Result.....: Pass

Tested by

:

Scott Shen

(Scott Shen)

Reviewed by

:

Duke Qian

(Duke Qian)

Approved by

:

Jack Wang

(Jack Wang)





TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF THE EUT	5
1.2 TEST FACTORY	6
2. FCC 47CFR § 2.1091 REQUIREMENT	7
2.1 TEST STANDARDS	7
2.2 LIMIT	7
2.3 TEST RESULT	9



Revision History

Rev.	Issue Date	Contents
00	Sept. 18, 2025	Initial Issue

1. GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF THE EUT

Product Name	DIY AMBIENT TABLE LAMP	
Brand	N/A	
Model Number	GM-0709A-1	
Series Model(s)	GM-0709A-2, GM-0709B-1, GM-0709B-2	
Model Difference	The internal circuit design is the same, only some of the appearance colors are different	
Product Description	The EUT is DIY AMBIENT TABLE LAMP	
	Operation Frequency:	2402~2480 MHz
	Modulation Type:	BT: GFSK, $\pi/4$ -DQPSK, 8DPSK BLE: GFSK
	Antenna gain:	2 dBi
	Antenna Designation:	PCB antenna
Power Supply	DC 3.7V 1200mAh	
Hardware version number	V1.0	
Software version number	V1.0	



1.2 TEST FACTORY

Company Name:	Flux Compliance Service Laboratory
Address:	Room 105 Floor Bao hao Technology Building 1 NO.15 Gong ye West Road Hi-Tech Industrial, Song shan lake Dongguan
Telephone:	+86-769-27280901
Fax:	+86-769-27280901
FCC Test Firm Registration Number: 514908 Designation number: CN0127 A2LA accreditation number: 5545.01 ISED Number: 25801 CAB ID : CN0097	



2. FCC 47CFR §2.1091 REQUIREMENT

2.1 TEST STANDARDS

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure requirement

KDB447498 D01v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

2.2 LIMIT

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)
Limits for Occupational / controlled Exposures			
300 - 1500	--	--	F/300
1500 – 100000	--	--	5.0
Limits for General population / Uncontrolled Exposure			
300 - 1500	--	--	F/1500
1500 – 100000	--	--	1.0

F= Frequency in MHz

Friss Formula

Friss Transmission Formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm² aaa

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.

Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance from the antenna should be included in the User manual. So, this device is classified as Mobile device.

2.3 TEST RESULT

Turn up

BT_Conducted	Mode	Frequency (MHz)		
Target (dBm)	GFSK	2402	2441	2480
		1	0	1
	$\pi/4$ -DQPSK	2402	2441	2480
		3	3	3
	8DPSK	2402	2441	2480
		3	3	4
Tolerance $\pm$ (dB)		1		
BLE_Conducted	Mode	Frequency (MHz)		
Target (dBm)	GFSK	2402	2440	2480
		1	1	1
Tolerance $\pm$ (dB)		1		

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
BT(BR+EDR)	5	3.16	2	1.585	0.001	1
BLE	2	1.58	2	1.585	0.0005	1

Results: PASS, NO SAR required.

*****END OF THE REPORT*****