

FCC RADIO TEST REPORT

FCC ID: 2BLHF-JT156M-H01

Product : Digital Calendar for Family Schedules

Trade Mark : N/A

Model Name : JT156M-H01

Family Model : Refer to page eight

Report No. : S24092304705002

Prepared for

Shenzhen Joyhong Tech Co.,Ltd
Building B6, 101, West Industrial Zone, Tantou Community,
Songgang Street, Bao'an District, Shenzhen

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
1/F, Building E, Fenda Science Park Sanwei, Xixiang, Bao'an
District, Shenzhen, Guangdong, China
Tel. 0755-23200050 Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION

Applicant's name : Shenzhen Joyhong Tech Co.,Ltd
Address..... : Building B6, 101, West Industrial Zone, Tantou Community,
Songgang Street, Bao'an District, Shenzhen

Manufacturer's Name : Shenzhen Joyhong Tech Co.,Ltd
Address..... : Building B6, 101, West Industrial Zone, Tantou Community,
Songgang Street, Bao'an District, Shenzhen

Product description

Product name : Digital Calendar for Family Schedules

Model and/or type reference : JT156M-H01

Family Model..... : Refer to page eight

Sample number : S240923047005

Standards : FCC Part15.407

Test procedure ANSI C63.10-2013 and KDB 789033 D02 General UNII Test
Procedures New Rules v02r01

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements/ the Industry Canada requirements.. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests..... Sept. 23, 2024 ~ Oct. 15, 2024

Date of Issue Oct. 15, 2024

Test Result..... **Pass**

Prepared : Gavan Zhang
By : Gavan Zhang
(Project Engineer)

Reviewed : Aaron Cheng
By : Aaron Cheng
(Supervisor)

Approved : Alex Li
By : Alex Li
(Manager)

Table of Contents

	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 FACILITIES AND ACCREDITATIONS	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	10
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	12
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	13
3 . TEST REQUIREMENTS	15
3.1 CONDUCTED EMISSION MEASUREMENT	15
3.2 RADIATED EMISSION MEASUREMENT	20
3.3 POWER SPECTRAL DENSITY TEST	37
3.4 26DB & 99% EMISSION BANDWIDTH	40
3.5 MINIMUM 6 DB BANDWIDTH	42
3.6 MAXIMUM CONDUCTED OUTPUT POWER	44
3.7 OUT OF BAND EMISSIONS	47
3.8 SPURIOUS RF CONDUCTED EMISSIONS	49
3.9 FREQUENCY STABILITY MEASUREMENT	50
4. ANTENNA REQUIREMENT	57
4.1 STANDARD REQUIREMENT	57
4.2 EUT ANTENNA	57

Revision History

Report No.	Version	Description	Issued Date
S24092304705002	Rev.01	Initial issue of report	Oct. 15, 2024

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.407) , Subpart E			
Standard Section	Test Item	Judgment	Remark
15.207	AC Power Line Conducted Emissions	PASS	
15.209(a), 15.407 (b)(1) 15.407 (b)(4)	Spurious Radiated Emissions	PASS	
15.407 (a)(1) 15.407 (a)(3)	26 dB and 99% Emission Bandwidth	PASS	
15.407(e)	Minimum 6 dB bandwidth	PASS	
15.407 (a)(1) 15.407 (a)(3)	Maximum Conducted Output Power	PASS	
15.407(b)(1) 15.407(b)(4)	Band Edge	PASS	
15.407 (a)(1) 15.407 (a)(3)	Power Spectral Density	PASS	
15.407(b)	Spurious Emissions at Antenna Terminals	PASS	
15.203	Antenna Requirement	PASS	
15.407(c)	Automatically discontinue transmission	PASS	
15.407(g)	Frequency Stability Measurement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

(2)11ax supports FULL RU Only.

1.1 FACILITIES AND ACCREDITATIONS

FACILITIES

All measurement facilities used to collect the measurement data are located at

1/F, Building E, Fenda Science Park Sanwei, Xixiang, Bao'an

District, Shenzhen, Guangdong, China.

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

CNAS-Lab. : The Certificate Registration Number is L5516.

IC-Registration : The Certificate Registration Number is 9270A.
CAB identifier:CN0074

FCC- Accredited : Test Firm Registration Number: 463705.
Designation Number: CN1184

A2LA-Lab. : The Certificate Registration Number is 4298.01
This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories.
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).

Name of Firm : Shenzhen NTEK Testing Technology Co., Ltd.

Site Location : 1/F, Building E, Fenda Science Park Sanwei, Xixiang, Bao'an
District, Shenzhen, Guangdong, China.

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.80\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(30MHz~1GHz)	$\pm 2.64\text{dB}$
5	All emissions, radiated(1GHz~6GHz)	$\pm 2.40\text{dB}$
6	All emissions, radiated(> 6GHz)	$\pm 2.52\text{dB}$
7	Temperature	$\pm 0.5^\circ\text{C}$
8	Humidity	$\pm 2\%$
9	All emissions, radiated(9KHz~30MHz)	$\pm 6\text{dB}$
10	Occupied bandwidth	$\pm 3.7\text{dB}$
11	POWER SPECTRAL DENSITY	$\pm 1.21\text{dB}$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Digital Calendar for Family Schedules
Trade Mark	N/A
Model Name	JT156M-H01
Family Model	Refer to page eight
Model Difference	All models are the same circuit and RF module, except for model names.
FCC ID	2BLHF-JT156M-H01
Product Description	IEEE 802.11 WLAN Mode Supported ☒ 802.11a/n/ac/ax (20MHz channel bandwidth) ☒ 802.11n/ac/ax (40MHz channel bandwidth)
	Data Rate 802.11a: 6,9,12,18,24,36,48,54Mbps; 802.11n(HT20/HT40):MCS0-MCS15; 802.11ac/ax(VHT20):MCS0-MCS8; 802.11ac/ax(VHT40):MCS0-MCS9;
	Modulation OFDM with BPSK/QPSK/16QAM/64QAM/256QAM for 802.11a/n/ac; OFDMA with BPSK/QPSK/16QAM/64QAM/256QAM /1024QAMfor 802.11ax;
	Operating Frequency Range ☒ 5180-5240MHz for 802.11a/n(HT20)/ac(VHT20)/ax20; ☒ 5190-5230MHz for 802.11n(HT40)/ac(VHT40)/ax40; ☐ 5210MHz for 802.11ac(VHT80)/ax80 ☒ 5745-5825 MHz for 802.11a/n(HT20)/ac(VHT20)/ax20; ☒ 5755-5795 MHz for 802.11n(HT40)/ac(VHT40)/ax40; ☐ 5775MHz for 802.11ac(VHT80)/ax80
	Number of Channels ☒ 4 channels for 802.11a/n20/ac20/ax20 in the 5180-5240MHz band ; ☒ 2 channels for 802.11 n40/ac40/ax40 in the 5190-5230MHz band ; ☐ 1 channels for 802.11 ac80/ax80 in the 5210MHz band ; ☒ 5 channels for 802.11a/n20/ac20/ax20 in the 5745-5825MHz band ; ☒ 2 channels for 802.11 n40/ac40/ax40 in the 5755-5795MHz band ; ☐ 1 channels for 802.11 ac80/ax80 in the 5775MHz band ;
	Antenna Type PCB antenna
	Antenna Gain 3.63 dBi
Based on the application, features, or specification exhibited in User's Manual, More details of EUT technical specification, please refer to the User's Manual.	
Adapter	Model: XC018WH-1201500U1 Input: 100-240V~50/60Hz 1.0A Output: 12.0V---1.5A 18.0W
Battery	N/A
Power supply	DC 12V from adapter
Connecting I/O Port(s)	Please refer to the User's Manual
Hardware Version	JHA133-DDR3-UT-C-VOL V1.0 20240918
Software Version	JHA133-DDR3-15.6-EDP-V1.0

Family Model

JT101M-A01, JT101M-C01, JT101M-T01, JT101M-K05, JT101M-C02, JT101M-D01, JT101M-H01.
 JT133M-D01, JT140M-X05, JT150M-102, JT156M-102, JT156M-002, JT156M-C05,
 C-1, C-2, DC-15001-W, AWFC10F, AWFC15F, JT101M-M01, JT101M-M02, JT101M-M05
 JD101M-B02, JD101M-A03, JD156M-002, JD156M-H01
 JD070X-XXX.JD071X-XXX.JD080X-XXX.JD081X-XXX
 JD082X-XXX.JD087X-XXX.JD090X-XXX.JD097X-XXX
 JD100X-XXX.JD101X-XXX.JD102X-XXX.JD104X-XXX
 JD108X-XXX.JD110X-XXX.JD116X-XXX.JD120X-XXX
 JD121X-XXX.JD130X-XXX.JD133X-XXX.JD135X-XXX
 JD140X-XXX.JD141X-XXX.JD142X-XXX.JD150X-XXX
 JD156X-XXX.JT070X-XXX.JT071X-XXX.JT080X-XXX.
 JT081X-XXX.JT082X-XXX.JT087X-XXX.JT108X-XXX.
 JT090X-XXX.JT097X-XXX.JT100X-XXX.JT101X-XXX.
 JT102X-XXX.JT104X-XXX.JT110X-XXX.JT116X-XXX.
 JT120X-XXX.JT121X-XXX.JT130X-XXX.JT133X-XXX.
 JT135X-XXX.JT140X-XXX.JT141X-XX.JT142X-XXX.
 JT150X-XXX.JT156X-XXX.(X stand for 0~9 or A~Z)(X stand for 0~9 or A~Z)

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2. Frequency and Channel list for 802.11a/n/ac/ax(20MHz) band I (5180-5240MHz):

802.11a/n/ac(20MHz)/ax20 Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220	-	-	-	-
40	5200	48	5240	-	-	-	-

Frequency and Channel list for 802.11n/ac(40MHz)/ax40 band I (5190-5230MHz):

802.11n/ac/ax(40MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	-	-	-	-	-	-
46	5230	-	-	-	-	-	-

Frequency and Channel list for 802.11a/n/ac(20 MHz)/ax20 band IV (5745-5825MHz):

802.11a/n/ac/ax(20 MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	153	5765	157	5785	161	5805
165	5825	-	-	-	-	-	-

Frequency and Channel list for 802.11n/ac(40MHz)/ax40 band IV (5755-5795MHz):

802.11n/ac/ax(40MHz) Carrier Frequency Channel					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
151	5755	159	5795	-	-

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	Normal Link Mode
Mode 2	802.11a / n 20 / ac 20/ax20 CH36/ CH40/ CH 48 802.11a / n 20 / ac 20/ax20 CH149/ CH157/ CH 165
Mode 3	802.11n40 / ac40/ax40 CH38/ CH 46 802.11n 40 / ac 40/ax40 CH 151 / CH 159


For Radiated Emission	
Final Test Mode	Description
Mode 1	Normal Link Mode
Mode 2	802.11a / n 20 / ac 20/ax20 CH36/ CH40/ CH 48 802.11a / n 20 / ac 20/ax20 CH149/ CH157/ CH 165
Mode 3	802.11n40 / ac40/ax40 CH38/ CH 46 802.11n 40 / ac 40/ax40 CH 151 / CH 159

Note:


- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED


For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



Note: 1.The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
AE-1	Adapter	XC018WH-1201500U1	N/A	Peripherals
AE-2	Notebook	N/A	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	Power Cable	NO	NO	1.8m
C-2	USB Cable	YES	NO	1.0m
C-3	RF Cable	YES	NO	0.1m

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation& Conducted Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4440A	MY41000130	2024.04.26	2025.04.25	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2024.04.25	2025.04.24	1 year
3	Spectrum Analyzer	R&S	FSV40	101417	2024.04.25	2025.04.24	1 year
4	Test Receiver	R&S	ESPI7	101318	2024.04.26	2025.04.25	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2024.05.12	2025.05.11	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2024.04.26	2027.04.25	3 year
7	Horn Antenna	EM	EM-AH-10180	2011071402	2024.05.12	2027.05.11	3 year
8	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	803	2024.05.12	2027.05.11	3 year
9	Amplifier	EMC	EMC051835SE	980246	2024.04.25	2025.04.24	1 year
10	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	055	2024.05.17	2027.05.16	3 year
11	Power Meter	DARE	RPR3006W	15100041SN084	2024.04.25	2025.04.24	1 year
12	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2023.05.06	2026.05.05	3 year
13	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2023.05.06	2026.05.05	3 year
14	High Test Cable(1G-40G Hz)	N/A	R-03	N/A	2023.05.06	2026.05.05	3 year
15	Filter	TRILTHIC	2400MHz	29	2024.04.26	2027.04.25	3 year
16	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

Note:

We will use the temporary antenna connector (soldered on the PCB board) When conducted test
And this temporary antenna connector is listed within the instrument list

AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2024.04.26	2025.04.25	1 year
2	LISN	R&S	ENV216	101313	2024.04.25	2025.04.24	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2024.04.25	2025.04.24	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2024.04.26	2027.04.25	3 year
5	Test Cable (9KHz-30M Hz)	N/A	C01	N/A	2023.05.06	2026.05.05	3 year
6	Test Cable (9KHz-30M Hz)	N/A	C02	N/A	2023.05.06	2026.05.05	3 year
7	Test Cable (9KHz-30M Hz)	N/A	C03	N/A	2023.05.06	2026.05.05	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Test Cable& Aux Equipment which is scheduled for calibration every 3 years.

Measurement Software

Item	Manufacturer	Software Name	Software Version	Description
1	MWRFTest	MTS 8310 2.4GHz/5GHz	2.0	RF Conducted Test
2	Farad	EZ-EMC_RE	AIT-03A	RadiatedTest
3	raditeq	RadiMation	2023.1.3	RadiatedTest
4	Farad	EZ-EMC_CE	AIT-03A	AC Conducted Test

3. TEST REQUIREMENTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 APPLICABLE STANDARD


According to FCC Part 15.207(a)

3.1.2 CONFORMANCE LIMIT

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. *Decreases with the logarithm of the frequency
 2. The lower limit shall apply at the transition frequencies
 3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3.1.3 TEST CONFIGURATION



3.1.4 TEST PROCEDURE

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.


3.1.5 TEST RESULTS

EUT :	Digital Calendar for Family Schedules	Model Name :	JT156M-H01
Temperature :	22°C	Relative Humidity :	57%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 12V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.2G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1532	45.73	9.44	55.17	65.82	-10.65	QP
0.1932	42.36	9.49	51.85	63.90	-12.05	QP
0.1932	27.47	9.49	36.96	53.90	-16.94	AVG
0.2575	27.75	9.63	37.38	51.51	-14.13	AVG
0.3215	28.91	9.73	38.64	49.67	-11.03	AVG
0.3336	40.89	9.75	50.64	59.36	-8.72	QP
0.5210	42.06	10.01	52.07	56.00	-3.93	QP
0.5731	29.64	10.11	39.75	46.00	-6.25	AVG
1.1290	38.05	11.28	49.33	56.00	-6.67	QP
1.3165	23.45	11.67	35.12	46.00	-10.88	AVG
9.6538	27.47	10.02	37.49	50.00	-12.51	AVG
10.0715	55.74	0.02	55.76	60.00	-4.24	QP

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Digital Calendar for Family Schedules	Model Name :	JT156M-H01
Temperature :	22°C	Relative Humidity :	57%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 12V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.2G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1572	47.23	9.46	56.69	65.61	-8.92	QP
0.1814	46.18	9.48	55.66	64.42	-8.76	QP
0.1892	23.89	9.50	33.39	54.07	-20.68	AVG
0.2534	41.02	9.61	50.63	61.64	-11.01	QP
0.3165	22.57	9.73	32.30	49.80	-17.50	AVG
0.4395	42.02	9.92	51.94	57.07	-5.13	QP
0.4444	26.06	9.91	35.97	46.98	-11.01	AVG
0.5731	21.12	10.11	31.23	46.00	-14.77	AVG
0.9183	34.90	10.84	45.74	56.00	-10.26	QP
1.0650	17.56	11.13	28.69	46.00	-17.31	AVG
10.0715	53.97	0.02	53.99	60.00	-6.01	QP
11.9961	36.37	-1.53	34.84	50.00	-15.16	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Digital Calendar for Family Schedules	Model Name :	JT156M-H01
Temperature :	22 °C	Relative Humidity :	57%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 12V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.8G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1532	46.23	9.44	55.67	65.82	-10.15	QP
0.1932	41.36	9.49	50.85	63.90	-13.05	QP
0.1932	26.47	9.49	35.96	53.90	-17.94	AVG
0.3215	27.91	9.73	37.64	49.67	-12.03	AVG
0.4395	42.67	9.92	52.59	57.07	-4.48	QP
0.5127	28.21	9.99	38.20	46.00	-7.80	AVG
0.5210	41.06	10.01	51.07	56.00	-4.93	QP
0.5731	28.64	10.11	38.75	46.00	-7.25	AVG
1.1290	38.05	11.28	49.33	56.00	-6.67	QP
1.3165	23.45	11.67	35.12	46.00	-10.88	AVG
9.6538	27.47	10.02	37.49	50.00	-12.51	AVG
10.0715	55.74	0.02	55.76	60.00	-4.24	QP

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Digital Calendar for Family Schedules	Model Name :	JT156M-H01
Temperature :	22 °C	Relative Humidity :	57%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 12V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.8G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1572	47.23	9.46	56.69	65.61	-8.92	QP
0.1814	46.18	9.48	55.66	64.42	-8.76	QP
0.1892	23.39	9.50	32.89	54.07	-21.18	AVG
0.2534	40.52	9.61	50.13	61.64	-11.51	QP
0.3165	22.57	9.73	32.30	49.80	-17.50	AVG
0.4395	42.02	9.92	51.94	57.07	-5.13	QP
0.4444	26.06	9.91	35.97	46.98	-11.01	AVG
0.5670	37.16	10.11	47.27	56.00	-8.73	QP
0.5670	21.62	10.11	31.73	46.00	-14.27	AVG
1.1290	18.44	11.28	29.72	46.00	-16.28	AVG
10.0715	54.47	0.02	54.49	60.00	-5.51	QP
11.9961	36.37	-1.53	34.84	50.00	-15.16	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 APPLICABLE STANDARD

According to FCC Part 15.407 (b) (9) (10) and 15.209

3.2.2 CONFORMANCE LIMIT

According to FCC Part 15.407 (b) (9) (10) : radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300
0.490~1.705	24000/F(KHz)	20 log (uV/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Remark :1. Emission level in dBuV/m=20 log (uV/m)

2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

3. For Frequency 9kHz~30MHz:

Distance extrapolation factor =40log(Specific distance/ test distance)(dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor.

For Frequency above 30MHz:

Distance extrapolation factor =20log(Specific distance/ test distance)(dB);


Limit line=Specific limits(dBuV) + distance extrapolation factor.

3.2.3 MEASURING INSTRUMENTS


The Measuring equipment is listed in the section 6.3 of this test report.

3.2.4 TEST CONFIGURATION


(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



3.2.5 TEST PROCEDURE

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.

Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 1MHz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	1 MHz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW [kHz]})$. , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

3.2.6 TEST RESULTS (9KHz – 30 MHz)

EUT:	Digital Calendar for Family Schedules	Model Name. :	JT156M-H01
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 12V
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	N/A
--	--	--	--	N/A

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


3.2.7 TEST RESULTS (30MHz – 1GHz)

EUT :	Digital Calendar for Family Schedules	Model Name. :	JT156M-H01
Temperature :	25℃	Relative Humidity :	55%
Pressure :	1010 hPa	Test Voltage :	DC 12V
Test Mode :	TX(5.2G)- 802.11ac20 (Mid CH)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	32.4060	19.55	16.93	36.48	40.00	-3.52	QP
V	55.2207	11.62	19.49	31.11	40.00	-8.89	QP
V	86.5027	17.78	14.86	32.64	40.00	-7.36	QP
V	103.8054	17.14	18.10	35.24	43.50	-8.26	QP
V	159.7844	17.02	15.10	32.12	43.50	-11.38	QP
V	459.1143	14.42	23.98	38.40	46.00	-7.60	QP

Remark:


Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	35.1276	9.25	17.35	26.60	40.00	-13.40	QP
H	56.1974	8.65	19.38	28.03	40.00	-11.97	QP
H	100.9339	11.18	17.89	29.07	43.50	-14.43	QP
H	159.7844	18.29	15.10	33.39	43.50	-10.11	QP
H	314.3763	19.05	20.76	39.81	46.00	-6.19	QP
H	459.1143	17.85	23.98	41.83	46.00	-4.17	QP

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Note(1)“802.11ac20” mode is the worst mode.


(2)Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

EUT :	Digital Calendar for Family Schedules	Model Name. :	JT156M-H01
Temperature :	25℃	Relative Humidity :	55%
Pressure :	1010 hPa	Test Voltage :	DC 12V
Test Mode :	TX(5.8G)- 802.11a (Mid CH)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	32.4060	19.55	16.93	36.48	40.00	-3.52	QP
V	55.2207	13.12	19.49	32.61	40.00	-7.39	QP
V	48.3316	10.96	19.70	30.66	40.00	-9.34	QP
V	103.8054	17.14	18.10	35.24	43.50	-8.26	QP
V	159.7844	18.02	15.10	33.12	43.50	-10.38	QP
V	459.1143	14.92	23.98	38.90	46.00	-7.10	QP

Remark:


Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	48.5015	7.37	19.72	27.09	40.00	-12.91	QP
H	100.9339	11.18	17.89	29.07	43.50	-14.43	QP
H	159.7844	18.29	15.10	33.39	43.50	-10.11	QP
H	283.9791	19.67	20.08	39.75	46.00	-6.25	QP
H	314.3763	19.55	20.76	40.31	46.00	-5.69	QP
H	459.1143	18.35	23.98	42.33	46.00	-3.67	QP

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Note(1) "802.11a" mode is the worst mode.

(2) Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

3.2.8 TEST RESULTS (1GHz-18GHz)

EUT :	Digital Calendar for Family Schedules	Model Name. :	JT156M-H01
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 12V
Test Mode :	TX(5.2G) - 802.11ac20_5180~5240MHz		

Polar	Frequency	Meter Reading	Cable loss	Antenna Factor	Preamplifier Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	dB/m	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G									
Vertical	3694.89	61.94	5.94	35.4	44	59.28	74	-14.72	Pk
Vertical	3694.86	43.13	5.94	35.4	44	40.47	54	-13.53	AV
Vertical	10360.75	58.78	8.46	39.75	44.5	62.49	68.2	-5.71	Pk
Vertical	15540.84	61.67	10.12	38.8	44.1	66.49	74	-7.51	Pk
Vertical	15540.93	39.92	10.12	38.8	42.7	46.14	54	-7.86	AV
Horizontal	3713.86	63.72	5.94	35.18	44	60.84	74	-13.16	Pk
Horizontal	3713.4	44.41	5.94	35.18	44	41.53	54	-12.47	AV
Horizontal	10360.75	59.69	8.46	38.71	44.5	62.36	68.2	-5.84	Pk
Horizontal	15540.99	57.84	10.12	38.38	44.1	62.24	74	-11.76	Pk
Horizontal	15541.2	41.77	10.12	38.38	44.1	46.17	54	-7.83	AV
middle Channel (5200 MHz)-Above 1G									
Vertical	3624.61	59.16	6.48	36.35	44.05	57.94	74	-16.06	Pk
Vertical	3624.85	43.69	6.48	36.35	44.05	42.47	54	-11.53	AV
Vertical	10400.55	60.5	8.47	37.88	44.51	62.34	68.2	-5.86	Pk
Vertical	15601.09	60.47	10.12	38.8	44.1	65.29	74	-8.71	Pk
Vertical	15600.71	40.08	10.12	38.8	42.7	46.3	54	-7.7	AV
Horizontal	4202.94	58.9	6.48	36.37	44.05	57.7	74	-16.3	Pk
Horizontal	4202.58	45.77	6.48	36.37	44.05	44.57	54	-9.43	AV
Horizontal	10400.56	62.13	8.47	38.64	44.5	64.74	68.2	-3.46	Pk
Horizontal	15601.48	60.56	10.12	38.38	44.1	64.96	74	-9.04	Pk
Horizontal	15601.36	41.93	10.12	38.38	44.1	46.33	54	-7.67	AV

High Channel (5240 MHz)-Above 1G									
Vertical	4598.14	64.5	7.1	37.24	43.5	65.34	74	-8.66	Pk
Vertical	4598.4	44.11	7.1	37.24	43.5	44.95	54	-9.05	AV
Vertical	10481.11	60.64	8.46	37.68	44.5	62.28	68.2	-5.92	Pk
Vertical	15720.86	62.25	10.12	38.8	44.1	67.07	74	-6.93	Pk
Vertical	15720.56	40.72	10.12	38.8	42.7	46.94	54	-7.06	AV
Horizontal	4589.81	61.47	7.1	37.24	43.5	62.31	74	-11.69	Pk
Horizontal	4589.68	42.39	7.1	37.24	43.5	43.23	54	-10.77	AV
Horizontal	10481.34	62.98	8.46	38.57	44.5	65.51	68.2	-2.69	Pk
Horizontal	15720.73	60.34	10.12	38.38	44.1	64.74	74	-9.26	Pk
Horizontal	15720.68	43.55	10.12	38.38	44.1	47.95	54	-6.05	AV

Note:"802.11 ac20" mode is the worst mode.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported. Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

EUT :	Digital Calendar for Family Schedules	Model Name. :	JT156M-H01
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 12V
Test Mode :	TX (5.8G) -- 802.11a_5745~5825MHz		

Polar	Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	dB/m	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G									
Vertical	2806	56.91	5.94	35.40	44.00	54.25	74.00	-19.75	Pk
Vertical	2806	44.46	5.94	35.40	44.00	41.80	54.00	-12.20	AV
Vertical	11490	57.77	8.46	39.75	44.50	61.48	74.00	-12.52	Pk
Vertical	11490	42.66	8.46	39.75	44.50	46.37	54.00	-7.63	AV
Vertical	17235	58.84	10.12	38.80	44.10	63.66	68.20	-4.54	Pk
Vertical	17235	58.99	10.12	38.80	44.10	63.81	68.20	-4.39	AV
Horizontal	2911	56.87	5.94	35.18	44.00	53.99	68.20	-14.21	Pk
Horizontal	2911	57.43	5.94	35.18	44.00	54.55	68.20	-13.65	AV
Horizontal	11490	56.52	8.46	38.71	44.50	59.19	74.00	-14.81	Pk
Horizontal	11490	45.43	8.46	38.71	44.50	48.10	54.00	-5.90	AV
Horizontal	17235	58.26	10.12	38.38	44.10	62.66	68.20	-5.54	Pk
Horizontal	17235	55.22	10.12	38.38	44.10	59.62	68.20	-8.58	AV
middle Channel (5785 MHz)-Above 1G									
Vertical	3763	58.52	6.48	36.35	44.05	57.30	74.00	-16.70	Pk
Vertical	3763	43.24	6.48	36.35	44.05	42.02	54.00	-11.98	AV
Vertical	11570	60.28	8.47	37.88	44.51	62.12	74.00	-11.88	Pk
Vertical	11570	42.65	8.47	37.88	44.51	44.49	54.00	-9.51	AV
Vertical	17355	55.16	10.12	38.8	44.10	59.98	68.20	-8.22	Pk
Vertical	17355	55.62	10.12	38.8	44.10	60.44	68.20	-7.76	AV
Horizontal	3561	55.31	6.48	36.37	44.05	54.11	68.20	-14.09	Pk
Horizontal	3561	57.99	6.48	36.37	44.05	56.79	68.20	-11.41	AV
Horizontal	11570	60.52	8.47	38.64	44.50	63.13	74.00	-10.87	Pk
Horizontal	11570	44.31	8.47	38.64	44.50	46.92	54.00	-7.08	AV
Horizontal	17355	59.77	10.12	38.38	44.10	64.17	68.20	-4.03	Pk
Horizontal	17355	56.81	10.12	38.38	44.10	61.21	68.20	-6.99	AV

High Channel (5825 MHz)-Above 1G									
Vertical	3907	56.25	7.10	37.24	43.50	57.09	74.00	-16.91	Pk
Vertical	3907	42.52	7.10	37.24	43.50	43.36	54.00	-10.64	AV
Vertical	11650	60.38	8.46	37.68	44.50	62.02	74.00	-11.98	Pk
Vertical	11650	45.35	8.46	37.68	44.50	46.99	54.00	-7.01	AV
Vertical	17475	58.57	10.12	38.8	44.10	63.39	68.20	-4.81	Pk
Vertical	17475	58.92	10.12	38.8	44.10	63.74	68.20	-4.46	AV
Horizontal	3912	56.71	7.10	37.24	43.50	57.55	74.00	-16.45	Pk
Horizontal	3912	42.71	7.10	37.24	43.50	43.55	54.00	-10.45	AV
Horizontal	11650	57.21	8.46	38.57	44.50	59.74	74.00	-14.26	Pk
Horizontal	11650	42.31	8.46	38.57	44.50	44.84	54.00	-9.16	AV
Horizontal	17475	56.25	10.12	38.38	44.10	60.65	68.20	-7.55	Pk
Horizontal	17475	57.45	10.12	38.38	44.10	61.85	68.20	-6.35	AV

Note:"802.11a" mode is the worst mode.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


3.2.9 TEST RESULTS (18GHz-40GHz)

EUT :	Digital Calendar for Family Schedules	Model Name. :	JT156M-H01
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 12V
Test Mode :	TX (5.2G)-802.11ac20 5180MHz~5240MHz, TX (5.8G)-802.11a 5745MHz~5825MHz		

All the modulation modes have been tested, and the worst result was report as below:

Low Channel (5180 MHz)-Above 1G


Horizontal



Measurement Result:

Frequency MHz	Meter Reading dBuV	Cable loss dB	Antenna Factor dB/m	Preamp Factor dB	Emission Level dBuV/m	Limits dBuV/m	Margin dB	Detector Type
39769.45	38.32	20.09	44.07	43.48	59	68.2	9.2	Peak
39769.26	27.56	20.09	44.04	43.48	48.21	54	5.79	AVG


Vertical



Measurement Result:


Frequency MHz	Meter Reading dBuV	Cable loss dB	Antenna Factor dB/m	Preamp Factor dB	Emission Level dBuV/m	Limits dBuV/m	Margin dB	Detector Type
39769.84	39.2	20.09	44.07	43.48	59.88	68.2	8.32	Peak
39769.6	26.06	20.09	44.04	43.48	46.71	54	7.29	AVG

High Channel (5240 MHz)-Above 1G



Measurement Result:

Frequency MHz	Meter Reading dBuV	Cable loss dB	Antenna Factor dB/m	Preamp Factor dB	Emission Level dBuV/m	Limits dBuV/m	Margin dB	Detector Type
35769.33	38.14	19.11	42.73	44.61	55.37	68.2	12.83	Peak
35769.61	27.89	19.11	42.73	44.61	45.12	54	8.88	AVG




Measurement Result:

Frequency MHz	Meter Reading dBuV	Cable loss dB	Antenna Factor dB/m	Preamp Factor dB	Emission Level dBuV/m	Limits dBuV/m	Margin dB	Detector Type
39769.7	40.99	20.09	44.07	43.48	61.67	68.2	6.53	Peak
39769.93	27.5	20.09	44.04	43.48	48.15	54	5.85	AVG

Low Channel (5745 MHz)-Above 1G


Horizontal



Measurement Result:

Frequency MHz	Meter Reading dBuV	Cable loss dB	Antenna Factor dB/m	Preamp Factor dB	Emission Level dBuV/m	Limits dBuV/m	Margin dB	Detector Type
39670.09	38.21	20.09	44.16	43.48	58.98	68.2	9.22	Peak
39670.19	27.63	20.09	44.16	43.48	48.4	54	5.6	AVG

Vertical




Measurement Result:

Frequency MHz	Meter Reading dBuV	Cable loss dB	Antenna Factor dB/m	Preamp Factor dB	Emission Level dBuV/m	Limits dBuV/m	Margin dB	Detector Type
39731.48	39.59	20.06	44.07	43.21	60.51	68.2	7.69	Peak
39731.71	28.02	20.06	44.07	43.21	48.94	54	5.06	AVG

High Channel (5825 MHz)-Above 1G


Horizontal



Measurement Result:

Frequency MHz	Meter Reading dBuV	Cable loss dB	Antenna Factor dB/m	Preamplifier Factor dB	Emission Level dBuV/m	Limits dBuV/m	Margin dB	Detector Type
39680.73	38.63	19.11	42.63	43.48	56.89	68.2	11.31	Peak
39680.7	26.38	19.12	42.63	43.48	44.65	54	9.35	AVG

Vertical



Measurement Result:

Frequency MHz	Meter Reading dBuV	Cable loss dB	Antenna Factor dB/m	Preamplifier Factor dB	Emission Level dBuV/m	Limits dBuV/m	Margin dB	Detector Type
39822	40.08	20.1	44.1	43.22	61.06	68.2	7.14	Peak
39822.12	29	20.1	44.1	43.22	49.98	54	4.02	AVG

3.2.10 Spurious Emission in Restricted Band 4.5GHz~5.150 GHz& 5.350GHz~5460GHz

EUT :	Digital Calendar for Family Schedules	Model Name. :	JT156M-H01
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 12V
Test Mode :	TX (5.2G)-802.11ac20 5150MHz~5250MHz,		

All the modulation modes have been tested, The report just record the worst data mode.

Frequen cy	Meter Reading	Cable Loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detec tor	Comment
(MHz)	(dBμV)	(dB)	dB/m	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
5.2G WIFI-802.11 ac20 Mode									
4500	60.36	5.2	35.6	44.2	56.96	74	-17.04	Pk	Horizontal
4500	49.63	5.2	35.6	44.2	46.23	54	-7.77	AV	Horizontal
4500	59.99	5.2	35.6	44.2	56.59	74	-17.41	Pk	Horizontal
4500	46.63	5.2	35.6	44.2	43.23	54	-10.77	AV	Horizontal
5150	75.06	5.36	35.66	44.22	71.86	74	-2.14	Pk	Horizontal
5150	51.55	5.36	35.66	44.22	48.35	54	-5.65	AV	Horizontal
5150	60.05	5.36	35.66	44.22	56.85	74	-17.15	Pk	Vertical
5150	54.4	5.36	35.66	44.22	51.2	54	-2.8	AV	Vertical
5350	69.53	5.68	35.68	44.22	66.67	74	-7.33	Pk	Vertical
5350	49.73	5.68	35.68	44.22	46.87	54	-7.13	AV	Vertical
5350	61.64	5.68	35.68	44.22	58.78	74	-15.22	Pk	Horizontal
5350	48.27	5.68	35.68	44.22	45.41	54	-8.59	AV	Horizontal

Note: (1) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor

(2) "802.11ac20 " mode is the worst mode. When PK value is lower than the Average value limit, average don't record.

3.3 POWER SPECTRAL DENSITY TEST

3.3.1 Applied procedures / limit

According to FCC §15.407(a)(3)

For the band 5.15-5.25 GHz,

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz

(3) For the band 5.725-5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

,

3.3.2 TEST PROCEDURE

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:

- a) Set $RBW \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $VBW \geq 3 RBW$.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/RBW)$ to the measured result, whereas $RBW (< 500 \text{ KHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1\text{MHz}/RBW)$ to the measured result, whereas $RBW (< 1 \text{ MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 KHz for the sections 5.c) and 5.d) above, since $RBW=100 \text{ KHz}$ is available on nearly all spectrum analyzers.

3.3.3 DEVIATION FROM STANDARD

No deviation.

3.3.4 TEST SETUP



3.3.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

3.3.6 TEST RESULTS

EUT :	Digital Calendar for Family Schedules	Model Name. :	JT156M-H01
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1015 hPa	Test Voltage :	DC 12V
Test Mode :	TX Frequency Band I (5150-5250MHz), Band IV (5725-5850MHz)		

Test data reference attachment.

3.4 26DB & 99% EMISSION BANDWIDTH

3.4.1 Applied procedures / limit


The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

3.4.2 TEST PROCEDURE

- Set RBW = approximately 1% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = Peak.
- Trace mode = max hold.
- Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

The following procedure shall be used for measuring (99 %) power bandwidth:

- Set center frequency to the nominal EUT channel center frequency.
- Set span = 1.5 times to 5.0 times the OBW.
- Set RBW = 1 % to 5 % of the OBW
- Set VBW $\geq 3 \cdot$ RBW
- Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- Use the 99 % power bandwidth function of the instrument (if available).
- If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.



3.4.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.4.4 TEST RESULTS

EUT :	Digital Calendar for Family Schedules	Model Name. :	JT156M-H01
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 12V
Test Mode :	TX Frequency Band I (5150-5250MHz), Band IV (5725-5850MHz)		

Test data reference attachment.

3.5 MINIMUM 6 DB BANDWIDTH

3.5.1 Applied procedures / limit

According to FCC §15.407(e)

(e) Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

3.5.2 TEST PROCEDURE


Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

3.5.3 DEVIATION FROM STANDARD

No deviation.

3.5.4 TEST SETUP



3.5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.5.6 TEST RESULTS

EUT :	Digital Calendar for Family Schedules	Model Name. :	JT156M-H01
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 12V
Test Mode :	TX (5G) Mode Frequency Band IV (5725-5850MHz)		

Test data reference attachment.

3.6 MAXIMUM CONDUCTED OUTPUT POWER

3.6.1 PPLIED PROCEDURES / LIMIT

According to FCC §15.407

The maximum conducted output power should not exceed:

Frequency Band(MHz)	Limit
5150~5250	250mW
5725~5850	1W

3.6.2 TEST PROCEDURE


Method PM is Measurement using an RF average power meter. The procedure for this method is as follows:

- a) Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the following conditions are satisfied:
 - 1) The EUT is configured to transmit continuously, or to transmit with a constant duty cycle.
 - 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
 - 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- b) If the transmitter does not transmit continuously, measure the duty cycle D of the transmitter output signal as described in 12.2.
- c) Measure the average power of the transmitter. This measurement is an average over both the ON and OFF periods of the transmitter.
- d) Adjust the measurement in dBm by adding $[10 \log (1 / D)]$, where D is the duty cycle {e.g., $[10 \log (1 / 0.25)]$, if the duty cycle is 25%}.

3.6.3 DEVIATION FROM STANDARD

No deviation.

3.6.4 TEST SETUP



3.6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.6.6 TEST RESULTS

EUT :	Digital Calendar for Family Schedules	Model Name. :	JT156M-H01
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 12V
Test Mode :	TX (5G) Mode Frequency Band I (5150-5250MHz), Band IV (5725-5850MHz)		

Test data reference attachment.

3.7 OUT OF BAND EMISSIONS

3.7.1 Applicable Standard

According to FCC §15.407(b)

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.


3.7.2 Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

3.7.3 DEVIATION FROM STANDARD

No deviation.

3.7.4 TEST SETUP



3.7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.7.6 TEST RESULTS

EUT :	Digital Calendar for Family Schedules	Model Name. :	JT156M-H01
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 12V

Test data reference attachment.

3.8 SPURIOUS RF CONDUCTED EMISSIONS

3.8.1 Conformance Limit

According to FCC §15.407(b)(1)(4)

3.8.2 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

3.8.3 Test Setup

Please refer to Section 6.1 of this test report.

3.8.4 Test Procedure

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=1MHz and VBW= 3MHz to measure the peak field strength , and measure frequency range from 30MHz to 40GHz.

3.8.5 Test Results

Remark: The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and band edge measurement data.

Test data reference attachment.

3.9 FREQUENCY STABILITY MEASUREMENT


3.9.1 LIMIT

Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

3.9.2 TEST PROCEDURES

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5. f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f)/f_c \times 10^6 \text{ ppm}$.
6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
7. Extreme temperature is $-20^\circ\text{C} \sim 70^\circ\text{C}$.

3.9.3 TEST SETUP LAYOUT



3.9.4 EUT OPERATION DURING TEST

The EUT was programmed to be in continuously un-modulation transmitting mode.

3.9.5 TEST RESULTS

EUT :	Digital Calendar for Family Schedules	Model Name. :	JT156M-H01
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 12V
Test Mode :	TX Frequency Band I (5150-5250MHz)		

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5180MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	12.00	5180.0161	5180	0.0161	-3.1081
		V max (V)	13.20	5180.0176	5180	0.0176	-3.3977
		V min (V)	10.80	5180.0355	5180	0.0355	-6.8533
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5180MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	12	T (°C)	-20	5180.0136	5180	0.0136	-2.6255
		T (°C)	-10	5180.0071	5180	0.0071	-1.3707
		T (°C)	0	5180.0568	5180	0.0568	-10.9653
		T (°C)	10	5180.0292	5180	0.0292	-5.6371
		T (°C)	20	5180.0242	5180	0.0242	-4.6718
		T (°C)	30	5180.0503	5180	0.0503	-9.7104
		T (°C)	40	5180.0090	5180	0.0090	-1.7375
		T (°C)	50	5180.0499	5180	0.0499	-9.6332
		T (°C)	60	5180.0172	5180	0.0172	-3.3205
		T (°C)	70	5180.0238	5180	0.0238	-4.5946
Limits				Within 5150-5250MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5200MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	12.00	5200.0449	5200	0.0449	-8.6346
		V max (V)	13.20	5200.0579	5200	0.0579	-11.1346
		V min (V)	10.80	5200.0030	5200	0.0030	-0.5769
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5200MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	12	T (°C)	-20	5200.0148	5200	0.0148	-2.8462
		T (°C)	-10	5200.0150	5200	0.0150	-2.8846
		T (°C)	0	5200.0415	5200	0.0415	-7.9808
		T (°C)	10	5200.0156	5200	0.0156	-3.0000
		T (°C)	20	5200.0639	5200	0.0639	-12.2885
		T (°C)	30	5200.0271	5200	0.0271	-5.2115
		T (°C)	40	5200.0396	5200	0.0396	-7.6154
		T (°C)	50	5200.0146	5200	0.0146	-2.8077
		T (°C)	60	5200.0751	5200	0.0751	-14.4423
		T (°C)	70	5200.0434	5200	0.0434	-8.3462
Limits				Within 5150-5250MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5240MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	12.00	5240.0349	5240	0.0349	-6.6603
		V max (V)	13.20	5240.0498	5240	0.0498	-9.5038
		V min (V)	10.80	5240.0612	5240	0.0612	-11.6794
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5240MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	12	T (°C)	-20	5240.0710	5240	0.0710	-13.5496
		T (°C)	-10	5240.0534	5240	0.0534	-10.1908
		T (°C)	0	5240.0423	5240	0.0423	-8.0725
		T (°C)	10	5240.0130	5240	0.0130	-2.4809
		T (°C)	20	5240.0134	5240	0.0134	-2.5573
		T (°C)	30	5240.0243	5240	0.0243	-4.6374
		T (°C)	40	5240.0190	5240	0.0190	-3.6260
		T (°C)	50	5240.0492	5240	0.0492	-9.3893
		T (°C)	60	5240.0348	5240	0.0348	-6.6412
		T (°C)	70	5240.0454	5240	0.0454	-8.6641
Limits				Within 5150-5250MHz			
Result				Complies			

EUT :	Digital Calendar for Family Schedules	Model Name. :	JT156M-H01
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 12V
Test Mode :	TX Frequency(5745-5825MHz)		

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	12.00	5745.0630	5745	0.06300	-10.9661
		V max (V)	13.20	5745.0614	5745	0.06140	-10.6876
		V min (V)	10.80	5745.0477	5745	0.04770	-8.3029
Limits				Within 5745-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	12	T (°C)	-20	5745.0448	5745	0.04480	-7.7981
		T (°C)	-10	5745.0313	5745	0.03130	-5.4482
		T (°C)	0	5745.0179	5745	0.01790	-3.1158
		T (°C)	10	5745.0649	5745	0.06490	-11.2968
		T (°C)	20	5745.0764	5745	0.07640	-13.2985
		T (°C)	30	5745.0654	5745	0.06540	-11.3838
		T (°C)	40	5745.0348	5745	0.03480	-6.0574
		T (°C)	50	5745.0492	5745	0.04920	-8.5640
		T (°C)	60	5745.0361	5745	0.03610	-6.2837
		T (°C)	70	5745.0159	5745	0.01590	-2.7676
Limits				Within 5745-5850MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	12.00	5785.0205	5785	0.02050	-3.5436
		V max (V)	13.20	5785.0675	5785	0.06750	-11.6681
		V min (V)	10.80	5785.0243	5785	0.02430	-4.2005
Limits				Within 5745-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	12	T (°C)	-20	5785.0253	5785	0.02530	-4.3734
		T (°C)	-10	5785.0266	5785	0.02660	-4.5981
		T (°C)	0	5785.0333	5785	0.03330	-5.7563
		T (°C)	10	5785.0607	5785	0.06070	-10.4927
		T (°C)	20	5785.0316	5785	0.03160	-5.4624
		T (°C)	30	5785.0649	5785	0.06490	-11.2187
		T (°C)	40	5785.0276	5785	0.02760	-4.7710
		T (°C)	50	5785.0646	5785	0.06460	-11.1668
		T (°C)	60	5785.0573	5785	0.05730	-9.9049
		T (°C)	70	5785.0665	5785	0.06650	-11.4952
Limits				Within 5745-5850MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	12.00	5825.0320	5825	0.03200	-5.4936
		V max (V)	13.20	5825.0509	5825	0.05090	-8.7382
		V min (V)	10.80	5825.0275	5825	0.02750	-4.7210
Limits				Within 5745-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	12	T (°C)	-20	5825.0310	5825	0.03100	-5.3219
		T (°C)	-10	5825.0317	5825	0.03170	-5.4421
		T (°C)	0	5825.0681	5825	0.06810	-11.6910
		T (°C)	10	5825.0502	5825	0.05020	-8.6180
		T (°C)	20	5825.0372	5825	0.03720	-6.3863
		T (°C)	30	5825.0348	5825	0.03480	-5.9742
		T (°C)	40	5825.0378	5825	0.03780	-6.4893
		T (°C)	50	5825.0524	5825	0.05240	-8.9957
		T (°C)	60	5825.0264	5825	0.02640	-4.5322
		T (°C)	70	5825.0027	5825	0.00270	-0.4635
Limits				Within 5745-5850MHz			
Result				Complies			

4. ANTENNA REQUIREMENT

4.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

4.2 EUT ANTENNA

The EUT antenna is permanent attached PCB antenna (antenna gain: band I : 4.53dBi;, band IV: 4.53dBi;). It comply with the standard requirement.

END OF REPORT