

FCC ID:2BLHF-JT156M-H01

Maximum Permissible Exposure (MPE)

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

According to KDB447498 D01 General RF Exposure Guidance V06

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

2.4G WIFI:

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz,
WIFI 802.11n HT40:2422-2452MHz
Power density limited: 1mW/ cm²

Antenna Type: PCB Antenna

Antenna gain: 4.53dBi;

R=20cm

mW=10^(dBm/10)

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm2)	Power density (mW/cm2)
		(dBm)		tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric		
2412	802.11b	13.63	14±1	15	31.623	4.53	2.84	0.0179	1
2437		14.81	15±1	16	39.811	4.53	2.84	0.0225	1
2462		13.82	14±1	15	31.623	4.53	2.84	0.0179	1
2412	802.11g	14.33	15±1	16	39.811	4.53	2.84	0.0225	1
2437		14.63	15±1	16	39.811	4.53	2.84	0.0225	1
2462		15.11	15±1	16	39.811	4.53	2.84	0.0225	1
2412	802.11n HT20	14.41	15±1	16	39.811	4.53	2.84	0.0225	1
2437		14.5	15±1	16	39.811	4.53	2.84	0.0225	1
2462		14.95	15±1	16	39.811	4.53	2.84	0.0225	1
2422	802.11n(H T40)	14.28	15±1	16	39.811	4.53	2.84	0.0225	1
2437		14.42	15±1	16	39.811	4.53	2.84	0.0225	1
2452		14.3	15±1	16	39.811	4.53	2.84	0.0225	1
2412	802.11 ax20	14.88	15±1	16	39.811	4.53	2.84	0.0225	1
2437		14.3	15±1	16	39.811	4.53	2.84	0.0225	1
2462		14.71	15±1	16	39.811	4.53	2.84	0.0225	1
2422	802.11 ax40	14.06	14±1	15	31.623	4.53	2.84	0.0179	1
2437		14.26	14±1	15	31.623	4.53	2.84	0.0179	1
2452		13.94	14±1	15	31.623	4.53	2.84	0.0179	1

5G WIFI:

Operation Frequency: WIFI 802.11a/ac/n(HT20): 5180-5240MHz; 5745-5825MHz;

WIFI 802.11ac/n(HT40): 5190-5230MHz;5755-5795MHz;

WIFI 802.11ac80:5210-5210MHz;5775-5775MHz

Power density limited: 1mW/cm

Antenna Type: PCB antenna

Antenna gain: 3.63dBi;

R=20cm

mW=10^(dBm/10)

5.2G

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density
		(dBm)		tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric	(mW/cm2)	(mW/cm2)
5180	a	12.24	12±1	13	19.953	3.63	2.31	0.0092	1
5200	a	12.16	12±1	13	19.953	3.63	2.31	0.0092	1
5240	a	12.35	12±1	13	19.953	3.63	2.31	0.0092	1
5180	n20	11.73	12±1	13	19.953	3.63	2.31	0.0092	1
5200	n20	12.1	12±1	13	19.953	3.63	2.31	0.0092	1
5240	n20	12.24	12±1	13	19.953	3.63	2.31	0.0092	1
5190	n40	12.35	12±1	13	19.953	3.63	2.31	0.0092	1
5230	n40	12.51	12±1	13	19.953	3.63	2.31	0.0092	1
5180	ac20	12.07	12±1	13	19.953	3.63	2.31	0.0092	1
5200	ac20	12.5	12±1	13	19.953	3.63	2.31	0.0092	1
5240	ac20	12.57	12±1	13	19.953	3.63	2.31	0.0092	1
5190	ac40	12.26	12±1	13	19.953	3.63	2.31	0.0092	1
5230	ac40	12.5	12±1	13	19.953	3.63	2.31	0.0092	1
5180	ax20	11.49	12±1	13	19.953	3.63	2.31	0.0092	1
5200	ax20	11.63	12±1	13	19.953	3.63	2.31	0.0092	1
5240	ax20	11.85	12±1	13	19.953	3.63	2.31	0.0092	1
5190	ax40	11.73	12±1	13	19.953	3.63	2.31	0.0092	1
5230	ax40	12.05	12±1	13	19.953	3.63	2.31	0.0092	1

5.8G

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density
		(dBm)		tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric	(mW/cm2)	(mW/cm2)
5745	a	10.52	11±1	12	15.849	3.63	2.31	0.0073	1
5785	a	11.08	11±1	12	15.849	3.63	2.31	0.0073	1
5825	a	10.98	11±1	12	15.849	3.63	2.31	0.0073	1
5745	n20	10.26	10.5±1	11.5	14.125	3.63	2.31	0.0065	1
5785	n20	10.95	10.5±1	11.5	14.125	3.63	2.31	0.0065	1
5825	n20	10.84	10.5±1	11.5	14.125	3.63	2.31	0.0065	1
5755	n40	10.45	10.5±1	11.5	14.125	3.63	2.31	0.0065	1
5795	n40	10.76	10.5±1	11.5	14.125	3.63	2.31	0.0065	1
5745	ac20	10.26	10.5±1	11.5	14.125	3.63	2.31	0.0065	1
5785	ac20	10.83	10.5±1	11.5	14.125	3.63	2.31	0.0065	1
5825	ac20	10.56	10.5±1	11.5	14.125	3.63	2.31	0.0065	1
5755	ac40	10.27	10.5±1	11.5	14.125	3.63	2.31	0.0065	1
5795	ac40	10.9	10.5±1	11.5	14.125	3.63	2.31	0.0065	1
5745	ax20	10.19	10.5±1	11.5	14.125	3.63	2.31	0.0065	1
5785	ax20	10.74	10.5±1	11.5	14.125	3.63	2.31	0.0065	1
5825	ax20	10.34	10.5±1	11.5	14.125	3.63	2.31	0.0065	1
5755	ax40	10.4	10.5±1	11.5	14.125	3.63	2.31	0.0065	1
5795	ax40	10.81	10.5±1	11.5	14.125	3.63	2.31	0.0065	1

Note: NO simultaneous transmissions are possible for this device of Wi-Fi 5G + Wi-Fi 2.4G.

Signature:

Date: 2024-10-30



NAME AND TITLE (Please print or type): alex li/Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E,
Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.