

FCC RADIO TEST REPORT

FCC ID: 2BLHF-JT215M-H01

Product : Digital Calendar for Family Schedules

Trade Mark : N/A

Model Name : JT215M-H01

Family Model : Refer to page eight

Report No. : S24101801003002

Prepared for

Shenzhen Joyhong Tech Co.,Ltd
Building B6, 101, West Industrial Zone, Tantou Community,
Songgang Street, Bao'an District, Shenzhen

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan
District, Shenzhen, Guangdong, People's Republic of China
Tel. 0755-23200050 Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION

Applicant's name : Shenzhen Joyhong Tech Co.,Ltd
Address..... : Building B6, 101, West Industrial Zone, Tantou Community,
 Songgang Street, Bao'an District, Shenzhen

Manufacturer's Name : Shenzhen Joyhong Tech Co.,Ltd
Address..... : Building B6, 101, West Industrial Zone, Tantou Community,
 Songgang Street, Bao'an District, Shenzhen

Product description

Product name : Digital Calendar for Family Schedules
Model and/or type reference : JT215M-H01
Family Model..... : Refer to page eight
Sample number : S241018010003

Standards : FCC Part15.407

Test procedure ANSI C63.10-2013 and KDB 789033 D02 General UNII Test
 Procedures New Rules v02r01

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements/ the Industry Canada requirements.. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests..... Oct. 18, 2024 ~ Nov. 13, 2024

Date of Issue Nov. 13, 2024

Test Result..... **Pass**

Prepared By : Yoyo Liang
 Yoyo Liang
 (Project Engineer)

Reviewed By : Aaron Cheng
 Aaron Cheng
 (Supervisor)

Approved By : Alex Li
 Alex Li
 (Manager)

Table of Contents

	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 FACILITIES AND ACCREDITATIONS	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	10
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	12
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	13
3 . TEST REQUIREMENTS	15
3.1 CONDUCTED EMISSION MEASUREMENT	15
3.2 RADIATED EMISSION MEASUREMENT	20
3.3 POWER SPECTRAL DENSITY TEST	36
3.4 26DB & 99% EMISSION BANDWIDTH	39
3.5 MINIMUM 6 DB BANDWIDTH	41
3.6 MAXIMUM CONDUCTED OUTPUT POWER	43
3.7 OUT OF BAND EMISSIONS	46
3.8 SPURIOUS RF CONDUCTED EMISSIONS	48
3.9 FREQUENCY STABILITY MEASUREMENT	49
4. ANTENNA REQUIREMENT	56
4.1 STANDARD REQUIREMENT	56
4.2 EUT ANTENNA	56

Revision History

Report No.	Version	Description	Issued Date
S24101801003002	Rev.01	Initial issue of report	Nov. 13, 2024

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.407) , Subpart E			
Standard Section	Test Item	Judgment	Remark
15.207	AC Power Line Conducted Emissions	PASS	
15.209(a), 15.407 (b)(1) 15.407 (b)(4)	Spurious Radiated Emissions	PASS	
15.407 (a)(1) 15.407 (a)(3)	26 dB and 99% Emission Bandwidth	PASS	
15.407(e)	Minimum 6 dB bandwidth	PASS	
15.407 (a)(1) 15.407 (a)(3)	Maximum Conducted Output Power	PASS	
15.407(b)(1) 15.407(b)(4)	Band Edge	PASS	
15.407 (a)(1) 15.407 (a)(3)	Power Spectral Density	PASS	
15.407(b)	Spurious Emissions at Antenna Terminals	PASS	
15.203	Antenna Requirement	PASS	
15.407(c)	Automatically discontinue transmission	PASS	
15.407(g)	Frequency Stability Measurement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

(2)11ax supports FULL RU Only.

1.1 FACILITIES AND ACCREDITATIONS

FACILITIES

All measurement facilities used to collect the measurement data are located at
No. 24 Xinfa East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen,
Guangdong, People's Republic of China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

CNAS-Lab. : The Certificate Registration Number is L5516.

IC-Registration : The Certificate Registration Number is 9270A.
CAB identifier:CN0074

FCC- Accredited : Test Firm Registration Number: 463705.
Designation Number: CN1184

A2LA-Lab. : The Certificate Registration Number is 4298.01
This laboratory is accredited in accordance with the recognized
International Standard ISO/IEC 17025:2005 General requirements for the
competence of testing and calibration laboratories.
This accreditation demonstrates technical competence for a defined
scope and the operation of a laboratory quality management system
(refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).

Name of Firm : Shenzhen NTEK Testing Technology Co., Ltd.

Site Location : No. 24 Xinfa East Road, Xiangshan Community, Xinqiao Street, Baoan
District, Shenzhen, Guangdong, People's Republic of China

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.80\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(30MHz~1GHz)	$\pm 2.64\text{dB}$
5	All emissions, radiated(1GHz~6GHz)	$\pm 2.40\text{dB}$
6	All emissions, radiated(> 6GHz)	$\pm 2.52\text{dB}$
7	Temperature	$\pm 0.5^\circ\text{C}$
8	Humidity	$\pm 2\%$
9	All emissions, radiated(9KHz~30MHz)	$\pm 6\text{dB}$
10	Occupied bandwidth	$\pm 3.7\text{dB}$
11	POWER SPECTRAL DENSITY	$\pm 1.21\text{dB}$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Digital Calendar for Family Schedules	
Trade Mark	N/A	
Model Name	JT215M-H01	
Family Model	Refer to page eight	
Model Difference	All models are the same circuit and RF module, except for model names.	
FCC ID	2BLHF-JT215M-H01	
Product Description	IEEE 802.11 WLAN Mode Supported	☒ 802.11a/n/ac/ax (20MHz channel bandwidth) ☒ 802.11n/ac/ax (40MHz channel bandwidth)
	Data Rate	802.11a: 6,9,12,18,24,36,48,54Mbps; 802.11n(HT20/HT40):MCS0-MCS15; 802.11ac/ax(VHT20):MCS0-MCS8; 802.11ac/ax(VHT40):MCS0-MCS9;
	Modulation	OFDM with BPSK/QPSK/16QAM/64QAM/256QAM for 802.11a/n/ac; OFDMA with BPSK/QPSK/16QAM/64QAM/256QAM /1024QAM for 802.11ax;
	Operating Frequency Range	☒ 5180-5240MHz for 802.11a/n(HT20)/ac(VHT20)/ax20; ☒ 5190-5230MHz for 802.11n(HT40)/ac(VHT40)/ax40; ☐ 5210MHz for 802.11ac(VHT80)/ax80 ☒ 5745-5825 MHz for 802.11a/n(HT20)/ac(VHT20)/ax20; ☒ 5755-5795 MHz for 802.11n(HT40)/ac(VHT40)/ax40; ☐ 5775MHz for 802.11ac(VHT80)/ax80
	Number of Channels	☒ 4 channels for 802.11a/n20/ac20/ax20 in the 5180-5240MHz band ; ☒ 2 channels for 802.11 n40/ac40/ax40 in the 5190-5230MHz band ; ☐ 1 channels for 802.11 ac80/ax80 in the 5210MHz band ; ☒ 5 channels for 802.11a/n20/ac20/ax20 in the 5745-5825MHz band ; ☒ 2 channels for 802.11 n40/ac40/ax40 in the 5755-5795MHz band ; ☐ 1 channels for 802.11 ac80/ax80 in the 5775MHz band ;
	Antenna Type	PCB Antenna
	Antenna Gain	3.68 dBi
Based on the application, features, or specification exhibited in User's Manual, More details of EUT technical specification, please refer to the User's Manual.		
Adapter	Model: XC036WZ-1203000U Input: 100-240V~50/60Hz 1A Output: 12.0V---3.0A 36.0W	
Battery	N/A	
Power supply	DC 12V from adapter	
Connecting I/O Port(s)	Please refer to the User's Manual	
Hardware Version	JHA133-DDR3-UT-C-VOL V1.0 20240621	
Software Version	JHA133-DDR3-21.5-LVDS-V1.0	

Family Model

JT215M-H02, JT215M-H05
 JT238M-H01, JD238M-H01, JT238M-H02, JD238M-H02, JT238M-H05, JD238M-H05
 JT240M-H01, JD240M-H01, JT240M-H02, JD240M-H02, JT240M-H05, JD240M-H05
 JT270M-H01, JD270M-H01, JT270M-H02, JD270M-H05, JT270M-H02, JD270M-H05
 JT320M-H01, JD320M-H01, JT320M-H02, JD320M-H05, JT320M-H02, JD320M-H05
 JT190M-T01, PFF-1970, JT190M-D01, AWS19F, JT170M-D03, JT170M-D02, JT170M-D01, AWS217F,
 JT170M-I02, PFF-1770, JT171M-I02, JT160M-T01, JT167M-D01, JT162M-D01, JT167M-C02,
 JT170M-C02, JT215M-W01, JT215M-W02, JT215M-W05,
 JD162M-D01, JD162M-C02, JD167M-C02, JD170M-D01, JD170M-D03, JD170M-D02, JD215M-W01,
 JD215M-W02,
 JD215M-W05, JD215M-H01, JD215M-H02, JD320M-W01, JD320M-W02, JD320M-W05, JD320M-H01,
 N162, N167, W215, W320, Z215, Z320, Z320-W1, Modern 19, C-3, AWFC21F, AWFC32F, EC13,
 DC-10001-W, DC-15001-W, DC-21001-W, DC-24001-W, DC-27001-W, DC-32001-W
 JD160X-XXX, JD170X-XXX, JD171X-XXX, JD172X-XXX, JD173X-XXX, JD180X-XXX, JD185X-XXX,
 JD190X-XXX, JD215X-XXX, JD240X-XXX, JD270X-XXX, JD320X-XXX, JT160X-XXX, JT170X-XXX,
 JT171X-XXX, JT172X-XXX, JT173X-XXX, JT180X-XXX, JT185X-XXX,
 JT190X-XXX, JT215X-XXX, JT240X-XXX, JT270X-XXX, JT320X-XXX
 (X stand for 0~9 or A~Z) (X stand for 0~9 or A~Z)

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2. Frequency and Channel list for 802.11a/n/ac/ax(20MHz) band I (5180-5240MHz):

802.11a/n/ac(20MHz)/ax20 Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220	-	-	-	-
40	5200	48	5240	-	-	-	-

Frequency and Channel list for 802.11n/ac(40MHz)/ax40 band I (5190-5230MHz):

802.11n/ac/ax(40MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	-	-	-	-	-	-
46	5230	-	-	-	-	-	-

Frequency and Channel list for 802.11a/n/ac(20 MHz)/ax20 band IV (5745-5825MHz):

802.11a/n/ac/ax(20 MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	153	5765	157	5785	161	5805
165	5825	-	-	-	-	-	-

Frequency and Channel list for 802.11n/ac(40MHz)/ax40 band IV (5755-5795MHz):

802.11n/ac/ax(40MHz) Carrier Frequency Channel					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
151	5755	159	5795	-	-

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	Normal Link Mode
Mode 2	802.11a / n 20 /ac 20/ax20 CH36/ CH40/ CH 48 802.11a / n 20 / ac 20/ax20 CH149/ CH157/ CH 165
Mode 3	802.11n40 / ac40/ax40 CH38/ CH 46 802.11n 40 / ac 40/ax40 CH 151 / CH 159


For Radiated Emission	
Final Test Mode	Description
Mode 1	Normal Link Mode
Mode 2	802.11a / n 20 /ac 20/ax20 CH36/ CH40/ CH 48 802.11a / n 20 / ac 20/ax20 CH149/ CH157/ CH 165
Mode 3	802.11n40 / ac40/ax40 CH38/ CH 46 802.11n 40 / ac 40/ax40 CH 151 / CH 159

Note:


- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED


For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



Note: 1.The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
AE-1	Adapter	XC036WZ-1203000U	N/A	Peripherals
AE-2	Notebook	N/A	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	Power Cable	NO	NO	1.8m
C-2	USB Cable	YES	NO	1.0m
C-3	RF Cable	YES	NO	0.1m

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation& Conducted Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4440A	MY41000130	2024.04.26	2025.04.25	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2024.04.25	2025.04.24	1 year
3	Spectrum Analyzer	R&S	FSV40	101417	2024.04.25	2025.04.24	1 year
4	Test Receiver	R&S	ESPI7	101318	2024.04.26	2025.04.25	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2024.05.12	2025.05.11	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2024.04.26	2027.04.25	3 year
7	Horn Antenna	EM	EM-AH-10180	2011071402	2024.05.12	2027.05.11	3 year
8	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	803	2024.05.12	2027.05.11	3 year
9	Amplifier	EMC	EMC051835SE	980246	2024.04.25	2025.04.24	1 year
10	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	055	2024.05.17	2027.05.16	3 year
11	Power Meter	DARE	RPR3006W	15100041SN084	2024.04.25	2025.04.24	1 year
12	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2023.05.06	2026.05.05	3 year
13	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2023.05.06	2026.05.05	3 year
14	High Test Cable(1G-40G Hz)	N/A	R-03	N/A	2023.05.06	2026.05.05	3 year
15	Filter	TRILTHIC	2400MHz	29	2024.04.26	2027.04.25	3 year
16	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

Note:

We will use the temporary antenna connector (soldered on the PCB board) When conducted test
And this temporary antenna connector is listed within the instrument list

AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2024.04.26	2025.04.25	1 year
2	LISN	R&S	ENV216	101313	2024.04.25	2025.04.24	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2024.04.25	2025.04.24	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2024.04.26	2027.04.25	3 year
5	Test Cable (9KHz-30M Hz)	N/A	C01	N/A	2023.05.06	2026.05.05	3 year
6	Test Cable (9KHz-30M Hz)	N/A	C02	N/A	2023.05.06	2026.05.05	3 year
7	Test Cable (9KHz-30M Hz)	N/A	C03	N/A	2023.05.06	2026.05.05	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Test Cable& Aux Equipment which is scheduled for calibration every 3 years.

Measurement Software

Item	Manufacturer	Software Name	Software Version	Description
1	MWRFTtest	MTS 8310 2.4GHz/5GHz	2.0	RF Conducted Test
2	Farad	EZ-EMC_RE	AIT-03A	RadiatedTest
3	raditeq	RadiMation	2023.1.3	RadiatedTest
4	Farad	EZ-EMC_CE	AIT-03A	AC Conducted Test

3. TEST REQUIREMENTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 APPLICABLE STANDARD


According to FCC Part 15.207(a)

3.1.2 CONFORMANCE LIMIT

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. *Decreases with the logarithm of the frequency
 2. The lower limit shall apply at the transition frequencies
 3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3.1.3 TEST CONFIGURATION



3.1.4 TEST PROCEDURE

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.


3.1.5 TEST RESULTS

EUT :	Digital Calendar for Family Schedules	Model Name :	JT215M-H01
Temperature :	25.3℃	Relative Humidity :	50.0%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 12V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.2G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1564	48.01	10.02	58.03	65.65	-7.62	QP
0.1580	33.03	10.02	43.05	55.57	-12.52	AVG
0.2985	40.02	10.29	50.31	60.28	-9.97	QP
0.3002	30.36	10.29	40.65	50.24	-9.59	AVG
0.4061	35.74	10.52	46.26	57.73	-11.47	QP
0.4061	29.27	10.52	39.79	47.73	-7.94	AVG
0.7300	27.04	11.17	38.21	56.00	-17.79	QP
0.7340	11.84	11.17	23.01	46.00	-22.99	AVG
3.3420	28.41	9.92	38.33	56.00	-17.67	QP
3.3420	15.38	9.92	25.30	46.00	-20.70	AVG
9.9580	41.25	0.90	42.15	60.00	-17.85	QP
10.0260	28.33	0.84	29.17	50.00	-20.83	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Digital Calendar for Family Schedules	Model Name :	JT215M-H01
Temperature :	25.3℃	Relative Humidity :	50.0%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 12V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.2G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1524	51.35	9.44	60.79	65.87	-5.08	QP
0.1540	37.36	9.44	46.80	55.78	-8.98	AVG
0.2660	38.24	9.65	47.89	61.24	-13.35	QP
0.2672	18.47	9.65	28.12	51.20	-23.08	AVG
0.4820	24.56	9.95	34.51	56.30	-21.79	QP
0.4820	8.31	9.95	18.26	46.30	-28.04	AVG
0.9940	24.05	10.99	35.04	56.00	-20.96	QP
1.0140	-0.12	11.03	10.91	46.00	-35.09	AVG
2.4700	28.87	9.09	37.96	56.00	-18.04	QP
2.4940	13.86	9.09	22.95	46.00	-23.05	AVG
13.1940	35.42	10.70	46.12	60.00	-13.88	QP
13.3300	24.40	10.72	35.12	50.00	-14.88	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Digital Calendar for Family Schedules	Model Name :	JT215M-H01
Temperature :	25.3 °C	Relative Humidity :	50.0%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 12V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.8G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1740	44.76	10.04	54.80	64.77	-9.97	QP
0.1740	28.37	10.04	38.41	54.77	-16.36	AVG
0.2580	40.83	10.21	51.04	61.50	-10.46	QP
0.2580	27.57	10.21	37.78	51.50	-13.72	AVG
0.3002	41.04	10.29	51.33	60.24	-8.91	QP
0.3002	30.36	10.29	40.65	50.24	-9.59	AVG
0.8180	27.75	11.36	39.11	56.00	-16.89	QP
0.8180	17.74	11.36	29.10	46.00	-16.90	AVG
2.1300	26.05	9.82	35.87	56.00	-20.13	QP
2.1420	13.32	9.82	23.14	46.00	-22.86	AVG
9.8940	42.32	0.96	43.28	60.00	-16.72	QP
9.9580	34.93	0.90	35.83	50.00	-14.17	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	Digital Calendar for Family Schedules	Model Name :	JT215M-H01
Temperature :	25.3 °C	Relative Humidity :	50.0%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 12V from Adapter AC 120V/60Hz	Test Mode :	Mode 1(5.8G)

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1750	45.54	9.46	55.00	64.72	-9.72	QP
0.1767	28.67	9.48	38.15	54.64	-16.49	AVG
0.2660	38.24	9.65	47.89	61.24	-13.35	QP
0.2700	16.01	9.65	25.66	51.12	-25.46	AVG
0.9700	18.96	10.95	29.91	56.00	-26.09	QP
0.9820	10.21	10.97	21.18	46.00	-24.82	AVG
2.4300	28.59	9.09	37.68	56.00	-18.32	QP
2.4700	18.34	9.09	27.43	46.00	-18.57	AVG
13.1940	35.42	10.70	46.12	60.00	-13.88	QP
13.4620	23.91	10.75	34.66	50.00	-15.34	AVG
19.5420	34.13	11.87	46.00	60.00	-14.00	QP
19.7980	23.85	11.91	35.76	50.00	-14.24	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 APPLICABLE STANDARD

According to FCC Part 15.407 (b) (9) (10) and 15.209

3.2.2 CONFORMANCE LIMIT

According to FCC Part 15.407 (b) (9) (10) : radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300
0.490~1.705	24000/F(KHz)	20 log (uV/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Remark :1. Emission level in dBuV/m=20 log (uV/m)

2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

3. For Frequency 9kHz~30MHz:

Distance extrapolation factor =40log(Specific distance/ test distance)(dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor.

For Frequency above 30MHz:

Distance extrapolation factor =20log(Specific distance/ test distance)(dB);


Limit line=Specific limits(dBuV) + distance extrapolation factor.

3.2.3 MEASURING INSTRUMENTS


The Measuring equipment is listed in the section 6.3 of this test report.

3.2.4 TEST CONFIGURATION


(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



3.2.5 TEST PROCEDURE

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.

Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 1MHz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	1 MHz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW [kHz]})$. , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

3.2.6 TEST RESULTS (9KHz – 30 MHz)

EUT:	Digital Calendar for Family Schedules	Model Name. :	JT215M-H01
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 12V
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	N/A
--	--	--	--	N/A

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


3.2.7 TEST RESULTS (30MHz – 1GHz)

EUT :	Digital Calendar for Family Schedules	Model Name. :	JT215M-H01
Temperature :	25.2℃	Relative Humidity :	52%
Pressure :	1010 hPa	Test Voltage :	DC 12V from Adapter AC 120V/60Hz
Test Mode :	TX(5.2G)- 802.11ac20 (Mid CH)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	39.5756	16.67	18.54	35.21	40.00	-4.79	QP
V	49.5328	10.72	19.73	30.45	40.00	-9.55	QP
V	71.8320	11.96	15.36	27.32	40.00	-12.68	QP
V	172.5987	21.77	15.61	37.38	43.50	-6.12	QP
V	203.5226	13.23	18.12	31.35	43.50	-12.15	QP
V	473.8346	9.95	24.13	34.08	46.00	-11.92	QP

Remark:


Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	63.5356	9.72	18.30	28.02	40.00	-11.98	QP
H	144.3345	12.40	14.49	26.89	43.50	-16.61	QP
H	162.6105	18.81	15.13	33.94	43.50	-9.56	QP
H	282.9850	18.50	20.06	38.56	46.00	-7.44	QP
H	473.8346	16.61	24.13	40.74	46.00	-5.26	QP
H	677.5797	11.04	27.93	38.97	46.00	-7.03	QP

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Note(1) "802.11ac20" mode is the worst mode.


(2) Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

EUT :	Digital Calendar for Family Schedules	Model Name. :	JT215M-H01
Temperature :	25.5℃	Relative Humidity :	52%
Pressure :	1010 hPa	Test Voltage :	DC 12V from Adapter AC 120V/60Hz
Test Mode :	TX(5.8G)- 802.11a (Mid CH)		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	39.5756	16.67	18.54	35.21	40.00	-4.79	QP
V	59.6492	11.39	18.88	30.27	40.00	-9.73	QP
V	90.5374	12.79	16.04	28.83	43.50	-14.67	QP
V	172.5987	21.77	15.61	37.38	43.50	-6.12	QP
V	473.8346	9.95	24.13	34.08	46.00	-11.92	QP
V	595.1326	9.58	26.15	35.73	46.00	-10.27	QP

Remark:


Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	48.5015	7.35	19.72	27.07	40.00	-12.93	QP
H	203.5226	15.56	18.12	33.68	43.50	-9.82	QP
H	271.3245	19.94	19.81	39.75	46.00	-6.25	QP
H	322.1884	16.40	20.93	37.33	46.00	-8.67	QP
H	473.8346	14.11	24.13	38.24	46.00	-7.76	QP
H	881.4067	8.49	30.81	39.30	46.00	-6.70	QP

Remark:

Emission Level = Meter Reading + Factor, Margin= Emission Level - Limit



Note(1) "802.11a" mode is the worst mode.

(2) Other emissions are attenuated more than 20dB below the permissible limits, so it does not recorded in the report.

3.2.8 TEST RESULTS (1GHz-18GHz)

EUT :	Digital Calendar for Family Schedules	Model Name. :	JT215M-H01
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 12V
Test Mode :	TX(5.2G) - 802.11ac20_5180~5240MHz		

Polar	Frequency	Meter Reading	Cable loss	Antenna Factor	Preamplifier Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	dB/m	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G									
Vertical	3015.641	62.09	5.94	35.40	44.00	59.43	68.2	-8.77	Pk
Vertical	10360	58.28	8.46	39.75	44.50	61.99	68.2	-6.21	Pk
Vertical	15540	60.24	10.12	38.80	44.10	65.06	74	-8.94	Pk
Vertical	15540	41.12	10.12	38.80	42.70	47.34	54	-6.66	AV
Horizontal	2981.465	61.96	5.94	35.18	44.00	59.08	68.2	-9.12	Pk
Horizontal	10360	59.82	8.46	38.71	44.50	62.49	68.2	-5.71	Pk
Horizontal	15540	58.44	10.12	38.38	44.10	62.84	74	-11.16	Pk
Horizontal	15540	38.32	10.12	38.38	44.10	42.72	54	-11.28	AV
middle Channel (5200 MHz)-Above 1G									
Vertical	3561.142	62.35	6.48	36.35	44.05	61.13	68.2	-7.07	Pk
Vertical	10400	60.36	8.47	37.88	44.51	62.20	68.2	-6.00	Pk
Vertical	15600	57.64	10.12	38.8	44.1	62.46	74	-11.54	Pk
Vertical	15600	40.93	10.12	38.8	42.7	47.15	54	-6.85	AV
Horizontal	3362.681	60.92	6.48	36.37	44.05	59.72	68.2	-8.48	Pk
Horizontal	10400	59.26	8.47	38.64	44.5	61.87	68.2	-6.33	Pk
Horizontal	15600	58.75	10.12	38.38	44.1	63.15	74	-10.85	Pk
Horizontal	15600	42.61	10.12	38.38	44.1	47.01	54	-6.99	AV
High Channel (5240 MHz)-Above 1G									
Vertical	3926.214	61.97	7.1	37.24	43.5	62.81	74	-11.19	Pk
Vertical	3926.214	43.82	7.1	37.24	43.5	44.66	54	-9.34	AV
Vertical	10480	59.92	8.46	37.68	44.5	61.56	68.2	-6.64	Pk
Vertical	15720	56.78	10.12	38.8	44.1	61.60	74	-12.40	Pk
Vertical	15720	33.34	10.12	38.8	42.7	39.56	54	-14.44	AV
Horizontal	3884.752	64.57	7.1	37.24	43.5	65.41	74	-8.59	Pk
Horizontal	3884.752	39.79	7.1	37.24	43.5	40.63	54	-13.37	AV
Horizontal	10480	58.23	8.46	38.57	44.5	60.76	68.2	-7.44	Pk
Horizontal	15720	58.86	10.12	38.38	44.1	63.26	74	-10.74	Pk
Horizontal	15720	38.78	10.12	38.38	44.1	43.18	54	-10.82	AV

Note: "802.11 ac20" mode is the worst mode.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported. Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamplifier Factor = Level.

EUT :	Digital Calendar for Family Schedules	Model Name. :	JT215M-H01
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 12V
Test Mode :	TX (5.8G) -- 802.11a_5745~5825MHz		

Polar	Frequency	Meter Reading	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector Type
(H/V)	(MHz)	(dBuV)	(dB)	dB/m	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G									
Vertical	2806.81	61.33	5.94	35.40	44.00	58.67	74.00	-15.33	Pk
Vertical	2806.81	42.89	5.94	35.40	44.00	40.23	54.00	-13.77	AV
Vertical	11490.45	59.11	8.46	39.75	44.50	62.82	74.00	-11.18	Pk
Vertical	11490.45	40.08	8.46	39.75	44.50	43.79	54.00	-10.21	AV
Vertical	17235.53	54.65	10.12	38.80	44.10	59.47	68.20	-8.73	Pk
Horizontal	2911.312	60.41	5.94	35.18	44.00	57.53	68.20	-10.67	Pk
Horizontal	11490.35	59.12	8.46	38.71	44.50	61.79	74.00	-12.21	Pk
Horizontal	11490.35	37.16	8.46	38.71	44.50	39.83	54.00	-14.17	AV
Horizontal	17235.49	56.09	10.12	38.38	44.10	60.49	68.20	-7.71	Pk
middle Channel (5785 MHz)-Above 1G									
Vertical	3763.537	58.07	6.48	36.35	44.05	56.85	74.00	-17.15	Pk
Vertical	3763.537	37.46	6.48	36.35	44.05	36.24	54.00	-17.76	AV
Vertical	11570.47	58.82	8.47	37.88	44.51	60.66	74.00	-13.34	Pk
Vertical	11570.47	40.23	8.47	37.88	44.51	42.07	54.00	-11.93	AV
Vertical	17355.46	54.08	10.12	38.8	44.10	58.90	68.20	-9.30	Pk
Horizontal	3561.542	56.86	6.48	36.37	44.05	55.66	68.20	-12.54	Pk
Horizontal	11570.45	54.98	8.47	38.64	44.50	57.59	74.00	-16.41	Pk
Horizontal	11570.45	39.02	8.47	38.64	44.50	41.63	54.00	-12.37	AV
Horizontal	17355.34	59.28	10.12	38.38	44.10	63.68	74.00	-10.32	Pk
Horizontal	17355.34	39.08	10.12	38.38	44.10	43.48	54.00	-10.52	AV

High Channel (5825 MHz)-Above 1G									
Vertical	3907.275	56.11	7.10	37.24	43.50	56.95	74.00	-17.05	Pk
Vertical	3907.275	39.14	7.10	37.24	43.50	39.98	54.00	-14.02	AV
Vertical	11650.45	56.37	8.46	37.68	44.50	58.01	74.00	-15.99	Pk
Vertical	11650.45	38.70	8.46	37.68	44.50	40.34	54.00	-13.66	AV
Vertical	17475.40	54.62	10.12	38.8	44.10	59.44	68.20	-8.76	Pk
Horizontal	3912.748	56.28	7.10	37.24	43.50	57.12	74.00	-16.88	Pk
Horizontal	3912.748	39.62	7.10	37.24	43.50	40.46	54.00	-13.54	AV
Horizontal	11650.46	58.56	8.46	38.57	44.50	61.09	74.00	-12.91	Pk
Horizontal	11650.46	38.91	8.46	38.57	44.50	41.44	54.00	-12.56	AV
Horizontal	17475.38	55.28	10.12	38.38	44.10	59.68	68.20	-8.52	Pk

Note:"802.11a" mode is the worst mode.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


3.2.9 TEST RESULTS (18GHz-40GHz)

EUT :	Digital Calendar for Family Schedules	Model Name. :	JT215M-H01
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 12V
Test Mode :	TX (5.2G)-802.11ac20 5180MHz~5240MHz, TX (5.8G)-802.11a 5745MHz~5825MHz		

All the modulation modes have been tested, and the worst result was report as below:

Low Channel (5180 MHz)-Above 1G


Horizontal



Measurement Result:

Frequency MHz	Meter Reading dBuV	Cable loss dB	Antenna Factor dB/m	Preamp Factor dB	Emission Level dBuV/m	Limits dBuV/m	Margin dB	Detector Type
39769.68	38.32	20.09	44.07	43.48	59	68.2	9.2	Peak
39769.51	27.56	20.09	44.04	43.48	48.21	54	5.79	AVG


Vertical



Measurement Result:


Frequency MHz	Meter Reading dBuV	Cable loss dB	Antenna Factor dB/m	Preamp Factor dB	Emission Level dBuV/m	Limits dBuV/m	Margin dB	Detector Type
39769.12	39.2	20.09	44.07	43.48	59.88	68.2	8.32	Peak
39769.37	26.06	20.09	44.04	43.48	46.71	54	7.29	AVG

High Channel (5240 MHz)-Above 1G



Measurement Result:

Frequency MHz	Meter Reading dBuV	Cable loss dB	Antenna Factor dB/m	Preamplifier Factor dB	Emission Level dBuV/m	Limits dBuV/m	Margin dB	Detector Type
35769.27	38.14	19.11	42.73	44.61	55.37	68.2	12.83	Peak
35769.13	27.89	19.11	42.73	44.61	45.12	54	8.88	AVG




Measurement Result:

Frequency MHz	Meter Reading dBuV	Cable loss dB	Antenna Factor dB/m	Preamplifier Factor dB	Emission Level dBuV/m	Limits dBuV/m	Margin dB	Detector Type
39769.21	40.99	20.09	44.07	43.48	61.67	68.2	6.53	Peak
39769.53	27.5	20.09	44.04	43.48	48.15	54	5.85	AVG

Low Channel (5745 MHz)-Above 1G


Horizontal



Measurement Result:

Frequency MHz	Meter Reading dBuV	Cable loss dB	Antenna Factor dB/m	Preamplifier Factor dB	Emission Level dBuV/m	Limits dBuV/m	Margin dB	Detector Type
39670.45	38.21	20.09	44.16	43.48	58.98	68.2	9.22	Peak
39670.12	27.63	20.09	44.16	43.48	48.4	54	5.6	AVG

Vertical




Measurement Result:

Frequency MHz	Meter Reading dBuV	Cable loss dB	Antenna Factor dB/m	Preamplifier Factor dB	Emission Level dBuV/m	Limits dBuV/m	Margin dB	Detector Type
39731.48	39.59	20.06	44.07	43.21	60.51	68.2	7.69	Peak
39731.71	28.02	20.06	44.07	43.21	48.94	54	5.06	AVG

High Channel (5825 MHz)-Above 1G


Horizontal



Measurement Result:

Frequency MHz	Meter Reading dBuV	Cable loss dB	Antenna Factor dB/m	Preamplifier Factor dB	Emission Level dBuV/m	Limits dBuV/m	Margin dB	Detector Type
39680.73	38.63	19.11	42.63	43.48	56.89	68.2	11.31	Peak
39680.47	26.38	19.12	42.63	43.48	44.65	54	9.35	AVG

Vertical



Measurement Result:

Frequency MHz	Meter Reading dBuV	Cable loss dB	Antenna Factor dB/m	Preamplifier Factor dB	Emission Level dBuV/m	Limits dBuV/m	Margin dB	Detector Type
39822.75	40.08	20.1	44.1	43.22	61.06	68.2	7.14	Peak
39822.12	29	20.1	44.1	43.22	49.98	54	4.02	AVG

3.2.10 Spurious Emission in Restricted Band 4.5GHz~5.150 GHz& 5.350GHz~5460GHz

EUT :	Digital Calendar for Family Schedules	Model Name. :	JT215M-H01
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 12V
Test Mode :	TX (5.2G)-802.11ac20 5150MHz~5250MHz,		

All the modulation modes have been tested, The report just record the worst data mode.

Frequen cy	Meter Reading	Cable Loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detec tor	Comment
(MHz)	(dBμV)	(dB)	dB/m	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
5.2G WIFI-802.11 ac20 Mode									
4500	62.60	5.2	35.6	44.2	59.20	74	-14.80	Pk	Horizontal
4500	44.51	5.2	35.6	44.2	41.11	54	-12.89	AV	Horizontal
4500	54.27	5.2	35.6	44.2	50.87	74	-23.13	Pk	Horizontal
4500	38.81	5.2	35.6	44.2	35.41	54	-18.59	AV	Horizontal
5150	69.97	5.36	35.66	44.22	66.77	74	-7.23	Pk	Horizontal
5150	51.58	5.36	35.66	44.22	48.38	54	-5.62	AV	Horizontal
5150	69.03	5.36	35.66	44.22	65.83	74	-8.17	Pk	Vertical
5150	50.30	5.36	35.66	44.22	47.10	54	-6.90	AV	Vertical
5350	63.13	5.68	35.68	44.22	60.27	74	-13.73	Pk	Vertical
5350	41.35	5.68	35.68	44.22	38.49	54	-15.51	AV	Vertical
5350	54.10	5.68	35.68	44.22	51.24	74	-22.76	Pk	Horizontal
5350	40.17	5.68	35.68	44.22	37.31	54	-16.69	AV	Horizontal

Note: (1) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor

(2) "802.11ac20" mode is the worst mode. When PK value is lower than the Average value limit, average don't record.

3.3 POWER SPECTRAL DENSITY TEST

3.3.1 Applied procedures / limit

According to FCC §15.407(a)(3)

For the band 5.15-5.25 GHz,

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz

(3) For the band 5.725-5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

,

3.3.2 TEST PROCEDURE

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:

- a) Set $RBW \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $VBW \geq 3 RBW$.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/RBW)$ to the measured result, whereas $RBW (< 500 \text{ KHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1\text{MHz}/RBW)$ to the measured result, whereas $RBW (< 1 \text{ MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 KHz for the sections 5.c) and 5.d) above, since $RBW=100 \text{ KHz}$ is available on nearly all spectrum analyzers.

3.3.3 DEVIATION FROM STANDARD

No deviation.

3.3.4 TEST SETUP



3.3.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

3.3.6 TEST RESULTS

EUT :	Digital Calendar for Family Schedules	Model Name. :	JT215M-H01
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1015 hPa	Test Voltage :	DC 12V
Test Mode :	TX Frequency Band I (5150-5250MHz), Band IV (5725-5850MHz)		

Test data reference attachment.

3.4 26DB & 99% EMISSION BANDWIDTH

3.4.1 Applied procedures / limit


The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

3.4.2 TEST PROCEDURE

- a) Set RBW = approximately 1% of the emission bandwidth.
- b) Set the VBW > RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW $\geq 3 \cdot$ RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.



3.4.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.4.4 TEST RESULTS

EUT :	Digital Calendar for Family Schedules	Model Name. :	JT215M-H01
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 12V
Test Mode :	TX Frequency Band I (5150-5250MHz), Band IV (5725-5850MHz)		

Test data reference attachment.

3.5 MINIMUM 6 DB BANDWIDTH

3.5.1 Applied procedures / limit

According to FCC §15.407(e)

(e) Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

3.5.2 TEST PROCEDURE


Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

3.5.3 DEVIATION FROM STANDARD

No deviation.

3.5.4 TEST SETUP



3.5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.5.6 TEST RESULTS

EUT :	Digital Calendar for Family Schedules	Model Name. :	JT215M-H01
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 12V
Test Mode :	TX (5G) Mode Frequency Band IV (5725-5850MHz)		

Test data reference attachment.

3.6 MAXIMUM CONDUCTED OUTPUT POWER

3.6.1 PPLIED PROCEDURES / LIMIT

According to FCC §15.407

The maximum conducted output power should not exceed:

Frequency Band(MHz)	Limit
5150~5250	250mW
5725~5850	1W

3.6.2 TEST PROCEDURE


Method SA-3 uses rms detection with max hold. The procedure for this method is as follows:

- Set span to encompass the entire 26 dB EBW or 99% OBW of the signal.
- Set sweep trigger to "free run."
- Set RBW = 1 MHz.
- Set VBW $\geq$ 3 MHz
- Number of points in sweep $\geq$ $[2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\leq$ RBW / 2, so that narrowband signals are not lost between frequency bins.)
- Sweep time $\leq$ $[(\text{number of points in sweep}) \times T]$, where T is defined in 12.2. If this gives a sweep time less than the auto sweep time of the instrument, then method SA-3A shall not be used. (The purpose of this step is so that averaging time in each bin is less than or equal to the minimum time of a transmission.)
- Detector = RMS (power averaging).
- Trace mode = max hold.
- Allow max hold to run for at least 60 s or longer as needed to allow the trace to stabilize.
- Compute power by integrating the spectrum across the 26 dB EBW or 99% OBW of the signal using the instrument's band power measurement function with band limits set equal to the EBW or OBW band edges. If the instrument does not have a band power function, then sum the spectrum levels (in power units) at 1 MHz intervals extending across the 26 dB EBW of the spectrum.

3.6.3 DEVIATION FROM STANDARD

No deviation.

3.6.4 TEST SETUP



3.6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.6.6 TEST RESULTS

EUT :	Digital Calendar for Family Schedules	Model Name. :	JT215M-H01
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 12V
Test Mode :	TX (5G) Mode Frequency Band I (5150-5250MHz), Band IV (5725-5850MHz)		

Test data reference attachment.

3.7 OUT OF BAND EMISSIONS

3.7.1 Applicable Standard

According to FCC §15.407(b)

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.


3.7.2 Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

3.7.3 DEVIATION FROM STANDARD

No deviation.

3.7.4 TEST SETUP



3.7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.7.6 TEST RESULTS

EUT :	Digital Calendar for Family Schedules	Model Name. :	JT215M-H01
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 12V

Test data reference attachment.

3.8 SPURIOUS RF CONDUCTED EMISSIONS

3.8.1 Conformance Limit

According to FCC §15.407(b)(1)(4)

3.8.2 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

3.8.3 Test Setup

Please refer to Section 6.1 of this test report.

3.8.4 Test Procedure

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=1MHz and VBW= 3MHz to measure the peak field strength , and measure frequency range from 30MHz to 40GHz.

3.8.5 Test Results

Remark: The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and band edge measurement data.

Test data reference attachment.

3.9 FREQUENCY STABILITY MEASUREMENT


3.9.1 LIMIT

Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

3.9.2 TEST PROCEDURES

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5. f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f)/f_c \times 10^6 \text{ ppm}$.
6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
7. Extreme temperature is $-20^\circ\text{C} \sim 70^\circ\text{C}$.

3.9.3 TEST SETUP LAYOUT



3.9.4 EUT OPERATION DURING TEST

The EUT was programmed to be in continuously un-modulation transmitting mode.

3.9.5 TEST RESULTS

EUT :	Digital Calendar for Family Schedules	Model Name. :	JT215M-H01
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 12V
Test Mode :	TX Frequency Band I (5150-5250MHz)		

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5180MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	12.00	5180.0013	5180	0.0013	0.2566
		V max (V)	13.20	5180.0017	5180	0.0017	0.3218
		V min (V)	10.80	5180.0007	5180	0.0007	0.1414
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5180MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	12	T (°C)	-20	5180.0015	5180	0.0015	0.2881
		T (°C)	-10	5180.0014	5180	0.0014	0.2661
		T (°C)	0	5180.0014	5180	0.0014	0.2776
		T (°C)	10	5180.0012	5180	0.0012	0.2319
		T (°C)	20	5180.0006	5180	0.0006	0.1157
		T (°C)	30	5180.0005	5180	0.0005	0.0873
		T (°C)	40	5180.0011	5180	0.0011	0.2056
		T (°C)	50	5180.0005	5180	0.0005	0.1044
		T (°C)	60	5180.0018	5180	0.0018	0.3480
		T (°C)	70	5180.0007	5180	0.0007	0.1290
Limits				Within 5150-5250MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5200MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	12.00	5200.0018	5200	0.0018	0.3530
		V max (V)	13.20	5200.0016	5200	0.0016	0.3003
		V min (V)	10.80	5200.0014	5200	0.0014	0.2709
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5200MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	12	T (°C)	-20	5200.0020	5200	0.0020	0.3816
		T (°C)	-10	5200.0005	5200	0.0005	0.0915
		T (°C)	0	5200.0011	5200	0.0011	0.2155
		T (°C)	10	5200.0012	5200	0.0012	0.2353
		T (°C)	20	5200.0018	5200	0.0018	0.3438
		T (°C)	30	5200.0016	5200	0.0016	0.3052
		T (°C)	40	5200.0008	5200	0.0008	0.1544
		T (°C)	50	5200.0015	5200	0.0015	0.2889
		T (°C)	60	5200.0020	5200	0.0020	0.3766
		T (°C)	70	5200.0016	5200	0.0016	0.3171
Limits				Within 5150-5250MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5240MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	12.00	5240.0016	5240	0.0016	0.3095
		V max (V)	13.20	5240.0013	5240	0.0013	0.2497
		V min (V)	10.80	5240.0002	5240	0.0002	0.0417
Limits				Within 5150-5250MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5240MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	12	T (°C)	-20	5240.0002	5240	0.0002	0.0431
		T (°C)	-10	5240.0017	5240	0.0017	0.3293
		T (°C)	0	5240.0006	5240	0.0006	0.1167
		T (°C)	10	5240.0014	5240	0.0014	0.2704
		T (°C)	20	5240.0007	5240	0.0007	0.1325
		T (°C)	30	5240.0009	5240	0.0009	0.1639
		T (°C)	40	5240.0007	5240	0.0007	0.1392
		T (°C)	50	5240.0009	5240	0.0009	0.1654
		T (°C)	60	5240.0010	5240	0.0010	0.1899
		T (°C)	70	5240.0010	5240	0.0010	0.1881
Limits				Within 5150-5250MHz			
Result				Complies			

EUT :	Digital Calendar for Family Schedules	Model Name. :	JT215M-H01
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 12V
Test Mode :	TX Frequency(5745-5825MHz)		

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	12.00	5745.0008	5745	0.0008	0.1355
		V max (V)	13.20	5745.0013	5745	0.0013	0.2270
		V min (V)	10.80	5745.0019	5745	0.0019	0.3385
Limits				Within 5745-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	12	T (°C)	-20	5745.0019	5745	0.0019	0.3340
		T (°C)	-10	5745.0003	5745	0.0003	0.0443
		T (°C)	0	5745.0012	5745	0.0012	0.2168
		T (°C)	10	5745.0018	5745	0.0018	0.3057
		T (°C)	20	5745.0019	5745	0.0019	0.3242
		T (°C)	30	5745.0019	5745	0.0019	0.3231
		T (°C)	40	5745.0013	5745	0.0013	0.2305
		T (°C)	50	5745.0003	5745	0.0003	0.0498
		T (°C)	60	5745.0008	5745	0.0008	0.1345
		T (°C)	70	5745.0002	5745	0.0002	0.0431
Limits				Within 5745-5850MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	12.00	5785.0015	5785	0.00148	-0.2562
		V max (V)	13.20	5785.0001	5785	0.00012	-0.0208
		V min (V)	10.80	5785.0008	5785	0.00085	-0.1466
Limits				Within 5745-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	12	T (°C)	-20	5785.0003	5785	0.0003	0.0510
		T (°C)	-10	5785.0010	5785	0.0010	0.1654
		T (°C)	0	5785.0001	5785	0.0001	0.0173
		T (°C)	10	5785.0016	5785	0.0016	0.2742
		T (°C)	20	5785.0005	5785	0.0005	0.0834
		T (°C)	30	5785.0008	5785	0.0008	0.1442
		T (°C)	40	5785.0004	5785	0.0004	0.0621
		T (°C)	50	5785.0005	5785	0.0005	0.0908
		T (°C)	60	5785.0012	5785	0.0012	0.2152
		T (°C)	70	5785.0000	5785	0.0000	0.0052
Limits				Within 5745-5850MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	12.00	5825.0006	5825	0.0006	0.1011
		V max (V)	13.20	5825.0015	5825	0.0015	0.2518
		V min (V)	10.80	5825.0003	5825	0.0003	0.0469
Limits				Within 5745-5850MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	12	T (°C)	-20	5825.0007	5825	0.0007	0.1129
		T (°C)	-10	5825.0012	5825	0.0012	0.2100
		T (°C)	0	5825.0005	5825	0.0005	0.0809
		T (°C)	10	5825.0015	5825	0.0015	0.2508
		T (°C)	20	5825.0011	5825	0.0011	0.1830
		T (°C)	30	5825.0011	5825	0.0011	0.1841
		T (°C)	40	5825.0013	5825	0.0013	0.2255
		T (°C)	50	5825.0004	5825	0.0004	0.0713
		T (°C)	60	5825.0010	5825	0.0010	0.1781
		T (°C)	70	5825.0005	5825	0.0005	0.0844
Limits				Within 5745-5850MHz			
Result				Complies			

4. ANTENNA REQUIREMENT

4.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

4.2 EUT ANTENNA

The EUT antenna is permanent attached PCB antenna (antenna gain: band I : 3.68dBi; band IV: 3.68dBi;). It comply with the standard requirement.

END OF REPORT