

Radio Test Report

Report No.:STS2410067H01

Issued for

SQi-AndiX

Na Dlouhem lanu 19/3, Prague, 16000, Czech Republic

Product Name: AndiScan

Brand Name: SQi-AndiX

Model Name: A3

Series Model(s): N/A

FCC ID: 2BLHR-ASA3

Test Standards: FCC 47CFR §2.1091

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.



TEST REPORT

Applicant's Name : SQi-AndiX

Address : Na Dlouhem lanu 19/3, Prague, 16000, Czech Republic

Manufacturer's Name : SQi-AndiX

Address : Na Dlouhem lanu 19/3, Prague, 16000, Czech Republic

Product Description

Product Name : AndiScan

Brand : SQi-AndiX

Model Number : A3

Series Model(s) : N/A

Standards : FCC 47CFR §2.1091
447498 D04 Interim General RF Exposure Guidance v01

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

Date of Test

Date of receipt of test item : 11 Oct. 2024


Date (s) of performance of tests : 11 Oct. 2024~01 Nov. 2024

Date of Issue : 01 Nov. 2024


Test Result : **Pass**

Testing Engineer : 

(Aaron Bu)

Technical Manager : 

(Tony Liu)

Authorized Signatory : 

(Bovey Yang)





TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF THE EUT	5
1.2 TEST FACTORY	5
2. FCC 47CFR §2.1091 REQUIREMENT	6
2.1 TEST STANDARDS	6
2.2 LIMIT	6
2.3 TEST RESULT	9

**Revision History**

Rev.	Issue Date	Report No.	Effect Page	Contents
00	01 Nov. 2024	STS2410067H01	ALL	Initial Issue



1. GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF THE EUT

Product Name	AndiScan									
Brand	SQi-AndiX									
Model Number	A3									
Series Model(s)	N/A									
Model Difference	N/A									
Product Description	<p>The EUT is AndiScan</p> <table border="1"><tr><td>Operation Frequency:</td><td>BLE:2402-2480MHz BT:2402-2480MHz 2.4G WIFI: 802.11b/g/n 20: 2412~2462 MHz 802.11n(40MHz):2422~2452MHz FDS:24.09 – 24.16 GHz</td></tr><tr><td>Modulation Type:</td><td>BLE:GFSK BT: GFSK(1Mbps), π/4-DQPSK(2Mbps), 8DPSK(3Mbps) 2.4G WIFI: 802.11b(DSSS):CCK,DQPSK,DBPSK 802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM FDS:CW Doppler radar - 24 GHz</td></tr><tr><td>Antenna gain:</td><td>BLE: 3dBi BT: 3dBi 2.4G WIFI: 3dBi FDS:10dBi</td></tr><tr><td>Antenna Designation:</td><td>Internal Antenna</td></tr></table>		Operation Frequency:	BLE:2402-2480MHz BT:2402-2480MHz 2.4G WIFI: 802.11b/g/n 20: 2412~2462 MHz 802.11n(40MHz):2422~2452MHz FDS:24.09 – 24.16 GHz	Modulation Type:	BLE:GFSK BT: GFSK(1Mbps), π/4-DQPSK(2Mbps), 8DPSK(3Mbps) 2.4G WIFI: 802.11b(DSSS):CCK,DQPSK,DBPSK 802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM FDS:CW Doppler radar - 24 GHz	Antenna gain:	BLE: 3dBi BT: 3dBi 2.4G WIFI: 3dBi FDS:10dBi	Antenna Designation:	Internal Antenna
Operation Frequency:	BLE:2402-2480MHz BT:2402-2480MHz 2.4G WIFI: 802.11b/g/n 20: 2412~2462 MHz 802.11n(40MHz):2422~2452MHz FDS:24.09 – 24.16 GHz									
Modulation Type:	BLE:GFSK BT: GFSK(1Mbps), π/4-DQPSK(2Mbps), 8DPSK(3Mbps) 2.4G WIFI: 802.11b(DSSS):CCK,DQPSK,DBPSK 802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM FDS:CW Doppler radar - 24 GHz									
Antenna gain:	BLE: 3dBi BT: 3dBi 2.4G WIFI: 3dBi FDS:10dBi									
Antenna Designation:	Internal Antenna									
Adapter	Input: DC 5V, 1A(max)									
Battery	Rated Voltage: 3.7V Charge Limit Voltage: 4.2V Capacity: 1200mAh									
Hardware Version	A3.1.0									
Software Version	A3.1.2									

1.2 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : 101, Building B, Zhuoke Science Park, No.190 Chongqing Road, ZhanChengShequ, Fuhai Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01



2. FCC 47CFR §2.1091 REQUIREMENT

2.1 TEST STANDARDS

Follow the maximum permissible exposure (MPE) limits specified in 447498 D04 Interim General Radio Frequency Exposure Guidelines v01. The gain of the antenna used in the product was extracted from the supplied antenna data sheet and the maximum total power input to the antenna was also measured. Calculate the distance from the product to the MPE limit by the formula.

2.2 LIMIT

For single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if:

(A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of Part 1.1307. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

(B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);



(C) Or using below table and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

RF Source frequency (MHz)	Threshold ERP(watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2f$.
1,500-100,000	$19.2R^2$.



For multiple RF sources: Multiple RF sources are exempt if:

(A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of Part 1.1307. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).

(B) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of Part 1.1307 for $P_{th,i}$, including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of Part 1.1307 for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

$P_{th,i}$ = the exemption threshold power ($P_{th,i}$) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i .

ERP_j = the ERP of fixed, mobile, or portable RF source j .

$ERP_{th,j}$ = exemption threshold ERP for fixed, mobile, or portable RF source j , at a distance of at least $\lambda/2\pi$ according to the applicable formula of paragraph (b)(3)(i)(C) of Part 1.1307.

$Evaluated_k$ = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

$Exposure\ Limit_k$ = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k , as applicable from § 1.1310.



2.3 TEST RESULT

Turn up

Mode	Detector	Power (dBuV/m) @3m	Power (dBm)	Turn up Power
24G	PK	108.18	12.98	12±1dBm

Note: Power (dBm) = dBuV/m@3m -95.2

Mode	Detector	Turn up Power
BLE	PK	11±1dBm
BT	PK	15±1dBm
2.4G WIFI	AV	19±1dBm

Protocol	Fre. (GHz)	Separation distance (cm)	EIRP (dBm)	ERP (dBm)	ERP (W)	Limit (W)	Ratio	Result
24G	24.09	20	12.98	10.83	0.012	0.768	0.0158	Pass
BLE	2.48	20	14.959	12.91	0.019	0.768	0.0249	Pass
BT	2.48	20	18.279	16.13	0.041	0.768	0.0534	Pass
2.4G WIFI	2.412	20	22.04	19.89	0.097	0.768	0.1270	Pass

Multiple transmission:

24G+2.4G WLAN =0.0158+0.127=0.143 < 1

Antenna gain:

BT/BLE/2.4G WIFI: 3dBi

24G:10dBi

Note: 1. The Maximum power is less than the limit, complies with the exemption requirements.

2. The Bluetooth and 2.4G WLAN can't simultaneous transmission at the same time.
3. ERP=EIRP-2.15

※※※※ END OF THE REPORT ※※※※