



## FCC TEST REPORT

### FCC ID:2BLL9-CAROBD

Report Number..... : ZKT-241008L12724E

Date of Test..... Sep. 24, 2024 to Oct. 15, 2024

Date of issue ..... : Oct. 15, 2024

Total number of pages ..... 30

Test Result ..... : PASS

Testing Laboratory..... : Shenzhen ZKT Technology Co., Ltd.

Address ..... : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name ..... : SPIRESH TECH INC.

Address ..... : 222 Queen Street, 1000 Ottawa, Ontario K1P 5V9 Canada

Manufacturer's name ..... : Shenzhen Chaoyue Technology Development Co.,Ltd.

Address ..... : Building C, Zhiyun Industrial Park, Dalang Street, Longhua District, Shenzhen

Test specification:

Standard..... : FCC CFR Title 47 Part 15 Subpart C Section 15.249  
ANSI C63.10:2013

Test procedure ..... : /

Non-standard test method ..... : N/A

**Test Report Form No.** ..... : TRF-EL-111\_V0

**Test Report Form(s) Originator** ..... : ZKT Testing

**Master TRF** ..... : Dated: 2022-02-17

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name ..... : Car OBD2 Scanner

Trademark ..... : VEEPEAK

Model/Type reference ..... : OBDCheck BLE+

Battery ..... : N/A

Ratings ..... : DC 9-16V



Testing procedure and testing location:

Testing Laboratory .....: Shenzhen ZKT Technology Co., Ltd.

Address .....: 1/F, No. 101, Building B, No. 6, Tangwei Community  
Industrial Avenue, Fuhai Street, Bao'an District,  
Shenzhen, China

Tested by (name + signature) .....: Alen He 

Reviewer (name + signature).....: Joe Liu 

Approved (name + signature) .....: Lake Xie   




Table of Contents

	Page
<b>1. VERSION</b>	<b>5</b>
<b>2.1 SUMMARY OF TEST RESULTS</b>	<b>6</b>
<b>2.11.1 TEST FACILITY</b>	<b>7</b>
<b>2.21.2 MEASUREMENT UNCERTAINTY</b>	<b>7</b>
<b>3. GENERAL INFORMATION</b>	<b>8</b>
<b>3.1 GENERAL DESCRIPTION OF EUT</b>	<b>8</b>
<b>3.2 1.1 DESCRIPTION OF TEST MODES</b>	<b>9</b>
<b>3.3 1.2 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED</b>	<b>9</b>
<b>3.4 1.3 DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE)</b>	<b>10</b>
<b>3.5 1.4 EQUIPMENTS LIST FOR ALL TEST ITEMS</b>	<b>11</b>
<b>4. EMC EMISSION TEST</b>	<b>12</b>
<b>4.1 1.5 CONDUCTED EMISSION MEASUREMENT</b>	<b>12</b>
<b>4.1.1 1.5.1 POWER LINE CONDUCTED EMISSION LIMITS</b>	<b>12</b>
<b>4.1.2 1.5.2 TEST PROCEDURE</b>	<b>12</b>
<b>4.1.3 1.5.3 DEVIATION FROM TEST STANDARD</b>	<b>12</b>
<b>4.1.4 1.5.4 TEST SETUP</b>	<b>13</b>
<b>4.1.5 1.5.5 EUT OPERATING CONDITIONS</b>	<b>13</b>
<b>4.1.6 TEST RESULTS</b>	<b>13</b>
<b>4.2 1.6 RADIATED EMISSION MEASUREMENT</b>	<b>14</b>
<b>4.2.1 1.6.1 RADIATED EMISSION LIMITS</b>	<b>14</b>
<b>4.2.2 1.6.2 TEST PROCEDURE</b>	<b>15</b>
<b>4.2.3 1.6.3 DEVIATION FROM TEST STANDARD</b>	<b>15</b>
<b>4.2.4 1.6.4 TEST SETUP</b>	<b>15</b>
<b>4.2.5 1.6.5 EUT OPERATING CONDITIONS</b>	<b>16</b>
<b>5. BANDWIDTH OF FREQUENCY BAND EDGE</b>	<b>22</b>
<b>5.1 TEST REQUIREMENT:</b>	<b>22</b>
<b>5.2 TEST PROCEDURE</b>	<b>22</b>
<b>5.3 DEVIATION FROM TEST STANDARD</b>	<b>22</b>
<b>5.4 TEST SETUP</b>	<b>22</b>
<b>5.5 EUT OPERATING CONDITIONS</b>	<b>23</b>
<b>5.6 TEST RESULT</b>	<b>24</b>
<b>6. CHANNEL BANDWIDTH</b>	<b>26</b>
<b>7.1 APPLIED PROCEDURES / LIMIT</b>	<b>26</b>
<b>7.2 2.1 TEST PROCEDURE</b>	<b>26</b>
<b>7.3 2.2 DEVIATION FROM STANDARD</b>	<b>26</b>
<b>7.4 2.3 TEST SETUP</b>	<b>26</b>



Table of Contents

	Page
7.5 2.4EUT OPERATION CONDITIONS	26
7.6 2.5TEST RESULTS	27
9.ANTENNA REQUIREMENT	29
10. TEST SETUP PHOTO	30
11. EUT CONSTRUCTIONAL DETAILS	30



### 1.VERSION

Report No.	Version	Description	Approved
ZKT-241008L12724E	Rev.01	Initial issue of report	Oct. 15, 2024



## 2.1 SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.249) , Subpart C			
Standard Section	Test Item	Judgment	Remark
FCC part 15.203	Antenna requirement	PASS	
FCC part 15.207	AC Power Line Conducted Emission	N/A	
FCC part 15.249	Fundamental &Radiated Spurious Emission Measurement	PASS	
FCC part 15.215 (c)	20dB Channel Bandwidth	PASS	
FCC part 15.205	Band Edge	PASS	

### NOTE:

(1)" N/A" denotes test is not applicable in this Test Report



#### 2.11.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.

Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225

Designation Number: CN1299

IC Registered No.: 27033

#### 2.21.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$  , where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of  $k=2$  , providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power conducted	$\pm 0.16\text{dB}$
3	Spurious emissions conducted	$\pm 0.21\text{dB}$
4	All emissions radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^\circ\text{C}$
7	Humidity	$\pm 2\%$



### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

Product Name:	Car OBD2 Scanner
Model No.:	OBDCheck BLE+
Model Different.:	N/A
Serial No.:	N/A
Hardware Version:	HV1.0
Software Version:	SV1.0
Sample(s) Status:	Engineer sample
Operation Frequency:	2402MHz~2480MHz
Channel Numbers:	40
Channel Separation:	2MHz
Modulation Type:	GFSK
Antenna Type:	PCB Antenna
Antenna gain:	1.3dBi
Power supply:	DC9-16V
SWITCHING POWER ADAPTER:	N/A
Battery:	N/A



Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402 MHz	11	2422 MHz	21	2442 MHz	31	2462 MHz
2	2404 MHz	12	2424 MHz	22	2444 MHz	32	2464 MHz
3	2406 MHz	13	2426 MHz	23	2446 MHz	33	2466 MHz
4	2408 MHz	14	2428 MHz	24	2448 MHz	34	2468 MHz
5	2410 MHz	15	2430 MHz	25	2450 MHz	35	2470 MHz
6	2412 MHz	16	2432 MHz	26	2452 MHz	36	2472 MHz
7	2414 MHz	17	2434 MHz	27	2454 MHz	37	2474 MHz
8	2416 MHz	18	2436 MHz	28	2456 MHz	38	2476 MHz
9	2418 MHz	19	2438 MHz	29	2458 MHz	39	2478 MHz
10	2420 MHz	20	2440 MHz	30	2460 MHz	40	2480 MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:


Channel	Frequency
The lowest channel	2402MHz
The middle channel	2440MHz
The Highest channel	2480MHz

### 3.2 1.1DESCRIPTION OF TEST MODES

Transmitting mode	Keep the EUT in continuously transmitting mode
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

Test Software	BT Test Tool
Power level setup	<0dBm

### 3.3 1.2BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED





### 3.4 1.3DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Car OBD2 Scanner	VEEPEAK	CP801	N/A	EUT
E-2	Battery	N/A	DC12V		

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	0.2M	DC Line

#### Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



## 3.51.4 EQUIPMENTS LIST FOR ALL TEST ITEMS

## Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	9020A	MY55370835	A.17.05	Nov. 02, 2023	Nov. 01, 2024
2	Spectrum Analyzer (10kHz-39.9GHz)	R&S	FSV40-N	100363	1.71 SP2	Nov. 02, 2023	Nov. 01, 2024
3	EMI Test Receiver (9kHz-7GHz)	R&S	ESCI7	101169	4.32	Nov. 02, 2023	Nov. 01, 2024
4	Bilog Antenna (30MHz-1500MHz)	Schwarzbeck	VULB9168	N/A	N/A	Nov. 13, 2023	Nov. 12, 2024
5	Horn Antenna (1GHz-18GHz)	Agilent	AH-118	071145	N/A	Nov. 13, 2023	Nov. 12, 2024
6	Horn Antenna (15GHz-40GHz)	A.H.System	SAS-574	588	N/A	Nov. 13, 2023	Nov. 12, 2024
7	Loop Antenna	TESEQ	HLA6121	58357	N/A	Nov. 16, 2023	Nov. 15, 2024
8	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	060747	N/A	Nov. 02, 2023	Nov. 01, 2024
9	Amplifier (1GHz-26.5GHz)	Agilent	8449B	3008A00315	N/A	Nov. 02, 2023	Nov. 01, 2024
10	Amplifier (500MHz-40GHz)	QuanJuDa	DLE-161	097	N/A	Nov. 02, 2023	Nov. 01, 2024
11	Test Cable	N/A	R-01	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
12	Test Cable	N/A	R-02	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
13	Test Cable	N/A	R-03	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
14	D.C. Power Supply	LongWei	TPR-6405D	N/A	N/A	\	\
15	EMC Software	Frad	EZ-EMC	Ver.EMC-CO N 3A1.1	N/A	\	\
16	Turntable	MF	MF-7802BS	N/A	N/A	\	\
17	Antenna tower	MF	MF-7802BS	N/A	N/A	\	\

## Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Last calibration	Calibrated until
1	LISN	R&S	ENV216	101471	N/A	Nov. 14, 2023	Nov. 13, 2024
2	LISN	CYBERTEK	EM5040A	E1850400149	N/A	Nov. 02, 2023	Nov. 01, 2024
3	Test Cable	N/A	C-01	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
4	Test Cable	N/A	C-02	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
5	Test Cable	N/A	C-03	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
6	EMI Test Receiver	R&S	ESCI3	101393	4.42 SP3	Nov. 02, 2023	Nov. 01, 2024
7	Triple-Loop Antenna	N/A	RF300	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
8	Absorbing Clamp	DZ	ZN23201	15034	N/A	Nov. 07, 2023	Nov. 06, 2024
9	EMC Software	Frad	EZ-EMC	Ver.EMC-CON 3A1.1	N/A	\	\



#### 4. EMC EMISSION TEST

##### 4.1 1.5 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

###### 4.1.1 1.5.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quas -peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) \*Decreases with the logarithm of the frequency.

###### 4.1.2 1.5.2 TEST PROCEDURE


- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

###### 4.1.3 1.5.3 DEVIATION FROM TEST STANDARD

No deviation



#### 4.1.4 1.5.4 TEST SETUP



**Note:**

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

#### 4.1.5 1.5.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

#### 4.1.6 TEST RESULTS

N/A,

Remark: Because the EUT employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Measurements to demonstrate compliance with the conducted limits are not required for devices.



## 4.2 1.6 RADIATED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150 Hz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average

## 4.2.1 1.6.1 RADIATED EMISSION LIMITS

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

## LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

## Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.



- (2) The tighter limit applies at the band edges.
- (3) Emission level (dB<sub>UV</sub>/m)=20log Emission level (uV/m).

#### 4.2.2 1.6.2TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 25GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-chamber test. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8m; above 1GHz, the height was 1.5m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

##### g. For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

#### 4.2.3 1.6.3DEVIATION FROM TEST STANDARD


No deviation

#### 4.2.4 1.6.4TEST SETUP


##### (A) Radiated Emission Test-Up Frequency Below 30MHz



## (B) Radiated Emission Test-Up Frequency 30MHz~1GHz



## (C) Radiated Emission Test-Up Frequency Above 1GHz



## 4.2.5 1.6.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

## 4.2.6 TEST RESULTS (Between 9KHz – 30 MHz)

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.



2Between 30MHz – 1GHz


Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	DC12V		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)
1	74.657	31.34	-16.97	14.37	40.00	-25.63	QP	
2	150.011	33.30	-12.44	20.86	43.50	-22.64	QP	
3	175.037	39.27	-14.00	25.27	43.50	-18.23	QP	
4	225.308	40.91	-15.12	25.79	46.00	-20.21	QP	
5 *	389.355	39.82	-10.54	29.28	46.00	-16.72	QP	
6	454.310	37.88	-8.74	29.14	46.00	-16.86	QP	



Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	DC12V		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	74.657	36.89	-16.97	19.92	40.00	-20.08	QP
2	227.691	37.12	-14.96	22.16	46.00	-23.84	QP
3	275.157	40.93	-13.47	27.46	46.00	-18.54	QP
4	325.596	41.19	-11.96	29.23	46.00	-16.77	QP
5 *	374.623	42.97	-10.86	32.11	46.00	-13.89	QP
6	425.028	39.49	-9.53	29.96	46.00	-16.04	QP

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

2. The emission levels of other frequencies are very lower than the limit and not show in test report.



Field Strength of The Fundamental Signal

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	93.91	27.58	5.39	30.18	96.70	114.00	-17.30	Vertical
2402.00	93.24	27.58	5.39	30.18	96.03	114.00	-17.97	Horizontal
2440.00	92.06	27.55	5.43	30.06	94.98	114.00	-19.02	Vertical
2440.00	86.54	27.55	5.43	30.06	89.46	114.00	-24.54	Horizontal
2480.00	93.12	27.52	5.47	29.93	96.18	114.00	-17.82	Vertical
2480.00	89.97	27.52	5.47	29.93	93.03	114.00	-20.97	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	82.63	27.58	5.39	30.18	85.42	94.00	-8.58	Vertical
2402.00	80.82	27.58	5.39	30.18	83.61	94.00	-10.39	Horizontal
2440.00	79.76	27.55	5.43	30.06	82.68	94.00	-11.32	Vertical
2440.00	75.75	27.55	5.43	30.06	78.67	94.00	-15.33	Horizontal
2480.00	83.21	27.52	5.47	29.93	86.27	94.00	-7.73	Vertical
2480.00	80.17	27.52	5.47	29.93	83.23	94.00	-10.77	Horizontal



## 1GHz~25GHz

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	

## Low Channel:2402MHz

V	4804.00	52.46	30.55	5.77	24.66	52.34	74.00	-21.66	Pk
V	4804.00	42.32	30.55	5.77	24.66	42.20	54.00	-11.80	AV
V	7206.00	50.55	30.33	6.32	24.55	51.09	74.00	-22.91	Pk
V	7206.00	43.03	30.33	6.32	24.55	43.57	54.00	-10.43	AV
V	9608.00	51.05	30.85	7.45	24.69	52.34	74.00	-21.66	Pk
V	9608.00	42.93	30.85	7.45	24.69	44.22	54.00	-9.78	AV
V	12010.00	51.15	31.02	8.99	25.57	54.69	74.00	-19.31	Pk
V	12010.00	42.93	31.02	8.99	25.57	46.47	54.00	-7.53	AV
H	4804.00	52.80	30.55	5.77	24.66	52.68	74.00	-21.32	Pk
H	4804.00	42.65	30.55	5.77	24.66	42.53	54.00	-11.47	AV
H	7206.00	51.44	30.33	6.32	24.55	51.98	74.00	-22.02	Pk
H	7206.00	42.70	30.33	6.32	24.55	43.24	54.00	-10.76	AV
H	9608.00	51.44	30.85	7.45	24.69	52.73	74.00	-21.27	Pk
H	9608.00	42.70	30.85	7.45	24.69	43.99	54.00	-10.01	AV
H	12010.00	51.44	31.02	8.99	25.57	54.98	74.00	-19.02	Pk
H	12010.00	41.70	31.02	8.99	25.57	45.24	54.00	-8.76	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	

## Middle Channel:2440MHz

V	4880.00	52.08	30.55	5.77	24.66	51.96	74.00	-22.04	Pk
V	4880.00	42.97	30.55	5.77	24.66	42.85	54.00	-11.15	AV
V	7320.00	50.61	30.33	6.32	24.55	51.15	74.00	-22.85	Pk
V	7320.00	42.65	30.33	6.32	24.55	43.19	54.00	-10.81	AV
V	9760.00	50.68	30.85	7.45	24.69	51.97	74.00	-22.03	Pk
V	9760.00	42.65	30.85	7.45	24.69	43.94	54.00	-10.06	AV
V	12200.00	50.58	31.02	8.99	25.57	54.12	74.00	-19.88	Pk
V	12200.00	42.65	31.02	8.99	25.57	46.19	54.00	-7.81	AV
H	4880.00	53.44	30.55	5.77	24.66	53.32	74.00	-20.68	Pk
H	4880.00	43.00	30.55	5.77	24.66	42.88	54.00	-11.12	AV
H	7320.00	54.15	30.33	6.32	24.55	54.69	74.00	-19.31	Pk
H	7320.00	42.78	30.33	6.32	24.55	43.32	54.00	-10.68	AV
H	9760.00	54.15	30.85	7.45	24.69	55.44	74.00	-18.56	Pk
H	9760.00	42.78	30.85	7.45	24.69	44.07	54.00	-9.93	AV
H	12200.00	54.65	31.02	8.99	25.57	58.19	74.00	-15.81	Pk
H	12200.00	42.78	31.02	8.99	25.57	46.32	54.00	-7.68	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	

## High Channel:2480MHz

V	4960.00	52.00	30.55	5.77	24.66	51.88	74.00	-22.12	Pk
V	4960.00	43.54	30.55	5.77	24.66	43.42	54.00	-10.58	AV
V	7440.00	54.51	30.33	6.32	24.55	55.05	74.00	-18.95	Pk
V	7440.00	43.86	30.33	6.32	24.55	44.40	54.00	-9.60	AV

Shenzhen ZKT Technology Co., Ltd.

1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China



V	9920.00	44.35	30.85	7.45	24.69	45.64	54.00	-8.36	AV
V	12400.00	54.51	31.02	8.99	25.57	58.05	74.00	-15.95	Pk
V	12400.00	43.75	31.02	8.99	25.57	47.29	54.00	-6.71	AV
H	4960.00	52.09	30.55	5.77	24.66	51.97	74.00	-22.03	Pk
H	4960.00	43.76	30.55	5.77	24.66	43.64	54.00	-10.36	AV
H	7440.00	53.68	30.33	6.32	24.55	54.22	74.00	-19.78	Pk
H	7440.00	44.02	30.33	6.32	24.55	44.56	54.00	-9.44	AV
H	9920.00	54.28	30.85	7.45	24.69	55.57	74.00	-18.43	Pk
H	9920.00	44.12	30.85	7.45	24.69	45.41	54.00	-8.59	AV
H	12400.00	54.18	31.02	8.99	25.57	57.72	74.00	-16.28	Pk
H	12400.00	44.12	31.02	8.99	25.57	47.66	54.00	-6.34	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,  
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value  
has no need to be reported.



## 5. BANDWIDTH OF FREQUENCY BAND EDGE

### 5.1 TEST REQUIREMENT:

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above	Peak	1MHz	3MHz	Peak
	1GHz	Average	1MHz	3MHz	Average

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation

### 5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported


### 5.3 DEVIATION FROM TEST STANDARD

No deviation

### 5.4 TEST SETUP



Radiated Emission Test-Up Frequency Above 1GHz



### 5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.




## 5.6 TEST RESULT

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101 kPa	Test Voltage :	DC12V
Test Mode :	TX Mode		


Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	38.53	27.25	5.38	30.18	40.98	74.00	-33.02	Horizontal
2400.00	40.15	27.26	5.39	30.18	42.62	74.00	-31.38	Horizontal
2390.00	37.87	27.25	5.38	30.18	40.32	74.00	-33.68	Vertical
2400.00	40.14	27.26	5.39	30.18	42.61	74.00	-31.39	Vertical

2402MHz Horizontal



2402MHz Vertical






Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101 kPa	Test Voltage :	DC12V
Test Mode :	TX Mode		


Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	44.17	27.25	5.47	29.93	46.96	74.00	-27.04	Horizontal
2500.00	47.22	27.26	5.49	29.93	50.04	74.00	-23.96	Horizontal
2483.50	44.15	27.25	5.47	29.93	46.94	74.00	-27.06	Vertical
2500.00	47.04	27.26	5.49	29.93	49.86	74.00	-24.14	Vertical

## 2480MHz Horizontal



## 2480MHz Vertical





## 6. CHANNEL BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.249/15.215
Test Method:	ANSI C63.10: 2013

### 7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.249) , Subpart C			
Section	Test Item	Frequency Range (MHz)	Result
15.249(c)	Bandwidth	2400-2483.5	PASS

### 7.2 2.1TEST PROCEDURE

1. Set resolution bandwidth (RBW) = 1-5% or DTS BW, not to exceed 100 kHz.
2. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### 7.3 2.2DEVIATION FROM STANDARD

No deviation.

### 7.4 2.3TEST SETUP



### 7.5 2.4EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




## 7.6 2.5TEST RESULTS

Temperature :	26°C	Relative Humidity :	54%
Test Mode :	GFSK	Test Voltage :	DC12V

Test channel	Channel Bandwidth (MHz)	Result
Lowest	0.504	Pass
Middle	0.499	
Highest	0.502	







## 8. ANTENNA REQUIREMENT

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
EUT Antenna:	
The antennas are PCB antenna, the best case gain of the antennas are 1.3dBi, reference to the appendix II for details	



## 9. TEST SETUP PHOTO

Reference to the appendix I for details.

## 10. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

\*\*\*\*\* END OF REPORT \*\*\*\*\*