



FCC TEST REPORT

FCC ID: 2BLQ7-GL02

Product	:	Gaming PC
Model Name	:	GL02,X1/M50/MTX240
Brand	:	AOACE
Report No.	:	PTC24090210203E-FC05

Prepared for

Shenzhen Zhuangji Master Electronic Commerce Co., Ltd.

3rd Floor, Building B, Innovation Silicon Valley Industrial Park, Jingtian Road, Laocun
Community, Guanhu Street, Longhua District, Shenzhen

Prepared by

Precise Testing & Certification Co., Ltd.

Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China.

**TEST RESULT CERTIFICATION**

Applicant's name : Shenzhen Zhuangji Master Electronic Commerce Co., Ltd.

Address : 3rd Floor, Building B, Innovation Silicon Valley Industrial Park, Jingtian Road, Laocun Community, Guanhu Street, Longhua District, Shenzhen

Manufacturer's name : Shenzhen Zhuangji Master Electronic Commerce Co., Ltd.

Address : 3rd Floor, Building B, Innovation Silicon Valley Industrial Park, Jingtian Road, Laocun Community, Guanhu Street, Longhua District, Shenzhen

Product name : Gaming PC

Model name : GL02,X1/M50/MTX240

Test procedure : FCC CFR47 Part 1.1307(b)(1)

Test Date : Sep. 11, 2024 to Dec. 05, 2024

Date of Issue : Dec. 05, 2024

Test Result : PASS

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink, appearing to read "Jack Zhou".

Jack Zhou / Engineer

Technical Manager:

A handwritten signature in black ink, appearing to read "Simon Pu".

Simon Pu / Manager



Contents

	Page
2 TEST SUMMARY	4
3 GENERAL INFORMATION	5
3.1 GENERAL DESCRIPTION OF E.U.T	5
4 RF EXPOSURE	7
4.1 REQUIREMENTS	7
4.2 THE PROCEDURES / LIMIT	7
4.3 MPE CALCULATION METHOD	8
4.4 TEST RESULT	8
4.5 SIMULTANEOUS MPE RESULT	9



2 Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	15.247 (i)	PASS
Remark:		
N/A: Not Applicable		

3 General Information

3.1 General Description of E.U.T.

Product Name	:	Gaming PC
Model Name	:	GL02
Additional model	:	X1/M50/MTX240
Specification	:	Bluetooth BDR+EDR; Bluetooth BLE 802.11b/g/n HT20/HT40 802.11a/n HT20/HT40/ac20/ac40/ac80
Operation Frequency	:	2402-2480MHz for BT 2412-2462MHz for 802.11b/g/ n(HT20) 2422-2452MHz for 802.11 n(HT40) 5G Wifi: 5180-5240MHz 5.8G Wifi: 5745-5825MHz
Number of Channel	:	79 channels for BDR+EDR 40 channels For DTS 11 channels for 802.11b/g/ n(HT20) 7 channels for 802.11n(HT40) 4 channels for 802.11a/n20/ac20 5180-5240 MHz 5 channels for 802.11a/n20/ac20 5745MHz~5825MHz 2 channels for 802.11n40/ac40 5190-5230 MHz 2 channels for 802.11n40/ac40 5755MHz~5795MHz 1 channels for 802.11 ac80
Type of Modulation	:	GFSK, Π/4-DQPSK,8DPSK For DSS GFSK, For DTS DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n/a/ac
Antenna installation	:	External antenna
Smart System	:	<input checked="" type="checkbox"/> SISO:(for 802.11 b/g/n20/n40) <input type="checkbox"/> MIMO:(for 802.11 b/g/n20/n40) <input checked="" type="checkbox"/> SISO:(802.11n/a/ac) <input type="checkbox"/> MIMO:(802.11n/a/ac)
Antenna Gain	:	2.4G: Ant1: 1.95 dBi Ant2:1.95 dBi 5G WiFi: Ant1: 3.11 dBi Ant2:3.11 dBi
Power supply	:	Input voltage:100VAC~240V~ Input current:8-4A Frequency:60-50Hz



Report No.: PTC24090210203E-FC05

	Maximum output wattage: 550W
Hardware Version	: N/A
Software Version	: N/A



4 RF Exposure

Test Requirement : FCC Part 1.1307(b)(1)

Evaluation Method : KDB 447498 D01 General RF Exposure Guidance v06

4.1 Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

4.2 The procedures / limit

(A) Limits for Occupational / Controlled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density



4.3 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } P_d \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = \frac{30 \times P \times G}{377 \times d^2} \theta \varphi$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

4.4 Test Result

Mode	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Tune up tolerance (dBm)	Max Tune Up Power (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)	Result
2402(DH5)	1.57	2.77	2.77±1	2.3823	0.000743	1	Pass
24440(BLE_1 M)	1.57	-4.41	-4.41±1	0.4560	0.000142	1	Pass
2412(Ant1_1 1G)	1.57	12.13	12.13±1	20.5589	0.006408	1	Pass
2437(Ant2_2 437)	1.57	12.20	12.20±1	20.8930	0.006512	1	Pass
5240(Ant1_1 1A)	2.05	13.74	13.74±1	29.7852	0.012126	1	Pass
5795(Ant2_1 1N40SISO)	2.05	13.69	13.69±1	29.4442	0.011988	1	Pass



4.5 simultaneous MPE Result

2437(Ant2_2437)MPE ratio	5240(Ant1_11A)MPE ratio	simultaneous MPE ratio	MPE Limits ratio	Test result
0.012698	0.012126	0.024824	1	PASS

Conclusion:

Both of the WLAN (5GHz) and WLAN (2.4GHz) can transmit simultaneously, the formula of calculated the exposure is:

$(CPD1/LPD1)+(CPD2/LPD2)+\dots\text{etc.}<1$

CPD=Calculation Power Density; LPD= Limit of Power Density

Therefore, the calculation of this situation is $(0.012698/1) + (0.012126/ 1)= 0.024824$.

which is less than the "1" limit.

*****THE END REPORT*****