

RF Exposure Evaluation Report

1 RF EXPOSURE

Product Name: Dash cam

Model No.: K2 PRO, A8, K1, K2, K4, K7, K8, K9, T20, T20 PRO, T30, T30 PRO, K40, K50, K60, K70, K80, K90, H330, D80, D90, H6, H8

FCC ID: 2BLQ8-HUIBAI

2. RF Exposure Evaluation

Applicable standard

FCC KDB447498 D01 General RF Exposure Guidance v06: Mobile and Portable Device, RF Exposure, Equipment Authorization Procedures.

FCC CFR 47 part1 1.1310: Radiofrequency radiation exposure limits.

FCC CFR 47 part2 2.1091: Radiofrequency radiation exposure evaluation: mobile devices.

According to KDB447498D01 General RF Exposure Guidance v06 4.3.1. Standalone SAR test exclusion considerations Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

2.1 LIMITS

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

F= Frequency in MHz Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$ Where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Result of RF Exposure Evaluation

BT ANT1: 2.16dBi; 5G- ANT1: 2.1dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.0 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

The Max Conducted Peak Output Power data refer to report report No.:DACE241011001RF001& DACE241011001RF002&DACE241011001RF003

BT/BLE-worst mode and channel:

Test channel	Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power		Calculated value (mW/cm ²)	Limit (mW/cm ²)
			(dBm)	(mW)		
2DH5-2441MHz	5.91	6±1	7	5.012	0.0016	1.0
BLE-2402MHz	4.49	5±1	6	3.981	0.0013	1.0

EUT RF Exposure Evaluation simultaneous transmission operations

According to 865664D02 2.2 d) 1):

The sum of the ratios of the spatially averaged results to the applicable frequency dependent MPE limits :

Simultaneous transmission mode	The sum of the ratios (mW/cm ²)	SUM (mW/cm ²)	Limit (mW/cm ²)
BT+ BLE	0.0016+0.0013	0.0029	1.0
Conclusion : 0.0029<1.0(mW/cm ²), So there is no sar requirement			

5GWIFI- worst mode and channel:

Mode Test channel	Output Power(dBm)	Tune up tolerance (dBm)	Max Tune up (dBm)	Maximum tune-up Power(mW)	Calculated value (mW/cm ²)	Limit (mW/cm ²)
802.11a-5180MHz	10.28	11±1	12.0	15.849	0.0051	1.0
802.11a-5200MHz	10.65	11±1	12.0	15.849	0.0051	1.0
802.11a-5240MHz	10.46	11±1	12.0	15.849	0.0051	1.0

Remark: Pd = (Pout*G)/(4* Pi * R²)=(15.849*1.622)/(4*3.1415*20*20)=0.0051, G=10^{gain/10} =1.622

EUT RF Exposure Evaluation simultaneous transmission operations

According to 865664D02 2.2 d) 1):

The sum of the ratios of the spatially averaged results to the applicable frequency dependent MPE limits :

Simultaneous transmission mode	The sum of the ratios	SUM	Limit
BT+ 5G WIFI	0.0029+0.0051	0.008	1.0
Conclusion : 0.008 < 1.0 , So there is no sar requirement			

NOTE:1. EUT is more than 20cm away from the human body.