

Test Report

24-1-0027301T002-TR1-R02


Number of pages:	16	Date of Report:	2024-Nov-08
Testing company:	cetecom advanced GmbH Untertuerkheimer Str. 6-10 66117 Saarbruecken GERMANY	Applicant:	Henke-Sass, Wolf GmbH
Product:	Veterinary Device		
Model:	IDAL 3G Mono		
FCC ID:	2BLRO-301A	IC:	--
Testing has been carried out in accordance with:	FCC Regulations Title 47 CFR, Chapter I, Subchapter A, Part 15 Subpart B Unintentional Radiators § 15.107 Conducted limits § 15.109 Radiated emission limits ISED-Regulations ICES-003, Issue 7 Information Technology Equipment (including Digital Apparatus)		
Test Results:	<input checked="" type="checkbox"/> The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document The current version of Test Report 24-1-0027301T002_TR1-R02 replaces the test report 24-1-0027301T002_TR1-R01 dated 2024-Oct-04. The replaced test report is herewith invalid.		
Signatures:			
	Wolfgang Markus Lab Manager Authorization of test report		Hicham Laayouni Testing Manager Responsible of test report

Table of Contents

Table of Annex	3
1 General information	4
1.1 Disclaimer and Notes.....	4
1.2 Attestation.....	4
1.3 Summary of Test Results	5
1.4 Summary of Test Methods	5
2 Administrative Data	6
2.1 Identification of the Testing Laboratory.....	6
2.2 General limits for environmental conditions.....	6
2.3 Test Laboratories sub-contracted.....	6
2.4 Organizational Items	6
2.5 Applicant's details	6
2.6 Manufacturer's details	6
2.7 Equipment under Test (EUT)	7
2.8 Untested Variant (VAR)	7
2.9 Auxiliary Equipment (AE).....	7
2.10 Connected cables (CAB).....	7
2.11 Software (SW).....	7
2.12 EUT set-ups.....	7
2.13 EUT operation modes.....	7
3 Equipment under test (EUT)	8
3.1 General Data of Main EUT as Declared by Applicant.....	8
3.2 Modifications on Test sample	8
4 Measurements.....	9
4.1 Radiated field strength emissions 30 MHz – 1 GHz	9
4.2 Radiated field strength emissions above 1 GHz	12
5 Results from external laboratory.....	16
6 Opinions and interpretations	16
7 List of abbreviations	16
8 Measurement Uncertainty valid for conducted/radiated measurements	16
9 Versions of test reports (change history)	16

Table of Annex			
Annex No.	Contents	Reference Description	Total Pages
Annex 201	Test result diagrams	24-1-0027301T002_TR1-A201-R02	4
Annex 102	Internal photographs of EUT	not applicable	--
Annex 101	External photographs of EUT	24-1-0027301T002_TR1-A101-R02	2
Annex 103	Test set-up photographs	24-1-0027301T002_TR1-A103-R02	4
The listed attachments are separate documents.			

1 General information

1.1 Disclaimer and Notes

The test results of this test report relate exclusively to the test item specified in this test report as specified in chapter 2.7. cetecom advanced does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of cetecom advanced.

The testing service provided by cetecom advanced has been rendered under the current "General Terms and Conditions for cetecom advanced".

cetecom advanced will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the cetecom advanced test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the cetecom advanced test report include or imply any product or service warranties from cetecom advanced, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by cetecom advanced.

All rights and remedies regarding vendor's products and services for which cetecom advanced has prepared this test report shall be provided by the party offering such products or services and not by cetecom advanced.

In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 10 years at cetecom advanced.

Also we refer on special conditions which the applicant should fulfill according §2.927 to §2.948, special focus regarding modification of the equipment and availability of sample equipment for market surveillance tests.

1.2 Attestation

I declare that all measurements were performed by me or under my supervision and that all measurements have been performed and are correct to my best knowledge and belief to Industry Canada standards. All of the above requirements are met in accordance with enumerated standards.

1.3 Summary of Test Results

Test case	Reference in FCC ☒	Reference in ISED ☒	Page	Remark	Result
AC-Power Lines Conducted Emissions	§15.107	ICES-003, Issue 7	--	--	N/A
Radiated field strength emissions 30 MHz – 1 GHz	§15.109 §15.33 §15.35	ICES-003, Issue 7	9	--	PASS
Radiated field strength emissions above 1 GHz	§15.109 §15.33 §15.35	ICES-003, Issue 7	13	--	PASS

PASSED

The EUT complies with the essential requirements in the standard.

FAILED

The EUT does not comply with the essential requirements in the standard.

N/A

Test case does not apply to the test object.

NP

The test was not performed by the cetecom advanced laboratory.

Decision Rule: cetecom advanced GmbH follows [ILAC G8:2019 chapter 4.2.1 \(Simple Acceptance Rule\)](#).

1.4 Summary of Test Methods

Test case	Test method
AC-Power Lines Conducted Emissions	ANSI C63.4-2014 chapter 7
Radiated field strength emissions 30 MHz – 1 GHz	ANSI C63.4-2014 chapter 8.2.3
Radiated field strength emissions above 1 GHz	ANSI C63.4-2014 chapter 8.3

2 Administrative Data

2.1 Identification of the Testing Laboratory

Company name:	cetecom advanced GmbH
Address:	Untertuerkheimer Str. 6-10 66117 Saarbruecken Germany
Responsible for testing laboratory:	Niels Jeß
Accreditation scope:	DAkkS Webpage: FCC ISED
IC Lab company No. / CAB ID:	3462D / DE0001
Test location 1:	Untertuerkheimer Str. 6-10; 66117 Saarbruecken
Test location 2:	--

2.2 General limits for environmental conditions

Temperature:	22±2 °C
Relative. humidity:	45±15% rH

2.3 Test Laboratories sub-contracted

Company name:	--
---------------	----

2.4 Organizational Items

Responsible test manager:	Hicham Laayouni
Receipt of EUT:	2024-Aug-20
Date(s) of test:	2024-Sep-20 to 2024-Sep-24
Version of template:	23.0401

2.5 Applicant's details

Applicant's name:	Henke-Sass, Wolf GmbH
Address:	Keltenstraße 1 78532 Tuttlingen Baden-Wuerttemberg Germany
Contact Person:	Hanife Akkaya
Contact Person's Email:	Hanife.Akkaya@henkesasswolf.de

2.6 Manufacturer's details

Manufacturer's name:	Henke-Sass, Wolf GmbH
Address:	Keltenstraße 1 78532 Tuttlingen Germany

2.7 Equipment under Test (EUT)

EUT No.*)	Sample No.	Product	Model	Type	SN	HW	SW
EUT 1	24-1-00273S05_C01	Veterinary Device	IDAL 3G Mono	Mono	--	0.07	1.13

*) EUT short description is used to simplify the identification of the EUT in this test report.

2.8 Untested Variant (VAR)

VAR No.*)	Sample No.	Product	Model	Type	SN	HW	SW

*) The listed additional untested model variant(s) (VAR) is/are not object of evaluation of compliance. For further information please see Annex 5: Declaration of applicant of model differences.

If the table above does not show any other line than the headline, no untested variants are available.

2.9 Auxiliary Equipment (AE)

AE No.*)	Sample No.	Auxiliary Equipment	Model	SN	HW	SW
AE 1	24-1-00273S12_C01	Li-Ion battery	N/A	N/A	N/A	N/A

*) AE short description is used to simplify the identification of the auxiliary equipment in this test report. If the table above does not show any other line than the headline, no AE was used during testing nor was taken into account for evaluation

2.10 Connected cables (CAB)

CAB No.*)	Sample No.	Cable Type	Connectors / Details	Length

*) CAB short description is used to simplify the identification of the connected cables in this test report. If the table above does not show any other line than the headline, no cable was used during testing nor was taken into account for evaluation

2.11 Software (SW)

SW No.*)	Sample No.	SW Name	Description	SW Status

*) SW short description is used to simplify the identification of the used software in this test report. If the table above does not show any other line than the headline, no SW was used during testing nor was taken into account for evaluation.

2.12 EUT set-ups

set-up no.*)	Combination of EUT and AE	Description
1	EUT 1 + AE 1	Used for all measurements

*) EUT set-up no. is used to simplify the identification of the EUT set-up in this test report.

2.13 EUT operation modes

EUT operating mode no.*)	Operating modes	Additional information
01	Trigger enabled	All radios off

*) EUT operating mode no. is used to simplify the test report.

3 Equipment under test (EUT)

3.1 General Data of Main EUT as Declared by Applicant

Firmware	<input checked="" type="checkbox"/> for normal use	<input type="checkbox"/> Special version for test execution
Power supply	<input type="checkbox"/> AC Mains	--
	<input type="checkbox"/> DC Mains	--
	<input checked="" type="checkbox"/> Battery	Rechargeable Lithium Ion battery 10.8 VDC
Operational conditions	$T_{\text{nom}} = +21 \text{ }^{\circ}\text{C}$	Value assumed, if not specified different by the manufacturer
EUT sample type	Pre-Production	
Weight	1.2 kg	
Size [LxWxH]	30 cm x 20 cm x 10 cm	
Interfaces/Ports	--	
For further details refer Applicants Declaration & technical documents		

3.2 Modifications on Test sample

Additions/deviations or exclusions	--
------------------------------------	----


4 Measurements

4.1 Radiated field strength emissions 30 MHz – 1 GHz

4.1.1 Description of the general test setup and methodology, see below example:

Test site: Measurements between 30 MHz and 1 GHz are performed in the NSA compliant Semi Anechoic Chamber (SAC) according to EMC basic standard. The test site is compliant to CISPR 16-1-4:2019 chap. 5.3 and ANSI C63.4:2014 chap. 5.4.2 to 5.4.4.

Schematic below 1 GHz:



Testing method below 1 GHz:

Step 1:

Pre-measurement, variation of turntable positions: The EUT is set in the worst case operating mode determined. The tests are also carried out as a pre-measurement with peak detector (PK), repetitive scan and max-hold mode. Azimuth step of turntable = 90°, antenna heights = 1.0 m & 1.82 m, both polarisations (H/V). If the mounting/usual operating position is defined, the under and the top side of the EUT/test set-up will not be measured. The results are documented in a diagram. The peak values shown in this graphic are not finally maximized. Peak values closer than 6 dB to the limit line are displayed explicitly in a table. If no critical frequencies are found (margin to limit >6 dB) the final measurement will be omitted.

Step 2:

Based on the exploratory measurements, the most critical frequencies are re-measured by maintaining the EUT's worst-case operation mode, cable position, etc. either on 10 m OATS or 5 m or 3 m semi-anechoic room.

Final measurement: For the critical frequencies a maximum search is done with PK and CISPR QP detectors: First a frequency zoom within +/- 1.2 MHz (= 10*IF-BW) of the critical frequencies, then the EUT/test set-up is rotated continuously (if applicable, the EUT orientation will be changed to measure the under and the top side) and the antenna height changed between 1 m & 4 m in order to find the worst case position. The final measurement with the QP detector is carried out in this position and the values are stored in the final result table, which can be found after the diagram.

Formula:

$$E_C = E_R + AF + C_L + D_F - G_A \quad (1)$$

AF = Antenna factor

C_L = Cable loss

$$M = L_T - E_C \quad (2)$$

D_F = Distance correction factor (if used)

E_C = Electrical field – corrected value

E_R = Receiver reading

G_A = Gain of pre-amplifier (if used)

L_T = Limit

M = Margin

All units are dB-units, positive margin means value is below limit.

4.1.2 Test receiver settings

Detector	Peak	Quasi peak
Min. attenuation	0 dB	0 dB
Resolution bandwidth	120 kHz	120 kHz
Dector Meas-time	10 ms	1 s
Step size	40 kHz	Selected frequencies
Preamp	Off	Off

4.1.3 Measurement Protocol(s)

Measurement No.	P1M1	
Environmental conditions	Temperature: 20.0 °C Humidity: 40.0 % rH	
Test date	2024-Sep-24	
Operator	Hicham Laayouni	
EuT power supply:	Battery	
Operating mode	01	
Setup	01	
Remarks	--	

Diagram	Measurement Details		Result
3.01	EUT position	<input checked="" type="checkbox"/> standing <input type="checkbox"/> laying <input checked="" type="checkbox"/> Mounting position / usual operating position is defined (under and top side of EUT are not measured) <input type="checkbox"/> Mounting position / usual operating position undefined (under and top side of EUT are measured)	PASS
	Critical frequencies found:	<input type="checkbox"/> no, margin to limit > 10 dB (only Step 1 carried out) <input checked="" type="checkbox"/> yes, final measurement (Step 2 carried out)	

Remark: for more information and graphical plot see annex A1 24-1-0027301T002_TR1-A201-R02

Measurement No.	P2M1	
Environmental conditions	Temperature: 20.0 °C Humidity: 40.0 % rH	
Test date	2024-Sep-24	
Operator	Hicham Laayouni	
EuT power supply:	Battery	
Operating mode	01	
Setup	01	
Remarks	--	

Diagram	Measurement Details		Result
3.02	EUT position	<input type="checkbox"/> standing <input checked="" type="checkbox"/> laying <input checked="" type="checkbox"/> Mounting position / usual operating position is defined (under and top side of EUT are not measured) <input type="checkbox"/> Mounting position / usual operating position undefined (under and top side of EUT are measured)	PASS
	Critical frequencies found:	<input type="checkbox"/> no, margin to limit > 10 dB (only Step 1 carried out) <input checked="" type="checkbox"/> yes, final measurement (Step 2 carried out)	

Remark: for more information and graphical plot see annex A1 24-1-0027301T002_TR1-A201-R02

4.1.4 Limits

Frequency Range [MHz]	Class B <input checked="" type="checkbox"/> (3 meters)		Class A <input checked="" type="checkbox"/> (10 meters)	
	Limit [μ V/m]	Limit [dB μ V/m]	Limit [μ V/m]	Limit [dB μ V/m]
30 - 88	100	40.0	90	39.0
88 - 216	150	43.5	150	43.5
216 - 960	200	46.0	210	46.4
960 - 1000	500	54.0	300	49.5

4.1.5 Result

Test case	Reference in FCC <input checked="" type="checkbox"/>	Reference in ISED <input checked="" type="checkbox"/>	Remark	Result
Radiated field strength emissions 30 MHz – 1 GHz	\$15.109 \$15.33 \$15.35	ICES-003, Issue 7	--	PASS

4.1.6 Measurement Location and Equipment list

ID	Description	Manufacturer	SerNo	CheckType	Last Check	Interval	Next Check
	120901 - SAC3 - Radiated Emission <1GHz			calchk	cal: 2015-Jul-21 chk: 2024-Jul-27	cal: 10Y chk: 12M	cal: 2025-Jul-21 chk: 2025-Jul-27
20341	Digital Multimeter Fluke 112	Fluke Deutschland GmbH / Glottental	81650455	cal	cal: 2024-May-13	cal: 24M	cal: 2026-May-13
20442	Semi Anechoic Chamber SAC3	ETS-Lindgren GmbH / Taufkirchen	without	cnn	cal: - chk: -	cal: - chk: -	cal: - chk: -
20482	Filter Matrix SAC3	cetecom advanced GmbH / Essen	without	cnn	cal: - chk: -	cal: - chk: -	cal: - chk: -
20574	Biconilog Hybrid Antenna BTA-L	Frankonia GmbH / Heideck	980026L	cal	cal: 2022-Jun-15	cal: 36M	cal: 2025-Jun-15
20620	EMI Test Receiver ESU26	Rohde & Schwarz Messgerätebau GmbH / Memmingen	100362	cal	cal: 2024-May-15	cal: 12M	cal: 2025-May-15
20885	Power Supply EA3632A	Agilent Technologies Deutschland GmbH	75305850	cnn	cal: - chk: -	cal: - chk: -	cal: - chk: -

4.1.7 Legend

Note / remarks	Interval of calibration & Verification
2W	2 weeks
12M	12 months
24M	24 months
36M	36 months
10Y	10 Years


Abbreviation Check Type	Description
cnn	Calibration and verification not necessary
cal	Calibration
calchk	Calibration plus intermediate Verification
chk	Verification
cpu	Verification before usage

4.2 Radiated field strength emissions above 1 GHz

4.2.1 Description of the general test setup and methodology, see below example:

Evaluating the emissions have to be done first by an exploratory emissions measurement and a final measurement for most critical frequencies. The tests are performed in a CISPR 18-1-4:2010 compliant fully anechoic room (FAR) recognized by the regulatory commission. The measurement distance was set to 3 meter for frequencies up to 18 GHz and 2 meter above 18 GHz. A logarithmic periodic antenna is used for the frequency range 30 MHz to 1 GHz. Horn antennas are used for frequency range 1 GHz to 40 GHz. The EUT is aligned within 3 dB beam width of the measurement antenna with three orthogonal axis measurements on the EUT.

Schematic:



Testing method:

The measurement is made according to relevant reference clauses:

(See Tables *Summary of Test Results* and *Summary of Test Methods* on page 5)

Exploratory, preliminary measurements

The EUT and its associated accessories are placed on a non-conductive position manipulator (tipping device) of 1.55 m height which is placed on the turntable. By rotating the turntable (range 0° to 360°, step 15°) and the EUT itself either on 3-orthogonal axis (portable equipment) or 2-orthogonal axis (defined operational position of EUT) the emission spectrum and its characteristics was recorded with an EMI-receiver, broadband antenna and software.

The measurements are performed in horizontal and vertical polarization of the measurement antennas. The results are documented in a diagram. Critical frequencies (low margin to limit) are saved within a table for further investigations. If various operating modes are supported, further investigations are made to find the worst-case of them. Also the interconnection cables and equipment position were varied in order to maximize the emissions.

Final measurement on critical frequencies

Based on the exploratory measurements, the most critical frequencies are re-measured by maintaining the EUT's worst-case operation mode, cable position, etc.

First a frequency zoom around the critical frequency is done to locate the frequency more precisely. After this step, for all identified critical frequencies, the maximum peak was determined.

Following parameters were varied: the turntable angle continuously in the range 0 to 360 degree, the EUT itself over 3-orthogonal axis and the height for EUT with large dimensions or three axis scan for portable/small equipment.

On the determined worst-case position, a final measurement with necessary bandwidth and detector according standard has been carried out.

Formula:

$$E_C = E_R + A_F + C_L + D_F - G_A \quad (1)$$

$$M = L_T - E_C \quad (2)$$

E_C = Electrical field – corrected value

E_R = Receiver reading

M = Margin

L_T = Limit

A_F = Antenna factor

C_L = Cable loss

D_F = Distance correction factor (if used)

G_A = Gain of pre-amplifier (if used)

All units are dB-units, positive margin means value is below limit.

4.2.2 Sample calculation

Raw-Value [dBuV/m]	Antenna factor	Distance Correction [dB]	Cable Loss + Preamplifier	Resulting correction value [dB]	Final result [dBuV/m]	Remarks
29.37	41.20	--	24.28	16.92	46.3	CableLoss and PreAmp data in one data correction file

Remark: This calculation is based on an example value at 10 GHz

4.2.3 Test receiver / spectrum analyzer settings

Detector	Peak	Average
Min. attenuation	10 dB	10 dB
Resolution bandwidth	1 MHz	1 MHz
Detector Meas-time	Pre-measurement 10 ms Final measurement 1 s	Pre-measurement 10 ms Final measurement 1 s
Step size	Pre-measurement: 400 kHz Final measurement: selected frequencies	Pre-measurement: 400 kHz Final measurement: selected frequencies
Preamplifier	Off below 6 GHz 30 dB above 6 GHz	Off below 6 GHz 30 dB above 6 GHz

4.2.1 Measurement Protocol(s)

Measurement No.	P2M1
Environmental conditions	Temperature: 22.0 °C Humidity: 45.0 % rH
Test date	2024-Sep-20
Operator	Hicham Laayouni
EuT power supply:	Battery
Operating mode	01
Setup	01
Remarks	

Diagram	Measurement Details			Result
4.01	<input checked="" type="checkbox"/> standing <input checked="" type="checkbox"/> laying <input type="checkbox"/> Mounting position / usual operating position is defined (under and top side of EUT are not measured) <input checked="" type="checkbox"/> Mounting position / usual operating position undefined (under and top side of EUT are measured)			PASS
	<input checked="" type="checkbox"/> no, margin to limit > 10 dB (only Step 1 carried out) <input type="checkbox"/> yes, final measurement (Step 2 carried out)			

Remark: for more information and graphical plot see annex A1 **24-1-0027301T002_TR1-A201-R02**

4.2.2 Limits

Frequency Range [MHz]	Class B <input checked="" type="checkbox"/> (3 meters)		Class A <input type="checkbox"/> (3 meters)		Detector
	Limit [μ V/m]	Limit [dB μ V/m]	Limit [μ V/m]	Limit [dB μ V/m]	
Above 1000	500	54	950	59.5	Average
Above 1000	5000	74	9500	79.5	Peak

4.2.3 Result

Test case	Reference in FCC <input checked="" type="checkbox"/>	Reference in ISED <input checked="" type="checkbox"/>	Remark	Result
Radiated field strength emissions above 1 GHz	\$15.109 \$15.33 \$15.35	ICES-003, Issue 7	--	PASS

4.2.4 Measurement Location and Equipment list

ID	Description	Manufacturer	SerNo	CheckType	Last Check	Interval	Next Check
	225911 - SAC1 - Radiated Emission <1GHz			calchk	cal: 2016-Apr-05 chk: 2024-Sep-24	cal: 120M chk: 12M	cal: 2026-Apr-05 chk: 2024-Sep-25
25316	Multifunction AC/DC Power Source Netwave 20	EM TEST GmbH / Kamen	V1227113059	cal	cal: 2024-Jun-05	cal: 36M	cal: 2027-Jun-05
25348	EMI Test Receiver ESR7	Rohde & Schwarz Messgerätebau GmbH / Memmingen	101600	cal	cal: 2023-May-25	cal: 24M	cal: 2025-May-25
25352	Open Switch and control Platform OSP120	Rohde & Schwarz Messgerätebau GmbH	101542-rV	cpu			
25357	Ultrabroadband Antenna HL562E	Rohde & Schwarz Messgerätebau GmbH / Memmingen	100824	cal	cal: 2024-Jan-17	cal: 36M	cal: 2027-Jan-17
25358	Semi Anechoic Chamber SAC1	Albatross Projects GmbH / Nattheim	P27281-016	cal	cal: 2022-Aug-12	cal: 120M	cal: 2032-Aug-12
25360	Antenna Mast BAM 4.5-P	maturo GmbH / Pfreimd	BAM 4.5-P/091/17791115	cnn	cal: - chk: -	cal: - chk: -	cal: - chk: -
25361	Controller NCD	maturo GmbH	NCD/202/17791115	cnn	cal: - chk: -	cal: - chk: -	cal: - chk: -
25362	Test Table PTT1.5x1.0x0.8-S_127	maturo GmbH / Pfreimd	without	cnn	cal: - chk: -	cal: - chk: -	cal: - chk: -
25363	Turn Table TT4.0-4t	maturo GmbH / Pfreimd	TT4.0-4t/553/17791115	cnn	cal: - chk: -	cal: - chk: -	cal: - chk: -
25376	Measurement Software EMC32 [SACS]	Rohde & Schwarz Messgerätebau GmbH / Memmingen	v10.60.20	cnn	cal: - chk: -	cal: - chk: -	cal: - chk: -

4.2.5 Legend

Note / remarks	Interval of calibration & Verification
2W	2 weeks
12M	12 months
24M	24 months
36M	36 months
10Y	10 Years

Abbreviation Check Type	Description
cnn	Calibration and verification not necessary
cal	Calibration
calchk	Calibration plus intermediate Verification
chk	Verification
cpu	Verification before usage

5 Results from external laboratory

None

-

6 Opinions and interpretations

None

-

7 List of abbreviations

None

-

8 Measurement Uncertainty valid for conducted/radiated measurements

The reported uncertainties are calculated based on the standard uncertainty multiplied with the appropriate coverage factor **k**, such that a confidence level of approximately 95% is achieved. For uncertainty determination, each component used in the concrete measurement set-up was taken in account and its contribution to the overall uncertainty according its statistical distribution calculated.

RF-Measurement	Reference	Frequency range	Calculated uncertainty based on a confidence level of 95%	Remarks
Conducted emissions (U _{CISPR})	CISPR 16-2-1	9 kHz - 150 kHz 150 kHz - 30 MHz	4.00 dB 3.58 dB	-
Radiated emissions Enclosure	CISPR 16-2-3	30 MHz - 300 MHz 300 MHz - 1 GHz 1 GHz - 6 GHz 1 GHz - 18 GHz	SAC1: 2.60 dB SAC2: 2.62 dB SAC3: 4.20 dB SAC1: 2.90 dB SAC2: 3.00 dB SAC3: 4.20 dB SAC2: 4.10 dB SAC1: 4.98 dB SAC3: 5.10 dB	E-Field

9 Versions of test reports (change history)

Version	Applied changes	Date of release
R01	Initial release	2024-Oct-04
R02	Change FCC ID	2024-Nov-08
--	--	--

End Of Test Report