

# RF Exposure Report

FCC ID:2BLTC-400L

**Report No.** : SSP24100081-2E

**Applicant** : Linhai xinchen electronic light-decoration co., LTD

**Product Name** : Smart LED Curtain light

**Model Name** : 2\*2M400L

**Test Standard** : FCC CFR 47 PART 1.1307(b)

**Date of Issue** : 2024-10-26



**Shenzhen CCUT Quality Technology Co., Ltd.**

1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen,  
Guangdong, China; (Tel.:+86-755-23406590 website: [www.ccutttest.com](http://www.ccutttest.com))

This test report is limited to the above client company and the product model only. It may not be duplicated  
without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.

**Test Report Basic Information**

**Applicant**.....: Linhai xinchen electronic light-decoration co., LTD  
5F, No. 1-68A, Xuanzhu Village, Dongcheng Town, Linhai City, Zhejiang  
Address of Applicant.....: Province, China

**Manufacturer**.....: Linhai xinchen electronic light-decoration co., LTD  
5F, No. 1-68A, Xuanzhu Village, Dongcheng Town, Linhai City, Zhejiang  
Address of Manufacturer.....: Province, China

**Product Name**.....: Smart LED Curtain light

**Brand Name**.....: -

**Main Model**.....: 2\*2M400L

**Series Models**.....: 1\*1M400L, 1.5\*1.5M400L, 3\*2M400L, 3\*3M400L

FCC CFR 47 PART 1.1307(b)

**Test Standard**.....: KDB 447498 D01 v06

**Date of Test** .....: 2024-10-11 to 2024-10-26

**Test Result**.....: PASS

**Tested By** .....: Coke Huang (Coke Huang)

**Reviewed By**.....: Lieber Ouyang (Lieber Ouyang)

**Authorized Signatory**.....: Lahm Peng (Lahm Peng)



Note : This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.. All test data presented in this test report is only applicable to presented test sample.

## CONTENTS

<b>1. General Information .....</b>	<b>5</b>
1.1 Product Information .....	5
1.2 Test Facilities .....	5
<b>2. RF Exposure .....</b>	<b>6</b>
2.1 Standard and Limit.....	6
2.2 Test Data and Results .....	7

### Revision History

Revision	Issue Date	Description	Revised By
V1.0	2024-10-26	Initial Release	Lahm Peng

## 1. General Information

### 1.1 Product Information

Product Name:	Smart LED Curtain light
Trade Name:	-
Main Model:	2*2M400L
Series Models:	1*1M400L, 1.5*1.5M400L, 3*2M400L, 3*3M400L
Rated Voltage:	DC 5V by adapter
Power Adapter:	INPUT: 100-240V~50/60Hz 0.6A, OUTPUT:5V=2.4A
Hardware Version:	V1.0
Software Version:	V1.0
Note 1: The test data is gathered from a production sample, provided by the manufacturer. Note 2: The appearance color and model name of the listed series models, the length of the lamp strip is different from that of the main model, but the circuit and electronic structure are the same, which shall be declared by the manufacturer.	

Wireless Specification	
Wireless Standard:	Bluetooth BR+EDR
Operating Frequency:	2402 MHz ~2480 MHz
RF Output Power:	2.05dBm
Antenna Gain:	0dBi
Type of Antenna:	PCB Antenna
Type of Device:	<input type="checkbox"/> Portable Device <input checked="" type="checkbox"/> Mobile Device <input type="checkbox"/> Modular Device

### 1.2 Test Facilities

Laboratory Name:	<b>Shenzhen CCUT Quality Technology Co., Ltd.</b> 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China
CNAS Laboratory No.:	L18863
A2LA Certificate No.:	6893.01
FCC Registration No.:	583813
ISED Registration No.:	CN0164
All measurement facilities used to collect the measurement data are located at 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China.	

## 2. RF Exposure

### 2.1 Standard and Limit

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

f = frequency in MHz

Friis transmission formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>,  $P_{out}$  = output power to antenna in mW;

$G$  = gain of antenna in linear scale,  $\pi = 3.1416$ ;

$r$  = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance  $r$  where the MPE limit is reached.

#### Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

## 2.2 Test Data and Results

For 2.4G WiFi

Mode	Output power to antenna (dBm)	Tune-up Power(dBm)	Max Tune-up Power(dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
8DPSK	2.05	2(±1)	3	2.00	0.0004	1.0	PASS

Remark: antenna gain=0dBi