

RF EXPOSURE EVALUATION

KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

EUT Specification

FCC ID	2BLU4-V12R
EUT	Vehicle PC
Frequency band (Operating)	☒ BT: 2.402GHz ~ 2.480GHz ☒ WLAN: 2.412GHz ~ 2.462GHz ☒ RLAN: 5.180GHz ~ 5.240GHz ☐ RLAN: 5.260GHz ~ 5.320GHz ☐ RLAN: 5.500GHz ~ 5.700GHz ☒ RLAN: 5.745GHz ~ 5.825GHz ☐ Others:
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others _____
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm2) ☒ General Population/Uncontrolled exposure (S=1mW/cm2)
Antenna diversity	☐ Single antenna ☒ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Antenna gain (Max)	BT: 2.47 dBi WiFi ANT1 2.4G: 2.47dBi WiFi ANT2 2.4G: 5.38dBi WiFi ANT1 5.2G: 3.73dBi WiFi ANT1 5.8G: 4.51dBi WiFi ANT2 5.2G: 4.98dBi WiFi ANT2 5.8G: 4.84dBi
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation



Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in Mw

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Max Measurement Result

Operating Mode	Measured Power	Tune up tolerance		Max. Tune up Power	Antenna Gain	Power density at 20cm	Power density Limits (mW/cm ²)
	(dBm)	(dBm)		(dBm)	(dBi)	(mW/cm ²)	
BDR&EDR	6.73	6.73	±1	7.73	2.47	0.0021	1
BLE	5.87	5.87	±1	6.87	2.47	0.0017	1
WiFi 2.4G ANT1	14.88	14.88	±1	15.88	2.47	0.0136	1
WiFi 2.4G ANT2	14.43	14.43	±1	15.43	5.38	0.0240	1
WiFi 5.2G ANT1	16.06	16.06	±1	17.06	3.73	0.0239	1
WiFi 5.2G ANT2	15.28	15.28	±1	16.28	4.98	0.0266	1
WiFi 5.8G ANT1	15.91	15.91	±1	16.91	4.51	0.0276	1
WiFi 5.8G ANT2	14.85	14.85	±1	15.85	4.84	0.0233	1

The Maximum simultaneous transmission for BDR+EDR+WiFi 5.2G(ANT 2)+WiFi 5.8G(ANT 1):

$$\sum_i \frac{S_i}{S_{Limit,i}}$$

$$= S_{BDR+EDR} / S_{limit-BDR+EDR} + S_{RLAN 5.2} / S_{limit-RLAN 5.2} + S_{RLAN 5.8} / S_{limit-RLAN 5.8}$$

Shenzhen Anbotek Compliance Laboratory Limited

Address: Sogood Industrial Zone Laboratory & 1/F. of Building D, Sogood Science and Technology Park, Sanwei Community, Hahgcheng Subdistrict, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86) 0755-26066440 Email: service@anbotek.com



Hotline
400-003-0500
www.anbotek.com



$$=0.0021/1+0.0266/1+0.0276/1$$

$$=0.0563$$

$$< 1.0$$

Result: No Standalone SAR test is required.

