

AVILOO Box Manual

MANUFACTURER

AVILOO GmbH
IZ NÖ-Süd, Straße 16, Objekt 69/5
2355 Wiener Neudorf | Austria

TYPE

AVILOO Box

DESCRIPTION

The AVILOO Box is a cloud based datalogger that requests and monitors data from a car's OBD-2-port or any CAN bus and transmits it to the AVILOO Battery Cloud.

TECHNICAL DATA

AND ENVIRONMENTAL INFORMATION

- Power Supply via OBD, 12 VDC or 24 VDC, Power consumption <15W
- Do not disassemble, crush, bend, deform, puncture, or shred the AVILOO Box.
- Do not use it in a humid, wet and/or corrosive environment.
- Do not put, store or leave the device in a high temperature location, in direct sunlight, in or near a heat source, in a microwave oven or in a pressurised container, and do not expose it to temperatures over 85 °C/185 °F or below -40 °C/-40 °F.
- Please note that exceeding these limits below may permanently damage the device!
- Avoid dropping the device. If the device is dropped and you suspect damage, please contact AVILOO Customer Support.
- In case you have received a damaged device, contact AVILOO Customer Support.

PRODUCT OVERVIEW

TECHNICAL DATA AND ENVIRONMENTAL INFORMATION

Dimensions: 145 x 60 x 38 mm

Weight: ~ 131g

Rated supply voltage: 12 V or 24 V

Supply voltage ext. range: 9–28 V

Power consumption:

RMS: 5 W; peak: 25 W

Ambient temperature:

0 °C/32 °F–50 °C/122 °F



Only used at altitude not exceeding 2000 m.



Only used in non-tropical climate regions.

ENGLISH (USA)

THE AVILOO BOX CONSISTS OF THE FOLLOWING MAIN COMPONENTS

VENDOR	MPN	DESCRIPTION
DH electronics GmbH	DHCOM STM32MP1	System-on-a-Module (SoM) based on a STM32MP157C
Quectel Wireless Solutions Co., Ltd	Quectel EG-25GGB-MINI-PCI-S	GSM/LTE modem in a Mini-Pcie form factor
AVILOO	AVILOO Box mainboard	Interconnection unit between SoM, modem and connectors
Molex	2125700100	LTE-cellular-antennas (2)
Molex	2065600100	GPS-antenna

NETWORK SPECIFICATIONS

Antenna: Internal only; Molex 2125700100; Maximum gain: 824–960 MHz 0,45 dBi; 1710–2170 MHz 1,76 dBi

Frequencies: LTE Bands: 1, 3, 4, 5, 7, 8, 12, 13, 18, 19, 20, 25, 26, 28, 38, 39, 40, 41; WCDMA Bands: 1, 2, 4, 5, 6, 8, 19

LTE Features:
LTE-FDD: Max. 150 Mbit/s (DL)/
Max. 50 Mbit/s (UL);
LTE-TDD: Max. 130 Mbit/s (DL)/
Max. 30 Mbit/s (UL)

OTHER SPECIFICATIONS

Processor: ARM Dual Cortex-A7 800 MHz with embedded ARM Cortex M4 209 MHzRAM

RAM: 1 GB DDR3 + 708 KByte SRAM

Storage:
- 16 GB eMMC
- 2 MByte SPI NOR Flash
- internal MicroSD-slot

Integrated modem for global operation:
- LTE Cat 4 (150 MBit/s Download and 50 MBit/s Upload)

- Regulative Compliance: GCF, CE, FCC, PTCRB, IC, Anatel, IFETEL, SRRC, NAL, CCC, KC, NCC, JATE, TELEC, RCM, IMDA, ICASA, NBTC

- Carrier Compliance: Deutsche Telekom, Verizon, AT&T, Sprint, US Cellular, Telus, T-Mobile, Rogers

Global positioning: GPS, Galileo

RTC with independent power supply

INTERFACE DESCRIPTION

Depending on the specific variant, the device has two Ethernet, one WiFi and one Cellular network interface. The Ethernet and WiFi interfaces expose an SSH service while the Cellular interface has no exposed services. All interfaces can be used by the device for outgoing NTP connections to a global network time server pool and to connect to AVILOO infrastructure using proprietary protocols secured by modern, industry standard TLS versions.

OBD-2-INTERFACE

The OBD-2-connector is used for communication between the AVILOO Box and the vehicle. The AVILOO Box is also supplied with voltage via this plug. The mechanical design and the pin assignment of the connector correspond to the SAE J1962 standard.

ETHERNET INTERFACE

The RJ-45 socket is not used during operation in vehicles and is only used for functional tests at the end of production line and for reprocessing of the devices. In customer operation, this interface is closed by a blind plug and is not accessible to any consumer.

INSTALLATION & OPERATION

- Connect the AVILOO Box to your car's OBD-2-port with the provided cable and mount the AVILOO Box in a safe and secure position. Avoid twisting of the cable.

- The AVILOO Box will automatically start requesting data from the vehicle and connect to the AVILOO Cloud Service to upload the data.

- This is a mobile device and the user must ensure that they maintain a distance of 20 cm during operation.

- Changes or modifications not expressly approved by AVILOO could void the user's authority to operate the equipment.