

## M2S User Guidance

### **Special reminder:**

The operating voltage of this product is 5V, and a voltage higher than 5V is prohibited

### **method of erection:**

1. Insert the USB screenshot into the car USB interface and connect to the host
2. Hide the extra lines to avoid affecting the driving
3. Put the host engine in the center console to avoid affecting the driving place

### **Correct use:**

Move the car to the open road after electrification

1. Display interface- -indicating the search satellite,
2. The display interface shows 0km, which indicates that the satellite can be used normally

### **matters need attention**

**When the satellite is not connected, try putting the product outside the window and wait for 5-10 minutes**

### **FCC STATEMENT**

1. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) This device must accept any interference received, including interference that may cause undesired operation.

2. Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.

However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

Reorient or relocate the receiving antenna.

Increase the separation between the equipment and receiver.

Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

Consult the dealer or an experienced radio/TV technician for help.