



3.5. DTS Bandwidth

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2)

Test Item	Limit	Frequency Range (MHz)
DTS Bandwidth	≥500 kHz (6dB bandwidth)	2400~2483.5

Report No.: CTC2025405102

Test Configuration



Test Procedure


- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- 2. DTS Spectrum Setting:
 - (1) Set RBW = 100 kHz.
 - (2) Set the video bandwidth (VBW) ≥ 3 RBW.
 - (3) Detector = Peak.
 - (4) Trace mode = Max hold.
 - (5) Sweep = Auto couple.
 - **OCB Spectrum Setting:**
 - (1) Set RBW = 1% ~ 5% occupied bandwidth.
 - (2) Set the video bandwidth (VBW) ≥ 3 RBW.
 - (3) Detector = Peak.
 - (4) Trace mode = Max hold.
 - (5) Sweep = Auto couple.

NOTE: The EUT was set to continuously transmitting in each mode and low, Middle and high channel for the test.

Test Mode

Please refer to the clause 2.4.

TRF No: CTC-TR-057_A2 For anti-fake verification, please visit the official website of China Inspection And Testing Society: yz.cncaq.com







Test Result


TestMode	Antenna	Frequency [MHz]	OCB [MHz]	DTS BW [MHz]	Limit[MHz]	Verdict
		2412	13.307	9.04	0.5	PASS
11B	Ant1	2437	13.467	9.04	0.5	PASS
		2462	13.387	9.08	0.5	PASS
		2412	17.223	16.36	0.5	PASS
11G	Ant1	2437	17.662	16.36	0.5	PASS
		2462	17.303	15.80	0.5	PASS
11N20SISO		2412	18.741	16.04	0.5	PASS
	Ant1	2437	18.222	17.56	0.5	PASS
		2462	18.182	17.64	0.5	PASS
11N40SISO		2422	36.843	33.36	0.5	PASS
	Ant1	2437	37.083	36.32	0.5	PASS
		2452	36.603	32.64	0.5	PASS
		2412	19.261	18.96	0.5	PASS
11AX20SISO	Ant1	2437	19.181	16.96	0.5	PASS
		2462	19.181	17.72	0.5	PASS
		2422	38.202	36.32	0.5	PASS
11AX40SISO	Ant1	2437	38.042	37.04	0.5	PASS
		2452	37 962	37.60	0.5	PASS


For anti-fake verification, please visit the official website of China Inspection And Testing Society : $\underline{\text{vz.cncaq.com}}$ TRF No: CTC-TR-057_A2




























CTC Laboratories, Inc.

Room 107, 108, 207, 208, 303 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn




















3.6. Peak Output Power

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3)

Section	Test Item	Limit	Frequency Range (MHz)
FCC CFR 47 Part15.247 (b)(3)	Maximum Conducted Output Power	1 Watt or 30dBm	2400~2483.5

Test Configuration




Test Procedure

- 1. The maximum conducted output power may be measured using a broadband RF power meter.
- 2. Power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor.
- 3. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.
- 4. Record the measurement data.

Test Mode

Please refer to the clause 2.4.

TRF No: CTC-TR-057_A2 For anti-fake verification, please visit the official website of China Inspection And Testing Society: yz.cncaq.com





Test Result

Test Mode	Antenna	Frequency[MHz]	Result [dBm]	Limit [dBm]	Verdict
		2412	13.98	≤30.00	PASS
11B	Ant1	2437	13.92	≤30.00	PASS
		2462	14.22	≤30.00	PASS
		2412	17.17	≤30.00	PASS
11G	Ant1	2437	17.80	≤30.00	PASS
		2462	17.68	≤30.00	PASS
	Ant1	2412	17.78	≤30.00	PASS
11N20SISO		2437	17.73	≤30.00	PASS
		2462	17.68	≤30.00	PASS
	Ant1	2422	17.59	≤30.00	PASS
11N40SISO		2437	17.78	≤30.00	PASS
		2452	17.57	≤30.00	PASS
		2412	17.59	≤30.00	PASS
11AX20SISO	Ant1	2437	17.91	≤30.00	PASS
		2462	18.04	≤30.00	PASS
		2422	18.15	≤30.00	PASS
11AX40SISO	Ant1	2437	18.23	≤30.00	PASS
		2452	18.28	≤30.00	PASS

For anti-fake verification, please visit the official website of China Inspection And Testing TRF No: CTC-TR-057_A2 $Society: \underline{\text{yz.cncaq.com}}$



Page 103 of 113 Report No.: CTC2025405102


3.7. Power Spectral Density

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (e)

Test Item	Limit	Frequency Range (MHz)	
Power Spectral Density	8 dBm (in any 3 kHz)	2400~2483.5	

Test Configuration



Test Procedure

- 1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- 2. The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to section 10.2 of KDB 558074 D01 DTS Meas Guidance v05r02.
- 3. Spectrum Setting:

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: 3 kHz. Set the VBW to: 10 kHz.

Detector: peak. Sweep time: auto.

Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.

Test Mode

Please refer to the clause 2.4.

TRF No: CTC-TR-057 A2

For anti-fake verification, please visit the official website of China Inspection And Testing Society: $\underline{\mathsf{vz.cncaq.com}}$






Test Result

TestMode	Antenna	Frequency[MHz]	Result[dBm/3-100kHz]	Limit[dBm/3kHz]	Verdict
		2412	-10.83	≤8.00	PASS
11B	Ant1	2437	-10.87	≤8.00	PASS
		2462	-10.86	≤8.00	PASS
		2412	-15.75	≤8.00	PASS
11G	Ant1	2437	-14.87	≤8.00	PASS
		2462	-14.86	≤8.00	PASS
11N20SISO	Ant1	2412	-13.49	≤8.00	PASS
		2437	-14.32	≤8.00	PASS
		2462	-14.52	≤8.00	PASS
11N40SISO	Ant1	2422	-17.03	≤8.00	PASS
		2437	-17.06	≤8.00	PASS
		2452	-17.79	≤8.00	PASS
		2412	-15.36	≤8.00	PASS
11AX20SISO	Ant1	2437	-14.93	≤8.00	PASS
		2462	-15.75	≤8.00	PASS
		2422	-17.02	≤8.00	PASS
11AX40SISO	Ant1	2437	-18.14	≤8.00	PASS
		2452	-17.67	≤8.00	PASS

TRF No: CTC-TR-057_A2 For anti-fake verification, please visit the official website of China Inspection And Testing Society: yz.cncaq.com


Test plot as follows:




CTC Laboratories, Inc.

Room 107, 108, 207, 208, 303 of Building A, Room 101 of Building B, No.7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn


























3.8. Duty Cycle

Limit

None, for report purposes only.

Test Configuration



Report No.: CTC2025405102

Test Procedure

- 1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- 2. The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to section 10.2 of KDB 558074 D01 DTS Meas Guidance v05r02.
- 3. Spectrum Setting:

Set analyzer center frequency to test channel center frequency.

Set the span to 0Hz.

Set the RBW to 10MHz.

Set the VBW to 10MHz.

Detector: Peak. Sweep time: Auto.

Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.

Test Mode

Please refer to the clause 2.4.

TRF No: CTC-TR-057_A2 For anti-fake verification, please visit the official website of China Inspection And Testing Society: yz.cncaq.com



Test Result

TestMode	Antenna	Frequency[MHz]	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]	1/T Minimum VBW (kHz)	Final Setting for VBW (kHz)
		2412	12.23	12.46	98.15	0.08	1
11B	Ant1	2437	12.22	12.41	98.47	0.08	1
		2462	12.23	12.42	98.47	0.08	1
		2412	1.90	2.06	92.23	0.53	1
11G	Ant1	2437	2.03	2.21	91.86	0.49	1
		2462	2.03	2.15	94.42	0.49	1
		2412	1.89	3.44	54.94	0.53	1
11N20SISO	Ant1	2437	1.90	2.09	90.91	0.53	1
		2462	1.89	2.11	89.57	0.53	1
		2422	0.93	1.10	84.55	1.08	2
11N40SISO	Ant1	2437	0.94	1.16	81.03	1.06	2
		2452	0.93	1.11	83.78	1.08	2
		2412	1.46	1.64	89.02	0.68	1
11AX20SISO	Ant1	2437	1.46	1.65	88.48	0.68	1
		2462	1.46	1.62	90.12	0.68	1
11AX40SISO		2422	0.76	0.92	82.61	1.32	2
	Ant1	2437	0.76	0.94	80.85	1.32	2
		2452	0.77	0.93	82.80	1.30	2



Page 113 of 113 Report No.: CTC2025405102

3.9. Antenna Requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i)

(i) Systems operating in the 2400~2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

Test Result

The directional	l gain of the	antenna is les	ss than 6dBi,	, please refe	r to the EUT	internal photo	graphs an	tenna
photo.								

CTC Laboratories, Inc.

For anti-fake verification, please visit the official website of China Inspection And Testing Society: $\underline{\mathsf{vz.cncaq.com}}$