



User Manual

T1



CONTENTS

CUSTOMER SERVICE	01
INTRODUCTION	02
PRODUCT OVERVIEW	02
PACKAGE CONTENTS	04
SPECIFICATION	05
UNIT STRUCTURE, APPEARANCE & BUTTONS	07
SHORTCUTS & UNDERSTANDING BUTTONS	08
INSTALL YOUR DASH CAM	10
INSTALLATION	11
TURNING YOUR CAMERA ON/OFF	13
MICROSD (TF) CARD	14
Which Memory Card Should I Get?	
Should I Only Get The OMBAR Ultimate Memory Cards?	
INSERTING/REMOVING A MICROSD CARD	15
FORMATTING MEMORY CARD	16
SETTING UP YOUR CAMERA	17
FIRST TIME USE	18
HOME SCREEN	21
LED STATUS INDICATOR	23
UNDERSTANDING 3 – CAMERA MODES	24
1. Recording Mode 2. Playback Mode 3. Setting Mode	

CUSTOMIZING YOUR T1 DASH CAM SETTING	27
PAIRING YOUR T1 WITH YOUR SMART PHONE USING WIFI	29
STEP 1: Search & Install the RoadRec APP	
STEP 2: Sign Up	
STEP 3: Turn the WiFi ON from the OMBAR T1 Settings.	
STEP 4: Getting Started with RoadRec APP	
GPS PLAYER INSTALLATION	38
UNDERSTANDING CAMERA SETTINGS	40
Video Resolution	
Loop Recording	
Video Recording G-Sensor	
PARKING MONITOR (OPTIONAL)	44
24 Hour Parking Monitor How Does It Work?	
Why Do I Need To Purchase an Additional Hardwire Kit?	
How Does The "Timelapse" Parking Monitor Work?	
How Does The "Motion Detection" Parking Mode Work?	
How Does The "Collision Detection" Parking Mode Work?	
What Level Should I Choose For My "Parking Mode G-sensor" Setting?	
ONE-YEAR LIMITED WARRANTY	51
SAFETY & LEGAL ASPECTS	52
TROUBLESHOOTING YOUR OMBAR T1 DASH CAM	54
A HEARTFELT EXPRESSION OF GRATITUDE	58

CUSTOMER SERVICE



Defective or damaged item?
Inaccurate description?
Missing parts or accessories?
Performance or quality not adequate?
Wrong item was sent?



service@ombars.com
Response in just 12 hours

Contact us before returning the item.
We will help you resolve any issue as
soon as possible.

INTRODUCTION

Thank you for purchasing the OMBAR T1 Dash Cam. This product can provide high-quality images and capture indisputable evidence, allowing you to understand what happened from the perspective of the dashboard. The OMBAR T1 Dash Cam is an elegant, convenient and durable vehicle dash cam.

PRODUCT OVERVIEW

This product is an ultra-high-definition digital vehicle recorder with full-color night vision that leads the same category. Equipped with the STARVIS 2 sensor, it has excellent low-light sensitivity and a high dynamic range, enabling you to continuously record high-quality video for playback. Even at night, it can provide extraordinary 4K ultra-high-definition resolution videos without the need for an infrared sensor. It boasts outstanding night vision technology and can shoot excellent videos under all low-light conditions. Moreover, it includes advanced built-in 5G Wi-Fi, built-in GPS, a G-sensor, an emergency video locking button, audio recording, loop recording, wide dynamic range, 24-hour non-stop recording, wide dynamic range, and a 24-hour automatic parking mode trigger, etc. Compared with most dashboard cameras, this uniquely designed product combines elegance with top-notch and unique features, allowing you to record unrivaled and stunning videos, and it is extremely convenient to operate.

WARNINGS

Kindly ensure to read and understand all instructions before using this product. Failure to follow the instructions may result in damage, consequently voiding the warranty.

- Avoid exposing this product to rain, moisture, or water at all costs, as it could lead to external or internal damage. The device is not designed to withstand damp environments.












- Do not attempt to open the cover or repair the device by yourself. For any issues with accessories, contact the seller for assistance.
- Ensure that the unit is not installed in a way that obstructs the driver's view of the road, mirrors, or airbag deployment.
- Refrain from placing the camera loosely on the dashboard or in front of airbags to prevent potential hazards.
- Mount the camera securely to avoid distractions or accidental falls while driving.
- Keep the device away from excessive heat, fire, dust, and avoid using chemicals for cleaning opt for a soft, moist cloth instead.
- Exercise caution when cleaning the lens surface to maintain video quality by using a soft, damp cloth.
- Do not operate or install the camera while driving, including attempting to change any settings. Make sure to pull off the road and do so only when it is safe.
- Handle the product with care and avoid dropping, puncturing, or disassembling it.
- Do not use the charger if the cord is broken or damaged, and keep it out of reach of children.
- Remember that this device is NOT a toy and should be kept away from children. It is intended for indoor use within a motor vehicle.
- Before inserting an external memory card, check for physical damage or cracks. Do not use a damaged memory card, as it can short-circuit and cause issues.

NOTE

In certain countries or states, including some in the USA, regulations prohibit drivers from mounting objects on windshields or in specific windshield areas. It is the responsibility of the owner/operator to ensure compliance with local laws when installing or using this device.

Please note that the company does NOT accept responsibility for any data loss or loss of content that may occur during operation or under any circumstances.

PACKAGE CONTENTS

		
OMBAR T1-DASH CAM ×1	GPS Bracket ×1	
		
Type-C Cigarette Lighter Power Cable(11.5ft/3.5m) ×1	Rear camera ×1	
		
Cable Clips ×5	Car Wire Trim Tool ×1	
		
Electrostatic Sticker ×4	3M Adhesive ×4	
		
User Manual ×1	128GB Memory Card ×1	Wet Cleaning Pads ×2

SPECIFICATION

Model Name	T1
Screen Size	2.0 Inch
Lens Aperture	F=1.8
Color	Black
Language	English/Germany/France/ Italian/Spanish/ Chinese
Video Format	MP4
Photo Format	JPG
Compression Format	H.264(Default)
WiFi	Supports 2.4GHz and 5GHz Dual-Band
GPS	Built-in GPS Geo-Tagging Support
GPS Player	Download GPS Player From www.ombars.com
APP Control	Download Roadrec APP, Free app, Easy control
Video Resolution	3 CHANNEL: 4K+1080P+1080P@30FPS 2K+1080P+1080P@30FPS 2 CHANNEL: 4K+1080P@30FPS 2K+1080P@30FPS 1 CHANNEL: 5K-5210*2160@30FPS 4K-3840*2160@30FPS 2K-1440*2160@30FPS

G-Sensor	Built-in 3-Axis Impact Accelerometer Gravitational Sensor to Lock & Protect Current Video.
Anti Flicker	60Hz, 50Hz
Loop Recording	Support-Seamless Loop Recording
Timelapse Record	Support (1frame per second, fast video playback)
24hr Auto Trigger Parking Mode	Support (OMBAR Type-C Hardwire kit Required, NOT Included)
Memory Card	TF Card Class 10, U3 Speed (Max Support 512 GB)
Mic/Speaker	Built-in Microphone & Speaker
Type-C USB Function	Charging
Battery/Supercapacitor	Built-in Supercapacitor
Power Interface	5V/2.5A
Temperature Guideline	Storage Temperature: -30°C(-22°F) ~ +85°C(185°F) Working Temperature: -20°C(-4°F) ~ +70°C(158°F)

NOTE

1. Please use the OMBAR car charger included in this package.
2. Always connect to power when in use. It has no internal battery, the built-in supercapacitor uses only a 1mAh lithium metal battery for memorize time.
3. We recommend using OMBAR's TF Card or other Class 10, U3 Speed cards for optimal performance. Using third-party or uncertified TF cards can affect the dashcam's performance and may, in some cases, result in random reboots during the recording process.

UNIT STRUCTURE, APPEARANCE & BUTTONS





- 07 -

SHORTCUTS & UNDERSTANDING BUTTONS


	POWER BUTTON	Preview status-short press to turn on/off the screen
		Recording status-short press on/off screen
		View Video-Delete
		View Photo-Delete
	MENU KEY	Long press for 3 seconds to toggle on/off
		Preview Status-Setup
		Recording Status-Emergency Recording Button Yoke
		Emergency recording status-unlock to enter normal recording
		Menu Settings-Return
		Enter playback-return
		Go to folder-Back
		Enter video list-Back
	LEFT BUTTON	View Current Video-Return
		Go to photo list-Back
		View current photo-Back
		Preview Status-WIFI Switch
		Video recording status-short press to take photo/long press to record switch
		Emergency recording status-short press to take photo/long press to record switch
		Menu Settings-Left button
		Go to playback-Left button

- 08 -

	RIGHT BUTTON	Preview status-short press to switch the screen/long press to close the middle of the road
		Record status-short press to toggle the screen/long press to close the center channel
		Emergency Record Status-Short press to toggle screen/long press to close center
		Menu Settings-Right click
		Go to playback-right click
		Go to folder-Right button
		Go to video list-Right button
		View current video-right-click/long-press to fast forward
		Go to photo list-right click
		View current photo-right click
	OK Button	Preview Status-Start Recording
		Recording Status-Stop Recording
		Emergency recording status-stop recording
		Preview Status-Start Recording
		Menu setting-OK key
		Enter playback-OK key
		Enter folder-OK key
		Enter video list-OK key
		Viewing the current video-play/pause
		Go to photo list-OK


INSTALL YOUR DASH CAM

We will walk you through the installation process step by step to make sure your dash cam is installed correctly. We will have a T1 camera installation video available for you to watch by scanning the QR code below. Whether you are a first time user or experienced, this video will provide helpful tips to ease you through the installation process.




INSTALLATION

Install the OMBAR T1 dash cam at the top of the front windshield. Remove any foreign matter and clean and dry the windshield before installation. The OMBAR T1 dash cam comes with default settings, allowing you to start using it right out of the box without any adjustments. Remember to format the memory card before first-time use.



Start the vehicle generator, and do a bench test before officially installing the dash cam: connect the car charger to the cigarette lighter port and the OMBAR T1 dash cam, connect the OMBAR T1 dash cam, and insert the MicroSD card to ensure that the dash cam can work normally.

1. **Installation Position:** Most people will install their OMBAR T1 dash cam next to the rearview mirror, on the opposite side of the driver. First, turn off the engine in a well-lit and safe location, then remove the key.
2. **Insert the microSD card** into the microSD slot of the dash cam and format your SD card for the first time use.
3. Make sure to clean your windshield from dust particles and evaporated grease from the dashboard surface.
4. Then peel off the electrostatic sticker from the cellophane, transfer it to the place you want to stick it,



5. Eliminate the air bubbles on the static stickers. It is recommended to install the dash cam after standing still for half an hour to make the static stickers stronger. Then stick the GPS bracket on top of the electrostatic film.
6. Attach the OMBAR T1 dash cam with the GPS mount. Set the camera lens to point forward to the center when installing it. We suggest angling the lens slightly downward (approximately 10° below horizontal) to achieve a 6:4 ratio of road to background in the recorded videos.
7. Use the power cord to connect the USB Port of the product to the car's cigarette lighter socket.
8. Hide the cable inside the trim and use the included cable clips for additional support to organize the cable if needed so it does not interfere with the driver's vision.
9. Start the engine and check if the product works properly.
10. The device will start up automatically and record as soon as power is supplied, and the device will save the last video file and power off automatically after cutting the power supply.

CAUTION

Make sure to remove the Plastic Lens Screen Protector from the lens before recording videos. Otherwise, your videos will look blurry and blocked. Do not remove the microSD card while the camera is turned ON. Otherwise, it may cause the memory card to be write protected and possible loss of data or damage your memory card. Remove/Insert the memory card only when the camera is turned OFF.

TURNING YOUR CAMERA ON/OFF

AUTO POWER ON/OFF

- **Auto Power On:** The OMBAR T1 Dash Cam is set to turn on and start recording by itself when it gets power, like when you start your car.
- **Auto Power Off:** The camera will automatically turn off a few seconds after it loses power, such as when you turn off your car.

CAUTION

Some trucks and cars have a power outlet that stays on even when the vehicle is off. If this is the case for your vehicle, the auto on/off feature won't work properly. Leaving the camera recording when the car is off can drain your battery, potentially causing starting issues next time. To avoid this, you have two options:

1. Nect your dash cam directly to your car's fuse box using OMBAR's 3-Lead Auto Trigger Hardwire Kit. You can purchase this kit at OMBAR store.
2. Connect your dash cam directly to your car's fuse box using OMBAR T1 3-Lead Auto Trigger Hardwire Kit.

MANUAL POWER ON/OFF

- To turn the camera on manually, press the power button once.
- To turn it off manually, press and hold the power button for about 2-3 seconds.

NOTE

Make sure to insert the memory card before turning on the camera. Don't insert or remove the memory card while the camera is on; only do this when it's turned off.

MICROSD (TF) CARD

WHICH MEMORY CARD SHOULD I GET?

ANSWER:

We strongly recommend OMBAR Ultimate microSD Cards. At OMBAR, We have higher standards, 1-Year Hassle-Free Warranty, and we have specifically designed our memory cards to work with our dash cams. In order to save time, money, and hassle in the long run, we simply recommend our OMBAR Ultimate microSD Cards. See a few details below to understand why?

SHOULD I ONLY GET THE OMBAR ULTIMATE MEMORY CARDS?

ANSWER:

No, you are not restricted to only purchasing OMBAR Ultimate memory cards. You have the flexibility to choose any brand of memory card, provided it meets the specifications of being Class 10 and U3 speed. While we have gathered valuable insights from assisting customers with troubleshooting over the years, it's important to acknowledge that opting for a different brand may carry uncertainties regarding quality and longevity.

Typically, return policies expire within 30 days of purchase. If an alternative branded memory card malfunctions after a few months, handling the warranty process rests with the respective manufacturer, and their level of assistance during replacement cannot be assured. With this in mind, to simplify the decision-making process and avoid potential complications, we now recommend our OMBAR Ultimate microSD Card. Upholding superior standards at OMBAR, we aim for seamless functionality between your camera and memory card, ensuring a hassle-free experience. Ultimately, our goal is to provide you with peace of mind, allowing you to focus on more significant aspects of life rather than grappling with memory card choices.

INSERTING/REMOVING A MICROSD CARD

1. With your dash cam turned off, insert the card into the slot with the label facing the back of your dash cam. You can remove the card by pressing it into the slot with your fingernail.
2. A MicroSD card (available for separate purchase) is required to store your videos and photos. Use a dedicated U3 Class 10 SD card; otherwise, your dash cam may experience malfunctions.
3. Over time, MicroSD cards may deteriorate and impact your dash cam's ability to save your media. If you encounter any issues, consider replacing an older card with a new one.



CAUTION

Do not insert or remove the microSD card while the camera is turned ON. Otherwise, it may cause the memory card to become write-protected, potentially resulting in data loss or damaging your memory card. Always remove or insert the memory card while the camera is turned OFF.

FORMATTING MEMORY CARD

1. Press **OK** to STOP video recording first or to clear the error message. If you have any on the screen.
2. Please press the **Menu** button once to enter the System Settings.
3. Then press the **Left** button to scroll down until you see Format SD card >> Then press the **OK** button to enter format submenu >> Then press the **Right** button to select Yes >> Then press **OK** the button to confirm to format the memory card (The formatting process will be super quick.).




NOTE

1. We recommend formatting the memory card every month (default) to ensure smooth operation and maintain cleanliness.
2. Please be aware that memory cards have a limited lifespan. With continuous data writing, they may eventually become inoperable. In such cases, we suggest replacing your memory card.

SETTING UP YOUR CAMERA

POWERING ON

Short press the  button to turn on your OMBAR T1 dash cam.



POWERING OFF



Press and hold the  button for 3 seconds to turn it off.

FIRST TIME USE

For first time setup, use this menu to set the preferred language, time zone, date and time, speed units, and memory card format. Press the OK button to proceed to the next step.



Language Setup Interface:
The default setting is English. Press the  button to move downwards to select your preferred language. Press "OK" to confirm the selection, then proceed to the date and time setup interface.

Time Zone Setting Interface:
To set the date & time, choose one of the following options below.

1. You can manually select your preferred date and time settings by accessing System Settings > Date/Time. Alternatively, you can opt to set the GMT time-zone value.
2. This way, the camera will automatically adjust the date and time based on the selected GMT value once it receives a GPS signal lock.




USA Time Zones - GMT (Greenwich Mean Time) Values

USA Time Zones - GMT (Greenwich Mean Time) Values		
Time Zones	When DayLight Savings Ends Nov - March	When DayLight Savings Begins March - Nov
Hawaii	GMT (-10:00)	
Alaska	GMT (-9:00)	GMT (-8:00)
Pacific Time Zone	GMT (-8:00)	GMT (-7:00)
Mountain Time Zone	GMT (-7:00)	GMT (-6:00)
Central Time Zone	GMT (-6:00)	GMT (-5:00)
Eastern Time Zone	GMT (-5:00)	GMT (-4:00)

Go to <https://greenwichmeantime.com/time-zone/usa/to> to find out your Correct GMT (Greenwich Mean Time) value based on your location outside of the USA.


NOTE

1. The dash cam will automatically synchronize the time after connecting to the phone.
2. The time zone setting does not automatically adjust the time when travelling through different time zones. It will solely ensure the precise date and time based on the chosen GMT time zone.

Date and Time Setup Interface: Press the  button to increase parameters or the  button to decrease parameters to adjust the date and time. After completing the settings, press  to confirm the selection, then proceed to the speed setup.




- 19 -

Speed Setup Interface: Select the desired speed unit, press the  to confirm the selection, and proceed to the formatting setup.



Formatting Interface:

Select "YES" and press the  button. After formatting is complete, the main interface will automatically open, and recording will start after 15 seconds.



- 20 -

HOME SCREEN



Recording interface



Emergency recording interface



Non-recording interface

ICONS	WHAT DOES IT MEAN?
	Emergency Video Lock
	Microphone ON/OFF
	Take a Snapshot
	White: Stop Video Recording
	Yellow: Stop Emergency Recording

	Enter the Menu
	WiFi On/Off
	Enter the Playback Mode
	Red LED Blinking: Recording Video No Red LED: Not Recording Video
	Red: Displays the recording status and recording time.
	White: Displays the remaining recording duration
	Yellow: Displays the emergency recording status and emergency recording time.
	Red GPS: Signal Present, No Positioning White GPS: No Signal, No Positioning Green GPS: Signal Present, Positioning Available
	Video Resolution
	Parking Monitor-Time-lapse ON
	Parking Monitor-Motion Detection ON
	Parking Monitor-Collision Detection ON
	Headlight Reminder ON
	Wide Dynamic Range (WDR) ON
	Loop Recording ON (1min/3mins/5mins per file)
	Microphone ON/OFF
	WiFi ON/OFF

LED STATUS INDICATOR

DIFFERENT SCENARIOS



When camera is plugged into the POWER

Indicator Light Color	Status Description
BLUE LED	It remains lit during normal recording.
RED LED	Stays illuminated during abnormal situations (including emergency recording, crashes, memory card errors, etc.).

UNDERSTANDING 3 – CAMERA MODES

OMBAR T1 Dash Cam has 3 different camera modes:

1. RECORDING MODE
2. PLAYBACK MODE
3. SETTING MODE

1. RECORDING MODE

Recording mode lets you record live videos and store them on the installed microSD card.



While in the Recording Mode:

- Short press the button to lock and unlock the screen.
- Press the while video is being recorded to manually lock the video, so it will not get deleted by loop cycle function.
- Press the button Once to Mute/UN-Mute Microphone while in Video Mode
- Press the button Once to take a snapshot while in Video Mode
- Press the button to Start/Stop video recording manually.

2. PLAYBACK MODE

Playback mode lets you play your Video file or photos.



- Press the **OK** button first to stop video recording or clear the error message, then press the **▶** button to ENTER PLAYBACK MODE.
- Select the folder you want to view (Normal Video/Emergency File/Photo)

While in the Playback Mode:



- Press the **◀** button to Back
- Press the **▶** button to Play/Pause video.
- Press the **▶** button to Delete current video.
- Press the **OK** button to scroll to Next video file.

3. SETTING MODE

Setup mode enables you to customize all desired settings. Press the **OK** button first to stop video recording or clear the error message, then press the **⚙** button to SETTING MODE.

While in the Setting Mode:



- Press the **⏮** button to BACK
- Press the **⏪** button to Scroll UP
- Press the **⏩** button to Scroll DOWN
- Press the **OK** button to CONFIRM

CUSTOMIZING YOUR T1 DASH CAM SETTING

Setting Interface Page 1

Playback: Normal video/Emergency file/Photo

Resolution:

Single Recording Mode

5K/4K/2K

Front+Internal Mode

4K+1080P

2K+1080P

Front+Rear Mode

4K+1080P

2K+1080P

Triple Recording Mode

4K+1080P+1080P

2K+1080P+1080P

Mirror settings: Rear Camera On/Off

Loop recording: 1/3/5mins

WDR: ON/OFF

EV(Exposure Value): +2.0, +1.7, +1.3,

+1.0, +0.7, +0.0, -0.3, -0.7, -1.0, -1.3,

-1.7, -2.0

Frequency: 60Hz/50Hz

G-Sensor (Gravity Sensor):

OFF/Low/Medium/High

WiFi: WIFI ON/OFF

SSID: T1-XXXXX

Password: 12345678

GPS: GPS ON/OFF > Speed

Units > KM/H&MPH



Setting Interface Page 2

Time Zone: You can choose the time zone you want.

Screen Saver: 1/3/5Mins/OFF

Volume Setting: Beep Sound ON/OFF

System Volume > 100%/70%/50%/OFF

Video Playback Sound >

100%/70%/50%/OFF

Voice Recording:

Sound Recording ON/OFF

Language:

Choose Your Prefer Language

Headlights Reminder: ON/OFF

Power Indicator Settings: ON/OFF

Fatigue Driver Alert: 1/2/4 Hours/OFF

Parking Monitor: Time-lapse/Parking

Mode/OFF

Date/Time: Set time and date



Setting Interface Page 3

Model NO.: This feature will allow you to insert a custom vehicle ID or Driver ID to be stamped on video.

Video Stamp:

You can select Date & Time/Speed/Brand/Model No./Coordinates to be displayed in the downloaded video.

Delete Videos Reminder: ON/OFF

Format Reminder: 15/30/60 Days/OFF

Format SD Card: All Date Will Be Deleted

Default setting: Restore all settings to the factory state

Card Storage Capacity:

You can see the storage space of the memory card

About: You can view the current system version



NOTE

1. For a clean, smooth, and comfortable user experience, it is recommended to format your MicroSD card once a month.
2. If there is no GPS signal or if the GPS signal is available but the timestamp is not activated, you will be unable to view the real-time vehicle route.
3. The dash cam features an integrated GPS function, allowing it to automatically update the time based on your location and time zone, eliminating the need for manual time adjustments. Daylight saving time can be adjusted through DST settings.

PAIRING YOUR T1 WITH YOUR SMART PHONE USING WIFI

STEP 1: Search & Install the RoadRec APP

Search for "RoadRec" in App Store or Google Play Store to find the App and then download and install it on your phone



NOTE

OMBAR T1 WiFi Connection pairing does NOT provide internet access. The WiFi Connection to OMBAR T1 is intended for transferring data between your phone and the OMBAR T1 dash cam.

STEP 2: Sign Up (For First Time Users Only), Skip this step if you already have an account

IMPORTANT:

Do NOT Connect your iOS/Android device to OMBAR T1 WiFi yet.

FIRST-TIME USERS:

A mobile app login screen with a blue header and a white body. It includes a "Guest mode" toggle at the top right. The main form has fields for "Email" and "Password", each with a "Please enter" placeholder. Below the password field is a checkbox for "I have read and agreed to the Terms Agreement and Privacy Agreement". A "Login" button is at the bottom, with "Register" and "Forgot the password" links below it.A mobile app "Forgot the password" screen with a blue header and a white body. It includes a close button (X) at the top right. The form has fields for "Email", "New password", and "Verification code", each with a "Please enter" placeholder. A "Submit" button is at the bottom.



You will need to register and create a free account using RoadRec APP, so you can keep your videos and data secure on your device. (To register-you will need internet access, so make sure to stay connected to the internet using your home wifi or cellular data while registering for the first time) - You will only need to do this once. You should stay logged in to your RoadRec account mostly unless you get logged out.

If you ever need to sign back into your RoadRec account again, then you will need to be connected to the internet first, then login to your account before pairing with OMBAR T1 WiFi.

STEP 3: Turn the WiFi ON from the OMBAR T1 Settings.

CONNECTING OMBAR T1 DASH CAM WITH SMART PHONE:



1. **TURN ON WIFI FROM THE CAMERA:** Press the  button briefly on the preview screen (the main screen when not recording) to access the Wi-Fi interface and turn on Wi-Fi.
2. Now open the RoadRec app on your smartphone, and click on the "Connect Dash Cam WiFi" button. This will open up your smartphone's Wi-Fi setting now; look for a Wi-Fi network named "DC-T1-*****" on the lists.


Wi-Fi Credentials	
WiFi Name SSID	DC-T1-*****
Default Password	12345678

3. Join the "DC-T1-*****" network using a default password displayed on your dash camera's screen.
(Default Password: 12345678)
4. Once your smartphone is connected to the OMBAR T1 Dash Cam WiFi, return to the RoadRec app. Select your dash cam model and proceed to establish the connection. You will then view the live video feed from the camera on the main home screen of the RoadRec app. You are now ready to access your recordings through the RoadRec app and delve deeper into them.


Wi-Fi CONNECTION

For Android phones:

For the initial setup, there is an additional step required. Upon connecting to OMBAR T1 Dash Cam WiFi, you may receive a "No internet" message, which is normal. Wait for about 10-15 seconds until you see a popup or notification. Simply tap on the notification that appears to confirm your desire to remain connected despite the lack of internet access. Once you select "OK", you are ready to proceed. Feel free to reach out if you require any assistance.



For iPhone:



When using an iPhone, you may encounter a message stating "No Internet Connection", which is expected and can be disregarded. Since the OMBAR T1 Dash Cam does not offer internet access, this message will appear on your iPhone. You are simply establishing a connection between your iPhone and the OMBAR T1 Dash Cam via Wi-Fi. Once you see this ✓ blue Check Mark, indicating the connection to the OMBAR T1 Dash Cam's Wi-Fi, you can proceed to open the RoadRec APP.

STEP 4: Getting Started with RoadRec APP


How to View, Download and Delete Video

1. Saving to the App:
Ensure your phone is connected to the OMBAR T1 dash cam. Click "Camera Files" on the homepage to access the Camera Files interface. Tap "Select" in the upper right corner to choose your desired video or photo. Finally, tap "Download" at the bottom of the interface to save it to the "Album" within the app.
(Note: This step saves exclusively in the app and not in the phone's native album).
2. Download videos and photos from the app to your phone:
Check that your desired videos and photos are saved in the "Album" section. Access the album interface by tapping "Album" at the bottom. Here, you can view the saved media. Start by selecting "Select" in the top right corner, then select the photos and videos you want. Once you have made your selections, click on 'Download' at the bottom of the interface to save them to your phone.
3. Deleting videos and photos:
In the "Album" interface, begin by clicking on "Select" in the top right corner, then choose the photos and videos you wish to select. After making your selections, click on "Delete" at the bottom of the interface to remove them.




CAUTION

Saving photos and videos requires TWO steps, first save from "Camera Files" to Album, then save from "Album" to your phone album.




How to customize DASH CAM settings via RoadRec APP

1. First, enter the main interface after connecting to the dashcam.
2. Click on "Settings" in the top right corner.
3. In the main interface of "Settings" you can customize your settings, and these settings will sync to your OMBAR T1 dash cam.



How to View Maps and GPS Tracks on the phone


1. First, ensure that your dash cam has a GPS signal and enable the GPS stamp.
2. Next, select the video you wish to watch and download.
3. Return to the app's home page and choose the **Album**.
4. Open the video and enjoy watching it.



GPS PLAYER INSTALLATION

How to View Maps and GPS Tracks on the Computer

1. Download the FREE GPS player from www.ombars.com > Support > Downloads and install it on your computer.
2. Install the OMBAR GPS player on your computer.
(Note: Please close or ignore any prompts from the antivirus software; we assure you that it will not pose any security risks to your computer.)
3. Connect your dashcam to the computer using a USB Type-C port, or remove the microSD card from the dashcam. Then, insert the card into the microSD card reader and connect it to a computer.
4. Click the "Open Files" button to navigate to and select the Movie or EMR folder on the microSD card within the GPS player interface. This will display all files in the normal, event, or parking folders.
5. Select "My Computer" and locate the memory card disk. Choose the video file you wish to play, then drag and drop the file directly into the player. You can access GPS information through the GPS player.




(Subject to the actual updated GPS player)



Why GPS Player? What are the features?

1. Play back your recorded videos
2. Check G-Sensor data
3. To see the Exact GPS route with the video on google maps
4. Check driving speed
5. Check driving direction (i.e. N, S, NW, SE, etc.)



UNDERSTANDING CAMERA SETTINGS

Short press the button to enter the setting interface after powering on. In this scenario, video recording will stop, and you will access the Settings Menu.

Attention: To EXIT the Settings Menu, press the button to go back.

VIDEO RESOLUTION

You can choose the video resolution you like. Higher-resolution videos will take up more storage space.

Single Camera Recording

5K: 5120*2160@30fps

4K: 3840*2160@30fps

2K: 2560*1440@30fps

Dual Camera Recording

4K+1080P: 3840*2160+1920*1080@30fps

2K+1080P: 2560*1440+1920*1080@30fps

Triple Camera Recording

4K+1080P+1080P: 3840*2160+1920*1080+1920*1080@30fps

2K+1080P+1080P: 2560*1440+1920*1080+1920*1080@30fps

Below are the estimations of how much time is stored on the memory card in the loop feature:

MEMORY CARD CAPACITY	RESOLUTION	RECORDING TIME
512G-Three Minute Loop Recording	5K P25 resolution	Recordable Duration: 406H 47mins
	4K P25+1080 P25 (front + inside) resolution	Recordable Duration: 33H 51mins
	4K P25+1080 P30 (front + rear) resolution	Recordable Duration: 81H 21mins
	4K P25+1080 P25+1080 P30 Resolution	Recordable Duration: 25H 25mins
256G-Three Minute Loop	5K P25 Resolution	Recordable Duration: 202H 30mins
	4K P25+1080 P25 (front + inside) resolution	Recordable Duration: 16H 50mins
	4K P25+1080 P30 (front + rear) resolution	Recordable Duration: 40H 27mins
	4K P25+1080 P25+1080 P30 Resolution	Recordable Duration: 12H 38mins
256G-Three Minute Loop	5K P25 Resolution	Recordable Duration: 100H 56mins
	4K P25+1080 P25 (front + inside) resolution	Recordable Duration: 8H 23mins
	4K P25+1080 P30 (front + rear) resolution	Recordable Duration: 20H 10mins
	4K P25+1080 P25+1080 P30 Resolution	Recordable Duration: 6H 17mins
64G-Three Minute Loop	5K P25 Resolution	Recordable Duration: 48H 44mins
	4K P25+1080 P25 (front + inside) resolution	Recordable Duration: 4H 3mins
	4K P25+1080 P30 (front + rear) resolution	Recordable Duration: 9H 44mins
	4K P25+1080 P25+1080 P30 Resolution	Recordable Duration: 3H 2mins

This is an approximation, with variations depending on the memory card. Lower resolutions will allow for more storage capacity, while higher resolutions will require more space.

LOOP RECORDING

This feature enables the camera to continuously record in loops, deleting the oldest video files automatically when the memory card reaches capacity, eliminating the need for manual deletion. Each video file is split into appropriate lengths based on your selection.

1 min	3 mins(Default)	5 mins
-------	-----------------	--------

IMPORTANT

The logic for the loop recording feature is as follows:

Let's assume that the total capacity of the memory card is 100%. When the combined normal and emergency videos exceed 90%, the dash cam will initiate loop recording.

The pre-allocation of directory space for normal and emergency videos is as follows: Normal Videos = 60%, Emergency Videos = 30%. If the number of emergency files is less than 30%, normal video files can utilize the unused emergency file allocation space until it reaches 90%, triggering loop recording.

In the presence of more emergency (Locked) video files, the emergency file directory space is reserved up to a maximum of 30%. If emergency files reach their maximum allocation of 30%, the camera will delete the oldest emergency (Locked) video files to accommodate the new latest emergency video. Therefore, it is important to understand that you cannot lock an unlimited number of videos on your memory card. If you lock any important video files, please be aware that even locked videos will be deleted following the loop cycle function, starting with the oldest file. If an event occurs and your locked video allocation is depleted, ensuring free space for a new locked emergency video in case of a real incident is crucial.

NOTE

We recommend downloading any emergency (Locked) videos immediately to prevent them from being deleted.

VIDEO RECORDING G-SENSOR

The G-Sensor is a three-axis accelerometer that detects physical impacts and gravitational forces acting on the camera.

While Video is Being Recorded: When the G-Sensor is triggered by a physical or gravitational impact force on the camera, the current loop cycle length of the video file in the emergency folder will be locked to prevent it from being deleted by the regular loop cycle function.

CAUTION

In the event of an accident, please ensure to retrieve your footage before using your camera again to prevent the loss of important video files due to the loop cycle function. This is crucial in case the force was minor and did not trigger the G-Sensor to lock the video file automatically. It is a best practice and highly recommended to retrieve all necessary video footage after any emergency of an accident before using your camera to prevent the loss of vital video files.

PARKING MONITOR (OPTIONAL)

OMBAR has custom-designed its parking monitor for the best user experience and automation. Please see the details below.

1. OMBAR Ultimate USB Type-C Hardwire Kit is not included and must be purchased separately.
2. Hardwire Kit is needed only when using Parking Monitor.
3. If Parking Monitor is desired, contact OMBAR to purchase.

CAUTION

Never connect the dash cam directly to your car's 12/24V battery by modifying wires. The dash cam is not designed to handle direct current from the battery. It needs a step-down circuit in the middle (Hardwire Kit) to adjust the current required by the dash cam. You must connect the dash cam using the OMBAR Ultimate USB Type-C Hardwire Kit and connect it to the car's fuse box (NOT to the battery terminals directly).

NOTE

The camera is equipped with a built-in temperature sensor. In hot and sunny afternoons, especially when the car is parked under direct sunlight, the interior temperature of the car can rise significantly due to the greenhouse effect. Depending on your location, this temperature increase may surpass the recommended operating limits for the camera. In such situations, the camera will automatically shut down to prevent any damage and ensure a longer product lifespan.

24 HOUR PARKING MONITOR HOW DOES IT WORK?

ANSWER:

OMBAR T1 includes a built-in Parking Mode feature that allows you to record in three different ways after parking your vehicle.



Before delving into specifics, it's important to NOTE that the OMBAR Ultimate USB Type-C Hardwire Kit is necessary for the parking mode to function.

WHY DO I NEED TO PURCHASE AN ADDITIONAL HARDWIRE KIT?

1. To enable the 24-hour parking monitor, you must supply power to your dash cam even when you are away from your vehicle. Hardwiring your dash cam to the car's fuse box is essential for providing power, and please note that the OMBAR Ultimate USB Type-C Hardwire Kit is NOT included in the packaging and must be purchased separately.
2. We acknowledge that not all users may require the hardwire kit for their particular installation requirements. Excluding it from the default packaging helps us maintain cost efficiency and reduce electronic waste, thereby addressing environmental concerns related to unnecessary accessories.
3. The hardwire kit also monitors the battery voltage and is programmed to disconnect power to the dash cam upon detecting low voltage. This feature is aimed at conserving sufficient power in your car's battery for your next startup.

HOW DOES THE "TIMELAPSE" PARKING MONITOR WORK?

Time-Lapse (See how this feature works)

1. When this feature is set to ON and the OMBAR Ultimate USB Type-C Hardwire Kit is properly installed.
2. Then, when you turn OFF the car's engine and turn the key to the lock position.
3. Then the camera will STOP the continuous video recording and it will go into the timelapse 1fps recording mode automatically.
4. Now, during the timelapse recording, if your car is hit and the impact reaches the set G-Sensor level, the camera will pause the timelapse video. It will then start recording a 1-minute continuous video, save and lock it in the EMERGENCY FILE, and afterward resume timelapse recording.

NOTE

When the Parking Monitor is activated, the camera will provide a voice alert stating "The parking mode got activated while you were away. Check the Emergency File to see what happened" when you start your car next time. If you hear this alert, it is recommended to check the EMERGENCY FILE to review what occurred.

5. The next time you start your car, the camera will automatically STOP the timelapse 1fps and G-Sensor parking mode. It will then switch back to normal video mode automatically to begin continuous video recording.

HOW DOES THE "MOTION DETECTION" PARKING MODE WORK?

Motion Detection (See how this feature works)

1. When this feature is turned ON and the OMBAR Ultimate USB Type-C Hardwire Kit is correctly installed.
2. Then, when you turn OFF the car's engine and turn the key to the lock position.
3. Then the camera will STOP the continuous video recording and switch to motion detection mode. The camera will remain ON and idle, but the SCREEN will turn OFF after a few seconds.
4. Now the camera will only record video when it detects motion within the field of view of the camera. It will continue recording until no more motion is detected.
5. While the camera is in Motion Detection mode, if your car is hit and the impact reaches the set G-Sensor level, the camera will pause the motion detection mode. It will then begin recording a 1-minute continuous video, save and lock that video in the Emergency File section, and finally resume the motion detection mode.

NOTE

When the Parking Monitor is activated, the camera will provide a voice alert stating "The parking mode got activated while you were away. Check the Emergency File to see what happened" when you start your car next time. If you hear this alert, it is recommended to check the EMERGENCY FILE to review what occurred.

6. The next time you start your car, the camera will automatically STOP the timelapse 1fps and G-Sensor parking mode. It will then switch back to normal video mode automatically to begin continuous video recording.

HOW DOES THE "COLLISION DETECTION" PARKING MODE WORK?

Collision Detection (See how this feature works)



1. When this feature is turned ON and the OMBAR Ultimate USB Type-C Hardwire Kit is correctly installed.
2. Then, when you turn OFF the car's engine and turn the key to the lock position.
3. Then the camera will STOP the continuous video recording and switch to collision detection mode. The camera will remain ON and idle, but the SCREEN will turn OFF after a few seconds.
4. Now, if your car is hit and the impact reaches the set "G-Sensor" level, the dash cam will activate and start recording a 1-minute video. Subsequently, it will save and lock that video in the EMERGENCY FILE before turning off.
5. The dash cam will continue to monitor for any impacts until another event occurs, such as a subsequent impact or until you start your car's engine.
6. However, let's say No One hits your car, and if the "Parking Mode G-Sensor" didn't get activated, you will NOT get any parking mode alert.
7. If you need to watch the activated parking mode videos, you will find them under the EMERGENCY FILE.

WHAT LEVEL SHOULD I CHOOSE FOR MY "PARKING MODE G-SENSOR" SETTING?



ANSWER:

This varies depending on different factors and personal preferences. Let's explore some of the most common scenarios to help you make an informed decision.

You have the option to choose between OFF/Low/Medium (Default)/High levels for the Parking Mode G-Sensor setting.



G-Sensor-HIGH Level

If you set your parking mode G-Sensor to the HIGH level, the dash cam will be highly sensitive. Even minimal vibrations, like closing the car's door, can trigger the OMBAR T1 dash cam. Opt for this setting if you prefer your dash cam to activate with even the slightest impact on the car.

- 49 -

However, there are drawbacks to consider. Your dash cam may trigger even when simply closing the car's door as you exit the vehicle, resulting in false alerts of the parking mode being activated. On the positive side, it means that your car/dash cam is responsive to minor bumps or impacts on your vehicle.

G-Sensor-LOW Level

If you set your parking mode G-sensor to the LOW level ensures that false alerts are not triggered by actions such as closing your car door, preventing inaccurate signals. When valid alerts are received, reviewing the last locked videos allows you to investigate unexpected events effectively, given the absence of false alarms.

However, this adjustment may lead to reduced sensitivity of your dash cam towards minor bumps or impacts, potentially causing you to overlook smaller events. On a positive note, if you utilize features like time-lapse with collision detection, your parking mode time-lapse videos are stored in regular folders. This setup enables you to review these videos when investigating potential incidents like someone hitting your car. We hope this explanation is clear and helpful to you.

NOTE

In conclusion, the sensitivity setting of the G-Sensor depends on various factors and personal preferences. The system default G-Sensor sensitivity is set to medium. If this does not meet your requirements, you can manually adjust the G-Sensor sensitivity to high or low.

- 50 -

ONE-YEAR LIMITED WARRANTY

OMBAR dash cam provides a worry-free warranty for one year. For any dash cam-related concerns, feel free to reach out to us. Our dedicated after-sales team is available online for 12 hours each day to assist you.

Warranty Terms Conditions:

1. The warranty is confined to the first purchaser of the product and is not transferable.
2. Service and repairs during the warranty period shall be carried out by company-authorized personnel only.
3. It is the responsibility of the purchaser to bring the product to the authorized service center at their cost and risk.
4. The company will not be liable for any hardware and/or data loss arising from the use of any third-party software, whether downloaded or otherwise.
5. In case of any physical damage to the product and/or misuse detected by the authorized service center personnel, the warranty will be void. Subsequent service/repairs will be conducted on a chargeable basis only and subject to part availability.
6. Under this warranty, the company's obligations are limited to repair or replacement of parts. In the event of a claim, the maximum claim amount will depend on the highest retail price or purchase price of the product (whichever is lower) and requires presentation of the original proof of purchase.
7. During the warranty period, if unforeseen circumstances arise where spare parts are unavailable, a commercial solution will be calculated based on the company's current depreciation rules for repair substitution, binding the purchaser.
8. The replaced unit will either be new or refurbished depending on availability. If we have ceased production of the current model, we reserve the right to upgrade you to the latest version, regardless of similarity.

SAFETY & LEGAL ASPECTS

ISED Notice

This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference.
 - (2) This device must accept any interference received, including interference that may cause undesired operation of the device.
- The digital apparatus complies with Canada ICES-3

(B)/NMB-3(B).

Cet appareil contient des émetteurs/récepteurs exemptés de licence qui sont conformes aux RSS exemptés de licence d'innovation, sciences et développement économique Canada. Le fonctionnement est soumis aux deux conditions suivantes:

- (1) Cet appareil ne doit pas causer d'interférences nuisibles, et
- (2) Cet appareil doit accepter toute interférence reçue, y compris les interférences susceptibles de provoquer un fonctionnement indésirable de l'appareil.

L'appareil numérique est conforme au Canada ICES-3 (B)/NMB-3(B).

This device complies with exemption from the current assessment limits in section 6.6 of CNR - 102 and RSS 102 RF exposure compliance, users can obtain Canadian data on RF field exposure and RF field exposure. This equipment complies with Canada radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum 20cm distance from a radiator or your body. This transmitter must not be co-located or operate in conjunction with any other antenna or transmitter.

Cet appareil est conforme à l'exemption des limites d'évaluation courante dans la section 6.6 du cnr -102 et conformité avec RSS 102 de l'exposition aux RF, les utilisateurs peuvent obtenir des données canadiennes sur l'exposition aux champs RF et la conformité. This equipment complies with Canada radiation exposure limits set forth for an uncontrolled environment. Cet équipement doit être installé et fonctionner à au moins 20cm de distance d'un radiateur ou de votre corps. Cet émetteur ne doit pas être co-localisé ou fonctionner en conjonction avec une autre antenne ou un autre émetteur.

FCC STATEMENT

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation.

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

RF warning:

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.

TROUBLESHOOTING YOUR OMBAR T1 DASH CAM

QUESTION: The dash cam won't power ON.

ANSWER:

1. Use a different Type-C USB data cable and USB charger. Now plug it into a 110V outlet in your home.
2. Once plugged in, the camera should power on. If it doesn't, press the power button once to see if it turns on. If it still doesn't power on, remove the memory card. Keep the camera connected to power. Now, using a pen tip or paperclip, press the reset button once (located at the bottom side). The dash cam should turn on now. If it still doesn't turn on, please contact us.

QUESTION: Dash cam gets HOT.

ANSWER:

It is normal for your camera to become slightly warm. The dash cam may heat up while recording videos at high speeds.

QUESTION: Unable to activate Parking Monitoring mode.

ANSWER:

OMBAR Ultimate USB Type-C Hardwire Kit is NOT Included in the packaging. Purchase separately. Once you've ensured that the OMBAR Ultimate USB Type-C Hardwire Kit is installed correctly, navigate to the settings interface and select your preferred parking monitoring mode under the parking monitor function to activate this feature.

QUESTION: I can't find my oldest video files.

ANSWER:

Your OMBAR T1 Dash Cam features Loop Cycle Recording. When set to intervals of 1, 3, or 5 minutes, it automatically deletes the oldest files to make space for newer recordings when the memory card reaches full capacity.

QUESTION: I want the dash cam to automatically lock more videos.

ANSWER:

Please adjust your G-sensor setting to a higher sensitivity level. This adjustment should align with the type of vehicle you drive and the level of vibrations it produces due to factors like suspension and road conditions.

QUESTION: The microSD card is misaligned or not inserting smoothly into the slot.

ANSWER:

Please ensure that you align the microSD card correctly with the gold contacts facing towards the screen.

QUESTION: The video is blurry.

ANSWER:

Please ensure that the camera lens is clean and there is no dirt or grease on the windshield. If the lens appears to be out of focus, we sincerely apologize for any inconvenience. This could potentially be a manufacturing defect. Kindly send us an email with a screenshot or a sample video so that we can address and resolve this issue for you promptly.

QUESTION: The dash cam displays "Please Insert microSD Card" or "Memory Error" even though the memory card is already inserted in the camera.

ANSWER:

1. Ensure that you are using a memory card of at least Class 10, U3, purchased from a reliable source. Be cautious of fake cards available online, as cheaper prices often indicate counterfeit products.
2. Next, access the system settings on your dash cam and proceed to format the memory card or use the RoadRec app for formatting. Remember to back up your videos before formatting.
3. After formatting the memory card, hold down the power button to switch off the camera. Disconnect the power cable, then reconnect it. The camera should automatically power on and start recording.

QUESTION: The camera is turning on and off frequently by itself.

ANSWER:

1. Ensure that you are using a memory card of at least Class 10, U3, purchased from a reliable source. Be cautious of fake cards available online, as cheaper prices often indicate counterfeit products.
2. Please reset your camera or attempt to update the firmware using the RoadRec app to resolve the issue. If the problem continues, kindly reach out to customer service for further assistance.

QUESTION: Why is it that I downloaded it but it is not in my phone album?

ANSWER:

Saving photos and videos requires two steps, first save from "Camera Files" to Album, then save from "Album" to your phone album. (Please refer to page 35 for details)

QUESTION: Camera is experiencing freezing, lagging, or crashing issues.

ANSWER:

Please trust us. If your camera freezes, lags, or stops recording after a few seconds during operation: it's most likely due to the memory card. The card you are using could be incorrect, fake, or defective. (Please be cautious of counterfeit products on the market as they can appear identical to genuine ones. Trust us, we have encountered numerous issues with memory cards. We take responsibility for our products and conduct extensive testing. Some customers may simply believe that the camera is faulty or unstable, but that is not the case. It is a memory card issue. Please contact us, and we will resolve this matter promptly.)

AGREEMENTS

Upon purchasing the OMBAR T1 Dash Cam, you are deemed to have consented to all terms and conditions governing the warranty, warnings, and precautions. If you do not agree with any of these terms for any reason, you may return the unused product in its original packaging within the designated return period to receive a full refund.

A HEARTFELT EXPRESSION OF GRATITUDE!!

We are truly grateful for your purchase of our OMBAR T1 dash cam. Your decision to choose our product means the world to us, and we sincerely hope it brings both utility and joy into your life.

In the event that you encounter any challenges during setup, please don't hesitate to reach out to us at service@ombars.com. We've got your back! Rest assured that nearly 99% of setup issues can be swiftly resolved, ensuring you're back on the road in no time.

Should there be a rare instance where our assistance falls short, we stand ready to offer you a hassle-free refund. Our ultimate goal is to see you delighted and proud to use your OMBAR Dash Cam!

While perfection may be elusive, our commitment to providing you with exceptional customer service remains unwavering. Your satisfaction is our priority, and we promise to go above and beyond to serve you with excellence.

Every detail of our user manual has been crafted with care. If you come across any inaccuracies or have suggestions for improvement, please share them with us. For the most current and updated user manual, along with other valuable content, be sure to check our website regularly.

Please note that upgrades to the dash cam, firmware updates, and changes to box contents may occur without prior notice. Visit our website anytime to access the latest information and stay informed about all things OMBAR.

Once again, thank you for choosing OMBAR. Your trust in our brand is what drives us to continually improve and provide you with top-notch products and service. We look forward to supporting you on your journey with OMBAR.