

FCC ID:2BM8S-3280A123

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is $<$ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BT:

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-13.78	0.04	-13±1	-12.00	0.06	<5	0.01956	3.00	YES
	2.441	-13.15	0.05	-13±1	-12.00	0.06	<5	0.01972	3.00	YES
	2.480	-13.07	0.05	-13±1	-12.00	0.06	<5	0.01987	3.00	YES

BLE:

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK 1Mbps	2.402	-13.60	0.04	-13±1	-12.00	0.06	<5	0.01956	3.00	YES
	2.44	-12.98	0.05	-12±1	-11.00	0.08	<5	0.02482	3.00	YES
	2.480	-12.98	0.05	-12±1	-11.00	0.08	<5	0.02502	3.00	YES

Conclusion:

For the max result : 0.2502 W/Kg \leq FCC Limit 3.0 for 1g SAR.

The Product unsupported at the same time to Transmitting.