

RF Exposure Report

1. RF Exposure Evaluation of EUT

1.1. Exposure conditions for standalone operations

Antenna Gain: -2.70 dBi

Max. transmitting Frequency: 917.5 MHz

Min. test separation distance: 5

Max. Power with tune up tolerance: 2 dB = 1.58 mW (Typical Power = Max 2 dB)

KDB 447498 D01 clause 4.3.1

Step 1) SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] ·
[$\sqrt{f(\text{GHz})}$] ≤ 3.0 for 1g SAR and ≤ 7.5 for 10g extremity SAR

Type of Modulation	Frequency [MHz]	Output Power [dBm]	Target Power [dBm]	Allowed Tolerance [dB]	Max tune Up power [dBm]	Max tune Up Power [mW]	Separation Distance [mm]	RF exposure	Limit
DTS	917.5	16.83	16	± 2	18	63.1	50	1.21	3

$$= [(63.1 \text{ mW} / 50 \text{ mm})] \times [\sqrt{0.9175 \text{ GHz}}] = 1.21$$

➔ SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required.