



EMC TEST REPORT

Report No.: STS2412237E01

Issued for

Sayme Monitorizacion Estructural SL

Poligono Tanos-Viernes, B4, 39300 Torrelavega, Spain

Product Name: SAYME Dumpster Lock

Brand Name: SAYME

Model Name: 2XER34615M

Series Model(s): N/A

FCC ID: 2BMD7-13EA2BMD7

Test Standards: FCC 47 CFR Part 15: Subpart B

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.



TEST REPORT

Applicant's Name : Sayme Monitorizacion Estructural SL

Address : Poligono Tanos-Viernoles, B4, 39300 Torrelavega, Spain

Manufacturer's Name : Sayme Monitorizacion Estructural SL

Address : Poligono Tanos-Viernoles, Parcela B4, 39300 Torrelavega, Spain

Product description

Product Name : SAYME Dumpster Lock

Brand Name : SAYME

Model Name : 2XER34615M

Series Model(s) : N/A

Standards : FCC 47 CFR Part 15: Subpart B

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

Date of Test :

Date of Receipt of Test Item : 27 Dec. 2024

Date (s) of performance of tests : 27 Dec. 2024 ~ 13 Jan. 2025

Date of Issue : 13 Jan. 2025

Test Result : **Pass**

Testing Engineer : *Star Deng*

Star Deng

(Star Deng)

Technical Manager : *Tony Liu*

Tony Liu

(Tony Liu)

Authorized Signatory : *Bovey Yang*

Bovey Yang

(Bovey Yang)





TABLE OF CONTENTS

1. TEST SUMMARY	5
1.1 TEST FACTORY	5
1.2 MEASUREMENT UNCERTAINTY	5
2. GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
2.2 DESCRIPTION OF TEST MODES	7
2.3 DESCRIPTION OF TEST SETUP	8
2.4 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL	8
2.5 MEASUREMENT INSTRUMENTS LIST	9
3. EMC EMISSION TEST	10
3.1 CONDUCTED EMISSION MEASUREMENT	10
3.2 RADIATED EMISSION MEASUREMENT	12
APPENDIX 1-PHOTO TEST OF EUT	19

Revision History

Rev.	Issue Date	Report No.	Effect Page	Contents
00	13 Jan. 2025	STS2412327E01	ALL	Initial Issue



1. TEST SUMMARY

Test procedures according to the technical standards:

EMC Emission			
Standard	Test Item	Result	Remark
FCC 47 CFR Part 15: Subpart B	Conducted Emission	N/A	Meet Class B limit
	Radiated Emissions	PASS	Meet Class B limit

Note:

(1) "N/A" denotes test is not applicable in this Test Report

1.1 TEST FACTORY

Company Name:	Shenzhen STS Test Services Co. Ltd.
Address:	101, Building B, Zhuoke Science Park, No.190 Chongqing Road, ZhanChengShequ, Fuhai Sub-District, Bao'an District, Shenzhen, Guang Dong, China
Telephone:	+86-755 3688 6288
Fax:	+86-755 3688 6277
Registration No.:	FCC test Firm Registration Number: 625569
	IC test Firm Registration Number: 12108A
	A2LA Certificate No.: 4338.01

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	Conducted Emission (9KHz-150KHz)	±2.19dB
2	Conducted Emission (150KHz-30MHz)	±2.53dB
3	All emissions, radiated(<1G) 30MHz-1000MHz	±4.18dB
4	All emissions, radiated(>1G) 1GHz-6GHz	±4.90dB
5	All emissions, radiated(>1G) 6GHz-18GHz	±5.24dB



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Product Name	SAYME Dumpster Lock	
Brand Name	SAYME	
Model Name	2XER34615M	
Series Model(s)	N/A	
Model Difference	N/A	
Product Description	<p>The EUT is a SAYME Dumpster Lock</p> <p>ITE equipment having a primary function of either (or a combination of) entry, storage, display, retrieval, transmission, processing, switching, or control of data and/or telecommunication messages and which may be equipped with one or more ports typically for information transfer.</p>	
Frequency Bands	Bluetooth	2402 ~2480 MHZ
	NB-IOT	Band2: 1850-1910 MHz Band4: 1710-1755 MHz Band12: 699-716 MHz Band13: 777-787 MHz Band26: 814-824 MHz Band66: 1710-1780 MHz Band71: 663-698 MHz
	NFC	13.56 MHz
	2.4G WLAN	802.11b/g/n(HT20):2412~2462 MHZ 802.11n(HT40):2422~2452 MHZ
Modulation Mode	NFC	ASK
	BT	BT BR(1Mbps): GFSK BT EDR(2Mbps): π/4-DQPSK BT EDR(3Mbps): 8DPSK
	BLE	GFSK
	NB-IOT	BPSK/QPSK
	2.4G WLAN	802.11b(DSSS):CCK,DQPSK,DBPSK 802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM
Rating	N/A	
Adapter	N/A	
Battery	Rated Voltage: DC 3.6V Capacity: 16500mAh	
Hardware Version	DLNB10	
Software Version	V11	



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	NFC
Mode 2	BT Link
Mode 3	WLAN link
Mode 4	LTE Link

For Radiated Test	
Final Test Mode	Description
Mode 1	NFC

Note:

1. In the radiation disturbance test, Mode 1 is the minimum margin mode, and this report only shows the minimum margin mode test data.
3. We tested for all available U.S. voltage and frequencies (For 120V, 50/60Hz) for which the device is capable of operation.



2.3 DESCRIPTION OF TEST SETUP



2.4 DESCRIPTION TEST PERIPHERAL AND EUT PERIPHERAL

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Note
N/A	N/A	N/A	N/A	N/A

Item	Equipment	Ferrite Core	Length	Note
N/A	N/A	N/A	N/A	N/A

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in «Length» column.



2.5 MEASUREMENT INSTRUMENTS LIST

2.5.1 CONDUCTED TEST SITE

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
EMI Test Receiver	R&S	ESCI	101427	2024.9.23	2025.9.22
LISN	R&S	AiT-F01220	8130179	2024.9.23	2025.9.22
Absorbing Clamp	R&S	MDS-21	100668	2024.4.15	2025.4.14
CE Cable	N/A	C01	N/A	2024.9.23	2025.9.22
Temperature & Humidity	Anymetre	JR900	240686	2024.10.15	2025.10.14
Testing Software	EZ-EMC(Ver.STSLAB-03A1 CE)				

2.5.2 RADIATED TEST SITE

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
EMI Test Receiver	R&S	ESCI	101427	2024.9.23	2025.9.22
Bi-log Antenna	TESEQ	CBL6111D	45873	2024.9.28	2025.9.27
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1343	2024.9.28	2025.9.27
Pre-amplifier(1G-26.5G)	Agilent	HP8449B	3008A02383	2024.2.23	2025.2.22
Pre-amplifier(0.1M-3GHz)	EM	EM330	060665	2024.2.23	2025.2.22
Spectrum Analyzer	Agilent	N9020A	MY49100060	2024.9.23	2025.9.22
RE Cable (9K-1G)	N/A	R01	N/A	2024.9.23	2025.9.22
RE Cable (1G-26G)	N/A	R02	N/A	2024.9.23	2025.9.22
Temperature & Humidity	Mieo	HH660	N/A	2024.9.26	2025.9.25
SAC	ChengYu	9*6*6	N/A	2023.9.05	2026.9.06
Testing Software	EZ-EMC(Ver.STSLAB-03A1 RE)				



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

FREQUENCY (MHz)	<input type="checkbox"/> Class A (dB μ V)		<input checked="" type="checkbox"/> Class B (dB μ V)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 ~ 0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.5 ~ 5	73.00	60.00	56.00	46.00
5 ~ 30	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. For the actual test configuration, please refer to the related item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



**Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMH) are 80 cm from EUT and at least 80 cm from other units and other metal planes**

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

3.1.6 TEST RESULTS

Temperature:	--°C	Relative Humidity:	--%
Phase:	L/N	Test Mode:	N/A
Test Voltage:	N/A	Test Date:	N/A

Note: not applicable



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Below 1 GHz

Measurement Method and Applied Limits:

ANSI C63.4:

Frequency (MHz)	<input type="checkbox"/> Class A		<input checked="" type="checkbox"/> Class B
	Field strength (dBuV/m) (at 10m)	Field strength (dBuV/m) (at 3m)	Field strength (dBuV/m) (at 3m)
30 ~ 88	39	49.5	40
88 ~ 216	43.5	54	43.5
216 ~ 960	46.4	56.9	46
Above 960	49.5	60	54

Above 1 GHz

Measurement Method and Applied Limits:

ANSI C63.4:

Frequency (MHz)	<input type="checkbox"/> Class A				<input checked="" type="checkbox"/> Class B	
	(dBuV/m) (at 3m)		(dBuV/m) (at 10m)		(dBuV/m) (at 3m)	
	Peak	Average	Peak	Average	Peak	Average
Above 1000	80	60	69.5	49.5	74	54

Frequency Range of Radiated Disturbance Measurement

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 ~ 108	1000
108 ~ 500	2000
500 ~ 1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower

Note:

- (1) . The limit for radiated test was performed in the following: FCC PART 15B.
- (2) The tighter limit applies at the band edges
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).



3.2.2 TEST PROCEDURE

- a. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. EUT as the center to the edge of the auxiliary device, the distance from the maximum edge to the center of the antenna is 3 meter.
- c. The height of antenna is varied from 1 meter to 4 meter above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meter and the rotatable table was turned from 0 degrees to 360 degree to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1GHz.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.


Note: Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP

(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 described unless otherwise a special operating condition is specified in the following during the testing.


3.2.6 TEST RESULTS

Temperature:	26.1°C	Relative Humidity:	53%
Phase:	Horizontal	Test Mode:	Mode 1
Test Voltage:	DC 3.8V form battery	Test Date:	2025.01.09

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	196.0420	50.52	-21.05	29.47	43.50	-14.03	QP
2	211.5262	61.66	-21.21	40.45	43.50	-3.05	QP
3	233.5284	48.88	-18.88	30.00	46.00	-16.00	QP
4	263.8190	47.78	-15.26	32.52	46.00	-13.48	QP
5	355.4273	45.23	-14.55	30.68	46.00	-15.32	QP
6	560.6928	37.64	-7.79	29.85	46.00	-16.15	QP

Remark:

1. All readings are Quasi-Peak.
2. Margin = Result (Result =Reading + Factor)–Limit.
3. Factor= Cable Loss +Antenna Factor-Amplifier Gain.






Temperature:	26.1°C	Relative Humidity:	53%
Phase:	Vertical	Test Mode:	Mode 1
Test Voltage:	DC 3.8V from battery	Test Date:	2025.1.09

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	175.6516	52.74	-20.43	32.31	43.50	-11.19	QP
2	195.7880	52.02	-21.06	30.96	43.50	-12.54	QP
3	202.1605	48.75	-20.89	27.86	43.50	-15.64	QP
4	245.6710	48.88	-18.22	30.66	46.00	-15.34	QP
5	274.1938	58.28	-16.02	42.26	46.00	-3.74	QP
6	539.4773	36.17	-9.29	26.88	46.00	-19.12	QP

Remark:

1. All readings are Quasi-Peak.
2. Margin = Result (Result = Reading + Factor)-Limit.
3. Factor= Cable Loss +Antenna Factor-Amplifier Gain.






3.2.7 TEST RESULT(1000-18000 MHz)

Temperature:	25.3°C	Relative Humidity:	43%
Phase:	Horizontal	Test Mode:	Mode 1
Test Voltage:	DC 3.8V form battery	Test Date:	2025.01.09

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	3762.500	41.45	3.74	45.19	74.00	-28.81	peak
2	3762.500	33.78	3.74	37.52	54.00	-16.48	AVG
3	6907.500	36.51	10.57	47.08	74.00	-26.92	peak
4	6907.500	28.32	10.57	38.89	54.00	-15.11	AVG
5	10775.000	35.83	14.03	49.86	74.00	-24.14	peak
6	10775.000	26.44	14.03	40.47	54.00	-13.53	AVG
7	12900.000	36.40	15.37	51.77	74.00	-22.23	peak
8	12900.000	27.34	15.37	42.71	54.00	-11.29	AVG
9	15271.500	36.41	17.60	54.01	74.00	-19.99	peak
10	15271.500	27.46	17.60	45.06	54.00	-8.94	AVG
11	17787.500	31.14	24.24	55.38	74.00	-18.62	peak
12	17787.500	22.18	24.24	46.42	54.00	-7.58	AVG

Remark:

1. All readings are Quasi-Peak.
2. Margin = Result (Result =Reading + Factor)–Limit.
3. Factor= Cable Loss +Antenna Factor-Amplifier Gain.






Temperature:	25.3°C	Relative Humidity:	43%
Phase:	Vertical	Test Mode:	Mode 1
Test Voltage:	DC 3.8V form battery	Test Date:	2025.01.09

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	2768.000	42.65	1.05	43.70	74.00	-30.30	peak
2	2768.000	33.30	1.05	34.35	54.00	-19.65	AVG
3	5853.500	38.27	7.50	45.77	74.00	-28.23	peak
4	5853.500	30.42	7.50	37.92	54.00	-16.08	AVG
5	7783.000	38.64	11.11	49.75	74.00	-24.25	peak
6	7783.000	29.22	11.11	40.33	54.00	-13.67	AVG
7	11336.000	37.00	14.40	51.40	74.00	-22.60	peak
8	11336.000	27.96	14.40	42.36	54.00	-11.64	AVG
9	13758.500	35.93	16.47	52.40	74.00	-21.60	peak
10	13758.500	27.08	16.47	43.55	54.00	-10.45	AVG
11	17753.500	31.72	23.68	55.40	74.00	-18.60	peak
12	17753.500	22.48	23.68	46.16	54.00	-7.84	AVG

Remark:

1. All readings are Quasi-Peak.
2. Margin = Result (Result =Reading + Factor)-Limit.
3. Factor= Cable Loss +Antenna Factor-Amplifier Gain.


80.0 dBuV/m

**Notes:**


1. Measuring frequencies from 1 GHz to 18GHz
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak and average detector mode of the emission shown in Actual FS column.
3. The frequency emission of 18-25GHz is at least 20dB lower than the limit, and the frequency emission mainly comes from environmental noise.

APPENDIX 1-PHOTO TEST OF EUT

RE (Below 1GHz)



RE (Above 1GHz)



END OF THE REPORT