



RF MEASUREMENT REPORT

FCC ID: 2BMDV-WAW1
Applicant: Shenzhen Aiper Intelligent Co., Ltd.
Product: SMART IRRIGATION
Model No.: WAW1
Brand Name: Aiper
FCC Classification: Digital Transmission System (DTS)
FCC Rule Part(s): Part 15 Subpart C (Section 15.247)
Result: Complies
Received Date: 2025-02-14
Test Date: 2025-03-20 ~ 2025-03-28

Reviewed By:

Denise Zhou

Approved By:

Robin Wu



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
R25S1034028-U202	V01	Initial Report	2025-04-09	Valid

CONTENTS

Description	Page
1. General Information	5
1.1. Applicant	5
1.2. Manufacturer	5
1.3. Testing Facility	6
1.4. Product Information.....	7
1.5. Radio Specification under Test	7
1.6. Working Frequencies	8
2. Test Configuration	9
2.1. Test Mode.....	9
2.2. Test System Connection Diagram.....	9
2.3. Test Software	9
2.4. Applied Standards.....	10
2.5. Test Environment Condition	10
3. Antenna Requirements	11
4. Measuring Instrument	12
5. Decision Rules and Measurement Uncertainty	13
5.1. Decision Rules	13
5.2. Measurement Uncertainty	13
6. Test Result.....	14
6.1. Summary	14
6.2. 6dB Bandwidth Measurement.....	15
6.2.1. Test Limit	15
6.2.2. Test Procedure	15
6.2.3. Test Setting	15
6.2.4. Test Setup	15
6.2.5. Test Result	15
6.3. Output Power Measurement	16
6.3.1. Test Limit	16
6.3.2. Test Procedure	16
6.3.3. Test Setting	16
6.3.4. Test Setup	16
6.3.5. Test Result	16
6.4. Power Spectral Density Measurement	17
6.4.1. Test Limit	17
6.4.2. Test Procedure	17

6.4.3.	Test Setting	17
6.4.4.	Test Setup	17
6.4.5.	Test Result	17
6.5.	Conducted Band Edge and Out-of-Band Emissions Measurement	18
6.5.1.	Test Limit	18
6.5.2.	Test Procedure	18
6.5.3.	Test Setting	18
6.5.4.	Test Setup	19
6.5.5.	Test Result	19
6.6.	Radiated Spurious Emission Measurement.....	20
6.6.1.	Test Limit	20
6.6.2.	Test Procedure	20
6.6.3.	Test Setting	20
6.6.4.	Test Setup	22
6.6.5.	Test Result	23
6.7.	Radiated Restricted Band Edge Measurement	24
6.7.1.	Test Limit	24
6.7.2.	Test Procedure	25
6.7.3.	Test Setting	25
6.7.4.	Test Setup	26
6.7.5.	Test Result	27
6.8.	AC Conducted Emissions Measurement	28
6.8.1.	Test Limit	28
6.8.2.	Test Setup	28
6.8.3.	Test Result	28
Appendix A - Test Result.....		29
A.1	Duty Cycle Test Result	29
A.2	6dB Bandwidth Test Result	30
A.3	Output Power Test Result	32
A.4	Power Spectral Density Test Result	33
A.5	Conducted Band Edge and Out-of-Band Emissions Test Result.....	35
A.6	Radiated Spurious Emission Test Result.....	39
A.7	Radiated Restricted Band Edge Test Result.....	43
A.8	AC Conducted Emissions Test Result	59
Appendix B - Test Setup Photograph		63
Appendix C - EUT Photograph		64

1. General Information

1.1. Applicant

Shenzhen Aiper Intelligent Co., Ltd.

Units 3201, 3203A and 3205, 32nd Floor, Block C, Minle Community, Minzhi Street, Longhua District,
Shenzhen China

1.2. Manufacturer

Shenzhen Aiper Intelligent Co., Ltd.

Units 3201, 3203A and 3205, 32nd Floor, Block C, Minle Community, Minzhi Street, Longhua District,
Shenzhen China

1.3. Testing Facility

☒	Test Site – MRT Suzhou Laboratory
	Laboratory Location (Suzhou - Wuzhong) D8 Building, No.2 Tian’edang Rd., Wuzhong Economic Development Zone, Suzhou, China
	Laboratory Location (Suzhou - SIP) 4b Building, Liando U Valley, No.200 Xingpu Rd., Shengpu Town, Suzhou Industrial Park, China
	Laboratory Location (Suzhou - Wujiang) Building 1, No.1 Xingdong Road, Wujiang, Suzhou, Jiangsu, People’s Republic of China
	Laboratory Accreditations
	A2LA: 3628.01 CNAS: L10551 FCC: CN1166 ISED: CN0001
	VCCI: ☐ R-20025 ☐ G-20034 ☐ C-20020 ☐ T-20020 ☐ R-20141 ☐ G-20134 ☐ C-20103 ☐ T-20104
☐	Test Site – MRT Shenzhen Laboratory
	Laboratory Location (Shenzhen) 1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China
	Laboratory Accreditations
	A2LA: 3628.02 CNAS: L10551 FCC: CN1284 ISED: CN0105
☐	Test Site – MRT Taiwan Laboratory
	Laboratory Location (Taiwan) No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)
	Laboratory Accreditations
	TAF: 3261 FCC: 291082, TW3261 ISED: TW3261

1.4. Product Information

Product Name	SMART IRRIGATION
Model No.	WAW1
EUT Identification No.	20250220Sample#17 (Conducted) 20250318Sample#02 (Radiated)
Wi-Fi Specification	802.11b/g/n
Bluetooth Specification	BLE only
Antenna Information	Refer to Section 1.5
Operating Temp.	0~40 °C
Power Type	AC Adapter Input
Accessories	
AC Adapter	Model: GC44-210180-1DG Input: 120V ~ 50-60Hz, 1.5A Output: 21.0V, 1.8A, 37.8W
Remark: The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer.	

1.5. Radio Specification under Test

Bluetooth Frequency	2402 ~ 2480MHz
Channel Number	40
Type of modulation	GFSK
Data Rate	1Mbps & 2Mbps
Antenna Type	FPC
Antenna Gain	-0.95 dBi

1.6. Working Frequencies

Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2404 MHz	02	2406 MHz
03	2408 MHz	04	2410 MHz	05	2412 MHz
06	2414 MHz	07	2416 MHz	08	2418 MHz
09	2420 MHz	10	2422 MHz	11	2424 MHz
12	2426 MHz	13	2428 MHz	14	2430 MHz
15	2432 MHz	16	2434 MHz	17	2436 MHz
18	2438 MHz	19	2440 MHz	20	2442 MHz
21	2444 MHz	22	2446 MHz	23	2448 MHz
24	2450 MHz	25	2452 MHz	26	2454 MHz
27	2456 MHz	28	2458 MHz	29	2460 MHz
30	2462 MHz	31	2464 MHz	32	2466 MHz
33	2468 MHz	34	2470 MHz	35	2472 MHz
36	2474 MHz	37	2476 MHz	38	2478 MHz
39	2480 MHz	--	--	--	--


2. Test Configuration

2.1. Test Mode

Mode 1: Transmit by BLE-1Mbps
Mode 2: Transmit by BLE-2Mbps

2.2. Test System Connection Diagram

The device was tested per the guidance ANSI C63.10: 2013 was used to reference the appropriate EUT setup for radiated emissions testing and AC line conducted testing.



2.3. Test Software

The test utility software used during testing was “nRF Connect for Desktop”, and the version was 5.1.0.

2.4. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15.247
- KDB 558074 D01v05r02
- ANSI C63.10-2013

2.5. Test Environment Condition

Ambient Temperature	15 ~ 35°C
Relative Humidity	20 ~75%RH

3. Antenna Requirements

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section”.

- The antenna of the device is **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The unit complies with the requirement of §15.203.

4. Measuring Instrument

Instrument	Manufacturer	Model No.	Asset No.	Cali. Interval	Cali. Due Date	Test Site
USB Power Sensor	Keysight	U2021XA	MRTSUE06446	1 year	2025-05-08	WZ-SR5
Thermohygrometer	testo	608-H1	MRTSUE06402	1 year	2025-05-12	WZ-SR5
Shielding Room	HUAMING	WZ-SR5	MRTSUE06442	N/A	N/A	WZ-SR5
Signal Analyzer	Keysight	N9010B	MRTSUE06457	1 year	2025-05-08	WZ-SR5
Attenuator	MVE	MVE2213	MRTSUE11092	1 year	2025-06-05	WZ-SR5
Active Loop Antenna	Schwarzbeck	FMZB 1519-60 D	MRTSUE07076	1 year	2025-11-19	WJ-AC2
EXA Signal Analyzer	Keysight	N9010B	MRTSUE07147	1 year	2025-04-28	WJ-AC2
TRILOG Broad Band Antenna	Schwarzbeck	VULB 9163	MRTSUE07097	1 year	2025-04-24	WJ-AC2
Preamplifier	EMCI	EMC118A45SE	MRTSUE07102	1 year	2025-04-11	WJ-AC2
Preamplifier	EMCI	EMC184045SE	MRTSUE07103	1 year	2025-04-14	WJ-AC2
Horn Antenna	RFSPIN	DRH18-E	MRTSUE07105	1 year	2025-05-12	WJ-AC2
Anechoic Chamber	TDK	WJ-AC2	MRTSUE07117	1 year	2025-05-14	WJ-AC2
Thermohygrometer	testo	608-H1	MRTSUE11315	1 year	2025-06-24	WJ-AC2
Thermohygrometer	testo	608-H1	MRTSUE11332	1 year	2025-06-24	WJ-AC2
Broadband Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE07100	1 year	2025-04-24	WJ-AC2
EMI Test Receiver	R&S	ESR3	MRTSUE07111	1 year	2025-04-18	WJ-AC2
EMI Test Receiver	R&S	ESR3	MRTSUE07112	1 year	2025-04-21	WJ-SR5
Shielding Room	TDK	WJ-SR5	MRTSUE07127	N/A	N/A	WJ-SR5
Two-Line V-Network	R&S	ENV216	MRTSUE07201	1 year	2025-05-26	WJ-SR5
Two-Line V-Network	R&S	ENV216	MRTSUE07202	1 year	2025-05-26	WJ-SR5
Thermohygrometer	testo	608-H1	MRTSUE11317	1 year	2025-06-24	WJ-SR5

Software	Version	Function
e3	230711	RE & CE
CONTROLLER CO3000	v 1.03.02	RE Antenna & Turntable
Agilent Power Analyzer/Agilent Power Panel	V R03.09.00	Power

5. Decision Rules and Measurement Uncertainty

5.1. Decision Rules

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.2.
(Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

5.2. Measurement Uncertainty

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

AC Conducted Emission Measurement
The maximum measurement uncertainty is evaluated as: 9kHz~150kHz: 3.58dB 150kHz~30MHz: 3.20dB
Radiated Emission Measurement
The maximum measurement uncertainty is evaluated as: Coaxial: 9kHz~30MHz: 2.35dB Coplanar: 9kHz~30MHz: 2.37dB Horizontal: 30MHz~200MHz: 3.47dB 200MHz~1GHz: 4.17dB 1GHz~40GHz: 4.97dB Vertical: 30MHz~200MHz: 4.07dB 200MHz~1GHz: 5.28dB 1GHz~40GHz: 4.84dB
Spurious Emissions, Conducted
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 2.5dB
Output Power
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 1.5dB
Power Spectrum Density
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 2.5dB
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 3.2%

6. Test Result

6.1. Summary

FCC Section(s)	Test Description	Test Condition	Verdict
15.247(a)(2)	6dB Bandwidth	Conducted	Pass
15.247(b)(3)	Output Power		Pass
15.247(e)	Power Spectral Density		Pass
15.247(d)	Band Edge / Out-of-Band Emissions		Pass
15.205 15.209	General Field Strength (Restricted Bands and Radiated Emission)	Radiated	Pass
15.207	AC Conducted Emissions 150kHz - 30MHz	Line Conducted	Pass

Note: The analyzer plots shown in this section were captured using a correction table to account for cable and attenuator losses in the system connecting the EUT to the analyzer across relevant frequencies.

6.2. 6dB Bandwidth Measurement

6.2.1. Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.


6.2.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.8

6.2.3. Test Setting

1. The Spectrum's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 6$. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. Set RBW = 100 kHz
3. $VBW \geq 3 \times RBW$
4. Detector = Peak
5. Trace mode = Max hold
6. Sweep = Auto couple
7. Allow the trace to stabilize

6.2.4. Test Setup



6.2.5. Test Result

Refer to Appendix A.2.

6.3. Output Power Measurement

6.3.1. Test Limit

The maximum output power shall be less 1 Watt (30dBm).

The conducted output power limit specified in paragraph FCC Part 15.247(b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs FCC Part 15.247(b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

6.3.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.9.1.3

ANSI C63.10 - 2013 - Section 11.9.2.3.2

6.3.3. Test Setting


Method PKPM1 (Peak Power Measurement of Signals with DTS BW $\leq$ 50MHz)

Peak power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The pulse sensor employs a VBW = 50MHz so this method was only used for signals whose DTS bandwidth was less than or equal to 50MHz.

Average Power Measurement

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.

6.3.4. Test Setup



6.3.5. Test Result

Refer to Appendix A.3.

6.4. Power Spectral Density Measurement

6.4.1. Test Limit

The maximum permissible power spectral density is 8dBm in any 3 kHz band.

The same method of determining the conducted output power shall be used to determine the power spectral density.


6.4.2. Test Procedure

ANSI C63.10-2013 Section 11.10.2

6.4.3. Test Setting

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the DTS channel bandwidth
3. RBW = 3kHz
4. VBW = 10kHz
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

6.4.4. Test Setup



6.4.5. Test Result

Refer to Appendix A.4.

6.5. Conducted Band Edge and Out-of-Band Emissions Measurement

6.5.1. Test Limit

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth per the PSD procedure.

6.5.2. Test Procedure

ANSI C63.10-2013 - Section 11.11

6.5.3. Test Setting


Reference level measurement

1. Set instrument center frequency to DTS channel center frequency
2. Set the span to ≥ 1.5 times the DTS bandwidth
3. Set the RBW = 100 kHz
4. Set the VBW $\geq 3 \times$ RBW
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Allow trace to fully stabilize

Emission level measurement

1. Set the center frequency and span to encompass frequency range to be measured
2. RBW = 100kHz
3. VBW = 300kHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

6.5.4. Test Setup



6.5.5. Test Result

Refer to Appendix A.5.

6.6. Radiated Spurious Emission Measurement

6.6.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

6.6.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.11 & 11.12

ANSI C63.10 - 2013 - Section 6.3 (General Requirements)

ANSI C63.10 - 2013 - Section 6.4 (Standard test method below 30MHz)

ANSI C63.10 - 2013 - Section 6.5 (Standard test method above 30MHz to 1GHz)

ANSI C63.10 - 2013 - Section 6.6 (Standard test method above 1GHz)

6.6.3. Test Setting

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000MHz	1MHz

Quasi-Peak Measurements below 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = as specified in Table 1
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

Peak Measurements above 1GHz


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Sweep time = Auto couple
6. Trace mode = Max hold
7. Trace was allowed to stabilize

Average Measurements above 1GHz (Method VB)


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; if the EUT is configured to transmit with duty cycle $\geq 98\%$, set VBW = 10Hz
If the EUT duty cycle is $< 98\%$, set $\text{VBW} \geq 1/T$. T is the minimum transmission duration.
4. As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = Auto
7. Trace mode = Max hold
8. Trace was allowed to stabilize

6.6.4. Test Setup


Below 30MHz Test Setup:



Below 1GHz Test Setup:



Above 1GHz Test Setup:



6.6.5. Test Result

Refer to Appendix A.6.

6.7. Radiated Restricted Band Edge Measurement

6.7.1. Test Limit

For 15.205 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a).

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41	--	--	--

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [μ V/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

6.7.2. Test Procedure

ANSI C63.10-2013 Section 6.3 & 6.6 & 11.13

6.7.3. Test Setting


Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; If the EUT is configured to transmit with duty cycle $\geq 98\%$, set VBW = 10 Hz.
If the EUT duty cycle is $< 98\%$, set VBW $\geq 1/T$. T is the minimum transmission duration.
4. As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = auto
7. Trace mode = max hold
8. Allow max hold to run for at least 50 times (1/duty cycle) traces

6.7.4. Test Setup



6.7.5. Test Result

Refer to Appendix A.7.

6.8. AC Conducted Emissions Measurement


6.8.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dB μ V)	AV (dB μ V)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

6.8.2. Test Setup



6.8.3. Test Result



Refer to Appendix A.8.

Appendix A - Test Result

A.1 Duty Cycle Test Result

Test Site	WZ-SR5	Test Engineer	Jeff Yang
Test Date	2025-03-20		


Test Mode	Duty Cycle
BLE-1Mbps	85.61%
BLE-2Mbps	33.17%
Duty Cycle (T = Transmission Duration)	
BLE-1Mbps (T = 2.142ms)	BLE-2Mbps (T = 207.0µs)

A.2 6dB Bandwidth Test Result

Test Site	WZ-SR5	Test Engineer	Jeff Yang
Test Date	2025-03-20		

Test Mode	Data Rate	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
BLE	1Mbps	00	2402	0.6991	≥ 0.5
BLE	1Mbps	19	2440	0.6955	≥ 0.5
BLE	1Mbps	39	2480	0.6953	≥ 0.5
BLE	2Mbps	00	2402	1.131	≥ 0.5
BLE	2Mbps	19	2440	1.135	≥ 0.5
BLE	2Mbps	39	2480	1.139	≥ 0.5



BLE-2Mbps 6dB Bandwidth


Channel 00 (2402MHz)



Channel 19 (2440MHz)



Channel 39 (2480MHz)



A.3 Output Power Test Result

Test Site	WZ-SR5	Test Engineer	Jeff Yang
Test Date	2025-03-20		

Test Result of Peak Output Power

Test Mode	Data Rate	Channel No.	Frequency (MHz)	Peak Power (dBm)	Limit (dBm)	Result
BLE	1Mbps	00	2402	4.77	≤ 30.00	Pass
BLE	1Mbps	19	2440	4.63	≤ 30.00	Pass
BLE	1Mbps	39	2480	4.17	≤ 30.00	Pass
BLE	2Mbps	00	2402	4.75	≤ 30.00	Pass
BLE	2Mbps	19	2440	4.62	≤ 30.00	Pass
BLE	2Mbps	39	2480	4.17	≤ 30.00	Pass


Test Result of Average Output Power (Reporting Only)

Test Mode	Data Rate	Channel No.	Frequency (MHz)	Average Power (dBm)	Limit (dBm)	Result
BLE	1Mbps	00	2402	4.01	≤ 30.00	Pass
BLE	1Mbps	19	2440	3.84	≤ 30.00	Pass
BLE	1Mbps	39	2480	3.32	≤ 30.00	Pass
BLE	2Mbps	00	2402	4.04	≤ 30.00	Pass
BLE	2Mbps	19	2440	3.80	≤ 30.00	Pass
BLE	2Mbps	39	2480	3.30	≤ 30.00	Pass

A.4 Power Spectral Density Test Result


Test Site	WZ-SR5	Test Engineer	Jeff Yang
Test Date	2025-03-20		

Test Mode	Data Rate	Channel No.	Frequency (MHz)	PSD Result (dBm / 3kHz)	Limit (dBm / 3kHz)	Result
BLE	1Mbps	00	2402	-11.71	≤ 8.00	Pass
BLE	1Mbps	19	2440	-11.50	≤ 8.00	Pass
BLE	1Mbps	39	2480	-12.23	≤ 8.00	Pass
BLE	2Mbps	00	2402	-13.37	≤ 8.00	Pass
BLE	2Mbps	19	2440	-13.79	≤ 8.00	Pass
BLE	2Mbps	39	2480	-14.40	≤ 8.00	Pass




BLE-2Mbps PSD

Channel 00 (2402MHz)



Channel 19 (2440MHz)



Channel 39 (2480MHz)



A.5 Conducted Band Edge and Out-of-Band Emissions Test Result


Test Site	WZ-SR5	Test Engineer	Jeff Yang
Test Date	2025-03-20		

Test Mode	Data Rate / Mbps	Channel No.	Frequency (MHz)	Limit (dBc)	Result
BLE	1	00	2402	20	Pass
BLE	1	19	2440	20	Pass
BLE	1	39	2480	20	Pass
BLE	2	00	2402	20	Pass
BLE	2	19	2440	20	Pass
BLE	2	39	2480	20	Pass




Channel 19 (2440MHz)

100kHz PSD Reference Level




Spurious Emission 30MHz ~ 25GHz




Channel 39 (2480MHz)


100kHz PSD Reference Level



High Band Edge



Spurious Emission 30MHz ~ 25GHz




BLE-2Mbps Out-of-Band Emissions

Channel 00 (2402MHz)


100kHz PSD Reference Level



Low Band Edge



Spurious Emission 30MHz ~ 25GHz




Channel 19 (2440MHz)

100kHz PSD Reference Level



Spurious Emission 30MHz ~ 25GHz



Channel 39 (2480MHz)


100kHz PSD Reference Level



High Band Edge



Spurious Emission 30MHz ~ 25GHz



A.6 Radiated Spurious Emission Test Result

Test Site	WJ-AC2	Test Engineer	Bob Zhang
Test Date	2025-03-27	Test Mode	BLE-1Mbps
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Test Channel	Frequency (MHz)	Reading Level (dBμV)	Factor (dB/m)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
00	4804.60	47.96	-0.02	47.94	54.00	-6.06	Average	Horizontal
	4804.60	51.52	-0.02	51.50	74.00	-22.50	Peak	Horizontal
	12012.60	43.95	5.01	48.96	74.00	-25.04	Peak	Horizontal
	15762.80	43.70	6.32	50.02	74.00	-23.98	Peak	Horizontal
	4804.60	48.51	-0.02	48.49	54.00	-5.51	Average	Vertical
	4804.60	51.87	-0.02	51.85	74.00	-22.15	Peak	Vertical
	11342.80	41.70	5.48	47.18	74.00	-26.82	Peak	Vertical
	12262.50	42.83	4.82	47.65	74.00	-26.35	Peak	Vertical
19	4879.40	47.53	0.02	47.55	54.00	-6.45	Average	Horizontal
	4879.40	51.09	0.02	51.11	74.00	-22.89	Peak	Horizontal
	7322.30	45.08	4.95	50.03	54.00	-3.97	Average	Horizontal
	7322.30	49.76	4.95	54.71	74.00	-19.29	Peak	Horizontal
	12199.60	45.07	4.95	50.02	74.00	-23.98	Peak	Horizontal
	4879.40	50.81	0.02	50.83	54.00	-3.17	Average	Vertical
	4879.40	54.10	0.02	54.12	74.00	-19.88	Peak	Vertical
	7322.30	45.18	4.95	50.13	74.00	-23.87	Peak	Vertical
	11905.50	43.15	4.90	48.05	74.00	-25.95	Peak	Vertical
39	4961.00	49.26	0.13	49.39	54.00	-4.61	Average	Horizontal
	4961.00	52.76	0.13	52.89	74.00	-21.11	Peak	Horizontal
	7439.60	45.89	4.98	50.87	54.00	-3.13	Average	Horizontal
	7439.60	49.45	4.98	54.43	74.00	-19.57	Peak	Horizontal
	12170.70	43.11	5.11	48.22	74.00	-25.78	Peak	Horizontal
	4961.00	49.81	0.13	49.94	54.00	-4.06	Average	Vertical
	4961.00	53.42	0.13	53.55	74.00	-20.45	Peak	Vertical
	7439.60	45.36	4.98	50.34	74.00	-23.66	Peak	Vertical
	12240.40	43.37	4.76	48.13	74.00	-25.87	Peak	Vertical

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Site	WJ-AC2	Test Engineer	Bob Zhang
Test Date	2025-03-27	Test Mode	BLE-2Mbps
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		


Test Channel	Frequency (MHz)	Reading Level (dBμV)	Factor (dB/m)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
00	4804.60	48.81	-0.02	48.79	54.00	-5.21	Average	Horizontal
	4804.60	51.98	-0.02	51.96	74.00	-22.04	Peak	Horizontal
	8162.10	39.02	5.49	44.51	74.00	-29.49	Peak	Horizontal
	12012.60	45.51	5.01	50.52	74.00	-23.48	Peak	Horizontal
	4804.60	48.95	-0.02	48.93	54.00	-5.07	Average	Vertical
	4804.60	51.90	-0.02	51.88	74.00	-22.12	Peak	Vertical
	8236.90	40.75	5.77	46.52	74.00	-27.48	Peak	Vertical
	11480.50	42.70	5.40	48.10	74.00	-25.90	Peak	Vertical
19	4879.40	48.72	0.02	48.74	54.00	-5.26	Average	Horizontal
	4879.40	51.97	0.02	51.99	74.00	-22.01	Peak	Horizontal
	7320.60	45.92	4.96	50.88	54.00	-3.12	Average	Horizontal
	7320.60	49.77	4.96	54.73	74.00	-19.27	Peak	Horizontal
	12203.00	44.93	4.95	49.88	74.00	-24.12	Peak	Horizontal
	4882.33	50.05	0.03	50.08	54.00	-3.92	Average	Vertical
	4882.33	55.17	0.03	55.20	74.00	-18.80	Peak	Vertical
	7319.39	44.48	4.96	49.44	74.00	-24.56	Peak	Vertical
	12198.92	44.92	4.95	49.87	74.00	-24.13	Peak	Vertical
39	4959.30	48.58	0.13	48.71	54.00	-5.29	Average	Horizontal
	4959.30	52.08	0.13	52.21	74.00	-21.79	Peak	Horizontal
	7439.60	45.35	4.98	50.33	54.00	-3.67	Average	Horizontal
	7439.60	49.13	4.98	54.11	74.00	-19.89	Peak	Horizontal
	11927.60	44.04	4.94	48.98	74.00	-25.02	Peak	Horizontal
	4959.30	49.78	0.13	49.91	54.00	-4.09	Average	Vertical
	4959.30	53.15	0.13	53.28	74.00	-20.72	Peak	Vertical
	7441.30	45.31	4.97	50.28	74.00	-23.72	Peak	Vertical
	12272.70	45.05	4.84	49.89	74.00	-24.11	Peak	Vertical

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

The Result of Radiated Emission below 1GHz:

Site	WJ-AC2	Test Date	2025-03-26
Temperature	17.9 °C	Humidity	34.3 %
Limit	FCC_Part 15.209_RSE (3m)	Test Engineer	Bob Zhang
Factor	VULB 9163_07097	Polarity	Horizontal
EUT	SMART IRRIGATION	Test Voltage	AC 120V/60Hz
Test Mode	Transmit by BLE 2Mbps at 2440MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1	*	139.068	10.10	13.74	23.84	-19.66	43.50	QP
2		157.725	7.50	14.32	21.82	-21.68	43.50	QP
3		179.072	7.50	15.49	22.99	-20.51	43.50	QP
4		338.994	-7.90	21.34	13.44	-32.56	46.00	QP
5		633.241	-8.90	26.51	17.61	-28.39	46.00	QP
6		865.177	-9.70	29.22	19.52	-26.48	46.00	QP

Notes:

1. " * ", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).
4. The amplitude of radiated emissions (frequency range from 9kHz to 30MHz and 18GHz to 25GHz) is that proximity to ambient noise, which also are attenuated more than 20 dB below the permissible value. Therefore, the data is not presented in the report.

Site	WJ-AC2	Test Date	2025-03-26
Temperature	17.9 °C	Humidity	34.3 %
Limit	FCC_Part 15.209_RSE (3m)	Test Engineer	Bob Zhang
Factor	VULB 9163_07097	Polarity	Vertical
EUT	SMART IRRIGATION	Test Voltage	AC 120V/60Hz
Test Mode	Transmit by BLE 2Mbps at 2440MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1	*	30.137	9.70	16.59	26.29	-13.71	40.00	QP
2		99.843	12.10	17.35	29.45	-14.05	43.50	QP
3		120.024	11.90	15.61	27.51	-15.99	43.50	QP
4		140.835	12.90	13.70	26.60	-16.90	43.50	QP
5		155.801	12.90	14.20	27.10	-16.40	43.50	QP
6		367.983	-7.20	21.61	14.41	-31.59	46.00	QP

Notes:

1. " * ", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).
4. The amplitude of radiated emissions (frequency range from 9kHz to 30MHz and 18GHz to 25GHz) is that proximity to ambient noise, which also are attenuated more than 20 dB below the permissible value. Therefore, the data is not presented in the report.

A.7 Radiated Restricted Band Edge Test Result

Site	WJ-AC2	Test Date	2025-03-27
Temperature	17.9 °C	Humidity	34.3 %
Limit	FCC_Part 15_Band Edge (3m)	Test Engineer	Bob Zhang
Factor	DRH18-E_07105	Polarity	Horizontal
EUT	SMART IRRIGATION	Test Voltage	AC 120V/60Hz
Test Mode	Transmit by BLE 1Mbps at 2402MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1	*	2386.656	26.98	29.58	56.56	-17.44	74.00	Peak
2		2390.000	24.54	29.59	54.13	-19.87	74.00	Peak
3		2401.998	58.74	29.64	88.38	N/A	N/A	Peak

Notes:

1. " * ", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC2	Test Date	2025-03-27
Temperature	17.9 °C	Humidity	34.3 %
Limit	FCC_Part 15_Band Edge (3m)	Test Engineer	Bob Zhang
Factor	DRH18-E_07105	Polarity	Horizontal
EUT	SMART IRRIGATION	Test Voltage	AC 120V/60Hz
Test Mode	Transmit by BLE 1Mbps at 2402MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1	*	2390.000	15.32	29.59	44.92	-9.08	54.00	Average
2		2402.103	57.78	29.64	87.42	N/A	N/A	Average

Notes:

1. " * ", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC2	Test Date	2025-03-27
Temperature	17.9 °C	Humidity	34.3 %
Limit	FCC_Part 15_Band Edge (3m)	Test Engineer	Bob Zhang
Factor	DRH18-E_07105	Polarity	Vertical
EUT	SMART IRRIGATION	Test Voltage	AC 120V/60Hz
Test Mode	Transmit by BLE 1Mbps at 2402MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1	*	2368.197	27.16	29.56	56.72	-17.28	74.00	Peak
2		2390.000	24.54	29.59	54.13	-19.87	74.00	Peak
3		2402.473	70.56	29.64	100.20	N/A	N/A	Peak

Notes:

1. " * ", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC2	Test Date	2025-03-27
Temperature	17.9 °C	Humidity	34.3 %
Limit	FCC_Part 15_Band Edge (3m)	Test Engineer	Bob Zhang
Factor	DRH18-E_07105	Polarity	Vertical
EUT	SMART IRRIGATION	Test Voltage	AC 120V/60Hz
Test Mode	Transmit by BLE 1Mbps at 2402MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1	*	2354.042	16.98	29.53	46.51	-7.49	54.00	Average
2		2390.000	15.19	29.59	44.78	-9.22	54.00	Average
3		2402.198	69.73	29.64	99.37	N/A	N/A	Average

Notes:

1. " * ", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC2	Test Date	2025-03-27
Temperature	17.9 °C	Humidity	34.3 %
Limit	FCC_Part 15_Band Edge (3m)	Test Engineer	Bob Zhang
Factor	DRH18-E_07105	Polarity	Horizontal
EUT	SMART IRRIGATION	Test Voltage	AC 120V/60Hz
Test Mode	Transmit by BLE 1Mbps at 2480MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Detector
1		2479.890	58.66	29.75	88.41	N/A	N/A	Peak
2		2483.500	25.61	29.76	55.37	-18.63	74.00	Peak
3	*	2497.587	27.36	29.79	57.15	-16.85	74.00	Peak

Notes:

1. " * ", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBUV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC2	Test Date	2025-03-27
Temperature	17.9 °C	Humidity	34.3 %
Limit	FCC_Part 15_Band Edge (3m)	Test Engineer	Bob Zhang
Factor	DRH18-E_07105	Polarity	Horizontal
EUT	SMART IRRIGATION	Test Voltage	AC 120V/60Hz
Test Mode	Transmit by BLE 1Mbps at 2480MHz		




No	Mark	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Detector
1		2480.174	57.84	29.75	87.60	N/A	N/A	Average
2		2483.500	15.60	29.76	45.37	-8.63	54.00	Average
3	*	2493.666	16.15	29.79	45.94	-8.06	54.00	Average

Notes:

1. " * ", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBUV/m) = Reading (dBUV) + C.F (dB/m).

Site	WJ-AC2	Test Date	2025-03-27
Temperature	17.9 °C	Humidity	34.3 %
Limit	FCC_Part 15_Band Edge (3m)	Test Engineer	Bob Zhang
Factor	DRH18-E_07105	Polarity	Vertical
EUT	SMART IRRIGATION	Test Voltage	AC 120V/60Hz
Test Mode	Transmit by BLE 1Mbps at 2480MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1		2479.883	71.51	29.75	101.26	N/A	N/A	Peak
2		2483.500	27.86	29.76	57.62	-16.38	74.00	Peak
3	*	2483.656	28.79	29.76	58.56	-15.44	74.00	Peak

Notes:

1. " * ", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC2	Test Date	2025-03-27
Temperature	17.9 °C	Humidity	34.3 %
Limit	FCC_Part 15_Band Edge (3m)	Test Engineer	Bob Zhang
Factor	DRH18-E_07105	Polarity	Vertical
EUT	SMART IRRIGATION	Test Voltage	AC 120V/60Hz
Test Mode	Transmit by BLE 1Mbps at 2480MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1		2480.156	70.75	29.75	100.50	N/A	N/A	Average
2		2483.500	16.52	29.76	46.28	-7.72	54.00	Average
3	*	2483.841	16.86	29.77	46.63	-7.37	54.00	Average

Notes:

1. " * ", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC2	Test Date	2025-03-27
Temperature	17.9 °C	Humidity	34.3 %
Limit	FCC_Part 15_Band Edge (3m)	Test Engineer	Bob Zhang
Factor	DRH18-E_07105	Polarity	Horizontal
EUT	SMART IRRIGATION	Test Voltage	AC 120V/60Hz
Test Mode	Transmit by BLE 2Mbps at 2402MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1	*	2327.813	27.11	29.45	56.56	-17.44	74.00	Peak
2		2390.000	24.63	29.59	54.22	-19.78	74.00	Peak
3		2401.704	58.72	29.64	88.36	N/A	N/A	Peak

Notes:

1. " * ", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC2	Test Date	2025-03-27
Temperature	17.9 °C	Humidity	34.3 %
Limit	FCC_Part 15_Band Edge (3m)	Test Engineer	Bob Zhang
Factor	DRH18-E_07105	Polarity	Horizontal
EUT	SMART IRRIGATION	Test Voltage	AC 120V/60Hz
Test Mode	Transmit by BLE 2Mbps at 2402MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1	*	2390.000	15.95	29.59	45.54	-8.46	54.00	Average
2		2402.103	56.51	29.64	86.15	N/A	N/A	Average

Notes:

1. " * ", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC2	Test Date	2025-03-27
Temperature	17.9 °C	Humidity	34.3 %
Limit	FCC_Part 15_Band Edge (3m)	Test Engineer	Bob Zhang
Factor	DRH18-E_07105	Polarity	Vertical
EUT	SMART IRRIGATION	Test Voltage	AC 120V/60Hz
Test Mode	Transmit by BLE 2Mbps at 2402MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1	*	2356.208	27.64	29.53	57.17	-16.83	74.00	Peak
2		2390.000	25.02	29.59	54.61	-19.39	74.00	Peak
3		2402.701	70.52	29.64	100.16	N/A	N/A	Peak

Notes:

1. " * ", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC2	Test Date	2025-03-27
Temperature	17.9 °C	Humidity	34.3 %
Limit	FCC_Part 15_Band Edge (3m)	Test Engineer	Bob Zhang
Factor	DRH18-E_07105	Polarity	Vertical
EUT	SMART IRRIGATION	Test Voltage	AC 120V/60Hz
Test Mode	Transmit by BLE 2Mbps at 2402MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1	*	2337.740	17.15	29.48	46.62	-7.38	54.00	Average
2		2390.000	16.04	29.59	45.63	-8.37	54.00	Average
3		2402.122	68.45	29.64	98.09	N/A	N/A	Average

Notes:

1. " * ", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC2	Test Date	2025-03-27
Temperature	17.9 °C	Humidity	34.3 %
Limit	FCC_Part 15_Band Edge (3m)	Test Engineer	Bob Zhang
Factor	DRH18-E_07105	Polarity	Horizontal
EUT	SMART IRRIGATION	Test Voltage	AC 120V/60Hz
Test Mode	Transmit by BLE 2Mbps at 2480MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1		2479.650	58.68	29.75	88.44	N/A	N/A	Peak
2		2483.500	25.15	29.76	54.91	-19.09	74.00	Peak
3	*	2492.128	27.18	29.79	56.97	-17.03	74.00	Peak

Notes:

1. " * ", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC2	Test Date	2025-03-27
Temperature	17.9 °C	Humidity	34.3 %
Limit	FCC_Part 15_Band Edge (3m)	Test Engineer	Bob Zhang
Factor	DRH18-E_07105	Polarity	Horizontal
EUT	SMART IRRIGATION	Test Voltage	AC 120V/60Hz
Test Mode	Transmit by BLE 2Mbps at 2480MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1		2480.077	56.31	29.75	86.06	N/A	N/A	Average
2		2483.500	15.94	29.76	45.71	-8.29	54.00	Average
3	*	2494.663	17.17	29.79	46.96	-7.04	54.00	Average

Notes:

1. " * ", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC2	Test Date	2025-03-27
Temperature	17.9 °C	Humidity	34.3 %
Limit	FCC_Part 15_Band Edge (3m)	Test Engineer	Bob Zhang
Factor	DRH18-E_07105	Polarity	Vertical
EUT	SMART IRRIGATION	Test Voltage	AC 120V/60Hz
Test Mode	Transmit by BLE 2Mbps at 2480MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1		2479.661	71.55	29.75	101.30	N/A	N/A	Peak
2		2483.500	26.84	29.76	56.60	-17.40	74.00	Peak
3	*	2483.678	30.13	29.76	59.90	-14.10	74.00	Peak

Notes:

1. " * ", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

Site	WJ-AC2	Test Date	2025-03-27
Temperature	17.9 °C	Humidity	34.3 %
Limit	FCC_Part 15_Band Edge (3m)	Test Engineer	Bob Zhang
Factor	DRH18-E_07105	Polarity	Vertical
EUT	SMART IRRIGATION	Test Voltage	AC 120V/60Hz
Test Mode	Transmit by BLE 2Mbps at 2480MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB/m)	Measurement (dBμV/m)	Margin (dB)	Limit (dBμV/m)	Detector
1		2480.088	69.32	29.75	99.07	N/A	N/A	Average
2	*	2483.500	19.10	29.76	48.87	-5.13	54.00	Average

Notes:

1. " * ", means this data is the worst emission level.
2. C.F (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBμV/m) = Reading (dBμV) + C.F (dB/m).

A.8 AC Conducted Emissions Test Result

Site	WJ-SR5	Test Date	2025-03-28
Temperature	21.4 °C	Humidity	48.3 %
Limit	FCC Part 15.207_CE	Test Engineer	Carl Jiang
Factor	ENV216-07202_L1_Filter Off_C	Polarity	Line
EUT	SMART IRRIGATION	Test Voltage	AC 120V/60Hz
Test Mode	Transmit by BLE 2Mbps at 2440MHz		




No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB)	Measurement (dBμV)	Margin (dB)	Limit (dBμV)	Detector
1		0.150	20.25	9.87	30.12	-25.88	56.00	Average
2		0.150	25.16	9.87	35.03	-30.97	66.00	QP
3		0.198	18.87	9.85	28.72	-24.98	53.69	Average
4		0.198	23.67	9.85	33.52	-30.18	63.69	QP
5		0.350	17.20	9.87	27.07	-21.89	48.96	Average
6		0.350	22.97	9.87	32.84	-26.12	58.96	QP
7	*	0.502	24.08	9.91	33.99	-12.01	46.00	Average
8		0.502	32.53	9.91	42.44	-13.56	56.00	QP
9		0.826	10.85	10.04	20.89	-25.11	46.00	Average
10		0.826	15.76	10.04	25.80	-30.20	56.00	QP
11		18.113	18.49	10.57	29.06	-20.94	50.00	Average
12		18.113	25.75	10.57	36.32	-23.68	60.00	QP

Notes:

1. " * ", means this data is the worst emission level.
2. C.F (dB) = LISN Factor (dB) + Cable Loss (dB).
3. Measurement (dB μ V) = Reading (dB μ V) + C.F (dB).

Site	WJ-SR5	Test Date	2025-03-28
Temperature	21.4 °C	Humidity	48.3 %
Limit	FCC Part 15.207_CE	Test Engineer	Carl Jiang
Factor	ENV216-07202_N_Filter Off_C	Polarity	Neutral
EUT	SMART IRRIGATION	Test Voltage	AC 120V/60Hz
Test Mode	Transmit by BLE 2Mbps at 2440MHz		



No	Mark	Frequency (MHz)	Reading (dBμV)	C.F (dB)	Measurement (dBμV)	Margin (dB)	Limit (dBμV)	Detector
1		0.150	19.56	9.76	29.32	-26.68	56.00	Average
2		0.150	34.15	9.76	43.91	-22.09	66.00	QP
3		0.362	15.68	9.79	25.47	-23.22	48.68	Average
4		0.362	21.16	9.79	30.95	-27.74	58.68	QP
5	*	0.502	23.95	9.83	33.78	-12.22	46.00	Average
6		0.502	31.10	9.83	40.93	-15.07	56.00	QP
7		3.918	1.97	10.10	12.07	-33.93	46.00	Average
8		3.918	9.00	10.10	19.10	-36.90	56.00	QP
9		10.381	6.67	10.36	17.03	-32.97	50.00	Average
10		10.381	12.88	10.36	23.24	-36.76	60.00	QP
11		18.385	17.06	10.58	27.64	-22.36	50.00	Average
12		18.385	23.25	10.58	33.83	-26.17	60.00	QP

Notes:

1. " * ", means this data is the worst emission level.
2. C.F (dB) = LISN Factor (dB) + Cable Loss (dB).
3. Measurement (dB μ V) = Reading (dB μ V) + C.F (dB).

Appendix B - Test Setup Photograph

Refer to "R25S1034028-UT" file.

Appendix C - EUT Photograph

Refer to "R25S1034028-UE" file.

The End
