

Aixin Green Energy (Zhejiang) Technology Co.,Ltd

MPE ASSESSMENT REPORT

Report Type:

FCC MPE assessment report

MODEL:

Refer to Description of EUT for detail.

REPORT NUMBER:

2404B0444SHA-004

ISSUE DATE:

August 1, 2025

DOCUMENT CONTROL NUMBER:

TTRFFCCMPE-01_V1 © 2018 Intertek



TEST REPORT

Applicant: Aixin Green Energy (Zhejiang) Technology Co.,Ltd
No.6, Zhenying Road, Juexi Street, Xiangshan County, Ningbo City, Zhejiang,
P.R. China

Manufacturer: Aixin Green Energy (Zhejiang) Technology Co.,Ltd
No.6, Zhenying Road, Juexi Street, Xiangshan County, Ningbo City, Zhejiang,
P.R. China

Factory: Aixin Green Energy (Zhejiang) Technology Co.,Ltd
No.6, Zhenying Road, Juexi Street, Xiangshan County, Ningbo City, Zhejiang,
P.R. China

FCC ID: 2BMDX-MAX30ACJN

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

KDB447498 D01 General RF Exposure Guidance v06
FCC Part2.1091, FCC Part1.1307(b)

PREPARED BY:

REVIEWED BY:



Project Engineer
Sky Yang



Reviewer
Eric Li

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Revision History

Report No.	Version	Description	Issued Date
2404B0444SHA-004	Rev. 01	Initial issue of report	August 1, 2025

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	Max Charger AC Wallbox
Type/Model:	MAX-US-AC10J-6H, MAX-US-AC10N-6H, MAX-US-AC10J-6HG, MAX-US-AC10N-6HG, MAX-US-AC10J-14H, MAX-US-AC10N-14H, MAX-US-AC10J-14HG, MAX-US-AC10N-14HG, MAX-US-AC12J-H, MAX-US-AC12N-H, MAX-US-AC12J-HG, MAX-US-AC12N-HG, MAX-US-AC20J-H, MAX-US-AC20N-H, MAX-US-AC20J-HG, MAX-US-AC20N-HG, MAX-US-AC10J-6HD, MAX-US-AC10N-6HD, MAX-US-AC10J-6HD-G, MAX-US-AC10N-6HD-G, MAX-US-AC10J-14HD, MAX-US-AC10N-14HD, MAX-US-AC10J-14HD-G, MAX-US-AC10N-14HD-G, MAX-US-AC12J-HD, MAX-US-AC12N-HD, MAX-US-AC12J-HD-G, MAX-US-AC12N-HD-G, MAX-US-AC20J-HD, MAX-US-AC20N-HD, MAX-US-AC20J-HD-G, MAX-US-AC20N-HD-G, MAX-US-AC10J-6B, MAX-US-AC10N-6B, MAX-US-AC10J-6BG, MAX-US-AC10N-6BG, MAX-US-AC10J-14B, MAX-US-AC10N-14B, MAX-US-AC10J-14BG, MAX-US-AC10N-14BG, MAX-US-AC12J-B, MAX-US-AC12N-B, MAX-US-AC12J-BG, MAX-US-AC12N-BG, MAX-US-AC20J-B, MAX-US-AC20N-B, MAX-US-AC20J-BG, MAX-US-AC20N-BG, MAX-US-AC10J-6BD, MAX-US-AC10N-6BD, MAX-US-AC10J-6BD-G, MAX-US-AC10N-6BD-G, MAX-US-AC10J-14BD, MAX-US-AC10N-14BD, MAX-US-AC10J-14BD-G, MAX-US-AC10N-14BD-G, MAX-US-AC12J-BD, MAX-US-AC12N-BD, MAX-US-AC12J-BD-G, MAX-US-AC12N-BD-G, MAX-US-AC20J-BD, MAX-US-AC20N-BD, MAX-US-AC20J-BD-G, MAX-US-AC20N-BD-G
Description of EUT:	The EUT is an electric vehicle AC charging station. EUT contains certified wireless modules, the FCC ID is XMR2022FCM100D and XMR2023EG800QNA. All models are electrically identical except input cable, output connector, number of output and rated power.
Rating:	MAX-US-AC10J-6H, MAX-US-AC10N-6H, MAX-US-AC10J-6HG, MAX-US-AC10N-6HG, MAX-US-AC10J-14H, MAX-US-AC10N-14H, MAX-US-AC10J-14HG, MAX-US-AC10N-14HG, MAX-US-AC10J-6HD, MAX-US-AC10N-6HD, MAX-US-AC10J-6HD-G, MAX-US-AC10N-6HD-G, MAX-US-AC10J-14HD, MAX-US-AC10N-14HD, MAX-US-AC10J-14HD-G, MAX-US-AC10N-14HD-G, MAX-US-AC10J-6B, MAX-US-AC10N-6B, MAX-US-AC10J-6BG, MAX-US-AC10N-6BG, MAX-US-AC10J-14B, MAX-US-AC10N-14B, MAX-US-AC10J-14BG, MAX-US-AC10N-14BG, MAX-US-AC10J-6BD, MAX-US-AC10N-6BD, MAX-US-AC10J-6BD-G, MAX-US-AC10N-6BD-G, MAX-US-AC10J-14BD, MAX-US-AC10N-14BD, MAX-US-AC10J-14BD-G, MAX-US-AC10N-14BD-G: 208VAC/240VAC, 60Hz, 40A Max MAX-US-AC12J-H, MAX-US-AC12N-H, MAX-US-AC12J-HG, MAX-US-AC12N-HG, MAX-US-AC12J-HD, MAX-US-AC12N-HD, MAX-US-AC12J-HD-G, MAX-US-AC12N-HD-G, MAX-US-AC12J-B, MAX-US-AC12N-B, MAX-US-AC12J-BG, MAX-US-AC12N-BG, MAX-US-AC12J-BD, MAX-US-AC12N-BD, MAX-US-AC12J-BD-G, MAX-US-AC12N-BD-G: 208VAC/240VAC, 60Hz, 50A Max MAX-US-AC20J-H, MAX-US-AC20N-H, MAX-US-AC20J-HG, MAX-US-AC20N-HG, MAX-US-AC20J-HD, MAX-US-AC20N-HD, MAX-US-AC20J-HD-G, MAX-US-AC20N-HD-G, MAX-US-AC20J-B, MAX-US-AC20N-B, MAX-US-AC20J-BG, MAX-US-AC20N-BG, MAX-US-AC20J-BD, MAX-US-AC20N-BD, MAX-US-AC20J-BD-G, MAX-US-AC20N-BD-G: 208VAC/240VAC, 60Hz, 80A Max

TEST REPORT

Category of EUT:	Class B
EUT type:	☒ Table top ☐ Floor standing
Software Version:	-
Hardware Version:	-
Serial numbers:	A250724-27
Sample received date:	July 24, 2025
Date of test:	July 24, 2025 ~ July 30, 2025

Model	Input cable	Output connector	Number of output	Max current
MAX-US-AC10J-6H, MAX-US-AC10J-6B MAX-US-AC10J-6HG, MAX-US-AC10J-6BG	6-50P	CCS1	1	40A
MAX-US-AC10N-6H, MAX-US-AC10N-6B MAX-US-AC10N-6HG, MAX-US-AC10N-6BG	6-50P	NACS	1	40A
MAX-US-AC10J-14H, MAX-US-AC10J-14B MAX-US-AC10J-14HG, MAX-US-AC10J-14BG	14-50P	CCS1	1	40A
MAX-US-AC10N-14H, MAX-US-AC10N-14B MAX-US-AC10N-14HG, MAX-US-AC10N-14BG	14-50P	NACS	1	40A
MAX-US-AC10J-6HD, MAX-US-AC10J-6BD MAX-US-AC10J-6HD-G, MAX-US-AC10J-6BD-G	6-50P	CCS1	2	40A
MAX-US-AC10N-6HD, MAX-US-AC10N-6BD MAX-US-AC10N-6HD-G, MAX-US-AC10N-6BD-G	6-50P	NACS	2	40A
MAX-US-AC10J-14HD, MAX-US-AC10J-14BD MAX-US-AC10J-14HD-G, MAX-US-AC10J-14BD-G	14-50P	CCS1	2	40A
MAX-US-AC10N-14HD, MAX-US-AC10N-14BD MAX-US-AC10N-14HD-G, MAX-US-AC10N-14BD-G	14-50P	NACS	2	40A
MAX-US-AC12J-H, MAX-US-AC12J-B MAX-US-AC12J-HG, MAX-US-AC12J-BG	\	CCS1	1	50A
MAX-US-AC12N-H, MAX-US-AC12N-B MAX-US-AC12N-HG, MAX-US-AC12N-BG	\	NACS	1	50A
MAX-US-AC12J-HD, MAX-US-AC12J-BD MAX-US-AC12J-HD-G, MAX-US-AC12J-BD-G	\	CCS1	2	50A
MAX-US-AC12N-HD, MAX-US-AC12N-BD MAX-US-AC12N-HD-G, MAX-US-AC12N-BD-G	\	NACS	2	50A
MAX-US-AC20J-H, MAX-US-AC20J-B MAX-US-AC20J-HG, MAX-US-AC20J-BG	\	CCS1	1	80A
MAX-US-AC20N-H, MAX-US-AC20N-B MAX-US-AC20N-HG, MAX-US-AC20N-BG	\	NACS	1	80A
MAX-US-AC20J-HD, MAX-US-AC20J-BD MAX-US-AC20J-HD-G, MAX-US-AC20J-BD-G	\	CCS1	2	80A
MAX-US-AC20N-HD, MAX-US-AC20N-BD MAX-US-AC20N-HD-G, MAX-US-AC20N-BD-G	\	NACS	2	80A

1.2 Technical Specification

Frequency Range:	13.56 MHz ~ 13.56 MHz
Modulation:	ASK
Antenna gain:	PCB antenna

1.3 Description of Test Facility

Name:	Intertek Testing Services (Shanghai FTZ) Co., Ltd.
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L21189
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Member No.: 3598 (Registration No.: R-14243, G-10845, C-14723, T-12252)
	A2LA Accreditation Lab Certificate Number: 3309.02

2 MPE Assessment

Test result: Pass

2.1 MPE Assessment Limit

Mobile device exposure for standalone operations:

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

Note: f = frequency in MHz. * = Plane-wave equivalent power density.

Mobile device exposure for simultaneous transmission operations: **the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is ≤ 1.0**

2.2 Assessment Results

Power density (S) is calculated according to the formula:

$$S = PG / (4\pi R^2)$$

Where S = power density in mW/cm²

P = Power in mW

G = numeric gain of transmit antenna

R = distance (cm)

Limit for 13.56MHz is 60.77 V/m

As we can see from the test report 2404B0444SHA-003:

$$60.6\text{dBuV/m}@3\text{m}, @20\text{cm}=@3\text{m}+40\log(3/0.2)=107.64\text{dBuV/m}=0.241\text{V/m}<60.77.$$

The power for WIFI module refers to certificate of FCC ID: XMR2022FCM100D

The power for LTE module refers to certificate of FCC ID: XMR2023EG800QNA

The calculations in the table below use the highest gain of antenna for client EUT. These calculations represent worst case in terms of the exposure levels.

Wireless Module	Frequency Range (MHz)	P		G		R (cm)	S (mW/cm ²)	Limits (mW/cm ²)
		(dBm)	(mW)	(dBi)	(numeric)			
XMR2022FCM100D	2.4G WLAN	19.12	81.658	-1	0.794	20	0.0129	1.0000
	Bluetooth	6.44	4.406	-1	0.794	20	0.000696	1.0000
XMR2023EG800QNA	LTE Band 2	25	316.23	4	2.512	20	0.158	1
	LTE Band 4	25	316.23	4	2.512	20	0.158	1
	LTE Band 5	25	316.23	4	2.512	20	0.158	0.549
	LTE Band 12	25	316.23	4	2.512	20	0.158	0.466
	LTE Band 13	25	316.23	4	2.512	20	0.158	0.518
	LTE Band 66	25	316.23	4	2.512	20	0.158	1

Note: 1 mW/cm² from 1.310 Table 1.

RFID, LTE and WIFI/Bluetooth can transmit simultaneously, so the maximum rate of MPE is, $0.241/60.77+0.0129/1+0.158/0.466=0.356 < 1.0$.

Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation.

To ensure compliance, operations at closer than this distance is not recommended.

*****END*****