

Aixin Green Energy (Zhejiang) Technology Co.,Ltd

RF TEST REPORT

Report Type:

FCC Part 15.225 RF report

MODEL:

UA-US-AC10J-6H, UA-US-AC10J-14H,
UA-US-AC10N-6H, UA-US-AC10N-14H,
UA-US-AC10J-6HG, UA-US-AC10J-14HG,
UA-US-AC10N-6HG, UA-US-AC10N-14HG,
UA-US-AC12J-H, UA-US-AC12N-H,
UA-US-AC12J-HG, UA-US-AC12N-HG,
UA-US-AC20J-H, UA-US-AC20N-H,
UA-US-AC20J-HG, UA-US-AC20N-HG

REPORT NUMBER:

2404B0444SHA-001

ISSUE DATE:

August 1, 2025

DOCUMENT CONTROL NUMBER:

TTRF15.225_V1 © 2018 Intertek



Applicant: Aixin Green Energy (Zhejiang) Technology Co.,Ltd
No.6, Zhenying Road, Juexi Street, Xiangshan County, Ningbo City, Zhejiang,
P.R. China

Manufacturer: Aixin Green Energy (Zhejiang) Technology Co.,Ltd
No.6, Zhenying Road, Juexi Street, Xiangshan County, Ningbo City, Zhejiang,
P.R. China

Factory: Aixin Green Energy (Zhejiang) Technology Co.,Ltd
No.6, Zhenying Road, Juexi Street, Xiangshan County, Ningbo City, Zhejiang,
P.R. China

FCC ID: 2BMDX-UAH10ACJN

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

47CFR Part 15 (2024): Radio Frequency Devices (Subpart C)

ANSI C63.10 (2020): American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

PREPARED BY:

REVIEWED BY:



Project Engineer
Sky Yang



Reviewer
Eric Li

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT

Content

REVISION HISTORY.....	4
MEASUREMENT RESULT SUMMARY	5
1 GENERAL INFORMATION	6
1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	6
1.2 TECHNICAL SPECIFICATION.....	7
1.3 DESCRIPTION OF TEST FACILITY.....	7
2 TEST SPECIFICATIONS.....	8
2.1 STANDARDS OR SPECIFICATION	8
2.2 MODE OF OPERATION DURING THE TEST	8
2.3 TEST SOFTWARE LIST	8
2.4 TEST PERIPHERALS LIST.....	8
2.5 TEST ENVIRONMENT CONDITION:.....	8
2.6 INSTRUMENT LIST	9
2.7 MEASUREMENT UNCERTAINTY.....	10
3 FUNDAMENTAL EMISSION	11
3.1 LIMIT	11
3.2 MEASUREMENT PROCEDURE	11
3.3 TEST CONFIGURATION	12
3.4 TEST RESULTS OF FUNDAMENTAL EMISSIONS	13
4 SPURIOUS EMISSION	14
4.1 LIMIT	14
4.2 MEASUREMENT PROCEDURE	14
4.3 TEST RESULTS OF RADIATED EMISSIONS	16
5 FREQUENCY STABILITY (TEMPERATURE VARIATION)	20
5.1 TEST LIMIT	20
5.2 TEST CONFIGURATION	20
5.3 TEST PROCEDURE AND TEST SETUP	21
5.4 TEST PROTOCOL.....	21
6 FREQUENCY STABILITY (VOLTAGE VARIATION)	22
6.1 TEST LIMIT	22
6.2 TEST CONFIGURATION	22
6.3 TEST PROCEDURE AND TEST SETUP	22
6.4 TEST PROTOCOL.....	23
7 CONDUCTED EMISSIONS	24
7.1 LIMIT	24
7.2 TEST CONFIGURATION	24
7.3 MEASUREMENT PROCEDURE	25
7.4 TEST RESULTS OF CONDUCTED EMISSIONS.....	26
8 20DB BANDWIDTH	28
8.1 LIMIT.....	28
8.2 TEST CONFIGURATION	28
8.3 TEST PROCEDURE AND TEST SET UP	29
8.4 TEST PROTOCOL	30
9 ANTENNA REQUIREMENT.....	31

Revision History

Report No.	Version	Description	Issued Date
2404B0444SHA-001	Rev. 01	Initial issue of report	August 1, 2025

Measurement result summary

TEST ITEM	FCC REFERENCE	RESULT
Fundamental emission	15.225(a) (b) (c)	Pass
Spurious emission	15.225(d)	Pass
Frequency stability	15.225(e)	Pass
Conducted emissions	15.207	Pass
99% and 20dB Bandwidth	15.215(c)	Pass
Antenna requirement	15.203	Pass

Notes: 1: NA =Not Applicable

2: Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	Ultra-H Charger AC Wallbox
Type/Model:	UA-US-AC10J-6H, UA-US-AC10J-14H, UA-US-AC10N-6H, UA-US-AC10N-14H, UA-US-AC10J-6HG, UA-US-AC10J-14HG, UA-US-AC10N-6HG, UA-US-AC10N-14HG, UA-US-AC12J-H, UA-US-AC12N-H, UA-US-AC12J-HG, UA-US-AC12N-HG, UA-US-AC20J-H, UA-US-AC20N-H, UA-US-AC20J-HG, UA-US-AC20N-HG
Description of EUT:	The EUT is an electric vehicle AC charging station. EUT contains certified wireless modules, the FCC ID is XMR2022FCM100D and XMR2023EG800QNA. All models are electrically identical except input cable, output connector and rated power. UA-US-AC10J-6H, UA-US-AC10J-6HG, UA-US-AC10N-6H and UA-US-AC10N-6HG are equipped with 6-50P input cable. UA-US-AC10J-14H, UA-US-AC10J-14HG, UA-US-AC10N-14H and UA-US-AC10N-14HG are equipped with 14-50P input cable. UA-US-AC10J-6H, UA-US-AC10J-14H, UA-US-AC12J-H, UA-US-AC20J-H, UA-US-AC10J-6HG, UA-US-AC10J-14HG, UA-US-AC12J-HG and UA-US-AC20J-HG are equipped with type1 output connector. UA-US-AC10N-6H, UA-US-AC10N-14H, UA-US-AC12N-H, UA-US-AC20N-H, UA-US-AC10N-6HG, UA-US-AC10N-14HG, UA-US-AC12N-HG and UA-US-AC20N-HG are equipped with NACS output connector. UA-US-AC10J-6H, UA-US-AC10J-14H, UA-US-AC10N-6H, UA-US-AC10N-14H, UA-US-AC12J-H, UA-US-AC12N-H, UA-US-AC20J-H and UA-US-AC20N-H doesn't have LTE function. UA-US-AC10J-6HG, UA-US-AC10J-14HG, UA-US-AC10N-6HG, UA-US-AC10N-14HG, UA-US-AC12J-HG, UA-US-AC12N-HG, UA-US-AC20J-HG and UA-US-AC20N-HG have LTE function. We test UA-US-AC20N-HG as representative and list the worst result in the report.
Rating:	UA-US-AC10J-6H, UA-US-AC10J-14H, UA-US-AC10N-6H, UA-US-AC10N-14H, UA-US-AC10J-6HG, UA-US-AC10J-14HG, UA-US-AC10N-6HG, UA-US-AC10N-14HG: 208VAC/240VAC, 60Hz, 40A Max UA-US-AC12J-H, UA-US-AC12N-H, UA-US-AC12J-HG, UA-US-AC12N-HG: 208VAC/240VAC, 60Hz, 50A Max UA-US-AC20J-H, UA-US-AC20N-H, UA-US-AC20J-HG, UA-US-AC20N-HG: 208VAC/240VAC, 60Hz, 80A Max
Category of EUT:	Class B
EUT type:	☒ Table top ☐ Floor standing
Software Version:	-
Hardware Version:	-
Serial numbers:	A250724-26
Sample received date:	July 24, 2025
Date of test:	July 24, 2025 ~ July 30, 2025

TEST REPORT

1.2 Technical Specification

Frequency Range:	13.56 MHz ~ 13.56 MHz
Modulation:	ASK
Antenna:	PCB antenna

1.3 Description of Test Facility

Name:	Intertek Testing Services (Shanghai FTZ) Co., Ltd.
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L21189
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Member No.: 3598 (Registration No.: R-14243, G-10845, C-14723, T-12252)
	A2LA Accreditation Lab Certificate Number: 3309.02

2 TEST SPECIFICATIONS

2.1 Standards or specification

47CFR Part 15 (2024)

ANSI C63.10 (2020)

2.2 Mode of operation during the test

While testing, the internal modulation and continuously transmission was applied.

2.3 Test software list

Test Items	Software	Manufacturer	Version
Conducted emission	SKET Auto EMC Test Software	Keleto	V3.0
Radiated emission	SKET Auto EMC Test Software	Keleto	V3.0

2.4 Test peripherals list

Item No	Description	Band and Model	S/No

2.5 Test environment condition:

Test items	Temperature	Humidity
Radiated emission	26°C	53% RH
Power line conducted emission	27°C	53% RH

TEST REPORT

2.6 Instrument list

Conducted Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Test Receiver	R&S	ESR7	EC 6194	2026-02-17
☒	A.M.N.	R&S	ESH2-Z5	EC 3119	2026-07-22
☒	Shielded room	Zhongyu	-	EC 2838	2027-01-08
Radiated Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Test Receiver	R&S	ESIB 26	EC 3045	2025-08-18
☒	Bilog Antenna	TESEQ	CBL 6112B	EC 6411	2025-09-11
☒	Active loop antenna	Schwarzbeck	FMZB1519	EC 5345	2025-08-10
☒	Semi-anechoic chamber	Albatross project	-	EC 3048	2026-07-11
RF test					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Spectrum Analyzer	Keysight	N9030B	EC 6078	2026-03-25
☒	Climate chamber	GWS	MT3065	EC 6021	2026-03-07
Additional instrument					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Thermo-Hygrograph	Testo	175h1	EC 6640	2025-08-29
☒	Thermo-Hygrograph	Testo	175h1	EC6642	2025-08-29

TEST REPORT

2.7 Measurement uncertainty

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Frequency	Expanded Uncertainty ($k=2$)
Conducted emission at mains ports	9kHz ~ 150kHz	3.52 dB
	150kHz ~ 30MHz	3.19 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	3.06 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	5.02 dB
	6GHz ~ 18GHz	5.28 dB

3 Fundamental Emission

Test result: Pass

3.1 Limit


Frequencies (MHz)	Limit at 30m (dBuV/m)	Limit at 3m (dBuV/m)
13.110 – 13.410	40.50	80.50
13.410 – 13.553	50.50	90.50
13.553 – 13.567	84.00	124.00
13.567 – 13.710	50.50	90.50
13.710 – 14.010	40.50	80.50

3.2 Measurement Procedure


- The EUT was placed on a 0.8m plank above the ground at a 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- Both X and Y axes of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to PK Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

TEST REPORT**3.3 Test Configuration**

3.4 Test Results of Fundamental Emissions



Antenna Polarization	Frequency (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin	Detector
X	13.56	59.7	124.00	64.3	PK
Y	13.56	58.7	124.00	65.3	PK

Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.
 2. Corrected Reading = Original Receiver Reading + Correct Factor
 3. Margin = Limit - Level

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,
 Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV,
 Limit = 40.00dBuV/m.
 Then Correct Factor = 30.20 + 2.00 – 32.00 = 0.20dB/m;
 Level = 10dBuV + 0.20dB/m = 10.20dBuV/m;
 Margin = 40.00dBuV/m - 10.20dBuV/m = 29.80dB.

4 Spurious Emission

Test result: Pass

4.1 Limit

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

4.2 Measurement Procedure

For Radiated emission below 30MHz:

- The EUT was placed on a 0.8m plank above the ground at a 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- Both X and Y axes of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz:

- The EUT was placed on a 0.8m plank above the ground at a 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.



TEST REPORT

- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
- 3. All modes of operation were evaluated and the worst-case emissions were reported

4.3 Test Results of Radiated Emissions



TEST REPORT

Test data below 30MHz:

Frequency	Limit (dBuV/m)	Level (dBuV/m)	Delta	Detector	Polarity
508.918kHz	73.5	58.3	-15.2	PK	X
748.196kHz	70.1	48.8	-21.3	PK	X
987.475kHz	67.7	38.6	-29.1	PK	X
10.319MHz	69.5	34.2	-35.3	PK	X
508.918kHz	73.5	55.0	-18.5	PK	Y
808.016kHz	69.5	48.3	-21.2	PK	Y
4.397MHz	69.5	37.7	-31.8	PK	Y
5.773MHz	69.5	34.4	-35.1	PK	Y
10.319MHz	69.5	34.9	-34.6	PK	Y

Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.

2. Level = Original Receiver Reading + Correct Factor

3. Delta = Level - Limit

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,

Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV,


Limit = 40.00dBuV/m.

Then Correct Factor = 30.20 + 2.00 – 32.00 = 0.20dB/m;


Level = 10dBuV + 0.20dB/m = 10.20dBuV/m;

Delta = 10.20dBuV/m - 44.00dBuV/m = -29.80dB.

H



V



TEST REPORT

Test data from 30MHz to 1000MHz:

Antenna Polarization	Frequency	Limit (dBuV/m)	Level (dBuV/m)	Delta (dB)	Detector
H	192.475MHz	43.5	32.8	-10.7	PK
H	200.526MHz	43.5	33.8	-9.7	PK
H	300.048MHz	46.0	37.4	-8.6	PK
H	400.055MHz	46.0	37.5	-8.5	PK
H	500.062MHz	46.0	39.4	-6.6	PK
H	600.069MHz	46.0	40.3	-5.7	PK
V	31.164MHz	40.0	24.5	-15.5	PK
V	43.677MHz	40.0	24.6	-15.4	PK
V	196.937MHz	43.5	24.8	-18.7	PK
V	500.062MHz	46.0	39.6	-6.4	PK
V	624.125MHz	46.0	35.2	-10.8	PK
V	800.083MHz	46.0	38.5	-7.5	PK

Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.

2. Level = Original Receiver Reading + Correct Factor

3. Delta = Level - Limit

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,

Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV,
Limit = 40.00dBuV/m.

Then Correct Factor = $30.20 + 2.00 - 32.00 = 0.20\text{dB/m}$;

Level = $10\text{dBuV} + 0.20\text{dB/m} = 10.20\text{dBuV/m}$;

Delta = $10.20\text{dBuV/m} - 44.00\text{dBuV/m} = -29.80\text{dB}$.


5 Frequency Stability (Temperature Variation)

Test result: PASS

5.1 Test limit

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+50$ degrees C at normal supply voltage.

5.2 Test Configuration



TEST REPORT

5.3 Test procedure and test setup

Test Procedure as per ANSI 63.10 clause 6.8.1.

5.4 Test protocol

Voltage (V)	Temp (°C)	Freq measured (MHz)	Freq nominal (MHz)	Tolerance (%)	Limit (%)
240	-20	13.5603	13.56	0.002	0.01
	-10	13.5596		-0.003	
	0	13.5598		-0.001	
	10	13.5602		0.001	
	20	13.5601		0.0007	
	30	13.5604		0.003	
	40	13.5597		-0.002	
	50	13.5601		0.0007	


6 Frequency Stability (Voltage Variation)

Test result: PASS

6.1 Test limit

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

6.2 Test Configuration



6.3 Test procedure and test setup

Test Procedure as per ANSI 63.10 clause 6.8.2.

6.4 Test protocol

Temp (°C)	Voltage (V)	Freq Measured (MHz)	Freq nominal (MHz)	Tolerance (%)	Limit (%)
20	176	13.5603	13.56	0.002	±0.01
	208	13.5601		0.0007	
	240	13.5597		-0.002	
	276	13.5604		0.003	

TEST REPORT

7 Conducted emissions


Test result: Pass

7.1 Limit

Frequency range (MHz)	Limits dB(μV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 ~ 56 *	56 ~ 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

Note: 1. * Means the limit decreasing linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz

7.2 Test Configuration



TEST REPORT**7.3 Measurement Procedure**

Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the 50 Ω LISN port (to which the EUT is connected), where permitted, terminated into a 50 Ω measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the 50 Ω measuring port is terminated by a measuring instrument having 50 Ω input impedance. All other ports are terminated in 50 Ω loads.

Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.


The bandwidth of the test receiver is set at 9 kHz.

TEST REPORT


7.4 Test Results of Conducted Emissions

Test Voltage: 240VAC/60Hz

L1 Line



L2 Line



No.	Frequency	Limit dBuV	Level dBuV	Margin dB	Detector	Phase
1	2.846MHz	56.00	48.60	7.40	QP	L1
2	2.870MHz	56.00	49.48	6.52	QP	L2
3	3.118MHz	56.00	47.94	8.06	QP	L2
4	3.338MHz	56.00	47.30	8.70	QP	L1
5	5.338MHz	60.00	55.47	4.53	QP	L2
6	5.374MHz	60.00	54.33	5.67	QP	L1
7	5.898MHz	60.00	53.49	6.51	QP	L1
8	6.086MHz	60.00	55.13	4.87	QP	L2
9	9.638MHz	60.00	54.23	5.77	QP	L2
10	9.810MHz	60.00	52.17	7.83	QP	L1
11	10.158MHz	60.00	54.96	5.04	QP	L2
12	10.362MHz	60.00	52.51	7.49	QP	L1
13	982.000kHz	46.00	37.40	8.60	CAV	L1
14	1.002MHz	46.00	37.05	8.95	CAV	L2
15	2.766MHz	46.00	38.49	7.51	CAV	L2
16	2.774MHz	46.00	37.88	8.12	CAV	L1
17	3.190MHz	46.00	36.61	9.39	CAV	L1
18	3.530MHz	46.00	35.87	10.13	CAV	L2
19	13.560MHz	-	-	-	-	L1
20	13.560MHz	-	-	-	-	L2

Remark: 1. Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.

2. Level = Original Receiver Reading + Factor

3. Margin = Limit – Level

4. the emissions of 13.56MHz are the product's RF signal.

Example: Assuming LISN Factor = 10.00dB, Cable Loss = 2.00dB,

Original Receiver Reading = 10.00dBuV, Limit = 66.00dBuV.

Then Factor = 10.00 + 2.00 = 12.00dB;

Level = 10dBuV + 12.00dB = 22.00dBuV;

Margin = 66.00dBuV - 22.00dBuV = 44.00dB.


8 20dB Bandwidth

Test result: Pass

8.1 Limit

The 20dB bandwidth should be fallen in the allocated operating frequency range.
No limit for 99% bandwidth.

8.2 Test configuration



8.3 Test procedure and test set up

The measurement was applied in a 3m semi-anechoic chamber.


The center of the loop antenna shall be 1 m above the horizontal metal ground plane.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set RBW = 1 % to 5 % of the OBW
3. Set VBW $\geq 3 \cdot$ RBW
4. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
5. Use the 99 % power bandwidth function of the instrument (if available).
6. the 20dB bandwidth is also measured with the same setting.

8.4 Test protocol

	Lower point (MHz)	Higher point (MHz)	Bandwidth (kHz)	Allocated bandwidth (MHz)
20dB Bandwidth	13.562161	13.562465	0.304	13.553 ~ 13.567
Occupied bandwidth	13.561701	13.562919	1.218	13.553 ~ 13.567



9 Antenna requirement

Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Result:

EUT uses permanently attached antenna to the intentional radiator, so it can comply with the provisions of this section.

***** END *****