

# FCC RF Exposure

EUT Description: wireless mouse

Model No.: 7043

FCC ID: 2BMFL-7043

## 1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$ 50 mm are determined by:

$[(\text{max power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$

Where:

$$\text{Result} = P/D \cdot \sqrt{f}$$

F= the RF channel transmit frequency in GHz

P= Maximum turn-up power in mw

D= Min. test separation distance in mm

## 2. Test Result of RF Exposure Evaluation

|         | Frequency (MHz) | Output power (dBm) | Tune Up Power (dBm) | Max Tune Up power (dBm/mW) | Min test separation distance (mm) | Result | Limit (mW/cm <sup>2</sup> ) | SAR Test Exclusion |
|---------|-----------------|--------------------|---------------------|----------------------------|-----------------------------------|--------|-----------------------------|--------------------|
| EDR     | 2480            | -1.85              | -2±1(-1)            | 0.794                      | 5                                 | 0.250  | 3.0                         | Pass               |
| 2.4G TX | 2480            | 4.54               | 4±1(5)              | 3.162                      | 5                                 | 0.996  | 3.0                         | Pass               |

Note:  
PK Output power= conducted power.  
Conducted power see the test report HK2410236232-1E/2E, antenna gain=3.55dBi  
 $EIRP(\text{dBm}) = 99.74(\text{dBuV/m}) - 95.2 = 4.54(\text{dBm})$   
2.4G TX and Bluetooth cannot be transmitted at the same time.

Per KDB 447498 D01, when the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.996 which is  $\leq 3$ , RF Exposure testing is not required.

Note: Exclusion Thresholds Results =  $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Distance=5mm