

FCC ID:2BMGL-65029**Portable device**

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHZ})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHZ})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is $<$ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

EDR:

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	3.769	2.38	3 \pm 1	4.00	2.51	<5	0.77860	3.00	YES
	2.441	3.645	2.31	3 \pm 1	4.00	2.51	<5	0.78490	3.00	YES
	2.480	3.553	2.27	3 \pm 1	4.00	2.51	<5	0.79114	3.00	YES
π /4DQPSK	2.402	4.454	2.79	4 \pm 1	5.00	3.16	<5	0.98020	3.00	YES
	2.441	4.357	2.73	4 \pm 1	5.00	3.16	<5	0.98813	3.00	YES
	2.480	4.225	2.65	4 \pm 1	5.00	3.16	<5	0.99599	3.00	YES
8DQPSK	2.402	4.711	2.96	4 \pm 1	5.00	3.16	<5	0.98020	3.00	YES
	2.441	4.593	2.88	4 \pm 1	5.00	3.16	<5	0.98813	3.00	YES
	2.480	4.443	2.78	4 \pm 1	5.00	3.16	<5	0.99599	3.00	YES

Conclusion:

For the max result : 0.99599 \leq FCC Limit 3.0 for 1g SAR.