



FCC TEST REPORT

FCC ID: 2BMIE-AS-42

Product	:	Speaker
Model Name	:	AS-42, MK1, MK2
Brand	:	AORS
Report No.	:	PTC24121306502E-FC02

Prepared for

Shenzhen Plack Audio Co.,Ltd

Room 201 Building H, JunXuan Technology Park, NO.16 YinKui Road, KuiChong Town,
DaPeng new district, Shenzhen city

Prepared by

Precise Testing & Certification Co., Ltd.

Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China.



Report No.: PTC24121306502E-FC02

TEST RESULT CERTIFICATION

Applicant's name : Shenzhen Plack Audio Co.,Ltd
Address : Room 201 Building H, JunXuan Technology Park, NO.16 YinKui Road, KuiChong Town, DaPeng new district, Shenzhen city
Manufacturer's name : Shenzhen Plack Audio Co.,Ltd
Address : Room 201 Building H, JunXuan Technology Park, NO.16 YinKui Road, KuiChong Town, DaPeng new district, Shenzhen city
Product name : Speaker
Model name : AS-42, MK1, MK2
Test procedure : FCC CFR47 Part 1.1307(b)(1)
Test Date : Dec. 23, 2024 to Jan. 7, 2025
Date of Issue : Jan. 7, 2025
Test Result : PASS

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink, appearing to read 'Jack Zhou'.

Jack Zhou / Engineer

Technical Manager:

A handwritten signature in black ink, appearing to read 'Simon Pu'.

Simon Pu / Manager



Contents

	Page
2 TEST SUMMARY	4
3 GENERAL INFORMATION	5
3.1 GENERAL DESCRIPTION OF E.U.T	5
4 RF EXPOSURE	6
4.1 REQUIREMENTS	6
4.2 THE PROCEDURES / LIMIT	6
4.3 MPE CALCULATION METHOD	7
4.4 TEST RESULT	7



2 Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	15.247 (i)	PASS
Remark:		
N/A: Not Applicable		



3 General Information

3.1 General Description of E.U.T.

Product Name	:	Speaker
Model Name	:	AS-42, MK1, MK2
Specification	:	Bluetooth BDR+EDR
Operation Frequency	:	2402-2480MHz for BT
Number of Channel	:	79 channels for BDR+EDR
Type of Modulation	:	GFSK, $\Pi/4$ -DQPSK,8DPSK For DSS
Antenna installation	:	PCB antenna
Antenna Gain	:	0 dBi
Power supply	:	Input: AC100-240V 50/60Hz Output: 50W*2
Hardware Version	:	N/A
Software Version	:	N/A



4 RF Exposure

Test Requirement : FCC Part 1.1307(b)(1)

Evaluation Method : KDB 447498 D01 General RF Exposure Guidance v06

4.1 Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

4.2 The procedures / limit

(A) Limits for Occupational / Controlled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density



4.3 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } P_d \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = \frac{30 \times P \times G}{377 \times d^2} \theta \varphi$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

4.4 Test Result

Mode	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Tune up tolerance (dBm)	Max Tune Up Power (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)	Result
2402(DH5)	1	4.53	4.53±1	3.5727	0.000711	1	Pass

Conclusion:

1. Calculate in the worst-case mode.
2. Max. Tune Up Power is declared by manufacturer, and used to calculate.

*****THE END REPORT*****