

CFR 47 FCC PART 15 SUBPART C(DTS)

TEST REPORT

For

Eagle

MODEL NUMBER: JMK1, JMK2

REPORT NUMBER: E04A24100876F00402

ISSUE DATE: December 19, 2024

FCC ID: 2BMIS-JMK1

Prepared for

Shenzhen Jimuyida Technology Co., Limited

21st Floor, Li-Ning Center, Shennan Avenue, Nanshan District, Shenzhen.

Prepared by

Guangdong Global Testing Technology Co., Ltd.

**Room 101-105, 203-210, Building 1, No.2, Keji 8 Road, Songshan Lake Park,
Dongguan city, Guangdong, People's Republic of China, 523808**

**This report is based on a single evaluation of the submitted sample(s) of the above mentioned product, it does not imply an assessment of the production of the products.
This report shall not be reproduced, except in full, without the written approval of
Guangdong Global Testing Technology Co., Ltd.**

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	December 19, 2024	Initial Issue	

Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
Antenna Requirement	N/A	FCC Part 15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	ANSI C63.10-2013, Clause 6.2	FCC Part 15.207	Pass
Conducted Output Power	ANSI C63.10-2013, Clause 11.9.1.3	FCC Part 15.247 (b)(3)	Pass
6dB Bandwidth and 99% Occupied Bandwidth	ANSI C63.10-2013, Clause 11.8.1	FCC Part 15.247 (a)(2)	Pass
Power Spectral Density	ANSI C63.10-2013, Clause 11.10.2	FCC Part 15.247 (e)	Pass
Conducted Band edge and spurious emission	ANSI C63.10-2013, Clause 11.11	FCC Part 15.247(d)	Pass
Radiated Band edge and Spurious Emission	ANSI C63.10-2013, Clause 11.11 & Clause 11.12	FCC Part 15.205/15.209	Pass
Duty Cycle	ANSI C63.10-2013, Clause 11.6	None; for reporting purposes only.	Pass

*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART C(DTS)> when <Accuracy Method> decision rule is applied.

CONTENTS

1. ATTESTATION OF TEST RESULTS.....	5
2. TEST METHODOLOGY.....	6
3. FACILITIES AND ACCREDITATION.....	6
4. CALIBRATION AND UNCERTAINTY	7
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	<i>7</i>
4.2. <i>MEASUREMENT UNCERTAINTY.....</i>	<i>7</i>
5. EQUIPMENT UNDER TEST	8
5.1. <i>DESCRIPTION OF EUT</i>	<i>8</i>
5.2. <i>CHANNEL LIST</i>	<i>9</i>
5.3. <i>Maximum Conducted Output Power.....</i>	<i>9</i>
5.4. <i>TEST CHANNEL CONFIGURATION.....</i>	<i>9</i>
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER</i>	<i>9</i>
5.6. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	<i>11</i>
5.7. <i>EUT ACCESSORY</i>	<i>11</i>
5.8. <i>SUPPORT UNITS FOR SYSTEM TEST.....</i>	<i>12</i>
5.9. <i>SETUP DIAGRAM</i>	<i>12</i>
6. MEASURING EQUIPMENT AND SOFTWARE USED.....	13
7. ANTENNA PORT TEST RESULTS	15
7.1. <i>Conducted Output Power.....</i>	<i>15</i>
7.2. <i>6dB Bandwidth and 99% Occupied Bandwidth</i>	<i>16</i>
7.3. <i>Power Spectral Density.....</i>	<i>18</i>
7.4. <i>Conducted Band edge and spurious emission</i>	<i>19</i>
7.5. <i>Duty Cycle</i>	<i>21</i>
8. RADIATED TEST RESULTS.....	22
8.1. <i>Radiated Band edge and Spurious Emission</i>	<i>28</i>
9. ANTENNA REQUIREMENT	44
10. AC POWER LINE CONDUCTED EMISSION	45
11. TEST DATA - Appendix A.....	48

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Shenzhen Jimuyida Technology Co., Limited
Address: 21st Floor, Li-Ning Center, Shennan Avenue, Nanshan District, Shenzhen.

Manufacturer Information

Company Name: Wuhan Chizi Technology Co., Ltd
Address: 2F, Building B, HaiRongJi Incubation Park, Great Wall Park 3rd Road, WuDaYuan Road, Hongshan District, Wuhan

EUT Information

Product Description: Eagle
Model: JMK1
Series Model: JMK2
Brand:



Sample Received Date: November 12, 2024
Sample Status: Normal
Sample ID: A24100876 001
Date of Tested: November 12, 2024 to December 19, 2024

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C(DTS)	Pass

Prepared By:

Win Huang

Win Huang

Project Engineer

Checked By:

Alan He

Alan He

Laboratory Leader

Approved By:

Shawn Wan

Shawn Wan

Laboratory Manager

2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART C(DTS)

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 6947.01) Guangdong Global Testing Technology Co., Ltd. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1343) Guangdong Global Testing Technology Co., Ltd. has been recognized to perform compliance testing on equipment subject to Supplier's Declaration of Conformity (SDoC) and Certification rules ISED (Company No.: 30714) Guangdong Global Testing Technology Co., Ltd. has been registered and fully described in a report filed with ISED. The Company Number is 30714 and the test lab Conformity Assessment Body Identifier (CABID) is CN0148.
---------------------------	--

Note: All tests measurement facilities use to collect the measurement data are located at Room 101-105, 203-210, Building 1, No.2, Keji 8 Road, Songshan Lake Park, Dongguan city, Guangdong, People's Republic of China, 523808

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Items	k	Uncertainty
DTS Bandwidth	1.96	±9.2 PPM
20dB Emission Bandwidth	1.96	±9.2 PPM
Carrier Frequency Separation	1.96	±9.2 PPM
Time of Occupancy	1.96	±0.57%
Conducted Output Power	1.96	±1.5 dB
Power Spectral Density Level	1.96	±1.9 dB
Conducted Spurious Emission	1.96	9 kHz-30 MHz: ± 0.95 dB 30 MHz-1 GHz: ± 1.5 dB 1GHz-12.75GHz: ± 1.8 dB 12.75 GHz-26.5 GHz: ± 2.1dB
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.		

Test Item	Measurement Frequency Range	K	U(dB)
Conducted emissions from the AC mains power ports (AMN)	150 kHz ~ 30 MHz	2	3.37
Radiated emissions	9 kHz ~ 30 MHz	2	4.16
Radiated emissions	30 MHz ~ 1 GHz	2	3.79
Radiated emissions	1 GHz ~ 18 GHz	2	5.62
Radiated emissions	18 GHz ~ 40 GHz	2	5.54
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.			

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name		Eagle
Model		JMK1
Series Model		JMK2
Model Difference		Structural difference: Compared with JMK1, the fisheye lens on the left, right and upper side of JMK2 is replaced with a glass cover to close the corresponding lens window, and other appearance shapes, colors and shipment matches are consistent. Module differences: JMK2 compared with JMK1, the left, right and upper side of the camera module are removed, and only the front side is retained. JMK1 and JMK2 all circuit boards and core modules, including motherboard, Lidar module, wifi module, GPS module, power module, data module, display module are all the same, data acquisition function, wifi function, GPS function, charging mode, output processing, display, etc.
Hardware Version		V1.0.002
Software Version		V1.0.001
Ratings		Input: 20V – 1.5A
Power Supply	AC	100-240V~ 50/60Hz 1.5A
	DC	20V
	Battery	DC 7.2V 6400mAh, 46.08Wh

Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2412 MHz to 2462 MHz
Support Standards:	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n-HT20, IEEE 802.11n-HT40
Type of Modulation:	IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK) IEEE 802.11g/n: OFDM(64-QAM, 16-QAM, QPSK, BPSK)
Data Rate:	IEEE 802.11b: Up to 11 Mbps IEEE 802.11g: Up to 54 Mbps IEEE 802.11n: Up to MCS7
Number of Channels:	IEEE 802.11b/g/n-HT20: 11 IEEE 802.11n-HT40: 7
Maximum Conducted Output Power:	IEEE 802.11b: 15.70 dBm IEEE 802.11g: 15.60 dBm IEEE 802.11n-HT20: 15.76 dBm IEEE 802.11n-HT40: 15.64 dBm
Antenna Type:	Integral Antenna
Antenna Gain:	Antenna1/2: 1.89 dBi
Normal Test Voltage:	20 Vdc
EUT Test software:	MobaXterm

Note:

The Antenna Gain was provided by customer, and this information may affect the validity of the results, customer should be responsible for this.

5.2. CHANNEL LIST

Channel List for 802.11b/g/n (20 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	4	2427	7	2442	10	2457
2	2417	5	2432	8	2447	11	2462
3	2422	6	2437	9	2452	/	/

Channel List for 802.11n (40 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	5	2432	7	2442	9	2452
4	2427	6	2437	8	2447	/	/

5.3. MAXIMUM CONDUCTED OUTPUT POWER

IEEE Std. 802.11	Frequency (MHz)	Channel Number	Maximum Conducted Output Power (dBm)	Maximum EIRP (dBm)
b	2412 ~ 2462	1-11[11]	15.70	/
g	2412 ~ 2462	1-11[11]	15.60	/
n HT20	2412 ~ 2462	1-11[11]	15.76	/
n HT40	2422 ~ 2452	3-9[7]	15.64	/

5.4. TEST CHANNEL CONFIGURATION

IEEE Std. 802.11	Test Channel Number	Frequency
b	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
g	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
n HT20	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
n HT40	CH 3(Low Channel), CH 6(MID Channel), CH 9(High Channel)	2422 MHz, 2437 MHz, 2452 MHz

5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band			
Test Software		MobaXterm	
Modulation Mode		Test Channel	
		NCB: 20MHz	NCB: 40MHz

	Transmit Antenna Number	CH 1	CH 6	CH 11	CH 3	CH 6	CH 9
802.11b	1	75	75	75	/		
	2	85	85	85			
802.11g	1	40	43	44			
	2	45	45	45			
802.11n HT20	1	33	33	35			
	2	39	41	43			
802.11n HT40	1	/			33	33	35
	2	/			39	41	41

WORST-CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.5.

Worst-case data rates as provided by the client were:

802.11b mode: 1 Mbps
 802.11g mode: 6 Mbps
 802.11n HT20 mode: MCS0
 802.11n HT40 mode: MCS0

The EUT has 2 separate antennas which correspond to 2 separate antenna ports. Core 0 and Core 1 correspond to antenna 1 and antenna 2 respectively.

The measured additional path loss was included in any path loss calculations for all RF cable used during tested.

Conducted output power, power spectral density tests separately on each port with all supported SISO & MIMO port combinations.

Conducted bandedge and spurious emissions tests were performed with SISO mode, as this port was found to have the worst case in terms of power settings amongst all supported possible SISO & MIMO port combinations.

Radiated emissions tests were performed with the MIMO modes. These were found to be the worst modulation scheme with regards to emissions after preliminary investigations and, as this mode emits the highest conducted output power level, it was deemed to be the worst case.

The EUT support Cyclic Shift Diversity(CDD), Space Time Coding(STBC), Spatial Division Multiplexing(SDM) modes. They use the same conducted power per chain in any given mode, so we only chose the worst case mode CDD for final testing.

5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2412-2462	Integral	1.89
2	2412-2462	Integral	1.89

The EUT support Cyclic Shift Diversity(CDD) mode.

MIMO output power port and MIMO PSD port summing were performed in accordance with KDB 662911 D01. For the CDD results the Directional Gain was calculated in accordance with the following method.

For output power measurements:

Directional gain= $G_{ANT} + \text{Array Gain} = 1.89 \text{ dBi}$

G_{ANT} : equal to the gain of the antenna having the highest gain

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$

For power spectral density (PSD) measurements:

Directional gain= $G_{ANT} + \text{Array Gain} = 4.90 \text{ dBi}$

Array Gain = $10 \log(N_{ANT}/N_{SS}) \text{ dB}$.

N_{ANT} : number of transmit antennas

N_{SS} : number of spatial streams, The worst case directional gain will occur when $N_{SS} = 1$

Test Mode	Transmit and Receive Mode	Description
IEEE 802.11b	☒ 2TX, 2RX	ANT 1 and ANT 2 can be used as transmitting/receiving antenna.
IEEE 802.11g	☒ 2TX, 2RX	ANT 1 and ANT 2 can be used as transmitting/receiving antenna.
IEEE 802.11n HT20	☒ 2TX, 2RX	ANT 1 and ANT 2 can be used as transmitting/receiving antenna.
IEEE 802.11n HT40	☒ 2TX, 2RX	ANT 1 and ANT 2 can be used as transmitting/receiving antenna.

Note:

5.7. EUT ACCESSORY

Adapter	
Model No.:	RH-PD65W-1
Input:	100-240V~ 50/60Hz 1.5A
Output:	5V = 3A/9V = 3A/12V = 3A/15V = 3A/20V = 3.25A 65W max
AC Cable:	/
DC Cable:	/

Cable	
Accessory:	USB-C cable
Model No.:	/
Description:	USB Type-C Plug Cable
Cable Type:	Unshielded without ferrite
Length:	1.52 Meter


5.8. SUPPORT UNITS FOR SYSTEM TEST

The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Laptop	Lenovo	Thinkpad T14	PF-3EAKYR	GTG Support

5.9. SETUP DIAGRAM

Radiated emissions & AC Power Line Conducted Emission:



6. MEASURING EQUIPMENT AND SOFTWARE USED

Test Equipment of Conducted RF					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Spectrum Analyzer	Rohde & Schwarz	FSV40	102257	2024/09/14	2025/09/13
Spectrum Analyzer	KEYSIGHT	N9020A	MY51285127	2024/09/14	2025/09/13
EXG Analog Signal Generator	KEYSIGHT	N5173B	MY61253075	2024/09/14	2025/09/13
Vector Signal Generator	Rohde & Schwarz	SMM100A	101899	2024/09/14	2025/09/13
RF Control box	MWRF-test	MW100-RFCB	MW220926GTG	2024/09/14	2025/09/13
Wideband Radio Communication Tester	Rohde & Schwarz	CMW270	102792	2024/09/14	2025/09/13
Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	103235	2024/09/14	2025/09/13
temperature humidity chamber	Espec	SH-241	SH-241-2014	2024/09/14	2025/09/13
RF Test Software	MWRF-test	MTS8310E (Ver. V2/0)	N/A	N/A	N/A

Test Equipment of Radiated emissions below 1GHz					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
3m Semi-anechoic Chamber	ETS	9m*6m*6m	Q2146	2022/08/30	2025/08/29
EMI Test Receiver	Rohde & Schwarz	ESCI3	101409	2024/09/14	2025/09/13
Spectrum Analyzer	KEYSIGHT	N9020A	MY51283932	2024/09/14	2025/09/13
Pre-Amplifier	HzEMC	HPA-9K0130	HYPA21001	2024/09/14	2025/09/13
Biconilog Antenna	Schwarzbeck	VULB 9168	01315	2022/10/10	2025/10/09
Biconilog Antenna	ETS	3142E	00243646	2022/03/23	2025/03/22
Loop Antenna	ETS	6502	243668	2022/03/30	2025/03/29
Test Software	Farad	EZ-EMC (Ver.FA-03A2 RE)	N/A	N/A	N/A

Test Equipment of Radiated emissions above 1GHz					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
3m Semi-anechoic Chamber	ETS	9m*6m*6m	Q2149	2022/08/30	2025/08/29
Spectrum Analyzer	Rohde & Schwarz	FSV40	101413	2024/09/14	2025/09/13
Spectrum Analyzer	KEYSIGHT	N9020A	MY51283932	2024/09/14	2025/09/13
Pre-Amplifier	A-INFO	HPA-1G1850	HYPA21003	2024/09/14	2025/09/13
Horn antenna	A-INFO	3117	246069	2022/03/11	2025/03/10
Pre-Amplifier	ZKJC	HPA-184057	HYPA21004	2024/09/14	2025/09/13

Horn antenna	ZKJC	3116C	246265	2022/03/29	2025/03/28
Test Software	Farad	EZ-EMC (Ver.FA-03A2 RE+)	N/A	N/A	N/A

Test Equipment of Conducted emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Shielded Room	CHENG YU	8m*5m*4m	N/A	2022/10/29	2025/10/28
EMI Test Receiver	Rohde & Schwarz	ESR3	102647	2024/09/14	2025/09/13
LISN/AMN	Rohde & Schwarz	ENV216	102843	2024/09/14	2025/09/13
NNLK 8129 RC	Schwarzbeck	NNLK 8129 RC	5046	2024/09/14	2025/09/13
Test Software	Farad	EZ-EMC (Ver. EMC-con-3A1 1+)	N/A	N/A	N/A

7. ANTENNA PORT TEST RESULTS

7.1. CONDUCTED OUTPUT POWER

LIMITS


CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3) ISED RSS-247 5.4 (d)	Peak Conduct Output Power	1 watt or 30 dBm	2400-2483.5

TEST PROCEDURE

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the peak output power, after any corrections for external attenuators and cables.

TEST SETUP



TEST ENVIRONMENT

Temperature	22.7°C	Relative Humidity	53%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

7.2. 6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2) ISED RSS-247 5.2 (a)	6 dB Bandwidth	≥ 500 kHz	2400-2483.5
ISED RSS-Gen Clause 6.7	99 % Occupied Bandwidth	For reporting purposes only.	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.


Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Frequency Span	For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission For 99 % Occupied Bandwidth: Between 1.5 times and 5.0 times the OBW
Detector	Peak
RBW	For 6 dB Bandwidth: 100 kHz For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth
VBW	For 6 dB Bandwidth: $\geq 3 \times$ RBW For 99 % Occupied Bandwidth: $\geq 3 \times$ RBW
Trace	Max hold
Sweep	Auto couple

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.

b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP



TEST ENVIRONMENT

Temperature	22.7°C	Relative Humidity	53%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

7.3. POWER SPECTRAL DENSITY

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e) ISED RSS-247 5.2 (b)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.10.


Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	PEAK
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	$1.5 \times \text{DTS bandwidth}$
Trace	Max hold
Sweep time	Auto couple

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST SETUP



TEST ENVIRONMENT

Temperature	22.7°C	Relative Humidity	53%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d) ISED RSS-247 5.5	Conducted Bandedge and Spurious Emissions	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.11 and 11.13.

Connect the EUT to the spectrum analyser and use the following settings for reference level measurement:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	$1.5 \times \text{DTS bandwidth}$
Trace	Max hold
Sweep time	Auto couple.


Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span}/\text{RBW}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.

TEST SETUP



TEST ENVIRONMENT

Temperature	22.7°C	Relative Humidity	53%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

7.5. DUTY CYCLE


LIMITS

None; for reporting purposes only.

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.6 Zero – Span Spectrum Analyzer method.

TEST SETUP



TEST ENVIRONMENT

Temperature	22.7°C	Relative Humidity	53%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

8. RADIATED TEST RESULTS

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Please refer to ISED RSS-GEN Clause 8.9 and Clause 8.10.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

ISED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz		
Frequency	Magnetic field strength (H-Field) (μA/m)	Measurement distance (m)
9 - 490 kHz ^{Note 1}	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

ISED Restricted bands please refer to ISED RSS-GEN Clause 8.10

Table 7 – Restricted frequency bands ^{Note 1}		
MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52625	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST PROCEDURE

Below 30 MHz

TRF No.: 04-E001-0B

Global Testing , Great Quality.

The setting of the spectrum analyser

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω. For example, the measurement frequency X KHz resulted in a level of Y dBuV/m, which is equivalent to $Y-51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyser

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high

pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

3. The EUT was placed on a turntable with 80 cm above ground.

4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.

5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

Above 1G

The setting of the spectrum analyser

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.

2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.


3. The EUT was placed on a turntable with 1.5 m above ground.

4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.

5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.


6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1.ON TIME AND DUTY CYCLE.


X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

TEST SETUP





TEST ENVIRONMENT

Temperature	22.1°C	Relative Humidity	51%
Atmosphere Pressure	101kPa		


TEST RESULTS

8.1. RADIATED BAND EDGE AND SPURIOUS EMISSION

Undesirable radiated Spurious Emission below 1GHz (30MHz to 1GHz)

All modes have been tested and the worst result as bellow:


Mode:	11N20 2412
Power:	DC 5V
TE:	Big
Date	2024/12/09
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	37.760	44.41	-18.76	25.65	40.00	14.35	PK+	H
2	39.700	44.38	-19.86	24.52	40.00	15.48	PK+	H
3	159.010	40.93	-21.64	19.29	43.50	24.21	PK+	H
4	383.080	39.17	-14.71	24.46	46.00	21.54	PK+	H
5	675.050	33.89	-7.9	25.99	46.00	20.01	PK+	H
6	960.230	36.83	-3.82	33.01	53.90	20.89	PK+	H

Mode:	11N20 2412
Power:	DC 5V
TE:	Big
Date	2024/12/09
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	33.880	49.05	-16.49	32.56	40.00	7.44	PK+	V
2	37.760	51.63	-18.76	32.87	40.00	7.13	PK+	V
3	436.430	38.89	-14.22	24.67	46.00	21.33	PK+	V
4	533.430	38.26	-10.61	27.65	46.00	18.35	PK+	V
5	766.230	38.52	-7.2	31.32	46.00	14.68	PK+	V
6	960.230	41.63	-3.82	37.81	53.90	16.09	PK+	V


Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Undesirable radiated Spurious Emission Above 1GHz (1GHz to 40GHz)

All modes have been tested and the worst result as bellow:


Mode:	11N20 2412
Power:	DC 5V
TE:	Big
Date	2024/12/10
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	2394.000	61.70	-8.53	53.17	74.00	20.83	PK+	H
2	2986.000	53.48	-6.97	46.51	74.00	27.49	PK+	H
3	4222.500	57.42	-12.69	44.73	74.00	29.27	PK+	H
4	5721.000	53.12	-9.42	43.70	74.00	30.30	PK+	H
5	7230.000	54.80	-8.1	46.70	74.00	27.30	PK+	H
6	17701.500	47.38	0.14	47.52	74.00	26.48	PK+	H


Mode:	11N20 2412
Power:	DC 5V
TE:	Big
Date	2024/12/10
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	1868.000	55.45	-10.38	45.07	74.00	28.93	PK+	V
2	2722.000	56.25	-8.49	47.76	74.00	26.24	PK+	V
3	3360.000	57.90	-14.5	43.40	74.00	30.60	PK+	V
4	5934.000	51.80	-8.87	42.93	74.00	31.07	PK+	V
5	10413.000	50.00	-5.51	44.49	74.00	29.51	PK+	V
6	17698.500	45.54	0.19	45.73	74.00	28.27	PK+	V


Mode:	11N20 2437
Power:	DC 5V
TE:	Big
Date	2024/12/10
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2112.000	53.66	-9.21	44.45	74.00	29.55	PK+	V
2	2722.000	56.11	-8.49	47.62	74.00	26.38	PK+	V
3	3762.000	56.02	-13.46	42.56	74.00	31.44	PK+	V
4	6399.000	51.11	-8.12	42.99	74.00	31.01	PK+	V
5	11292.000	47.87	-4.2	43.67	74.00	30.33	PK+	V
6	17658.000	46.23	0.09	46.32	74.00	27.68	PK+	V


Mode:	11N20 2437
Power:	DC 5V
TE:	Big
Date	2024/12/10
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2392.000	60.09	-8.53	51.56	74.00	22.44	PK+	H
2	2902.000	54.64	-7.82	46.82	74.00	27.18	PK+	H
3	4224.000	55.94	-12.69	43.25	74.00	30.75	PK+	H
4	5689.500	52.80	-9.21	43.59	74.00	30.41	PK+	H
5	10611.000	49.22	-5.22	44.00	74.00	30.00	PK+	H
6	17728.500	47.28	-0.37	46.91	74.00	27.09	PK+	H


Mode:	11N20 2462
Power:	DC 5V
TE:	Big
Date	2024/12/10
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2392.000	60.15	-8.53	51.62	74.00	22.38	PK+	H
2	2936.000	52.97	-7.5	45.47	74.00	28.53	PK+	H
3	4222.500	54.32	-12.69	41.63	74.00	32.37	PK+	H
4	6066.000	51.30	-8.01	43.29	74.00	30.71	PK+	H
5	16087.500	47.48	-1.79	45.69	74.00	28.31	PK+	H
6	17713.500	46.61	-0.11	46.50	74.00	27.50	PK+	H

Mode:	11N20 2462
Power:	DC 5V
TE:	Big
Date	2024/12/10
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	2720.000	54.98	-8.48	46.50	74.00	27.50	PK+	V
2	3360.000	57.82	-14.5	43.32	74.00	30.68	PK+	V
3	6336.000	50.62	-8.02	42.60	74.00	31.40	PK+	V
4	9465.000	49.97	-6.62	43.35	74.00	30.65	PK+	V
5	13066.500	48.31	-4.66	43.65	74.00	30.35	PK+	V
6	17698.500	46.22	0.19	46.41	74.00	27.59	PK+	V

Note:


1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

For the frequency above 18 GHz, a pre-scan was performed, and the result was 20 dB lower than the limit line, the test data was not shown in the report.

Band Edge

All modes have been tested and the worst result as bellow:


Mode:	11N20 2412
Power:	DC 5V
TE:	Big
Date	2024/12/10
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2344.320	27.37	22.69	50.06	74.00	23.94	PK+	V
2	2390.080	25.61	22.72	48.33	74.00	25.67	PK+	V

Mode:	11N20 2412
Power:	DC 5V
TE:	Big
Date	2024/12/10
T/A/P	22.1°C/51%/101Kpa




Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2384.490	31.08	22.61	53.69	74.00	20.31	PK+	H
2	2389.950	34.57	22.72	57.29	74.00	16.71	PK+	H

Final_Result

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.	Verdict
1	2389.950	27.62	22.72	50.34	53.90	3.56	AVG	H	PASS


Mode:	11N20 2462
Power:	DC 5V
TE:	Big
Date	2024/12/10
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2483.360	29.04	23.15	52.19	74.00	21.81	PK+	V
2	2499.040	27.83	23.11	50.94	74.00	23.06	PK+	V


Mode:	11N20 2462
Power:	DC 5V
TE:	Big
Date	2024/12/10
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2483.360	25.30	23.15	48.45	74.00	25.55	PK+	H
2	2530.880	27.47	23.17	50.64	74.00	23.36	PK+	H

Mode:	11N40 2422
Power:	DC 5V
TE:	Big
Date	2024/12/10
T/A/P	22.1°C/51%/101Kpa




Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2387.610	33.58	22.67	56.25	74.00	17.75	PK+	H
2	2390.080	31.96	22.72	54.68	74.00	19.32	PK+	H

Final_Result

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.	Verdict
1	2387.610	27.52	22.67	50.19	53.90	3.71	AVG	H	PASS
2	2390.080	25.89	22.72	48.61	53.90	5.29	AVG	H	PASS


Mode:	11N40 2422
Power:	DC 5V
TE:	Big
Date	2024/12/10
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2324.430	28.32	22.49	50.81	74.00	23.19	PK+	V
2	2390.080	25.47	22.72	48.19	74.00	25.81	PK+	V


Mode:	11N40 2452
Power:	DC 5V
TE:	Big
Date	2024/12/10
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2483.360	27.87	23.15	51.02	74.00	22.98	PK+	V
2	2489.120	29.01	23.14	52.15	74.00	21.85	PK+	V

Mode:	11N40 2452
Power:	DC 5V
TE:	Big
Date	2024/12/10
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2483.360	28.17	23.15	51.32	74.00	22.68	PK+	H
2	2500.640	26.99	23.11	50.10	74.00	23.90	PK+	H

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

9. ANTENNA REQUIREMENT

REQUIREMENT

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DESCRIPTION

Pass

10. AC POWER LINE CONDUCTED EMISSION

LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8


FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

TEST PROCEDURE

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.


The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST SETUP



TEST ENVIRONMENT


Temperature	25.2°C	Relative Humidity	54%
Atmosphere Pressure	101kPa		

TEST RESULTS

Phase: L1

Mode: N20 2412MHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1500	37.85	9.77	47.62	66.00	-18.38	QP
2	0.1500	30.51	9.77	40.28	56.00	-15.72	AVG
3	0.2265	33.33	9.78	43.11	62.58	-19.47	QP
4	0.2265	26.04	9.78	35.82	52.58	-16.76	AVG
5	0.3885	35.54	9.79	45.33	58.10	-12.77	QP
6	0.3885	25.93	9.79	35.72	48.10	-12.38	AVG
7	0.6000	38.70	9.79	48.49	56.00	-7.51	QP
8	0.6000	30.04	9.79	39.83	46.00	-6.17	AVG
9	0.7530	35.81	9.80	45.61	56.00	-10.39	QP
10	0.7530	25.09	9.80	34.89	46.00	-11.11	AVG
11	7.9035	33.81	9.99	43.80	60.00	-16.20	QP
12	7.9035	21.58	9.99	31.57	50.00	-18.43	AVG



Phase: N

Mode: N20 2412MHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1508	35.25	9.67	44.92	65.96	-21.04	QP
2	0.1508	27.46	9.67	37.13	55.96	-18.83	AVG
3	0.2265	32.86	9.68	42.54	62.58	-20.04	QP
4	0.2265	25.92	9.68	35.60	52.58	-16.98	AVG
5	0.4515	31.36	9.69	41.05	56.85	-15.80	QP
6	0.4515	23.47	9.69	33.16	46.85	-13.69	AVG
7	0.5280	32.96	9.69	42.65	56.00	-13.35	QP
8	0.5280	25.74	9.69	35.43	46.00	-10.57	AVG
9	0.6765	36.58	9.70	46.28	56.00	-9.72	QP
10	0.6765	28.56	9.70	38.26	46.00	-7.74	AVG
11	26.9970	32.46	10.30	42.76	60.00	-17.24	QP
12	26.9970	18.03	10.30	28.33	50.00	-21.67	AVG

Note: 1. Result = Reading + Correct Factor.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).


4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.


Note: All the modes have been tested, only the worst data was recorded in the report.


11. TEST DATA - Appendix A


Duty Cycle


Condition	Mode	Frequency (MHz)	Antenna	On Time (ms)	Period (ms)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)	Final settingFor VBW (kHz)
NVNT	b	2412	Ant1	12.42	12.91	96.2	0.17	0.08	1
NVNT	b	2412	Ant2	12.42	12.85	96.65	0.15	0.08	1
NVNT	b	2437	Ant1	12.42	12.82	96.88	0.14	0.08	1
NVNT	b	2437	Ant2	12.42	12.83	96.8	0.14	0.08	1
NVNT	b	2462	Ant1	12.42	12.79	97.11	0.13	0.08	1
NVNT	b	2462	Ant2	12.42	12.81	96.96	0.13	0.08	1
NVNT	g	2412	Ant1	2.06	2.18	94.5	0.25	0.48	1
NVNT	g	2412	Ant2	2.06	2.26	91.15	0.4	0.48	1
NVNT	g	2437	Ant1	2.07	2.29	90.39	0.44	0.48	1
NVNT	g	2437	Ant2	2.07	2.23	92.83	0.32	0.48	1
NVNT	g	2462	Ant1	2.06	2.18	94.5	0.25	0.48	1
NVNT	g	2462	Ant2	2.06	2.21	93.21	0.31	0.48	1
NVNT	n20	2412	Ant1	1.92	2.1	91.43	0.39	0.52	1
NVNT	n20	2412	Ant2	1.92	2.07	92.75	0.33	0.52	1
NVNT	n20	2437	Ant1	1.92	2.06	93.2	0.31	0.52	1
NVNT	n20	2437	Ant2	1.92	2.11	91	0.41	0.52	1
NVNT	n20	2462	Ant1	1.92	2.14	89.72	0.47	0.52	1
NVNT	n20	2462	Ant2	1.92	2.03	94.58	0.24	0.52	1
NVNT	n40	2422	Ant1	0.95	1.11	85.59	0.68	1.06	1
NVNT	n40	2422	Ant2	0.95	1.09	87.16	0.6	1.05	1
NVNT	n40	2437	Ant1	0.95	1.14	83.33	0.79	1.06	1
NVNT	n40	2437	Ant2	0.94	1.16	81.03	0.91	1.06	1
NVNT	n40	2452	Ant1	0.94	1.1	85.45	0.68	1.06	1
NVNT	n40	2452	Ant2	0.95	1.08	87.96	0.56	1.05	1


































Maximum Conducted Output Power


Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	b	2412	Ant1	15.54	30	Pass
NVNT	b	2412	Ant2	15.69	30	Pass
NVNT	b	2437	Ant1	15.7	30	Pass
NVNT	b	2437	Ant2	15.49	30	Pass
NVNT	b	2462	Ant1	15.44	30	Pass
NVNT	b	2462	Ant2	15.05	30	Pass
NVNT	g	2412	Ant1	15.29	30	Pass
NVNT	g	2412	Ant2	15.44	30	Pass
NVNT	g	2437	Ant1	15.58	30	Pass
NVNT	g	2437	Ant2	14.34	30	Pass
NVNT	g	2462	Ant1	15.6	30	Pass
NVNT	g	2462	Ant2	14.39	30	Pass
NVNT	n20	2412	Ant1	12.23	30	Pass
NVNT	n20	2412	Ant2	12.87	30	Pass
NVNT	n20	2412	Sum	15.57	30	Pass
NVNT	n20	2437	Ant1	12.47	30	Pass
NVNT	n20	2437	Ant2	12.61	30	Pass
NVNT	n20	2437	Sum	15.55	30	Pass
NVNT	n20	2462	Ant1	12.67	30	Pass
NVNT	n20	2462	Ant2	12.82	30	Pass
NVNT	n20	2462	Sum	15.76	30	Pass
NVNT	n40	2422	Ant1	12.56	30	Pass
NVNT	n40	2422	Ant2	12.23	30	Pass
NVNT	n40	2422	Sum	15.41	30	Pass
NVNT	n40	2437	Ant1	12.36	30	Pass
NVNT	n40	2437	Ant2	12.34	30	Pass
NVNT	n40	2437	Sum	15.36	30	Pass
NVNT	n40	2452	Ant1	12.59	30	Pass
NVNT	n40	2452	Ant2	12.67	30	Pass
NVNT	n40	2452	Sum	15.64	30	Pass


-6dB Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	b	2412	Ant1	10.06	0.5	Pass
NVNT	b	2412	Ant2	10.08	0.5	Pass
NVNT	b	2437	Ant1	10.07	0.5	Pass
NVNT	b	2437	Ant2	10.05	0.5	Pass
NVNT	b	2462	Ant1	10.07	0.5	Pass
NVNT	b	2462	Ant2	10.07	0.5	Pass
NVNT	g	2412	Ant1	15.44	0.5	Pass
NVNT	g	2412	Ant2	15.67	0.5	Pass
NVNT	g	2437	Ant1	15.68	0.5	Pass
NVNT	g	2437	Ant2	15.69	0.5	Pass
NVNT	g	2462	Ant1	16.25	0.5	Pass
NVNT	g	2462	Ant2	15.65	0.5	Pass
NVNT	n20	2412	Ant1	16.3	0.5	Pass
NVNT	n20	2412	Ant2	16.53	0.5	Pass
NVNT	n20	2437	Ant1	16	0.5	Pass
NVNT	n20	2437	Ant2	16.27	0.5	Pass
NVNT	n20	2462	Ant1	15.65	0.5	Pass
NVNT	n20	2462	Ant2	16.53	0.5	Pass
NVNT	n40	2422	Ant1	35.12	0.5	Pass
NVNT	n40	2422	Ant2	35.1	0.5	Pass
NVNT	n40	2437	Ant1	35.01	0.5	Pass
NVNT	n40	2437	Ant2	35.09	0.5	Pass
NVNT	n40	2452	Ant1	35.07	0.5	Pass
NVNT	n40	2452	Ant2	35.08	0.5	Pass
































Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	b	2412	Ant1	14.603
NVNT	b	2412	Ant2	14.519
NVNT	b	2437	Ant1	14.615
NVNT	b	2437	Ant2	14.555
NVNT	b	2462	Ant1	14.651
NVNT	b	2462	Ant2	14.561
NVNT	g	2412	Ant1	16.402
NVNT	g	2412	Ant2	16.372
NVNT	g	2437	Ant1	16.402
NVNT	g	2437	Ant2	16.414
NVNT	g	2462	Ant1	16.426
NVNT	g	2462	Ant2	16.408
NVNT	n20	2412	Ant1	17.56
NVNT	n20	2412	Ant2	17.572
NVNT	n20	2437	Ant1	17.596
NVNT	n20	2437	Ant2	17.584
NVNT	n20	2462	Ant1	17.59
NVNT	n20	2462	Ant2	17.56
NVNT	n40	2422	Ant1	36.128
NVNT	n40	2422	Ant2	36.128
NVNT	n40	2437	Ant1	36.116
NVNT	n40	2437	Ant2	36.116
NVNT	n40	2452	Ant1	36.128
NVNT	n40	2452	Ant2	36.152

