

Shenzhen Lian Hui Technology Creative Limited

CD Playe

Model No.: Jaek Audio C20

Prepared for : Sanwa Electronic Instrument Co., Ltd
Address : No.9,Jinyuan two road, Xinqiao third industrial district,Baoan
District,Shenzhen

Prepared By : Shenzhen Alpha Product Testing Co., Ltd.
Address : Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,
Shenzhen, Guangdong, China

Prediction of MPE at a given distance

1. Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

2. Test Procedure

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

3. Result

Mode	Frequency (MHz)	Prediction distance (cm)	Rated Peak RF power output		MPE (mW/cm ²)	Limit (mW/cm ²)	SAR Test Exclusion
			dBm	mW			
EDR	2441	20	2.51	1.7824	0.00031	1	Yes
BLE 2M	2440	20	4.972	3.142	0.00055	1	Yes

BT Antenna Gain: -0.58dBi, 0.87(numeric) Then

SAR evaluation is not required.