



FCS202508246W03

FCC RF Exposure

EUT Description:Bluetooth Speaker

Model No.:SSX25P152, SSX25P112, SSX26P122, SSX26P132, SSX26P142, SSX26P152, SSX26P172, SSX26P192

FCC ID: 2BMMN-SSX25P152

Equipment type: Portable devices

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1093, Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numericasimulation, is not required when the corresponding SAR Test Exclusion Thresholocondition(s), listed below, is (are) satisfied.

For 100 MHz to 6 GHz and test separation distances < 50 mm, the 1-g and 10-g SAR testexclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance mm})] \cdot [f(\text{GHz})] < 3.0$ for 1-g SAR, and $s 7.5$ for 10-g extremity SAR, where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

$$\text{EIRP} = \text{EMeas} + 20 \log(\text{dmeas}) - 104.7$$

EIRP is the equivalent isotropically radiated power,

EMeas in dBm is the field strength of the emission at the measurement distance, in dB u V/m

dmeas is the measurement distance, in m

BR

Output power(dBm)	Max tune-up(mW)	Frequency(MHz)	Min. distance(mm)	Calc. thresholds	limit
2.53	1.7906	2402	5	0.5550	3.0
3.61	2.2961	2441	5	0.7175	3.0
3.73	2.3605	2480	5	0.7435	3.0

BLE

Output power(dBm)	Max tune-up(mW)	Frequency(MHz)	Min. distance(mm)	Calc. thresholds	limit
0.52	1.1272	2402	5	0.3494	3.0
1.41	1.3836	2440	5	0.4323	3.0
0.17	1.0399	2480	5	0.3275	3.0

Conclusion: No SAR is required