

TEST REPORT

Applicant Name: JME & CO. NYC. LLC
Address: 469 7TH AVE 14TH FLOOR NEW YORK, NY 10018 United States
Report Number: 2501P18231E-RF-00B
FCC ID: 2BMOI-MA1134

Test Standard (s)

FCC PART 15.247

Sample Description

Product Type: MVMT MINI PORTABLE BT THERMAL PRINTER 3 REGULAR ROLLS 2 STICKERS
Model No.: MA1134-PKA
Multiple Model(s) No.: MA1134-BLA, MA1134-BLP, MA1134-FCA, MA1134-WHK
Trade Mark: N/A
Date Received: 2025-01-16
Issue Date: 2025-03-25

Test Result:	Pass▲
--------------	-------

▲ In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:Allen. BaiAllen Bai
RF Engineer**Approved By:**Michelle ZengMichelle Zeng
RF Supervisor

Note: The information marked[#] is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.

This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China
Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	3
GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
SUMMARY OF TEST RESULTS	9
TEST EQUIPMENT LIST	10
REQUIREMENTS AND TEST PROCEDURES	12
AC LINE CONDUCTED EMISSIONS.....	12
UNWANTED EMISSION FREQUENCIES AND RESTRICTED BANDS	14
6 dB EMISSION BANDWIDTH.....	17
PEAK OUTPUT POWER MEASUREMENT	18
100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	19
POWER SPECTRAL DENSITY	20
DUTY CYCLE	21
ANTENNA REQUIREMENT	22
TEST DATA AND RESULTS.....	23
AC LINE CONDUCTED EMISSIONS.....	23
UNWANTED EMISSION FREQUENCIES AND RESTRICTED BANDS	26
6dB EMISSION BANDWIDTH.....	58
MAXIMUM CONDUCTED OUTPUT POWER	60
POWER SPECTRAL DENSITY	62
100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	64
DUTY CYCLE	66
RF EXPOSURE EVALUATION	68
EUT PHOTOGRAPHS.....	69
TEST SETUP PHOTOGRAPHS	70

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	2501P18231E-RF-00B	Original Report	2025-03-25

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	MVMT MINI PORTABLE BT THERMAL PRINTER 3 REGULAR ROLLS 2 STICKERS
Tested Model	MA1134-PKA
Multiple Model(s)	MA1134-BLA, MA1134-BLP, MA1134-FCA, MA1134-WHK
Frequency Range	2402~2480MHz
Maximum Conducted Output Peak Power	7.51dBm
Modulation Technique	GFSK
Antenna Specification[#]	-2.97dBi (provided by the applicant)
Voltage Range	DC 3.7V from battery or DC 5V from type C port
Sample serial number	2XM1-1 (Assigned by BACL, Shenzhen)
Sample/EUT Status	Good condition
Adapter Information	N/A

Note: The Multiple models are electrically identical with the test model except for model number and color. Please refer to the declaration letter[#] for more detail, which was provided by manufacturer.

Objective

This report is in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209, 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		109.2kHz(k=2, 95% level of confidence)
RF output power, conducted		0.86dB(k=2, 95% level of confidence)
Power Spectral Density		0.90dB(k=2, 95% level of confidence)
AC Power Lines Conducted Emissions	9kHz~150 kHz	3.63dB(k=2, 95% level of confidence)
	150 kHz ~30MHz	3.66dB(k=2, 95% level of confidence)
Radiated Emissions	0.009MHz~30MHz	3.60dB(k=2, 95% level of confidence)
	30MHz~200MHz (Horizontal)	5.32dB(k=2, 95% level of confidence)
	30MHz~200MHz (Vertical)	5.43dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Horizontal)	5.77dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Vertical)	5.73dB(k=2, 95% level of confidence)
	1GHz - 6GHz	5.34dB(k=2, 95% level of confidence)
	6GHz - 18GHz	5.40dB(k=2, 95% level of confidence)
	18GHz - 40GHz	5.64dB(k=2, 95% level of confidence)
Temperature		±1°C
Humidity		±1%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 715558, the FCC Designation No. : CN5045.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

EUT Exercise Software

Exercise Software [#]	FCC_assist 1.0.2.2.exe		
Power Level [#]			
Mode	Low Channel	Middle Channel	High Channel
BLE 1M	Default	Default	Default
BLE 2M	Default	Default	Default

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Shenzhen Keyu Power	Adapter	KA20A-US	Unknown
OUPU	Receptacle	PDU-OP1606K	6971041358020

External I/O Cable


Cable Description	Length (m)	From Port	To
Unshielded detachable USB cable	0.3	Adapter	EUT
Unshielded un-detachable AC cable	1.0	Receptacle	LISN/AC Mains

Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions below 1GHz:



For Radiated Emissions above 1GHz:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.203	Antenna Requirement	Compliant
FCC §15.207(a)	AC Line Conducted Emissions	Compliant
FCC §15.205,§15.209,§15.247(d)	Radiated Spurious Emission	Compliant
FCC §15.207(a)(2)	6dB Emission Bandwidth	Compliant
FCC §15.247(b)(1)	Maximum Conducted Output Power	Compliant
FCC §15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
FCC §15.247(e)	Power Spectral Density	Compliant
/	Duty Cycle	/
FCC §1.1307&§2.1093&§15.247 (i)	RF Exposure	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2024/12/04	2025/12/03
Rohde & Schwarz	LISN	ENV216	101613	2024/12/04	2025/12/03
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2024/05/21	2025/05/20
Unknown	CE Cable	Unknown	UF A210B-1-0720-504504	2024/05/21	2025/05/20
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
Radiated Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR3	102455	2024/12/04	2025/12/03
Sonoma instrument	Pre-amplifier	310N	186238	2024/05/21	2025/05/20
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2023/07/20	2026/07/19
Unknown	Cable	XH500C	J-10M-A	2024/06/18	2025/06/17
BACL	Active Loop Antenna	1313-1A	4031911	2024/05/14	2027/05/13
Unknown	Cable	2Y194	0735	2024/12/04	2025/12/03
Unknown	Cable	PNG214	1354	2024/12/04	2025/12/03
Rohde&Schwarz	Spectrum Analyzer	FSV40	101605	2024/03/27	2025/03/26
A.H.System	Preamplifier	PAM-0118P	489	2024/11/15	2025/11/14
Schwarzbeck	Horn Antenna	BBHA9120D(12 01)	1143	2023/07/26	2026/07/25
Unknown	RF Cable	KMSE	0735	2024/12/06	2025/12/05
Unknown	RF Cable	UFA147	219661	2024/12/06	2025/12/05
Unknown	RF Cable	XH750A-N	J-10M	2024/12/06	2025/12/05
JD	Multiplex Switch Test Control Set	DT7220FSU	DQ77926	2024/06/18	2025/06/17
JD	Multiplex Switch Test Control Set	DT7220SCU	DS79903	2024/09/09	2025/09/08
A.H.System	Pre-amplifier	PAM-1840VH	190	2024/06/18	2025/06/17
Electro-Mechanics Co	Horn Antenna	3116	9510-2270	2023/09/18	2026/09/17
UTIFLEX	RF Cable	NO. 13	232308-001	2024/12/18	2025/12/17
Audix	EMI Test software	E3	191218(V9)	NCR	NCR

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
R&S	Spectrum Analyzer	FSU26	200120	2024/12/04	2025/12/03
Unknown	10dB Attenuator	Unknown	F-03-EM190	2024/06/27	2025/06/26
Micro-Tronics	RF Cable	8082135	W1113	2024/06/27	2025/06/26

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).


REQUIREMENTS AND TEST PROCEDURES

AC Line Conducted Emissions

Applicable Standard

FCC§15.207

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:



$$\text{Over Limit} = \text{Level} - \text{Limit}$$


$$\text{Level} = \text{Read Level} + \text{Factor}$$

Note: The term "cable loss" refers to the combination of a cable and a 10dB transient limiter (attenuator).

Unwanted Emission Frequencies and Restricted Bands**Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

EUT Setup**9 kHz-30MHz:****30MHz-1GHz:**

Above 1GHz:

The radiated emission tests were performed in the 3meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.205, FCC 15.209, FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9 kHz-1GHz:

Frequency Range	RBW	Video B/W	IF B/W	Measurement	Detector
9 kHz – 150 kHz	/	/	200 Hz	QP	QP
	300 Hz	1 kHz	/	PK	Peak
150 kHz – 30 MHz	/	/	9 kHz	QP	QP
	10 kHz	30 kHz	/	PK	Peak
30 MHz – 1000 MHz	/	/	120 kHz	QP	QP
	100 kHz	300 kHz	/	PK	Peak

1-25GHz:

Pre-scan

Measurement	Duty cycle	RBW	Video B/W	Detector
PK	Any	1MHz	3 MHz	Peak
AV	>98%	1MHz	5 kHz	Peak
	<98%	1MHz	≥1/Ton	Peak

Final measurement for emission identified during pre-scan

Measurement	Duty cycle	RBW	Video B/W	Detector
PK	Any	1MHz	3 MHz	Peak
AV	>98%	1MHz	10 Hz	Peak
	<98%	1MHz	≥1/Ton	Peak

Note: Ton is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

All emissions under the average limit and under the noise floor have not recorded in the report.

Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Over Limit/Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

6 dB Emission Bandwidth

Standard Applicable

According to FCC §15.247(a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.


Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.8.1 & Clause 6.9.3

- a. Set RBW = 100 kHz.
- b. Set the VBW $\geq [3 \times \text{RBW}]$.
- c. Detector = peak.
- d. Trace mode = max hold.
- e. Sweep = auto couple.
- f. Allow the trace to stabilize.
- g. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. Procedure as below

- a. The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b. The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- c. Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level.
- d. Step a) through step c) might require iteration to adjust within the specified range.
- e. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f. Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g. If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h. The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).



Peak Output Power Measurement


Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.9.1.1

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.
4. Set the RBW \geq DTS bandwidth.
5. Set the VBW $\geq [3 \times \text{RBW}]$.
6. Set span $\geq [3 \times \text{RBW}]$.
7. Sweep time = auto couple.
8. Detector = peak.
9. Trace mode = max hold.
10. Allow the trace to stabilize.
11. Use peak marker function to determine the peak amplitude level.



Note: A short RF cable with low cable loss connected to the EUT antenna port, which was provided by client or lab, the cable loss was add with offset into test equipment, the total offset consists of attenuator and/or RF cable loss

100 kHz Bandwidth of Frequency Band Edge

Applicable Standard


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.11

1. Set the RBW =100 kHz.
2. Set the VBW $\geq 3 \times$ RBW.
3. Detector = peak
4. Sweep time = auto couple.
5. Trace mode=max hold
6. All trace to fully stabilize
7. Use the peak marker function to determine the maximum amplitude level.
Ensure that amplitude of all unwanted emissions outside of the authorized frequency band(excluding restricted frequency bands) is attenuated by at least the minimum requirement specified in 11.11.
Report the three highest emissions relative to the limit.



Power Spectral Density

Applicable Standard


According to FCC §15.247(e):

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.10.2

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set analyzer center frequency to DTS channel center frequency
3. Set the span to 1.5 times the DTS bandwidth.
4. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
5. Set the VBW $\geq 3 \times \text{RBW}$.
6. Detector = peak.
7. Sweep time = auto couple.
8. Trace mode = max hold.
9. Allow trace to fully stabilize.
10. Use the peak marker function to determine the maximum amplitude level within the RBW.
11. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Note: A short RF cable with low cable loss connected to the EUT antenna port, which was provided by client or lab, the cable loss was add with offset into test equipment, the total offset consists of attenuator and/or RF cable loss


Duty Cycle

Test Procedure

According to ANSI C63.10-2013 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)



ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached, the antenna gain[#] is -2.97dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliant


TEST DATA AND RESULTS

AC Line Conducted Emissions

Environmental Conditions

Temperature (°C)	24.1	Relative Humidity (%)	43
ATM Pressure (kPa)	101	Test engineer	Macy Shi
Test date	2025/2/10		
EUT operation mode	Transmitting (Maximum output power mode, BLE 2M, high channel)		

AC 120V 60 Hz, Line



Condition: Line


Project : 2501P18231E-RF

tester : Macy.shi Note:Transmitting

Setting : RBW:9kHz VBW:30KHz Detector Peak

	Freq	Read Level	LISN Level	Cable Factor	Limit Loss	Line Limit	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.155	7.82	28.37	10.43	10.12	55.74	-27.37	Average
2	0.155	18.50	39.05	10.43	10.12	65.74	-26.69	QP
3	0.206	6.38	27.16	10.69	10.09	53.36	-26.20	Average
4	0.206	14.80	35.58	10.69	10.09	63.36	-27.78	QP
5	0.415	7.46	28.11	10.54	10.11	47.55	-19.44	Average
6	0.415	13.02	33.67	10.54	10.11	57.55	-23.88	QP
7	0.690	12.09	33.12	10.88	10.15	46.00	-12.88	Average
8	0.690	17.76	38.79	10.88	10.15	56.00	-17.21	QP
9	2.285	2.09	23.33	11.06	10.18	46.00	-22.67	Average
10	2.285	7.85	29.09	11.06	10.18	56.00	-26.91	QP
11	18.426	6.07	27.06	10.80	10.19	50.00	-22.94	Average
12	18.426	12.20	33.19	10.80	10.19	60.00	-26.81	QP

AC 120V 60 Hz, Neutral



Condition: Neutral

Project : 2501P18231E-RF

tester : Macy.shi Note:Transmitting

Setting : RBW:9kHz VBW:30KHz Detector Peak


Freq	Read		LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV					
1	0.165	8.07	28.71	10.53	10.11	55.21	-26.50 Average
2	0.165	17.63	38.27	10.53	10.11	65.21	-26.94 QP
3	0.200	5.94	26.83	10.80	10.09	53.62	-26.79 Average
4	0.200	14.70	35.59	10.80	10.09	63.62	-28.03 QP
5	0.502	11.36	32.00	10.50	10.14	46.00	-14.00 Average
6	0.502	14.93	35.57	10.50	10.14	56.00	-20.43 QP
7	0.529	9.45	30.10	10.52	10.13	46.00	-15.90 Average
8	0.529	14.88	35.53	10.52	10.13	56.00	-20.47 QP
9	2.650	3.47	24.46	10.82	10.17	46.00	-21.54 Average
10	2.650	8.45	29.44	10.82	10.17	56.00	-26.56 QP
11	18.039	7.28	28.28	10.81	10.19	50.00	-21.72 Average
12	18.039	15.03	36.03	10.81	10.19	60.00	-23.97 QP

Unwanted Emission Frequencies and Restricted Bands**Environmental Conditions**

Temperature (°C)	23.8-24.2	Relative Humidity (%)	42-63
ATM Pressure (kPa):	101	Test engineer:	Anson Su&Visen Wu
Test date:	2025/02/10~2025/03/11		
EUT operation mode:	Below 1GHz: Transmitting (Maximum output power mode, BLE 2M, high channel) Above 1GHz: Transmitting		
Note:	<ol style="list-style-type: none">1. For the radiated spurious emission below 30MHz, only the worst case (parallel) was recorded.2. For the radiated spurious emission below 30MHz, When the test result of peak was less than the limit of QP/Average more than 6dB, just peak value were recorded.3. After pre-scan in the X, Y and Z axes of orientation, the worst case z-axis of orientation were recorded.		

Below 1GHz:


9kHz-150kHz



Site : Chamber A
Condition : 3m
Project Number : 2501P18231E-RF
Test Mode : BLE Transmitting
Detector: Peak RBW/VBW: 0.3/1kHz
Tester : Anson Su

Freq	Factor	Read	Limit	Over	Remark	
		Level	Level	Line		
1	0.01	32.08	22.94	55.02	126.66	-71.64 Peak
2	0.02	30.10	19.20	49.30	120.92	-71.62 Peak
3	0.04	27.01	22.08	49.09	114.70	-65.61 Peak
4	0.06	25.63	21.28	46.91	112.39	-65.48 Peak
5	0.09	22.87	28.69	51.56	108.76	-57.20 Peak
6	0.10	21.92	29.89	51.81	107.49	-55.68 Peak


150kHz-30MHz



Site : Chamber A
Condition : 3m
Project Number : 2501P18231E-RF
Test Mode : BLE Transmitting
Detector: Peak RBW/VBW: 10/30kHz
Tester : Anson Su

	Freq	Factor	Read Level	Limit Level	Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	0.29	10.50	45.44	55.94	98.21	-42.27	Peak
2	0.59	5.26	45.87	51.13	72.11	-20.98	Peak
3	0.88	2.10	47.63	49.73	68.60	-18.87	Peak
4	1.18	0.68	43.02	43.70	65.97	-22.27	Peak
5	1.48	-0.13	40.04	39.91	64.02	-24.11	Peak
6	1.75	-0.91	42.31	41.40	69.54	-28.14	Peak


30MHz-1GHz_Horizontal



Site : Chamber A
Condition : 3m Horizontal
Project Number : 2501P18231E-RF
Test Mode : BLE Transmitting
Detector: Peak RBW/VBW: 100/300kHz
Tester : Anson Su

	Freq	Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	64.57	-18.00	49.04	31.04	40.00	-8.96	Peak
2	69.51	-17.87	48.85	30.98	40.00	-9.02	Peak
3	144.33	-12.18	47.20	35.02	43.50	-8.48	Peak
4	204.69	-13.41	48.26	34.85	43.50	-8.65	Peak
5	233.76	-13.62	52.76	39.14	46.00	-6.86	Peak
6	237.58	-13.43	52.55	39.12	46.00	-6.88	Peak

30MHz-1GHz_Vertical



Site : Chamber A
Condition : 3m Vertical
Project Number : 2501P18231E-RF
Test Mode : BLE Transmitting
Detector: Peak RBW/VBW: 100/300kHz
Tester : Anson Su

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m	dBuV/m	
1	45.55	-16.21	49.40	33.19	40.00	-6.81	Peak
2	50.25	-17.96	51.46	33.50	40.00	-6.50	Peak
3	51.91	-18.21	51.37	33.16	40.00	-6.84	Peak
4	58.18	-18.22	51.90	33.68	40.00	-6.32	Peak
5	64.04	-18.00	48.44	30.44	40.00	-9.56	Peak
6	143.89	-12.17	42.07	29.90	43.50	-13.60	Peak

Above 1GHz:

Frequency (MHz)	Reading (dB μ V)	PK/AV	Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
BLE 1M							
Low Channel							
4804	53.43	PK	H	-7.79	45.64	74	-28.36
4804	45.66	AV	H	-7.79	37.87	54	-16.13
4804	51.29	PK	V	-7.79	43.50	74	-30.50
4804	43.51	AV	V	-7.79	35.72	54	-18.28
Middle Channel							
4880	53.98	PK	H	-7.59	46.39	74	-27.61
4880	46.90	AV	H	-7.59	39.31	54	-14.69
4880	52.29	PK	V	-7.59	44.70	74	-29.30
4880	44.38	AV	V	-7.59	36.79	54	-17.21
High Channel							
4960	55.23	PK	H	-7.56	47.67	74	-26.33
4960	47.14	AV	H	-7.56	39.58	54	-14.42
4960	52.24	PK	V	-7.56	44.68	74	-29.32
4960	45.09	AV	V	-7.56	37.53	54	-16.47
BLE 2M							
Low Channel							
4804	52.67	PK	H	-7.79	44.88	74	-29.12
4804	45.84	AV	H	-7.79	38.05	54	-15.95
4804	51.25	PK	V	-7.79	43.46	74	-30.54
4804	43.42	AV	V	-7.79	35.63	54	-18.37
Middle Channel							
4880	53.45	PK	H	-7.59	45.86	74	-28.14
4880	46.82	AV	H	-7.59	39.23	54	-14.77
4880	51.85	PK	V	-7.59	44.26	74	-29.74
4880	44.74	AV	V	-7.59	37.15	54	-16.85
High Channel							
4960	54.26	PK	H	-7.56	46.70	74	-27.30
4960	47.52	AV	H	-7.56	39.96	54	-14.04
4960	51.86	PK	V	-7.56	44.30	74	-29.70
4960	45.31	AV	V	-7.56	37.75	54	-16.25

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss - Amplifier Factor


Corrected Amplitude/Level = Corrected Factor + Reading

Margin = Corrected Amplitude/Level - Limit

The other spurious emission which is in the noise floor level was not recorded.

Test plots


Left Band edge_Horizontal_BLE_1M



Condition : Horizontal
Project No. : 2501P18231E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BLE_1M_2402

	Freq	Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2317.396	-10.80	61.70	50.90	74.00	-23.10	peak
2	2390.000	-10.98	58.32	47.34	74.00	-26.66	Peak


Left Band edge_Vertical_BLE_1M



Condition : Vertical
Project No. : 2501P18231E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BLE_1M_2402

	Freq	Read Factor	Level	Limit Level	Over Line	Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2378.019	-10.96	62.51	51.55	74.00	-22.45	Peak
2	2390.000	-10.98	59.04	48.06	74.00	-25.94	Peak


Right Band edge_Horizontal_BLE_1M



Condition : Horizontal
Project No. : 2501P18231E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BLE_1M_2480

	Freq	Read Factor	Level	Limit Level	Over Line	Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	60.73	49.76	74.00	-24.24	Peak
2	2489.889	-10.98	62.96	51.98	74.00	-22.02	Peak

Right Band edge_Vertical_BLE_1M



Condition : Vertical

Project No. : 2501P18231E-RF


Tester : Visen Wu

Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak

Note : BLE_1M_2480

	Freq	Read Factor	Level	Limit Level	Over Line	Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	60.88	49.91	74.00	-24.09	Peak
2	2497.525	-11.00	63.00	52.00	74.00	-22.00	Peak


Left Band edge_Horizontal_BLE_2M



Condition : Horizontal
Project No. : 2501P18231E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BLE_2M_2402

	Freq	Read Factor	Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2333.793	-10.85	62.04	51.19	74.00	-22.81	Peak
2	2390.000	-10.98	58.98	48.00	74.00	-26.00	Peak


Left Band edge_Vertical_BLE_2M



Condition : Vertical
Project No. : 2501P18231E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BLE_2M_2402

	Freq	Read Factor	Level	Limit Level	Over Line	Limit	Remark
	MHz	dB/m	dB _{uV}	dB _{uV/m}	dB _{uV/m}	dB	
1	2382.549	-10.98	62.24	51.26	74.00	-22.74	Peak
2	2390.000	-10.98	60.08	49.10	74.00	-24.90	Peak


Right Band edge_Horizontal_Peak_BLE 2M



Condition : Horizontal
Project No. : 2501P18231E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BLE_2M_2480

	Freq	Read Factor	Level	Limit Level	Over Line	Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	60.40	49.43	74.00	-24.57	Peak
2	2485.366	-10.97	67.15	56.18	74.00	-17.82	Peak


Right Band edge_Horizontal_Average_BLE_2M



Condition : Horizontal
Project No. : 2501P18231E-RF
Tester : Visen Wu
Spectrum setting: Average reading: RBW:1MHz VBW:5kHz Detector:Peak
Note : BLE_2M_2480

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dB _{uV}	dB _{uV/m}		
1	2483.500	-10.97	50.45	39.48	54.00	-14.52	Average
2	2483.500	-10.97	50.45	39.48	54.00	-14.52	Average


Right Band edge_Vertical_Peak_BLE 2M



Condition : Vertical
Project No. : 2501P18231E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BLE_2M_2480

	Freq	Read Factor	Level	Limit Level	Over Line	Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.500	-10.97	60.06	49.09	74.00	-24.91	Peak
2	2485.576	-10.97	66.22	55.25	74.00	-18.75	Peak

Right Band edge_Vertical_Average_BLE_2M




Condition : Vertical
Project No. : 2501P18231E-RF
Tester : Visen Wu
Spectrum setting: Average reading: RBW:1MHz VBW:5kHz Detector:Peak
Note : BLE_2M_2480

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dB _{uV}	dB _{uV/m}		
1		2483.500	-10.97	49.34	38.37	54.00	-15.63 Average
2		2496.580	-10.99	49.57	38.58	54.00	-15.42 Average

1-18GHz (Listed with the worst harmonic margin test plot)


1-4GHz_Horizontal_BLE_1M



Condition : Horizontal
Project No. : 2501P18231E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BLE_1M_2480

	Freq	Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
1	3747.594	-9.60	56.46	46.86	74.00	-27.14	Peak


1-4GHz_Vertical_BLE_1M



Condition : Vertical
Project No. : 2501P18231E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BLE_1M_2480

	Freq	Read Factor	Limit Level	Over Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	3895.737	-9.85	56.25	46.40	74.00	-27.60 Peak


4-18GHz_Horizontal_Peak_BLE 1M



Condition : Horizontal
Project No. : 2501P18231E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BLE_1M_2480

	Freq	Read Factor	Level	Limit Level	Over Line	Limit	Remark
1	4960.000	-7.56	55.23	47.67	74.00	-26.33	Peak
2	17924.740	12.83	47.58	60.41	74.00	-13.59	Peak


4-18GHz_Horizontal_Average_BLE_1M



Condition : Horizontal
Project No. : 2501P18231E-RF
Tester : Visen Wu
Spectrum setting: Average reading: RBW:1MHz VBW:3kHz Detector:Peak
Note : BLE_1M_2480

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dB _{uV}	dB _{uV/m}		
1	4960.000	-7.56	47.14	39.58	54.00	-14.42	Average
2	17994.750	13.17	33.28	46.45	54.00	-7.55	Average


4-18GHz_Vertical_Peak_BLE 1M



Condition : Vertical
Project No. : 2501P18231E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BLE_1M_2480

	Freq	Read Factor	Level	Limit Level	Over Line	Limit	Remark
1	4960.000	-7.56	52.24	44.68	74.00	-29.32	Peak
2	17966.750	13.03	48.58	61.61	74.00	-12.39	Peak


4-18GHz_Vertical_Average_BLE 1M



Condition : Vertical
Project No. : 2501P18231E-RF
Tester : Visen Wu
Spectrum setting: Average reading: RBW:1MHz VBW:3kHz Detector:Peak
Note : BLE_1M_2480

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	4960.000	-7.56	45.09	37.53	54.00	-16.47	Average
2	18000.000	13.20	33.27	46.47	54.00	-7.53	Average


18-25GHz_Horizontal_BLE 1M



Condition : Horizontal
Project No. : 2501P18231E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BLE_1M_2480

Freq	Read Factor	Level	Limit Level	Over Line	Limit	Remark
		dB/m	dB _{uV}	dB _{uV/m}	dB _{uV/m}	
1	19372.670	15.11	37.07	52.18	74.00	-21.82 Peak


18-25GHz_Vertical_BLE_1M



Condition : Vertical
Project No. : 2501P18231E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BLE_1M_2480

Freq	Read Factor	Level	Limit Level	Over Line	Over Limit	Remark
1 19372.670	15.11	36.97	52.08	74.00	-21.92	Peak


1-4GHz_Horizontal_BLE_2M



Condition : Horizontal
Project No. : 2501P18231E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BLE_2M_2480

	Freq	Read Factor	Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB/m	dB _{uV}	dB _{uV/m}	dB _{uV/m}	dB	
1	3653.082	-9.76	55.76	46.00	74.00	-28.00	Peak


1-4GHz_Vertical_BLE_2M



Condition : Vertical
Project No. : 2501P18231E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BLE_2M_2480

	Freq	Read Factor	Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3748.344	-9.60	55.84	46.24	74.00	-27.76	Peak


4-18GHz_Horizontal_Peak_BLE 2M



Condition : Horizontal
Project No. : 2501P18231E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BLE_2M_2480

	Freq	Read Factor	Level	Limit Level	Over Line	Limit	Remark
1	4960.000	-7.56	54.26	46.70	74.00	-27.30	Peak
2	17957.990	13.00	47.24	60.24	74.00	-13.76	Peak


4-18GHz_Horizontal_Average_BLE 2M



Condition : Horizontal
Project No. : 2501P18231E-RF
Tester : Visen Wu
Spectrum setting: Average reading: RBW:1MHz VBW:5kHz Detector:Peak
Note : BLE_2M_2480

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dB _{uV}	dB _{uV/m}		
1	4960.000	-7.56	47.52	39.96	54.00	-14.04	Average
2	17982.500	13.11	34.86	47.97	54.00	-6.03	Average


4-18GHz_Vertical_Peak_BLE 2M



Condition : Vertical
Project No. : 2501P18231E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BLE_2M_2480

	Freq	Read Factor	Level	Limit Level	Over Line	Limit	Remark
1	4960.000	-7.56	51.86	44.30	74.00	-29.70	Peak
2	17972.000	13.06	48.71	61.77	74.00	-12.23	Peak


4-18GHz_Vertical_Average_BLE 2M



Condition : Vertical
Project No. : 2501P18231E-RF
Tester : Visen Wu
Spectrum setting: Average reading: RBW:1MHz VBW:5kHz Detector:Peak
Note : BLE_2M_2480

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	4960.000	-7.56	45.31	37.75	54.00	-16.25	Average
2	17989.500	13.16	34.78	47.94	54.00	-6.06	Average


18-25GHz_Horizontal_BLE_2M



Condition : Horizontal
Project No. : 2501P18231E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BLE_2M_2480

Freq	Read Factor	Level	Limit Level	Over Line	Over Limit	Remark
MHz	dB/m	dB _{uV}	dB _{uV/m}	dB _{uV/m}	dB	
1 19005.130	15.24	36.84	52.08	74.00	-21.92	Peak

18-25GHz_Vertical_BLE_2M



Condition : Vertical
Project No. : 2501P18231E-RF
Tester : Visen Wu
Spectrum setting: Peak reading: RBW:1MHz VBW:3MHz Detector:Peak
Note : BLE_2M_2480

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dB _{uV}	dB _{uV/m}		
1	19891.740	15.42	37.26	52.68	74.00	-21.32	Peak

6dB Emission Bandwidth**Test Information:**

Sample No.:	2XM1-1	Test Date:	2025/02/10
Test Site:	RF	Test Mode:	Transmitting
Tester:	Cheeb Huang	Test Result:	Pass

Environmental Conditions:







Temperature: (°C)	23.5	Relative Humidity: (%)	45	ATM Pressure: (kPa)	101
-----------------------------	------	----------------------------------	----	-------------------------------	-----

Test Data:**BLE 1M**

Channel	Result (MHz)	Limit (MHz)	Verdict
Low Channel	0.710	≥0.5	Pass
Middle Channel	0.720	≥0.5	Pass
High Channel	0.695	≥0.5	Pass

BLE 2M

Channel	Result (MHz)	Limit (MHz)	Verdict
Low Channel	1.178	≥0.5	Pass
Middle Channel	1.163	≥0.5	Pass
High Channel	1.178	≥0.5	Pass

BLE 1M**BLE_1M_Low_Channel****BLE_1M_Middle_Channel****BLE_1M_High_Channel****BLE_2M_Low_Channel****BLE_2M_Middle_Channel****BLE_2M_High_Channel**

Maximum Conducted Output Power**Test Information:**

Sample No.:	2XM1-1	Test Date:	2025/02/10
Test Site:	RF	Test Mode:	Transmitting
Tester:	Cheeb Huang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	23.5	Relative Humidity: (%)	45	ATM Pressure: (kPa)	101
-----------------------------	------	----------------------------------	----	-------------------------------	-----

Test Data:**BLE 1M**

Channel	Peak Output Power (dBm)	Limit (dBm)	Verdict
Low Channel	7.11	30.00	Pass
Middle Channel	7.36	30.00	Pass
High Channel	7.47	30.00	Pass



BLE 2M

Channel	Peak Output Power (dBm)	Limit (dBm)	Verdict
Low Channel	7.13	30.00	Pass
Middle Channel	7.40	30.00	Pass
High Channel	7.51	30.00	Pass

BLE 1M**BLE_1M_Low_Channel****BLE_1M_Middle_Channel**



ProjectNo.:2501P18231E-RF Tester:Cheeb Huang
Date: 10.FEB.2025 17:15:22

ProjectNo.:2501P18231E-RF Tester:Cheeb Huang
Date: 10.FEB.2025 17:16:56

BLE_1M_High_Channel**BLE_2M_Low_Channel**

ProjectNo.:2501P18231E-RF Tester:Cheeb Huang
Date: 10.FEB.2025 17:19:36

ProjectNo.:2501P18231E-RF Tester:Cheeb Huang
Date: 10.FEB.2025 17:22:39

BLE_2M_Middle_Channel**BLE_2M_High_Channel**

ProjectNo.:2501P18231E-RF Tester:Cheeb Huang
Date: 10.FEB.2025 17:24:14

ProjectNo.:2501P18231E-RF Tester:Cheeb Huang
Date: 10.FEB.2025 17:28:00

Power Spectral Density**Test Information:**

Sample No.:	2XM1-1	Test Date:	2025/02/10
Test Site:	RF	Test Mode:	Transmitting
Tester:	Cheeb Huang	Test Result:	Pass

Environmental Conditions:


Temperature: (°C)	23.5	Relative Humidity: (%)	45	ATM Pressure: (kPa)	101
-----------------------------	------	----------------------------------	----	-------------------------------	-----

Test Data:**BLE 1M**


Channel	Result (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Low Channel	-8.46	8	Pass
Middle Channel	-8.12	8	Pass
High Channel	-8.07	8	Pass

BLE 2M


Channel	Result (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Low Channel	-11.21	8	Pass
Middle Channel	-10.97	8	Pass
High Channel	-10.85	8	Pass

BLE 1M**BLE_1M_Low_Channel**


ProjectNo.:2501P18231E-RF Tester:Cheeb Huang
Date: 10.FEB.2025 17:15:40

BLE_1M_Middle_Channel


ProjectNo.:2501P18231E-RF Tester:Cheeb Huang
Date: 10.FEB.2025 17:17:15

BLE 2M**BLE_1M_High_Channel**


ProjectNo.:2501P18231E-RF Tester:Cheeb Huang
Date: 10.FEB.2025 17:19:55

BLE_2M_Low_Channel

ProjectNo.:2501P18231E-RF Tester:Cheeb Huang
Date: 10.FEB.2025 17:23:05

BLE_2M_Middle_Channel

ProjectNo.:2501P18231E-RF Tester:Cheeb Huang
Date: 10.FEB.2025 17:24:40

BLE_2M_High_Channel



ProjectNo.:2501P18231E-RF Tester:Cheeb Huang
Date: 10.FEB.2025 17:28:26

100 kHz Bandwidth of Frequency Band Edge**Test Information:**

Sample No.:	2XM1-1	Test Date:	2025/02/10
Test Site:	RF	Test Mode:	Transmitting
Tester:	Cheeb Huang	Test Result:	Pass



Environmental Conditions:

Temperature: (°C)	23.5	Relative Humidity: (%)	45	ATM Pressure: (kPa)	101
-----------------------------	------	----------------------------------	----	-------------------------------	-----

BLE 1M**BLE_1M_Low_Channel****BLE_1M_High_Channel**

ProjectNo.:2501P18231E-RF Tester:Cheeb Huang
Date: 10.FEB.2025 17:14:20

ProjectNo.:2501P18231E-RF Tester:Cheeb Huang
Date: 10.FEB.2025 17:18:18

BLE 2M**BLE_2M_Low_Channel****BLE_2M_High_Channel**

ProjectNo.:2501P18231E-RF Tester:Cheeb Huang
Date: 10.FEB.2025 17:21:02

ProjectNo.:2501P18231E-RF Tester:Cheeb Huang
Date: 10.FEB.2025 17:26:42

Duty Cycle**Test Information:**

Sample No.:	2XM1-1	Test Date:	2025/02/10
Test Site:	RF	Test Mode:	Transmitting
Tester:	Cheeb Huang	Test Result:	N/A

Environmental Conditions:



Temperature: (°C)	23.5	Relative Humidity: (%)	45	ATM Pressure: (kPa)	101
-----------------------------	------	----------------------------------	----	-------------------------------	-----

Test Data:**BLE 1M**

Channel	Ton (ms)	Ton+Toff (ms)	Duty Cycle (%)	Duty Cycle Factor(dB)	1/Ton (Hz)	VBW Setting (kHz)
Middle Channel	0.384	0.625	61.44	2.12	2604	3

BLE 2M

Channel	Ton (ms)	Ton+Toff (ms)	Duty Cycle (%)	Duty Cycle Factor(dB)	1/Ton (Hz)	VBW Setting (kHz)
Middle Channel	0.204	0.625	32.64	4.86	4902	5

BLE 1M**BLE_1M_Middle_Channel****BLE 2M****BLE_2M_Middle_Channel**

ProjectNo.:2501P18231E-RF Tester:Cheeb Huang
Date: 10.FEB.2025 17:11:50

ProjectNo.:2501P18231E-RF Tester:Cheeb Huang
Date: 10.FEB.2025 17:13:17

RF EXPOSURE EVALUATION

RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance v06.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Measurement Result

For worst case:

Mode	Frequency (MHz)	Max tune-up conducted power [#] (dBm)	Max tune-up conducted power [#] (mW)	Distance (mm)	Calculated value	Threshold (1-g SAR)	SAR Test Exclusion
BLE	2402-2480	8.0	6.31	5	2.0	3	Yes
Bluetooth	2402-2480	8.0	6.31	5	2.0	3	Yes

Note: The maximum tune-up conducted power[#] was declared and provided by the applicant

Result: Compliant

EUT PHOTOGRAPHS

Please refer to the attachment 2501P18231E-RF External photo and 2501P18231E-RF Internal photo.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2501P18231E-RF Test Setup photo.

***** **END OF REPORT** *****