

TEST REPORT

Applicant: Bel Air Lighting Inc.
Address of Applicant: 28104 Witherspoon, pkwy, Valencia, CA. 91355, U.S.A
Manufacturer: Home Star International Ltd
Address of Manufacturer: Room 201 & 301, Building No 4, No 9 Jiangcheng West Road, Shangjiangcheng Village, Gaobu Town, Dongguan City, China
Factory: Home Star International Ltd
Address of Factory: Room 201 & 301, Building No 4, No 9 Jiangcheng West Road, Shangjiangcheng Village, Gaobu Town, Dongguan City, China
Equipment Under Test (EUT)
Product Name: Portable LED Speaker Lamp
Model No.: LED-O00140;HS-9016
Trade Mark: N/A
FCC ID: 2BMPCGC178541HS140A
Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247
Date of sample receipt: 2024/11/19
Date of Test: 2024/11/20-2024/12/10
Date of report issued: 2024/12/13
Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:




Robinson Luo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	2024/12/13	Original

Prepared By:


Project Engineer

Date:

2024/12/13

Check By:


Reviewer

Date:

2024/12/13

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	7
5.3 DESCRIPTION OF SUPPORT UNITS	7
5.4 DEVIATION FROM STANDARDS	7
5.5 ABNORMALITIES FROM STANDARD CONDITIONS	7
5.6 TEST FACILITY	7
5.7 TEST LOCATION	7
5.8 ADDITIONAL INSTRUCTIONS	7
6 TEST INSTRUMENTS LIST	8
7 TEST RESULTS AND MEASUREMENT DATA	10
7.1 ANTENNA REQUIREMENT	10
7.2 CONDUCTED EMISSIONS	11
7.3 CONDUCTED PEAK OUTPUT POWER	14
7.4 20dB EMISSION BANDWIDTH	15
7.5 CARRIER FREQUENCIES SEPARATION	16
7.6 HOPPING CHANNEL NUMBER	17
7.7 DWELL TIME	18
7.8 SPURIOUS EMISSION IN NON-RESTRICTED & RESTRICTED BANDS	19
7.8.1 Conducted Emission Method	19
7.8.2 Radiated Emission Method	20
8 TEST SETUP PHOTO	37
9 EUT CONSTRUCTIONAL DETAILS	37

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna Requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(1)	Pass
20dB Occupied Bandwidth	15.247 (a)(1)	Pass
Carrier Frequencies Separation	15.247 (a)(1)	Pass
Hopping Channel Number	15.247 (a)(1)(iii)	Pass
Dwell Time	15.247 (a)(1)(iii)	Pass
Radiated Emission	15.205/15.209	Pass
Band Edge	15.247(d)	Pass

Remarks:

1. Pass: The EUT complies with the essential requirements in the standard.
2. Test according to ANSI C63.10:2013

Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	RF conducted power	$\pm 0.75\text{dB}$
5	RF power density	$\pm 3\text{dB}$
6	Conducted Spurious emissions	$\pm 2.58\text{dB}$
7	AC Power Line Conducted Emission	$\pm 3.44\text{dB}$ (0.15MHz ~ 30MHz)
8	Radiated Spurious emission test	$\pm 3.1\text{dB}$ (9kHz-30MHz)
		$\pm 3.8039\text{dB}$ (30MHz-200MHz)
		$\pm 3.9679\text{dB}$ (200MHz-1GHz)
		$\pm 4.29\text{dB}$ (1GHz-18GHz)
		$\pm 3.30\text{dB}$ (18GHz-40GHz)
9	Temperature test	$\pm 1^\circ\text{C}$
10	Humidity test	$\pm 3\%$
11	Time	$\pm 3\%$

5 General Information

5.1 General Description of EUT

Product Name:	Portable LED Speaker Lamp
Model No.:	LED-O00140;HS-9016
Test Model No.:	LED-O00140
Remark: The models are only difference is model name for commercial purpose	
Test sample(s) ID:	GTSL2024120052-1
Sample(s) Status:	Engineer sample
S/N:	N/A
Operation Frequency:	2402MHz~2480MHz
Channel numbers:	79
Channel separation:	1MHz
Modulation type:	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Antenna Type:	PCB Antenna
Antenna gain:	-0.5dbi
Power supply:	DC 5V, 2A(Adapter:120V/60Hz)

Remark:

1. Antenna gain information provided by the customer
2. The relevant information of the sample is provided by the entrusting company, and the laboratory is not responsible for its authenticity.

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2440MHz
The Highest channel	2480MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
-------------------	---

5.3 Description of Support Units

None

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations: • FCC—Registration No.: 381383 Designation Number: CN5029 Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. • ISED —Registration No.: 9079A CAB identifier: CN0091 The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of ISED for radio equipment testing • NVLAP (LAB CODE:600179-0) Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

5.7 Test Location

All tests were performed at:
Global United Technology Services Co., Ltd. Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960

5.8 Additional Instructions

Test Software	Special test software provided by manufacturer
Power level setup	Default

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Jun. 22, 2024	Jun. 21, 2027
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Apr. 11, 2024	Apr. 10, 2025
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9168	GTS640	Mar. 19, 2023	Mar. 18, 2025
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	Apr. 17, 2023	Apr. 16, 2025
6	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	Apr. 11, 2024	Apr. 10, 2025
7	Loop Antenna	ZHINAN	ZN30900A	GTS534	Nov.12, 2024	Nov.11, 2025
8	Broadband Preamplifier	SCHWARZBECK	BBV9718	GTS535	Apr. 11, 2024	Apr. 10, 2025
9	Amplifier(1GHz-26.5GHz)	HP	8449B	GTS601	Apr. 11, 2024	Apr. 10, 2025
10	Horn Antenna (15GH-40GHz)	SCHWARZBECK	01296	GTS691	Mar. 07, 2024	Mar. 06, 2025
11	FSV·Signal Analyzer (10Hz-40GHz)	Keysight	FSV-40-N	GTS666	Mar. 12, 2024	Mar. 11, 2025
12	Amplifier	/	LNA-1000-30S	GTS650	Apr. 11, 2024	Apr. 10, 2025
13	CDNE M2+M3-16A	HCT	30MHz-300MHz	GTS692	Nov. 07, 2024	Nov. 06, 2025
14	Wideband Amplifier	/	WDA-01004000-15P35	GTS602	Apr. 11, 2024	Apr. 10, 2025
15	Thermo meter	JINCHUANG	GSP-8A	GTS643	Apr. 18, 2024	Apr. 17, 2025
16	RE cable 1	GTS	N/A	GTS675	Jul. 02, 2024	Jul. 01, 2025
17	RE cable 2	GTS	N/A	GTS676	Jul. 02, 2024	Jul. 01, 2025
18	RE cable 3	GTS	N/A	GTS677	Jul. 02, 2024	Jul. 01, 2025
19	RE cable 4	GTS	N/A	GTS678	Jul. 02, 2024	Jul. 01, 2025
20	RE cable 5	GTS	N/A	GTS679	Jul. 02, 2024	Jul. 01, 2025
21	RE cable 6	GTS	N/A	GTS680	Jul. 02, 2024	Jul. 01, 2025
22	RE cable 7	GTS	N/A	GTS681	Jul. 05, 2024	Jul. 04, 2025
23	RE cable 8	GTS	N/A	GTS682	Jul. 05, 2024	Jul. 04, 2025
24	EMI Test Software	AUDIX	E3-6.100614a	GTS725	N/A	N/A

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	Jul. 12, 2022	Jul. 11, 2027
2	EMI Test Receiver	R&S	ESCI 7	GTS552	Apr. 11, 2024	Apr. 10, 2025
3	LISN	ROHDE & SCHWARZ	ENV216	GTS226	Apr. 11, 2024	Apr. 10, 2025
4	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
5	Thermo meter	JINCHUANG	GSP-8A	GTS642	Apr. 18, 2024	Apr. 17, 2025
6	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	Apr. 11, 2024	Apr. 10, 2025
7	ISN	SCHWARZBECK	NTFM 8158	GTS565	Apr. 11, 2024	Apr. 10, 2025
8	High voltage probe	SCHWARZBECK	TK9420	GTS537	Apr. 11, 2024	Apr. 10, 2025
9	Antenna end assembly	Weinschel	1870A	GTS560	Apr. 11, 2024	Apr. 10, 2025
10	EMI Test Software	AUDIX	E3-6.100622	GTS726	N/A	N/A

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	Apr. 13, 2024	Apr. 12, 2025
2	EMI Test Receiver	R&S	ESCI 7	GTS552	Apr. 13, 2024	Apr. 12, 2025
3	PSA Series Spectrum Analyzer	Agilent	E4440A	GTS536	Apr. 13, 2024	Apr. 12, 2025
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	Apr. 13, 2024	Apr. 12, 2025
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	Apr. 13, 2024	Apr. 12, 2025
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	Apr. 13, 2024	Apr. 12, 2025
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	Apr. 13, 2024	Apr. 12, 2025
8	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	Apr. 13, 2024	Apr. 12, 2025
9	Thermo meter	JINCHUANG	GSP-8A	GTS641	Apr. 18, 2024	Apr. 17, 2025


General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	KUMAO	SF132	GTS647	Apr. 18, 2024	Apr. 17, 2025

7 Test results and Measurement Data

7.1 Antenna requirement


Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
E.U.T Antenna:	
The antenna is PCB antenna, reference to the appendix II for details.	

7.2 Conducted Emissions


Test Requirement:	FCC Part15 C Section 15.207					
Test Method:	ANSI C63.10:2013					
Test Frequency Range:	150KHz to 30MHz					
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto					
Limit:	Frequency range (MHz)		Limit (dBuV)			
			Quasi-peak		Average	
	0.15-0.5		66 to 56*		56 to 46*	
	0.5-5		56		46	
	5-30		60		50	
* Decreases with the logarithm of the frequency.						
Test setup:	Reference Plane  <i>Remark</i> E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m					
Test procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Measurement data:

Pre-scan all test modes, found worst case at GFSK 2402MHz, and so only show the test result of it
Line:




Neutral:



Notes:


1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss

7.3 Conducted Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(1)
Test Method:	ANSI C63.10:2013
Limit:	30dBm
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer, showing a frequency spectrum on its screen, is connected to an E.U.T. (Equipment Under Test) by a red cable. Both the Spectrum Analyzer and the E.U.T. are positioned on a Non-Conducted Table. This table is supported by a Ground Reference Plane, which is represented by a thick grey bar at the bottom of the setup.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data: The detailed test data see Appendix for BT EDR.

7.4 20dB Emission Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Limit:	N/A
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data: The detailed test data see Appendix for BT EDR.

7.5 Carrier Frequencies Separation

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=300KHz, VBW=300KHz, detector=Peak
Limit:	0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer, showing a frequency spectrum on its screen, is connected to an E.U.T. (Equipment Under Test) box by a red cable. Both the Spectrum Analyzer and the E.U.T. are positioned on a table labeled 'Non-Conducted Table'. This table is supported by a 'Ground Reference Plane'.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data: The detailed test data see Appendix for BT EDR.

7.6 Hopping Channel Number

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=VBW=300kHz, Frequency range=2398MHz-2485.5MHz, Detector=Peak
Limit:	15 channels
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer, shown with a grid and a green curve, is connected to an E.U.T (Equipment Under Test) box by a red cable. Both the Spectrum Analyzer and the E.U.T are positioned on a table labeled 'Non-Conducted Table'. This table is supported by two vertical legs and rests on a thick grey bar labeled 'Ground Reference Plane'.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for BT EDR.


7.7 Dwell Time

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=VBW=0.91MHz, Span=0Hz, Detector=Peak RBW=VBW=100kHz, Span=0Hz, Detector=Peak
Limit:	0.4 Second
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for BT EDR.


7.8 Spurious Emission in Non-restricted & restricted Bands



7.8.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100kHz, VBW=300kHz, Detector=Peak
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for BT EDR.

7.8.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Note: For Duty cycle $\geq 98\%$, average detector set as above For Duty cycle $< 98\%$, average detector set as below: $VBW \geq 1 / T$					
Limit:	Frequency	Limit (uV/m)	Value	Measurement Distance	
	0.009MHz-0.490MHz	2400/F(KHz)	PK/QP/AV	300m	
	0.490MHz-1.705MHz	24000/F(KHz)	QP	30m	
	1.705MHz-30MHz	30	QP	30m	
	30MHz-88MHz	100	QP	3m	
	88MHz-216MHz	150	QP		
	216MHz-960MHz	200	QP		
	960MHz-1GHz	500	QP		
	Above 1GHz	500	Average		
		5000	Peak		
Test setup:	For radiated emissions from 9kHz to 30MHz				
					

	For radiated emissions from 30MHz to 1GHz  For radiated emissions above 1GHz 
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details

Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Measurement data:

Remarks:


1. During the test, pre-scan the GFSK, $\pi/4$ -DQPSK, 8-DPSK modulation, and found the GFSK modulation which it is worse case.
2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

■ 9kHz~30MHz


The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

■ Below 1GHz

Pre-scan all test modes, found worst case at GFSK 2402MHz, and so only show the test result of it
Horizontal:



Vertical:



■ Above 1GHz

■ Unwanted Emissions in Non-restricted Frequency Bands

Test Mode	GFSK	Test channel:	Lowest channel
-----------	------	---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
1714	49.45	25.96	3.46	34.56	44.31	74.00	-29.69	Vertical
4808	60.38	31.27	5.87	35.70	61.82	74.00	-12.18	Vertical
7188	40.05	35.65	7.11	33.78	49.03	74.00	-24.97	Vertical
1714	36.87	25.96	3.46	34.56	31.73	74.00	-42.27	Horizontal
4808	57.08	31.27	5.87	35.70	58.52	74.00	-15.48	Horizontal
7188	45.45	35.65	7.11	33.78	54.43	74.00	-19.57	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
1714	22.43	25.96	3.46	34.56	17.29	54.00	-36.71	Vertical
4808	36.67	31.27	5.87	35.70	38.11	54.00	-15.89	Vertical
7188	21.56	35.65	7.11	33.78	30.54	54.00	-23.46	Vertical
1714	19.89	25.96	3.46	34.56	14.75	54.00	-39.25	Horizontal
4808	22.14	31.27	5.87	35.70	23.58	54.00	-30.42	Horizontal
7188	23.60	35.65	7.11	33.78	32.58	54.00	-21.42	Horizontal

Test Mode	GFSK	Test channel:	Middle channel
-----------	------	---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
1748	53.48	26.04	3.50	34.55	48.47	74.00	-25.53	Vertical
4876	56.80	31.35	5.91	35.66	58.40	74.00	-15.60	Vertical
7324	46.87	35.98	7.17	33.83	58.40	74.00	-17.81	Vertical
1748	37.36	26.04	3.50	34.55	32.35	74.00	-41.65	Horizontal
4876	52.03	31.35	5.91	35.66	53.63	74.00	-20.37	Horizontal
7324	42.91	35.98	7.17	33.83	52.23	74.00	-21.77	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
1748	21.06	26.04	3.50	34.55	16.05	54.00	-37.95	Vertical
4876	22.39	31.35	5.91	35.66	23.99	54.00	-30.01	Vertical
7324	21.39	35.98	7.17	33.83	30.71	54.00	-23.29	Vertical
1748	20.50	26.04	3.50	34.55	15.49	54.00	-38.51	Horizontal
4876	41.26	31.35	5.91	35.66	42.86	54.00	-11.14	Horizontal
7324	20.79	35.98	7.17	33.83	30.11	54.00	-23.89	Horizontal

Test Mode	GFSK	Test channel:	Highest channel
-----------	------	---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
1714	51.82	25.96	3.46	34.56	46.68	74.00	-27.32	Vertical
4944	65.31	31.43	5.95	35.63	67.06	74.00	-6.94	Vertical
7426	45.72	36.22	7.22	33.87	55.29	74.00	-18.71	Vertical
1714	35.06	25.96	3.46	34.56	29.92	74.00	-44.08	Horizontal
4944	57.85	31.43	5.95	35.63	59.60	74.00	-14.40	Horizontal
7426	48.26	36.22	7.22	33.87	57.83	74.00	-16.17	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
1714	21.16	25.96	3.46	34.56	16.02	54.00	-37.98	Vertical
4944	22.31	31.43	5.95	35.63	34.06	54.00	-29.94	Vertical
7426	22.22	36.22	7.22	33.87	31.79	54.00	-22.21	Vertical
1714	20.25	25.96	3.46	34.56	15.11	54.00	-38.89	Horizontal
4944	41.98	31.43	5.95	35.63	43.73	54.00	-10.27	Horizontal
7426	22.81	36.22	7.22	33.87	32.38	54.00	-21.62	Horizontal

Remarks:

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

■ Unwanted Emissions in Restricted Frequency Bands

Test Mode	GFSK	Test channel:	Lowest channel
-----------	------	---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310	34.76	27.26	4.03	35.15	30.90	74.00	-43.10	Horizontal
2390	34.23	27.40	4.09	35.32	30.40	74.00	-43.60	Horizontal
2310	36.72	27.26	4.03	35.15	32.86	74.00	-41.14	Vertical
2390	34.37	27.40	4.09	35.32	30.54	74.00	-43.46	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310	20.38	27.26	4.03	35.15	16.52	54.00	-37.48	Horizontal
2390	24.75	27.40	4.09	35.32	20.92	54.00	-33.08	Horizontal
2310	18.84	27.26	4.03	35.15	14.98	54.00	-39.02	Vertical
2390	20.99	27.40	4.09	35.32	17.16	54.00	-36.84	Vertical

Test Mode	GFSK	Test channel:	Highest channel
-----------	------	---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.5	49.10	27.57	4.17	35.52	45.32	74.00	-28.68	Horizontal
2500	32.87	27.60	4.18	35.55	29.10	74.00	-44.90	Horizontal
2483.5	44.46	27.57	4.17	35.52	40.68	74.00	-33.32	Vertical
2500	31.87	27.60	4.18	35.55	28.10	74.00	-45.90	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.5	37.96	27.57	4.17	35.52	34.18	54.00	-19.82	Horizontal
2500	19.32	27.60	4.18	35.55	15.55	54.00	-38.45	Horizontal
2483.5	29.48	27.57	4.17	35.52	25.70	54.00	-28.30	Vertical
2500	20.91	27.60	4.18	35.55	17.14	54.00	-36.86	Vertical

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

■ Unwanted Emissions in Non-restricted Frequency Bands

Test Mode	$\pi/4$ DQPSK	Test channel:	Lowest channel
-----------	---------------	---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
1986	49.65	26.66	3.76	34.50	45.57	74.00	-28.43	Vertical
4808	52.38	31.27	5.87	35.70	53.82	74.00	-20.18	Vertical
7188	42.41	35.65	7.11	33.78	51.39	74.00	-22.61	Vertical
1986	37.79	26.66	3.76	34.50	33.71	74.00	-40.29	Horizontal
4808	53.74	31.27	5.87	35.70	55.18	74.00	-18.82	Horizontal
7188	44.03	35.65	7.11	33.78	53.01	74.00	-20.99	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
1986	20.68	26.66	3.76	34.50	16.60	54.00	-37.40	Vertical
4808	32.35	31.27	5.87	35.70	33.79	54.00	-20.21	Vertical
7188	21.23	35.65	7.11	33.78	30.21	54.00	-23.79	Vertical
1986	21.02	26.66	3.76	34.50	16.94	54.00	-37.06	Horizontal
4808	34.64	31.27	5.87	35.70	36.08	54.00	-17.92	Horizontal
7188	22.05	35.65	7.11	33.78	31.03	54.00	-22.97	Horizontal

Test Mode	π /4 QPSK	Test channel:	Middle channel
-----------	---------------	---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
1748	50.13	26.04	3.50	34.55	45.12	74.00	-28.88	Vertical
4876	58.13	31.35	5.91	35.66	59.98	74.00	-14.02	Vertical
7324	45.94	35.98	7.17	33.83	55.26	74.00	-18.74	Vertical
1748	36.41	26.04	3.50	34.55	31.40	74.00	-42.60	Horizontal
4876	54.27	31.35	5.91	35.66	55.87	74.00	-18.13	Horizontal
7324	45.35	35.98	7.17	33.83	54.67	74.00	-19.33	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
1748	22.16	26.04	3.50	34.55	17.15	54.00	-36.85	Vertical
4876	31.25	31.35	5.91	35.66	32.85	54.00	-21.15	Vertical
7324	22.03	35.98	7.17	33.83	31.35	54.00	-22.65	Vertical
1748	20.13	26.04	3.50	34.55	15.12	54.00	-38.88	Horizontal
4876	36.69	31.35	5.91	35.66	38.29	54.00	-15.71	Horizontal
7324	21.66	35.98	7.17	33.83	30.98	54.00	-23.02	Horizontal

Test Mode	π /4 DQPSK	Test channel:	Highest channel
-----------	----------------	---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
1748	48.86	26.04	3.50	34.55	43.85	74.00	-30.15	Vertical
4944	53.58	31.43	5.95	35.63	55.33	74.00	-18.67	Vertical
7426	44.32	36.22	7.22	33.87	53.89	74.00	-20.11	Vertical
1748	32.88	26.04	3.50	34.55	27.87	74.00	-46.13	Horizontal
4944	58.25	31.43	5.95	35.63	60.00	74.00	-14.00	Horizontal
7426	46.60	36.22	7.22	33.87	56.17	74.00	-17.73	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
1748	24.09	26.04	3.50	34.55	19.08	54.00	-34.92	Vertical
4944	36.07	31.43	5.95	35.63	37.82	54.00	-16.18	Vertical
7426	21.65	36.22	7.22	33.87	31.22	54.00	-22.78	Vertical
1748	19.99	26.04	3.50	34.55	14.98	54.00	-39.02	Horizontal
4944	41.70	31.43	5.95	35.63	43.45	54.00	-10.55	Horizontal
7426	22.39	36.22	7.22	33.87	31.96	54.00	-22.04	Horizontal

Remarks:

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

■ Unwanted Emissions in Restricted Frequency Bands

Test Mode	$\pi/4$ DQPSK	Test channel:	Lowest channel
-----------	---------------	---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310	33.37	27.26	4.03	35.15	29.51	74.00	-44.49	Horizontal
2390	34.06	27.40	4.09	35.32	30.23	74.00	-43.77	Horizontal
2310	37.13	27.26	4.03	35.15	33.27	74.00	-40.73	Vertical
2390	34.02	27.40	4.09	35.32	30.19	74.00	-43.81	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310	19.21	27.26	4.03	35.15	15.35	54.00	-38.65	Horizontal
2390	20.84	27.40	4.09	35.32	17.01	54.00	-36.99	Horizontal
2310	18.69	27.26	4.03	35.15	14.83	54.00	-39.17	Vertical
2390	20.37	27.40	4.09	35.32	16.54	54.00	-37.46	Vertical

Test Mode	$\pi/4$ DQPSK	Test channel:	Highest channel
-----------	---------------	---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.5	52.56	27.57	4.17	35.52	48.78	74.00	-25.22	Horizontal
2500	32.86	27.60	4.18	35.55	29.09	74.00	-44.91	Horizontal
2483.5	47.76	27.57	4.17	35.52	43.98	74.00	-30.02	Vertical
2500	31.60	27.60	4.18	35.55	27.83	74.00	-46.17	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.5	23.98	27.57	4.17	35.52	20.20	54.00	-33.80	Horizontal
2500	21.70	27.60	4.18	35.55	17.93	54.00	-36.07	Horizontal
2483.5	30.70	27.57	4.17	35.52	26.92	54.00	-27.08	Vertical
2500	21.23	27.60	4.18	35.55	17.46	54.00	-36.54	Vertical

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

■ Unwanted Emissions in Non-restricted Frequency Bands

Test Mode	8-DPSK	Test channel:	Lowest channel
-----------	--------	---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2122	45.41	26.92	3.88	34.76	41.45	74.00	-32.55	Vertical
4808	51.59	31.27	5.87	35.70	53.03	74.00	-20.97	Vertical
7188	42.85	35.65	7.11	33.78	51.83	74.00	-22.17	Vertical
2122	42.24	26.92	3.88	34.76	38.28	74.00	-35.72	Horizontal
4808	53.13	31.27	5.87	35.70	54.57	74.00	-19.43	Horizontal
7188	45.02	35.65	7.11	33.78	54.00	74.00	-20.00	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2122	21.13	26.92	3.88	34.76	17.17	54.00	-36.83	Vertical
4808	32.46	31.27	5.87	35.70	33.90	54.00	-20.10	Vertical
7188	20.76	35.65	7.11	33.78	29.74	54.00	-24.26	Vertical
2122	20.65	26.92	3.88	34.76	16.69	54.00	-37.31	Horizontal
4808	32.64	31.27	5.87	35.70	34.08	54.00	-19.92	Horizontal
7188	21.32	35.65	7.11	33.78	30.30	54.00	-23.70	Horizontal

Test Mode	8-DPSK	Test channel:	Middle channel
-----------	--------	---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2122	49.01	26.92	3.88	34.76	45.05	74.00	-28.95	Vertical
4876	52.00	31.35	5.91	35.66	53.60	74.00	-20.40	Vertical
7324	42.35	35.98	7.17	33.83	51.67	74.00	-22.33	Vertical
2122	35.69	26.92	3.88	34.76	31.73	74.00	-42.27	Horizontal
4876	52.42	31.35	5.91	35.66	54.02	74.00	-19.98	Horizontal
7324	42.52	35.98	7.17	33.83	51.74	74.00	-22.16	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2122	21.18	26.92	3.88	34.76	17.22	54.00	-36.78	Vertical
4876	31.27	31.35	5.91	35.66	32.87	54.00	-21.13	Vertical
7324	21.98	35.98	7.17	33.83	31.30	54.00	-22.70	Vertical
2122	21.13	26.92	3.88	34.76	17.17	54.00	-36.83	Horizontal
4876	24.94	31.35	5.91	35.66	26.54	54.00	-27.46	Horizontal
7324	22.21	35.98	7.17	33.83	31.53	54.00	-22.47	Horizontal

Test Mode	8-DPSK	Test channel:	Highest channel
-----------	--------	---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2156	49.50	26.98	3.90	34.83	45.55	74.00	-28.45	Vertical
4944	58.86	31.43	5.95	35.63	60.61	74.00	-13.39	Vertical
7426	41.85	36.22	7.22	33.87	51.42	74.00	-22.58	Vertical
2156	41.28	26.98	3.90	34.83	37.33	74.00	-36.67	Horizontal
4944	51.74	31.43	5.95	35.63	53.49	74.00	-20.51	Horizontal
7426	44.50	36.22	7.22	33.87	54.07	74.00	-19.93	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2156	22.44	26.98	3.90	34.83	18.49	54.00	-35.51	Vertical
4944	35.73	31.43	5.95	35.63	37.48	54.00	-16.52	Vertical
7426	24.00	36.22	7.22	33.87	33.57	54.00	-20.43	Vertical
2156	20.75	26.98	3.90	34.83	16.80	54.00	-37.20	Horizontal
4944	39.30	31.43	5.95	35.63	41.05	54.00	-12.95	Horizontal
7426	21.52	36.22	7.22	33.87	31.09	54.00	-22.91	Horizontal

Remarks:

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

■ Unwanted Emissions in Restricted Frequency Bands

Test Mode	8-DPSK	Test channel:	Lowest channel
-----------	--------	---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310	32.04	27.26	4.03	35.15	28.18	74.00	-45.82	Horizontal
2390	35.66	27.40	4.09	35.32	31.83	74.00	-42.17	Horizontal
2310	36.92	27.26	4.03	35.15	33.06	74.00	-40.94	Vertical
2390	33.13	27.40	4.09	35.32	29.30	74.00	-44.70	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310	21.42	27.26	4.03	35.15	17.56	54.00	-36.44	Horizontal
2390	20.91	27.40	4.09	35.32	17.08	54.00	-36.92	Horizontal
2310	19.42	27.26	4.03	35.15	15.56	54.00	-38.44	Vertical
2390	22.66	27.40	4.09	35.32	18.83	54.00	-35.17	Vertical

Test Mode	8-DPSK	Test channel:	Highest channel
-----------	--------	---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.5	54.20	27.57	4.17	35.52	50.42	74.00	-23.58	Horizontal
2500	33.14	27.60	4.18	35.55	29.37	74.00	-44.63	Horizontal
2483.5	48.00	27.57	4.17	35.52	44.22	74.00	-29.78	Vertical
2500	32.20	27.60	4.18	35.55	28.43	74.00	-45.57	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.5	37.88	27.57	4.17	35.52	34.10	54.00	-19.90	Horizontal
2500	22.90	27.60	4.18	35.55	19.13	54.00	-34.87	Horizontal
2483.5	27.82	27.57	4.17	35.52	24.04	54.00	-29.96	Vertical
2500	20.61	27.60	4.18	35.55	16.84	54.00	-37.16	Vertical

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----