

TEST REPORT

Applicant: TOUCH DYNAMIC INC.
Address: 121 Corporate Blvd, South Plainfield, NJ 07080, USA
Equipment Type: QuestGamingTablet
Model Name: QuestGamingTablet
Brand Name: TOUCH_DYNAMIC
FCC ID: 2BMQJ-QUESTBINGO10
Test Standard: FCC 47 CFR Part 2.1093
(refer to section 3.1)
Maximum SAR: Body (1 g@0mm): 1.16 W/kg
Sample Arrival Date: Oct. 11, 2024
Test Date: Nov. 24, 2024 - Nov. 25, 2024
Date of Issue: Jan. 08, 2025

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Guo Guangwei**Checked by:** Xu Rui**Approved by:** Tolan Tu
(Testing Director)

Revision History

Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>Jan. 08, 2025</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	4
1.1	Test Laboratory	4
1.2	Test Location	4
1.3	Test Environment Condition.....	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information.....	5
2.3	General Description for Equipment under Test (EUT).....	5
2.4	Ancillary Equipment.....	5
2.5	Technical Information	6
3	SUMMARY OF TEST RESULT	7
3.1	Test Standards	7
3.2	Device Category and SAR Limit	8
3.3	Test Result Summary	9
3.4	Test Uncertainty	10
4	MEASUREMENT SYSTEM	11
4.1	Specific Absorption Rate (SAR) Definition	11
4.2	DASY SAR System	12
5	SYSTEM VERIFICATION	19
5.1	Purpose of System Check	19
5.2	System Check Setup	19
6	TEST POSITION CONFIGURATIONS	20
6.1	Laptop Exposure Condition.....	20
6.2	Tablet Exposure Condition.....	21

7	MEASUREMENT PROCEDURE	22
7.1	Measurement Process Diagram	22
7.2	SAR Scan General Requirement	23
7.3	Measurement Procedure	24
7.4	Area & Zoom Scan Procedure	24
7.5	Interim Procedures for WIFI 6E	24
8	CONDUCTED RF OUPUT POWER	25
8.1	WIFI.....	25
8.2	Bluetooth	31
9	TEST EXCLUSION CONSIDERATION	32
9.1	Tablet Mode antenna location sketch	32
9.2	SAR Test Consideration Table	33
10	TEST RESULT	36
10.1	WIFI 2.4GHz.....	36
10.2	WIFI 5GHz.....	36
10.3	WIFI 6GHz.....	37
10.4	Bluetooth	38
11	SAR Measurement Variability	39
12	SIMULTANEOUS TRANSMISSION.....	40
13	TEST EQUIPMENTS LIST	41
ANNEX A	SIMULATING LIQUID VERIFICATION RESULT	42
ANNEX B	SYSTEM CHECK RESULT	43
ANNEX C	TEST DATA.....	54
ANNEX D	EUT EXTERNAL PHOTOS.....	66
ANNEX E	SAR TEST SETUP PHOTOS	66
ANNEX F	CALIBRATION REPORT	66
ANNEX G	TUNE-UP PROCEDURE.....	66

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☐ Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☒ 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

1.3 Test Environment Condition

Ambient Temperature	18°C to 25°C
Ambient Relative Humidity	30% to 70%

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	TOUCH DYNAMIC INC.
Address	121 Corporate Blvd, South Plainfield, NJ 07080, USA

2.2 Manufacturer Information

Manufacturer	TOUCH DYNAMIC INC.
Address	121 Corporate Blvd, South Plainfield, NJ 07080, USA

2.3 General Description for Equipment under Test (EUT)

EUT Name	QuestGamingTablet
Model Name Under Test	QuestGamingTablet
Series Model Name	N/A
Description of Model Name Differentiation	N/A
Hardware Version	V1.0
Software Version	S0461_TOUCH_DYNAMIC_COMBO_20240821
Dimensions (Approx.)	332.9mm*180.9mm*21.2mm
Weight (Approx.)	1.23kg

2.4 Ancillary Equipment

Ancillary Equipment 1	Li-Polymer Battery 1	
	Brand Name	N/A
	Model No.	S0461
	Serial No.	N/A
	Capacitance	Rated: 11700mAh/ 45.05Wh Typical: 12000mAh/ 46.20Wh
	Rated Voltage	3.85 V
	Limited Voltage	4.40 V
	Manufacturer	Guangdong Fenghua New Energy co., Ltd.

2.5 Technical Information

Network and Wireless connectivity	Bluetooth (BR+EDR+BLE) WIFI 802.11a, 802.11b, 802.11g, 802.11n, 802.11ac, 802.11ax
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	2.4G WIFI, 5G WIFI, 6G WIFI, Bluetooth	
Frequency Range	802.11b/g/n(HT20/HT40)	2412 MHz ~ 2462 MHz
	802.11ax(HE20/HE40)	2412 MHz ~ 2462 MHz
	802.11a/n(HT20/HT40)/ac(VHT20/VHT40/VHT80/160)	5150 MHz ~ 5250 MHz
		5250 MHz ~ 5350 MHz
		5470 MHz ~ 5725 MHz
	802.11ax(HE20/HE40/HE80/HE160)	5725 MHz ~ 5850 MHz
		5150 MHz ~ 5250 MHz
		5250 MHz ~ 5350 MHz
		5470 MHz ~ 5725 MHz
		5725 MHz ~ 5850 MHz
	802.11ax(HE20/HE40/HE80/HE160)	5925 MHz ~ 6425 MHz
		6425 MHz ~ 6525 MHz
		6525 MHz ~ 6875 MHz
		6875 MHz ~ 7125 MHz
	Bluetooth	2402 MHz ~ 2480 MHz
Antenna Type	WIFI: FPC Antenna Bluetooth: FPC Antenna	
Hotspot Function	N/A	
Exposure Category	General Population/Uncontrolled exposure	
Product Type	Portable Device	
EUT Type	☒ Production unit	☐ Identical prototype

3 SUMMARY OF TEST RESULT

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 2.1093	Radiofrequency radiation exposure evaluation: portable devices
2	ANSI C95.1-1992	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz
3	FCC KDB 447498 D04	RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices
4	FCC KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
5	FCC KDB 865664 D02 v01r02	RF Exposure Reporting
6	KDB 248227 D01 v02r02	SAR Guidance for IEEE 802.11 (Wi-Fi) Transmitters
7	IEC/IEEE 62209-1528:2020	Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Part 1528: Human models, instrumentation, and procedures (Frequency range of 4 MHz to 10 GHz)

3.2 Device Category and SAR Limit

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user.

Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

Table of Exposure Limits:

Body Position	SAR Value (W/Kg)	
	General Population/ Uncontrolled Exposure	Occupational/ Controlled Exposure
Whole-Body SAR (averaged over the entire body)	0.08	0.4
Partial-Body SAR (averaged over any 1 gram of tissue)	1.60	8.0
SAR for hands, wrists, feet and ankles (averaged over any 10 grams of tissue)	4.0	20.0

NOTE:

General Population/Uncontrolled Exposure: Locations where there is the exposure of individuals who have no knowledge or control of their exposure. General population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Occupational/Controlled Exposure: Locations where there is exposure that may be incurred by persons who are aware of the potential for exposure. In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

3.3 Test Result Summary

3.3.1 Highest SAR (1 g Value)

Equipment Class	Band	Maximum Scaled SAR (W/kg)	Maximum Report SAR (W/kg)
		Body (0mm)	Body (0mm)
WIFI	2.4G	0.81	1.16
	5.3G	1.16	
	5.6G	0.98	
	5.8G	0.99	
	6G	0.71	
DSS	3DH5	0.26	
Limit (W/kg)		1.60	
Verdict		Pass	

3.4 Test Uncertainty

According to KDB 865664 D01, when the highest measured 1 g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis is not required in SAR reports submitted for equipment approval.

The maximum 1 g SAR for the EUT in this report is 1.16 W/kg, which is lower than 1.5 W/kg, so the extensive SAR measurement uncertainty analysis is not required in this report.

4 MEASUREMENT SYSTEM

4.1 Specific Absorption Rate (SAR) Definition

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by


$$SAR = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue,

ρ is the mass density of the tissue and E is the RMS electrical field strength.

4.2 DASY SAR System

4.2.1 DASY SAR System Diagram



The DASY system for performing compliance tests consists of the following items:

1. A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).
2. A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
3. A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
4. A unit to operate the optical surface detector which is connected to the EOC.
5. The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY measurement server.
6. The DASY measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.
7. DASY software and SEMCAD data evaluation software.
8. Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.
9. The generic twin phantom enabling the testing of left-hand and right-hand usage.
10. The device holder for handheld mobile phones.
11. Tissue simulating liquid mixed according to the given recipes.
12. System validation dipoles allowing to validate the proper functioning of the system.

4.2.2 Robot

The Dasy SAR system uses the high precision robots. Symmetrical design with triangular core Built-in optical fiber for surface detection system For the 6-axis controller system, Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents). The robot series have many features that are important for our application:



- High precision
(repeatability ± 0.02 mm)
- High reliability
(industrial design)
- Low maintenance costs
(virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements
(brush less synchron motors; no stepper motors)
- Low ELF interference
(motor control _elds shielded via the closed metallic construction shields)

4.2.3 E-Field Probe

The probe is specially designed and calibrated for use in liquids with high permittivities for the measurements the Specific Dosimetric E-Field Probe EX3DV4-SN: 7893 with following specifications is used.

Construction	Symmetrical design with triangular core Built-in optical fiber for surface detection system Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., glycolether)
Calibration	ISO/IEC 17025 calibration service available
Frequency	4 MHz to 10 GHz; Linearity: ± 0.2 dB
Directivity	± 0.2 dB in HSL (rotation around probe axis) ; ± 0.4 dB in HSL (rotation normal to probe axis)
Dynamic range	5 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB
Dimensions	Overall length: 337 mm (Tip: 9 mm) Tip diameter: 2.5 mm (Body: 10 mm) Distance from probe tip to dipole centers: 1.0 mm
Application	General dosimetry up to 3 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms (EX3DV4)



E-Field Probe Calibration Process

Probe calibration is realized, in compliance with IEC/IEEE 62209-1528 and IEEE 1528 std, with CALISAR, Antennessa proprietary calibration system. The calibration is performed with the IEC/IEEE 62209-1528 annexe technique using reference guide at the five frequencies.

4.2.4 Data Acquisition Electronics


The data acquisition electronics (DAE) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.



- Input Impedance: 200M Ω
- The Inputs: Symmetrical and Floating
- Common Mode Rejection: Above 80dB

4.2.5 Phantoms

Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of below 10 GHz. ELI4 is fully compatible with the latest draft of the standard IEC 62209 Part II and all known tissue simulating liquids. ELI4 has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points.



· Flat phantom

Photo of Phantom SN2159



Serial Number	Shell Thickness (mm)	Major ellipse axis (mm)	Minor axis (mm)
SN 2159 ELI4	2.0 ± 0.2	600	400

4.2.6 Device Holder


The DASY device holder has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of 65° . The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. This device holder is used for standard mobile phones or PDA's only. If necessary an additional support of polystyrene material is used. Larger DUT's (e.g. notebooks) cannot be tested using this device holder. Instead a support of bigger polystyrene cubes and thin polystyrene plates is used to position the DUT in all relevant positions to find and measure spots with maximum SAR values. Therefore those devices are normally only tested at the flat part of the SAM.



The positioning system allows obtaining cheek and tilting position with a very good accuracy. Incompliance with CENELEC, the tilt angle uncertainty is lower than 1° .

4.2.7 Simulating Liquid

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5%.



The following table gives the recipes for tissue simulating liquid and the theoretical Conductivity/Permittivity.

The following table gives the recipes for tissue simulating liquid.

TSL	Manufacturer / Model	Freq Range (MHz)	Main Ingredients
Head WideBand	SPEAG HBBL600-10000V6	600-10000	Ethenediol, Sodium petroleum sulfonate, Hexylene Glycol / 2-Methyl-pentane-2.4-diol, Alkoxylated alcohol


5 SYSTEM VERIFICATION

5.1 Purpose of System Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

5.2 System Check Setup


In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



6 TEST POSITION CONFIGURATIONS

6.1 Laptop Exposure Condition

This DUT should consider one position which is bottom of laptop touching with phantom 0 mm air gap and the screen portion of the device shall be an open position at a 90° angle.



6.2 Tablet Exposure Condition

This DUT was tested in four different positions. They are back side, left edge, right edge and top edge in these positions, the surface of DUT is touching with phantom 0mm.





Fig Illustration for Lap-touching Position

7 MEASUREMENT PROCEDURE

7.1 Measurement Process Diagram



7.2 SAR Scan General Requirement

Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1 g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2013.

			≤3GHz	>3GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5±1 mm	½·δ·ln(2)±0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			30°±1°	20°±1°
Maximum area scan spatial resolution: Δx Area , Δy Area			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3–4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx Zoom , Δy Zoom			≤ 2 GHz: ≤ 8 mm 2 –3 GHz: ≤ 5 mm*	3–4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: Δz Zoom (n)		≤ 5 mm	3–4 GHz: ≤ 4 mm
				4–5 GHz: ≤ 3 mm
				5–6 GHz: ≤ 2 mm
	graded grid	Δz Zoom (1): between 1st two points closest to phantom surface	≤ 4 mm	3–4 GHz: ≤ 3 mm
				4–5 GHz: ≤ 2.5 mm
		Δz Zoom (n>1): between subsequent points	≤ 1.5·Δz Zoom (n-1)	
Minimum zoom scan volume	x, y, z		≥30 mm	3–4 GHz: ≥ 28 mm
				4–5 GHz: ≥ 25 mm
				5–6 GHz: ≥ 22 mm

Note:

- δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.
- * When zoom scan is required and the reported SAR from the area scan based 1 g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

7.3 Measurement Procedure

The following steps are used for each test position

- a. Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- b. Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- c. Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- d. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

7.4 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01v01r04 quoted below.

When the 1 g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

7.5 Interim Procedures for WIFI 6E

Interim procedures for FCC radio frequency (RF) exposure evaluations of U-NII 6-7 GHz band portable devices have been made available during the TCB workshop in April 2021. The procedure is summarized below:

- a. Evaluate SAR / APD with DASY6 Module SAR V16.0 or higher. The configurations to be tested are defined in the relevant Knowledge Database (KDB). The psSAR and absorbed psPD are reported.
- b. For the configuration with the highest SAR, evaluate the incident power density with DASY6 Module mmWave V2.4.2 or higher. The incident psPD must be adjusted per amount that the measurement uncertainty exceeds 30% before it is included in the test report.

8 CONDUCTED RF OUTPUT POWER

8.1 WIFI

8.1.1 2.4G WIFI

Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Tune-up Limit (dBm)	SAR Test Require.
2.4 (2.4~2.4835)	802.11b	1	2412	17.59	18.00	Yes
		6	2437	17.49	18.00	Yes
		11	2462	17.42	18.00	Yes
	802.11g	1	2412	16.85	17.50	No
		6	2437	16.99	17.50	No
		11	2462	16.95	17.50	No
	802.11n(HT20)	1	2412	15.76	16.50	No
		6	2437	15.87	16.50	No
		11	2462	15.88	16.50	No
	802.11n(HT40)	3	2422	15.35	16.50	No
		6	2437	15.41	16.50	No
		9	2452	15.41	16.50	No
	802.11ax(HE20)	1	2412	16.01	16.50	No
		6	2437	16.00	16.50	No
		11	2462	16.06	16.50	No
	802.11ax(HE40)	3	2422	15.40	16.50	No
		6	2437	15.35	16.50	No
		9	2452	15.34	16.50	No

Note: According KDB 248227 D01 SAR is not required for the following 2.4 GHz OFDM conditions. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

Adjusted SAR = Report SAR * (max power (OFDM)/ max power (DSSS)) = 0.808 * (56.230mW/63.100mW) = 0.720 W/Kg, so the 2.4G OFDM SAR test is not required.

8.1.2 5G WIFI

Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Tune-up Power Limit (dBm)	SAR Test Require.
5.2G	802.11a	36	5180	14.30	14.50	No
		44	5220	14.18	14.50	No
		48	5240	14.11	14.50	No
	802.11n(HT20)	36	5180	13.83	14.50	No
		44	5220	14.06	14.50	No
		48	5240	13.41	14.50	No
	802.11n(HT40)	38	5190	14.03	14.50	No
		46	5230	14.12	14.50	No
	802.11ac(VHT20)	36	5180	13.87	14.50	No
		44	5220	14.10	14.50	No
		48	5240	14.00	14.50	No
	802.11ac(VHT40)	38	5190	14.05	14.50	No
		46	5230	14.14	14.50	No
	802.11ac(VHT80)	42	5210	13.85	14.50	Yes
	802.11ax(HE20)	36	5180	14.20	14.50	No
		44	5220	14.21	14.50	No
		48	5240	14.18	14.50	No
	802.11ax(HE40)	38	5190	13.85	14.50	No
		46	5230	13.86	14.50	No
	802.11ax(HE80)	42	5210	14.33	14.50	No
5.3G	802.11a	52	5260	14.21	14.50	No
		60	5300	13.91	14.50	No
		64	5320	14.06	14.50	No
	802.11n(HT20)	52	5260	14.10	14.50	No
		60	5300	13.84	14.50	No
		64	5320	13.84	14.50	No
	802.11n(HT40)	54	5270	14.18	14.50	No
		62	5310	14.01	14.50	No
	802.11ac(VHT20)	52	5260	14.09	14.50	No
		60	5300	14.34	14.50	No
		64	5320	14.32	14.50	No
	802.11ac(VHT40)	54	5270	14.20	14.50	No
		62	5310	14.03	14.50	No
	802.11ac(VHT80)	58	5290	13.83	14.50	Yes
	802.11ac(VHT160)	50	5250	13.95	14.00	No
	802.11ax(HE20)	52	5260	14.17	14.50	No
		60	5300	14.18	14.50	No
		64	5320	14.18	14.50	No
	802.11ax(HE40)	54	5270	13.89	14.50	No

		62	5310	13.81	14.50	No
	802.11ax(HE80)	58	5290	13.76	14.50	No
	802.11ax(HE160)	50	5250	13.60	14.00	No
5.6G (5.47~5.725)	802.11a	100	5500	12.61	13.00	No
		116	5580	12.36	13.00	No
		140	5700	12.07	13.00	No
	802.11n(HT20)	100	5500	12.04	13.00	No
		116	5580	12.22	13.00	No
		140	5700	11.99	13.00	No
	802.11n(HT40)	102	5510	12.20	13.00	No
		118	5590	12.21	13.00	No
		134	5670	12.26	13.00	No
	802.11ac(VHT20)	100	5500	12.46	13.00	No
		116	5580	12.75	13.00	No
		140	5700	12.53	13.00	No
	802.11ac(VHT40)	102	5510	12.30	13.00	No
		118	5590	12.26	13.00	No
		134	5670	12.24	13.00	No
	802.11ac(VHT80)	106	5530	12.44	13.00	No
		122	5610	12.23	13.00	No
	802.11ac(VHT160)	114	5570	12.69	13.00	Yes
	802.11ax(HE20)	100	5500	12.26	13.00	No
		116	5580	12.35	13.00	No
		140	5700	12.29	13.00	No
	802.11ax(HE40)	102	5510	12.54	13.00	No
		118	5590	12.59	13.00	No
		134	5670	12.50	13.00	No
	802.11ax(HE80)	106	5530	12.51	13.00	No
		122	5610	12.51	13.00	No
	802.11ax(HE160)	114	5570	12.65	13.00	No
5.8G (5.725~5.850)	802.11a	149	5745	12.78	13.50	No
		157	5785	13.11	13.50	No
		165	5825	13.09	13.50	No
	802.11n(HT20)	149	5745	12.66	13.50	No
		157	5785	12.91	13.50	No
		165	5825	12.44	13.50	No
	802.11n(HT40)	151	5755	12.90	13.50	No
		159	5795	12.93	13.50	No
	802.11ac(VHT20)	149	5745	13.22	13.50	No
		157	5785	12.87	13.50	No
		165	5825	12.93	13.50	No
	802.11ac(VHT40)	151	5755	12.82	13.50	No
		159	5795	12.88	13.50	No

	802.11ac(VHT80)	155	5775	12.88	13.50	Yes
	802.11ax(HE20)	149	5745	12.99	13.50	No
		157	5785	13.03	13.50	No
		165	5825	12.74	13.50	No
	802.11ax(HE40)	151	5755	13.20	13.50	No
		159	5795	13.15	13.50	No
	802.11ax(HE80)	155	5775	13.13	13.50	No

Note: When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR.

8.1.3 6G WIFI

Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Tune-up Power Limit (dBm)	SAR Test Require.
6G	802.11ax(HE20)	1	5955	6.72	7.00	No
		45	6175	6.76	7.00	No
		93	6415	6.22	7.00	No
		97	6435	6.33	7.00	No
		105	6475	6.76	7.00	No
		113	6515	6.19	7.00	No
		117	6535	6.48	7.00	No
		149	6695	6.06	7.00	No
		181	6855	6.15	7.00	No
		185	6875	6.47	7.00	No
		209	6995	6.19	7.00	No
		233	7115	6.40	7.00	No
	802.11ax(HE40)	3	5965	9.35	10.00	No
		43	6165	9.52	10.00	No
		91	6405	8.92	10.00	No
		99	6445	9.12	10.00	No
		107	6485	9.38	10.00	No
		115	6525	9.41	10.00	No
		147	6685	9.79	10.00	No
		179	6845	9.60	10.00	No
		187	6885	9.51	10.00	No
		211	7005	9.53	10.00	No
		227	7085	9.47	10.00	No
	802.11ax(HE80)	7	5985	11.49	12.00	No
		39	6225	11.90	12.00	No
		87	6385	11.54	12.00	No
		103	6465	11.38	12.00	No
		119	6545	11.23	12.00	No
		135	6625	11.39	12.00	No
		151	6705	11.77	12.00	No
		167	6785	11.74	12.00	No
		183	6865	11.63	12.00	No
		199	6945	11.50	12.00	No
		215	7025	11.34	12.00	No
	802.11ax(HE160)	15	6025	14.25	15.00	Yes
		47	6185	14.52	15.00	Yes
		79	6345	14.53	15.00	Yes
		111	6505	14.37	15.00	Yes
		143	6665	14.63	15.00	Yes

		207	6985	14.40	15.00	Yes
--	--	-----	------	-------	-------	-----

8.2 Bluetooth


Mode	GFSK			$\pi/4$ -DQPSK		
Channel	0	39	78	0	39	78
Frequency (MHz)	2402	2441	2480	2402	2441	2480
Conducted Power (dBm)	8.93	8.95	8.95	11.55	11.52	11.53
Tune-Up Limit (dBm)	10.00	10.00	10.00	12.00	12.00	12.00
SAR Test Require	No	No	No	No	No	No
Mode	8-DPSK			/		
Channel	0	39	78	/	/	/
Frequency (MHz)	2402	2441	2480	/	/	/
Conducted Power (dBm)	11.94	11.88	12.03	/	/	/
Tune-Up Limit (dBm)	12.50	12.50	12.50	/	/	/
SAR Test Require	Yes	Yes	Yes	/	/	/
Mode	BLE-1Mbps			BLE-2Mbps		
Channel	0	19	39	1	19	38
Frequency (MHz)	2402	2440	2480	2402	2440	2480
Conducted Power (dBm)	5.59	5.66	5.42	5.68	5.78	5.56
Tune-Up Limit (dBm)	6.50	6.50	6.50	6.50	6.50	6.50
SAR Test Require	No	No	No	No	No	No

Note: Since Bluetooth EDR mode is the maximum output power mode, SAR measurements were performed with test software using 3DH5 modulation, and SAR measurement is not required for the BR and LE. When the secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode.

The Bluetooth duty cycle is 73.78 % as following figure, according to 2016 Oct. TCB workshop for Bluetooth SAR scaling need further consideration and the maximum duty cycle is 100%, therefore the actual duty cycle will be scaled up to 100% for Bluetooth reported SAR calculation.

Duty Cycle

Bluetooth-8-DPSK



9 TEST EXCLUSION CONSIDERATION

9.1 Tablet Mode antenna location sketch

For antenna location and support bands please refer the document “BL-SH2490675-AI EUT internal photo.pdf”.

9.2 SAR Test Consideration Table

According with FCC KDB 447498 D04, Appendix B, The SAR-based exemption formula applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold Pth (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). The following table shows the power threshold from 5mm to 50mm.

Power Thresholds (mW)					
Frequency (MHz)	At separation distance of ≤ 5 mm	At separation distance of 10 mm	At separation distance of 15 mm	At separation distance of 20 mm	At separation distance of 25 mm
300	39 mW	65 mW	88 mW	110 mW	129 mW
450	22 mW	44 mW	67 mW	89 mW	112 mW
835	9 mW	25 mW	44 mW	66 mW	90 mW
1900	3 mW	12 mW	26 mW	44 mW	66 mW
2450	3 mW	10 mW	22 mW	38 mW	59 mW
3600	2 mW	8 mW	18 mW	32 mW	49 mW
5800	1 mW	6 mW	14 mW	25 mW	40 mW
Frequency (MHz)	At separation distance of 30 mm	At separation distance of 35 mm	At separation distance of 40 mm	At separation distance of 45 mm	At separation distance of 50 mm
300	148 mW	166 mW	184 mW	201 mW	217 mW
450	135 mW	158 mW	180 mW	203 mW	226 mW
835	116 mW	145 mW	175 mW	207 mW	240 mW
1900	92 mW	122 mW	157 mW	195 mW	236 mW
2450	83 mW	111 mW	143 mW	179 mW	219 mW
3600	71 mW	96 mW	125 mW	158 mW	195 mW
5800	58 mW	80 mW	106 mW	136 mW	169 mW

9.2.1 Tablet mode SAR Test Consideration

This host is a notebook computer, under normal use the RF exposure scenarios are shown in the table below:

RF exposure Position	RF exposure scenarios
Back Side	Body
Left Edge	Body
Right Edge	Body
Top Edge	Body
Bottom Edge	Body

Antenna Body RF exposure scenarios

Test Position Configurations	Mode	Bluetooth	2.4GWIFI	UNII-2A	UNII-2C	UNII-3
Calculated Frequency(MHz)		2480	2462	5290	5610	5750
Back Side	Distance to User (mm)	5				
	Max. Peak Power (dBm)	12.50	18.00	14.50	13.00	13.50
	Max. Peak Power (mW)	17.78	63.10	28.18	19.95	22.39
	Exclusion Threshold (mW)	2.72	2.73	1.48	1.41	1.39
	SAR Test Required	Yes	Yes	Yes	Yes	Yes
Left Edge	Distance to User (mm)	5				
	Max. Peak Power (dBm)	12.50	18.00	14.50	13.00	13.50
	Max. Peak Power (mW)	17.78	63.10	28.18	19.95	22.39
	Exclusion Threshold (mW)	2.72	2.73	1.48	1.41	1.39
	SAR Test Required	Yes	Yes	Yes	Yes	Yes
Right Edge	Distance to User (mm)	295				
	Max. Peak Power (dBm)	12.50	18.00	14.50	13.00	13.50
	Max. Peak Power (mW)	17.78	63.10	28.18	19.95	22.39
	Exclusion Threshold (mW)	6415.58	6411.64	6839.15	6873.14	6887.45
	SAR Test Required	No	No	No	No	No
Top Edge	Distance to User (mm)	5				
	Max. Peak Power (dBm)	12.50	18.00	14.50	13.00	13.50
	Max. Peak Power (mW)	17.78	63.10	28.18	19.95	22.39
	Exclusion Threshold (mW)	2.72	2.73	1.48	1.41	1.39
	SAR Test Required	Yes	Yes	Yes	Yes	Yes
Bottom Edge	Distance to User (mm)	175				
	Max. Peak Power (dBm)	12.50	18.00	14.50	13.00	13.50
	Max. Peak Power (mW)	17.78	63.10	28.18	19.95	22.39
	Exclusion Threshold (mW)	2372.79	2373.29	2321.23	2317.28	2315.63
	SAR Test Required	No	No	No	No	No

Note:

1. Maximum power is the source-based time-average power and represents the maximum RF output power including tune-up tolerance among production units
2. Per KDB 447498 D04, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
3. Per KDB 447498 D04, standalone SAR test exclusion threshold is applied; If the distance of the antenna to the user is < 5mm, 5mm is used to determine SAR exclusion threshold
4. Per KDB 447498 D04, for separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive), the threshold Pth (mW) is given by Following:

$$P_{th}(mW) = \begin{cases} ERP_{20cm}(d/20cm)^x & d \leq 20cm \\ ERP_{20cm} & 20cm < d \leq 40cm \end{cases}$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20cm}\sqrt{f}} \right)$$

- a. f(GHz) is the RF channel transmit frequency in GHz
- b. d is the separation distance (cm), The result is rounded to one decimal place for comparison
- c. ERP_{20cm} are determined by:

$$ERP_{20cm}(mW) = f(x) = \begin{cases} 2040f & 0.3GHz \leq f < 1.5GHz \\ 3060 & 1.5GHz \leq f \leq 6GHz \end{cases}$$

5. Per KDB 248227 D01, choose the highest output power channel to test SAR and determine further SAR exclusion.8. For each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of these configurations is less than 1/4dB higher than those measured at the lowest data rate
6. Per KDB 248227 D01 SAR is not required for the following 2.4 GHz OFDM conditions.
 - a. When KDB Publication 447498 D04 SAR test exclusion applies to the OFDM configuration.
 - b. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
7. Per KDB 248227 D01 SAR is not required for the following U-NII-1 and U-NII-2A bands conditions.
 - a. When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR.
 - b. When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration; otherwise, each band is tested independently for SAR.
8. For Limb SAR, SAR test exemption considered by applying a factor of 2.5 to the applicable power level thresholds.

10 TEST RESULT

10.1WIFI 2.4GHz

Mode	Antenna	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1 g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	1g Report SAR (W/kg)	Meas. No.
Body														
802.11 b	Ant.0	Back side	0	1	2412	0.18	0.134	17.59	18.00	1.099	95.09	1.052	0.155	/
		Left Edge	0	1	2412	0.06	0.132	17.59	18.00	1.099	95.09	1.052	0.153	/
		Top Edge	0	1	2412	-0.05	0.699	17.59	18.00	1.099	95.09	1.052	0.808	1#
		Top Edge	0	6	2437	0.08	0.631	17.49	18.00	1.125	95.09	1.052	0.747	/
		Top Edge	0	11	2462	-0.10	0.622	17.42	18.00	1.143	95.09	1.052	0.748	/
Note: Refer to ANNEX C for the detailed test data for each test configuration.														

10.2WIFI 5GHz

Band	Mode	Antenna	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1 g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune- up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	1g Report SAR (W/kg)	Meas. No.
Body															
5.3G	802.11ac(VHT80)	Ant.0	Back side	0	58	5290	0.06	0.258	13.83	14.50	1.167	88.73	1.127	0.339	/
			Left Edge	0	58	5290	-0.15	0.114	13.83	14.50	1.167	88.73	1.127	0.150	/
			Top Edge	0	58	5290	-0.09	0.879	13.83	14.50	1.167	88.73	1.127	1.156	2#
			Top Edge	0	42	5210	0.05	0.873	13.85	14.50	1.161	88.73	1.127	1.142	/
5.6G	802.11ac(VHT160)	Ant.0	Back side	0	114	5530	0.06	0.234	12.69	13.00	1.074	85.41	1.171	0.294	/
			Left Edge	0	114	5530	0.16	0.148	12.69	13.00	1.074	85.41	1.171	0.186	/
			Top Edge	0	114	5530	0.03	0.777	12.69	13.00	1.074	85.41	1.171	0.977	3#
5.8G	802.11ac(VHT80)	Ant.0	Back side	0	155	5775	-0.19	0.149	12.88	13.50	1.153	88.73	1.127	0.194	/
			Left side	0	155	5775	-0.05	0.145	12.88	13.50	1.153	88.73	1.127	0.188	/
			Top Edge	0	155	5775	-0.17	0.759	12.88	13.50	1.153	88.73	1.127	0.986	4#
Note: Refer to ANNEX C for the detailed test data for each test configuration.															

10.3WIFI 6GHz

Band	Mode	Antenna	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1 g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune- up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	1g Report SAR (W/kg)	Measured APD (W/m²)	Scaled APD (W/m²)	Meas. No.
Body																	
6G	802.11ax (HE160)	Ant.0	Back side	0	143	6185	0.08	0.113	14.63	15.00	1.089	85.23	1.173	0.144	0.688	0.879	/
			Left Edge	0	143	6185	0.08	0.055	14.63	15.00	1.089	85.23	1.173	0.070	0.385	0.492	/
			Top Edge	0	143	6185	0.08	0.445	14.63	15.00	1.089	85.23	1.173	0.568	2.830	3.615	/
			Top Edge	0	15	6025	0.08	0.441	14.25	15.00	1.189	85.23	1.173	0.615	3.110	4.338	/
			Top Edge	0	47	6185	0.08	0.506	14.52	15.00	1.117	85.23	1.173	0.663	3.290	4.311	/
			Top Edge	0	79	6345	0.08	0.488	14.53	15.00	1.114	85.23	1.173	0.638	3.210	4.195	/
			Top Edge	0	111	6505	-0.11	0.524	14.37	15.00	1.156	85.23	1.173	0.711	3.620	4.909	5#
			Top Edge	0	207	6985	-0.13	0.475	14.40	15.00	1.148	85.23	1.173	0.640	3.160	4.255	/
Note: Refer to ANNEX C for the detailed test data for each test configuration.																	

10.4Bluetooth

Mode	Antenna	Position	Dist. (mm)	Ch.	Freq. (MHz)	1 g cSAR SAR (W/kg)	10g cSAR SAR (W/kg)	Power Drift (dB)	1 g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	1g Report SAR (W/kg)	Meas. No.
Body																
3-DH5	Ant.0	Back side	0	78	2480	0.065	0.026	0.17	0.065	12.03	12.50	1.114	73.78	1.355	0.098	/
		Left Edge	0	78	2480	0.040	0.017	0.19	0.040	12.03	12.50	1.114	73.78	1.355	0.060	/
		Top Edge	0	78	2480	0.228	0.093	0.05	0.152	12.03	12.50	1.114	73.78	1.355	0.229	/
		Top Edge	0	0	2402	0.244	0.107	0.15	0.168	11.94	12.50	1.138	73.78	1.355	0.259	6#
		Top Edge	0	39	2441	0.083	0.036	0.11	0.144	11.88	12.50	1.153	73.78	1.355	0.225	/
Note: Refer to ANNEX C for the detailed test data for each test configuration.																

11 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
2. When the highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 , or when the original or repeated measurement is ≥ 1.45 W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 , and the original, first or second repeated measurement is ≥ 1.5 W/kg, perform a third repeated measurement.

Frequency Band (MHz)	Wireless Band	RF Exposure Conditions	Test Position	Highest Measured SAR (W/kg)	Repeated SAR (Yes/No)	Repeated ^{1st} Measured SAR (W/kg)	Largest to Smallest SAR Radio
5290	WIFI 5GHz	Body	Top Edge	0.879	Yes	0.852	1.03

Note: The ratio of largest to smallest SAR for the original and first repeated measurements is < 1.20 , the second repeated measurement. is not required.

12 SIMULTANEOUS TRANSMISSION

Note: This product has only one antenna, so simultaneous transmission evaluation is not required in this report.

13 TEST EQUIPMENTS LIST

Description	Manufacturer	Model	Serial No./Version	Cal. Date	Cal. Due
PC	Dell	N/A	N/A	N/A	N/A
Test Software	Speag	DASY8	16.2.2.1588	N/A	N/A
2450MHz Validation Dipole	Speag	D2450V2	SN: 952	2024/05/07	2027/05/06
5GHz Validation Dipole	Speag	D5GHzV2	SN: 1200	2024/05/09	2027/05/08
6.5GHz Validation Dipole	Speag	D6.5GHzV2	SN: 1037	2024/05/28	2027/05/27
Data Acquisition Electronicsr	Speag	DAE4	SN: 1711	2024/03/18	2025/03/17
E-Field Probe	Speag	EX3DV4	SN: 7893	2024/09/05	2025/09/04
Signal Generator	R&S	SMB100A	177746	2024/04/24	2025/04/23
Power Meter	R&S	NRVD-B2	835843/014	2024/08/08	2025/08/07
Power Sensor	R&S	NRV-Z4	100381	2024/08/08	2025/08/07
Power Sensor	R&S	NRV-Z2	100211	2024/08/08	2025/08/07
Network Analyzer	Agilent	E5071C	MY46103472	2024/09/11	2025/09/10
Thermometer	Elitech	RC-4HC	EF7239002655	2024/10/31	2025/10/30
Thermometer	Elitech	RC-4HC	EF7216002974	2024/10/31	2025/10/30
Power Amplifier	Mini-Circuits	ZVA-183W-S+	932502132	N/A	N/A
Dielectric Probe Kit	Speag	DAK3.5	SN: 1312	N/A	N/A
Phantom	Speag	ELI V8.0	SN: 2159	N/A	N/A
Attenuator	COM-MW	ZA-S1-31	1305003187	N/A	N/A
Directional coupler	AA-MCS	AAMCS-UDC	000272	N/A	N/A

Note: For dipole antennas, BALUN has adopted 3 years as calibration intervals, and on annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

1. There is no physical damage on the dipole;
2. System validation with specific dipole is within 10% of calibrated value;
3. Return-loss in within 20% of calibrated measurement.
4. Impedance (real or imaginary parts) in within 5 Ohms of calibrated measurement.

ANNEX A SIMULATING LIQUID VERIFICATION RESULT

The dielectric parameters of the liquids were verified prior to the SAR evaluation using a DAK3.5 Dielectric Probe Kit.

Date	Liquid Type	Fre. (MHz)	Temp. (°C)	Meas. Conductivity (σ) (S/m)	Meas. Permittivity (ϵ)	Target Conductivity (σ) (S/m)	Target Permittivity (ϵ)	Conductivity Tolerance (%)	Permittivity Tolerance (%)
2024.11.24	Head	2450	21.1	1.81	39.58	1.80	39.20	0.56	0.97
2024.11.24	Head	5250	21.1	4.70	35.83	4.71	35.93	-0.21	-0.28
2024.11.24	Head	5600	21.1	5.06	35.17	5.07	35.53	-0.20	-1.01
2024.11.24	Head	5750	21.1	5.17	35.48	5.22	35.36	-0.96	0.34
2024.11.25	Head	6500	21.4	5.98	34.81	6.07	34.46	-1.48	1.02
Note: The tolerance limit of Conductivity and Permittivity is $\pm 5\%$.									

ANNEX B SYSTEM CHECK RESULT

Comparing to the original SAR value provided by SPEAG, the validation data should be within its specification of 10 % (for 1 g).

Date	Liquid Type	Freq. (MHz)	Power (mW)	Measured SAR (W/kg)	Normalized SAR (W/kg)	Dipole SAR (W/kg)	Tolerance (%)
2024.11.24	Head	2450	100	5.35	53.50	52.60	1.71
2024.11.24	Head	5250	100	7.32	73.20	77.70	-5.79
2024.11.24	Head	5600	100	8.23	82.30	81.30	1.23
2024.11.24	Head	5750	100	7.69	76.90	77.60	-0.90
2024.11.25	Head	6500	100	29.10	291.00	299.00	-2.68
Note: The tolerance limit of System validation $\pm 10\%$.							

System Performance Check Data (2450MHz)

Exposure Conditions

Phantom	Position,	Band	Group,	Frequency	Conversion	TSL	TSL	Ambient	Liquid
Section, TSL	Test		UID	[MHz],	Factor	Conductivity	Permittivity	Temperatur	Temperatur
	Distance			Channel		[S/m]		e	e
	[mm]			Number				[°C]	[°C]
Flat,		D2450	CW,	2450.0,	6.98	1.81	39.6	22.1	21.1
HSL			0--	2450					


Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-11-24	EX3DV4 - SN7893, 2024-09-05	DAE4 Sn1711, 2024-03-18

Scan Setup

Measurement Results

	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	80.0 x 80.0	30.0 x 30.0 x 30.0	Date	2024-11-24	2024-11-24
Grid Steps [mm]	8.0 x 10.0	5.0 x 5.0 x 1.5	psSAR1g [W/kg]	5.32	5.35
Sensor Surface	3.0	1.4	psSAR10g [W/kg]	2.29	2.34
[mm]			Power Drift [dB]	0.03	0.13
Graded Grid	Yes	Yes	Power Scaling	Disabled	Disabled
Grading Ratio	1.5	1.5	Scaling Factor		
MAIA	N/A	N/A	[dB]		
Surface Detection	All points	All points	TSL Correction	No correction	No correction
Scan Method	Measured	Measured	M2/M1 [%]		80.1
			Dist 3dB Peak		8.5
			[mm]		



System Performance Check Data (5250MHz)

Exposure Conditions

Phantom	Position,	Band	Group,	Frequency	Conversion	TSL	TSL	Ambient	Liquid
Section, TSL	Test		UID	[MHz],	Factor	Conductivity	Permittivity	Temperatur	Temperatur
	Distance			Channel		[S/m]		e	e
	[mm]			Number				[°C]	[°C]
Flat,		D5GHz	CW,	5250.0,	5.44	4.70	35.8	22.1	21.1
HSL			0--	5250					


Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-11-24	EX3DV4 - SN7893, 2024-09-05	DAE4 Sn1711, 2024-03-18

Scan Setup

Measurement Results

	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	80.0 x 80.0	22.0 x 22.0 x 22.0	Date	2024-11-24	2024-11-24
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4	psSAR1g [W/kg]	6.52	7.32
Sensor Surface	3.0	1.4	psSAR10g [W/kg]	1.96	2.16
[mm]			Power Drift [dB]	0.11	-0.12
Graded Grid	Yes	Yes	Power Scaling	Disabled	Disabled
Grading Ratio	1.5	1.4	Scaling Factor		
MAIA	N/A	N/A	[dB]		
Surface Detection	All points	All points	TSL Correction	No correction	No correction
Scan Method	Measured	Measured	M2/M1 [%]		64.8
			Dist 3dB Peak		7.4
			[mm]		



System Performance Check Data (5600MHz)

Exposure Conditions

Phantom	Position,	Band	Group,	Frequency	Conversion	TSL	TSL	Ambient	Liquid
Section, TSL	Test		UID	[MHz],	Factor	Conductivity	Permittivity	Temperatur	Temperatur
	Distance			Channel		[S/m]		e	e
	[mm]			Number				[°C]	[°C]
Flat,		D5GHz	CW,	5600.0,	4.91	5.06	35.2	22.1	21.1
HSL			0--	5600					


Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-11-24	EX3DV4 - SN7893, 2024-09-05	DAE4 Sn1711, 2024-03-18

Scan Setup

Measurement Results

	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	80.0 x 80.0	22.0 x 22.0 x 22.0	Date	2024-11-24	2024-11-24
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4	psSAR1g [W/kg]	8.05	8.23
Sensor Surface	3.0	1.4	psSAR10g [W/kg]	2.26	2.38
[mm]			Power Drift [dB]	-0.11	0.17
Graded Grid	Yes	Yes	Power Scaling	Disabled	Disabled
Grading Ratio	1.5	1.4	Scaling Factor		
MAIA	N/A	N/A	[dB]		
Surface Detection	All points	All points	TSL Correction	No correction	No correction
Scan Method	Measured	Measured	M2/M1 [%]		62.6
			Dist 3dB Peak		7.3
			[mm]		



System Performance Check Data (5750MHz)

Exposure Conditions

Phantom	Position,	Band	Group,	Frequency	Conversion	TSL	TSL	Ambient	Liquid
Section, TSL	Test		UID	[MHz],	Factor	Conductivity	Permittivity	Temperatur	Temperatur
	Distance			Channel		[S/m]		e	e
	[mm]			Number				[°C]	[°C]
Flat,		D5GHz	CW,	5750.0,	4.98	5.17	35.5	22.1	21.1
HSL			0--	5750					


Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-11-24	EX3DV4 - SN7893, 2024-09-05	DAE4 Sn1711, 2024-03-18

Scan Setup

Measurement Results

	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	80.0 x 80.0	22.0 x 22.0 x 22.0	Date	2024-11-24	2024-11-24
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4	psSAR1g [W/kg]	7.74	7.69
Sensor Surface	3.0	1.4	psSAR10g [W/kg]	2.07	2.13
[mm]			Power Drift [dB]	-0.06	0.03
Graded Grid	Yes	Yes	Power Scaling	Disabled	Disabled
Grading Ratio	1.5	1.4	Scaling Factor		
MAIA	N/A	N/A	[dB]		
Surface Detection	All points	All points	TSL Correction	No correction	No correction
Scan Method	Measured	Measured	M2/M1 [%]		61.7
			Dist 3dB Peak		8.3
			[mm]		



System Performance Check Data (6500MHz)

Exposure Conditions

Phantom	Position, Section, TSL	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature [°C]	Liquid Temperature [°C]
Flat, HSL		D6.5GHz	CW, 0--	6500.0, 6500	5.11	5.98	34.8	22.3	21.4


Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-11-25	EX3DV4 - SN7893, 2024-09-05	DAE4 Sn1711, 2024-03-18

Scan Setup

Measurement Results

	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	85.0 x 85.0	22.0 x 22.0 x 22.0	Date	2024-11-25	2024-11-25
Grid Steps [mm]	8.5 x 8.5	3.4 x 3.4 x 1.4	psSAR1g [W/kg]	29.7	29.1
Sensor Surface [mm]	3.0	1.4	psSAR10g [W/kg]	5.09	5.35
Graded Grid	Yes	Yes	APD 4cm ² [W/m ²]		132
Grading Ratio	1.5	1.4	Power Drift [dB]	0.07	-0.01
MAIA	N/A	N/A	Power Scaling	Disabled	Disabled
Surface Detection	All points	All points	Scaling Factor		
Scan Method	Measured	Measured	[dB]		
			TSL Correction	No correction	No correction
			M2/M1 [%]		49.3
			Dist 3dB Peak [mm]		4.6



ANNEX C TEST DATA

Meas.1 Body Plane with Top Edge 0mm on 1 Channel in IEEE802.11b mode with Antenna 0

Exposure Conditions

Phantom	Position	Band	Group	Frequency [MHz]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature [°C]	Liquid Temperature [°C]
Section, TSL	Test Distance [mm]		UID	Channel Number					
Flat, HSL	EDGE TOP, 0.00	WLAN 2.4GHz	WLAN 10012-CAB	2412.0, 1	6.98	1.76	39.8	22.1	21.1

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-11-24	EX3DV4 - SN7893, 2024-09-05	DAE4 Sn1711, 2024-03-18

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 120.0	30.0 x 30.0 x 30.0
Grid Steps [mm]	12.0 x 12.0	5.0 x 5.0 x 5.0
Sensor Surface [mm]	3.0	1.4
Graded Grid	Yes	Yes
Grading Ratio	1.5	1.5
MAIA	N/A	N/A
Surface	VMS + 6p	VMS + 6p
Detection		
Scan Method	Measured	Measured

Measurement Results

	Area Scan	Zoom Scan
Date	2024-11-24	2024-11-24
psSAR1g [W/kg]	0.584	0.699
psSAR10g [W/kg]	0.270	0.324
Power Drift [dB]	-0.07	-0.05
Power Scaling	Disabled	Disabled
Scaling Factor [dB]		
TSL Correction	No correction	No correction
M2/M1 [%]		51.0
Dist 3dB Peak [mm]		8.1



Meas.2 Body Plane with Top Edge 0mm on 58 Channel in IEEE802.11ac80 mode with Antenna 0

Exposure Conditions

Phantom	Position	Band	Group	Frequency	Conversion Factor	TSL Conductivity	TSL Permittivity	Ambient Temperature	Liquid Temperature
Section, TSL	Distance [mm]		UID	Channel Number		[S/m]		[°C]	[°C]
Flat, HSL	EDGE TOP, 0.00	WLAN, N 5GHz	WLAN, 10544-AAD	5290.0, 58	5.44	4.79	35.3	22.1	21.1

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-11-24	EX3DV4 - SN7893, 2024-09-05	DAE4 Sn1711, 2024-03-18

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 120.0	24.0 x 24.0 x 22.0
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 2.0
Sensor Surface [mm]	3.0	1.4
Graded Grid	Yes	Yes
Grading Ratio	1.5	1.4
MAIA	Y	N/A
Surface Detection	VMS + 6p	VMS + 6p
Scan Method	Measured	Measured

Measurement Results

	Area Scan	Zoom Scan
Date	2024-11-24	2024-11-24
psSAR1g [W/kg]	0.701	0.879
psSAR10g [W/kg]	0.235	0.265
Power Drift [dB]	0.11	-0.09
Power Scaling	Disabled	Disabled
Scaling Factor [dB]		
TSL Correction	No correction	No correction
M2/M1 [%]		53.1
Dist 3dB Peak [mm]		6.4



Meas.3 Body Plane with Top Edge 0mm on 114 Channel in IEEE802.11ac160 mode with Antenna 0

Exposure Conditions

Phantom	Position	Band	Group	Frequency [MHz]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature	Liquid Temperature
Section, TSL	Distance [mm]		UID	Channel Number				[°C]	[°C]
Flat, HSL	EDGE TOP, 0.00	WLAN, N 5GHz	WLAN, 10554-AAD	5530.0, 114	4.91	4.95	36.0	22.1	21.1

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-11-24	EX3DV4 - SN7893, 2024-09-05	DAE4 Sn1711, 2024-03-18

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 120.0	24.0 x 24.0 x 22.0
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 2.0
Sensor Surface [mm]	3.0	1.4
Graded Grid	Yes	Yes
Grading Ratio	1.5	1.4
MAIA	Y	N/A
Surface	VMS + 6p	VMS + 6p
Detection		
Scan Method	Measured	Measured

Measurement Results

	Area Scan	Zoom Scan
Date	2024-11-24	2024-11-24
psSAR1g [W/kg]	0.599	0.777
psSAR10g [W/kg]	0.199	0.231
Power Drift [dB]	0.09	0.03
Power Scaling	Disabled	Disabled
Scaling Factor [dB]		
TSL Correction	No correction	No correction
M2/M1 [%]		50.8
Dist 3dB Peak [mm]		6.4



Meas.4 Body Plane with Top Edge 0mm on 155 Channel in IEEE802.11ac80 mode with Antenna 0

Exposure Conditions

Phantom	Position	Band	Group	Frequency [MHz],	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature	Liquid Temperature
Section, TSL	Distance [mm]		UID	Channel Number				[°C]	[°C]
Flat, HSL	EDGE TOP, 0.00	WLAN, N 5GHz	WLAN, 10544-AAD	5775.0, 155	4.98	5.22	35.2	22.1	21.1

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-11-24	EX3DV4 - SN7893, 2024-09-05	DAE4 Sn1711, 2024-03-18

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 120.0	24.0 x 24.0 x 22.0
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 2.0
Sensor Surface [mm]	3.0	1.4
Graded Grid	Yes	Yes
Grading Ratio	1.5	1.4
MAIA	Y	N/A
Surface	VMS + 6p	VMS + 6p
Detection		
Scan Method	Measured	Measured

Measurement Results

	Area Scan	Zoom Scan
Date	2024-11-24	2024-11-24
psSAR1g [W/kg]	0.642	0.759
psSAR10g [W/kg]	0.224	0.246
Power Drift [dB]	0.03	-0.17
Power Scaling	Disabled	Disabled
Scaling Factor [dB]		
TSL Correction	No correction	No correction
M2/M1 [%]		48.5
Dist 3dB Peak [mm]		6.6



Meas.5 Body Plane with Top Edge 0mm on 111 Channel in IEEE802.11ax160 mode with Antenna 0

Exposure Conditions

Phantom	Position	Band	Group	Frequency [MHz],	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature	Liquid Temperature
Section,	Distance		UID	Channel				°C	°C
TSL	Distance [mm]			Number					
Flat,	EDGE	U-	WLAN,	6505.0,	5.11	6.15	34.6	22.3	21.4
HSL	TOP,	NII-6	10755-	111					
	0.00		AAC						

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-11-25	EX3DV4 - SN7893, 2024-09-05	DAE4 Sn1711, 2024-03-18

Scan Setup

	Area Scan	Zoom Scan
Grid Extents	136.0 x 136.0	22.0 x 22.0 x 22.0
[mm]		
Grid Steps [mm]	8.5 x 8.5	3.4 x 3.4 x 1.4
Sensor Surface	3.0	1.4
[mm]		
Graded Grid	Yes	Yes
Grading Ratio	1.5	1.4
MAIA	Y	N/A
Surface	All points	All points
Detection		
Scan Method	Measured	Measured

Measurement Results

	Area Scan	Zoom Scan
Date	2024-11-25	2024-11-25
psSAR1g	0.491	0.524
[W/kg]		
psSAR10g	0.146	0.154
[W/kg]		
APD 4cm ²		3.62
[W/m ²]		
Power Drift [dB]	-0.07	-0.11
Power Scaling	Disabled	Disabled
Scaling Factor		
[dB]		
TSL Correction	No correction	No correction
M2/M1 [%]		50.2
Dist 3dB Peak		5.5
[mm]		



Meas.6 Body Plane with Top Edge 0mm on 0 Channel in Bluetooth mode with Antenna 0

Exposure Conditions

Phantom	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature [°C]	Liquid Temperature
Flat, HSL	EDGE TOP, 0.00	ISM 2.4 GHz Band	Bluetooth, 10038-CAA	2402.0, 0	6.98	1.75	39.9	22.1	21.1

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-11-24	EX3DV4 - SN7893, 2024-09-05	DAE4 Sn1711, 2024-03-18

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 120.0	30.0 x 30.0 x 30.0
Grid Steps [mm]	12.0 x 12.0	5.0 x 5.0 x 5.0
Sensor Surface [mm]	3.0	1.4
Graded Grid	Yes	Yes
Grading Ratio	1.5	1.5
MAIA	Y	Y
Surface	VMS + 6p	VMS + 6p
Detection		
Scan Method	Measured	Measured

Measurement Results

	Area Scan	Zoom Scan
Date	2024-11-24	2024-11-24
psSAR1g [W/kg]	0.158	0.168
psSAR10g [W/kg]	0.071	0.077
Power Drift [dB]	0.12	0.15
Power Scaling	Disabled	Disabled
Scaling Factor [dB]		
TSL Correction	No correction	No correction
M2/M1 [%]		50.3
Dist 3dB Peak [mm]		8.1



ANNEX D EUT EXTERNAL PHOTOS

Please refer the document “BL-SH2490675-AW.pdf”.

ANNEX E SAR TEST SETUP PHOTOS

Please refer the document “BL-SH2490675-AS-1.pdf”.

ANNEX F CALIBRATION REPORT

Please refer the document “BL-SH2490675-AC-1.pdf”.

ANNEX G TUNE-UP PROCEDURE

Please refer the document “BL-SH2490675-AT.pdf”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--