

## FCC ID: 2BMTF-Z10

### Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $<$  5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
802.11b	2.412	6.85	4.84	6 $\pm$ 1	7.00	5.01	<5	1.55675	3.00	YES
802.11g	2.462	6.31	4.28	6 $\pm$ 1	7.00	5.01	<5	1.57280	3.00	YES
802.11n2 0	2.437	4.75	2.99	4 $\pm$ 1	5.00	3.16	<5	0.98732	3.00	YES
802.11n4 0	2.452	3.99	2.51	4 $\pm$ 1	5.00	3.16	<5	0.99035	3.00	YES

### Conclusion:

For the max result :  $1.57280 < 3$ , the SAR testing is not required.