


TEST REPORT

Application No.: BTEK241216075A01-T01
Applicant: Tianyin Technology (Huizhou) Co., Ltd.
Address of Applicant: Room 1413, V1 BLDG, Zhongliang V city, Renmin 6th, Rd., Danshui, Huiyang, Huizhou, Guangdong, China
Manufacturer: Tianyin Technology (Huizhou) Co., Ltd.
Address of Manufacturer: Room 1413, V1 BLDG, Zhongliang V city, Renmin 6th, Rd., Danshui, Huiyang, Huizhou, Guangdong, China
Equipment Under Test (EUT):
EUT Name: GUITAR AMPLIFIER
Test Model.: EG10PRO
Adding Model(s): EG10
Trade Mark: SKYSONIC
FCC ID: 2BMU7-EG10PRO
Standard(s) : 47 CFR Part 2 Subpart J Section 2.1093
447498 D01 General RF Exposure Guidance v06
Date of Receipt Sample(s): 2024-12-17
Date of Test: 2024-12-18 to 2024-12-28
Date of Issue: 2024-12-30

Test Result:**Pass***


* In the configuration tested, the EUT complied with the standards specified above.



Lion Cai/ Approved & Authorized
EMC Laboratory Manager



Revision Record			
Version	Issue Date	Revisions	Remarks
V0	2024-12-30	Initial	Valid

Authorized for issue by:			
			
		Karl Liu / File Editor	
			
		June Li/Reviewer	

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.



2 Contents

	Page
1 Cover Page	1
2 Contents	3
3 General Information	4
3.1 Details of E.U.T.	4
3.2 Description of Support Units	4
3.3 Test Location	4
3.4 Deviation from Standards	4
3.5 Abnormalities from Standard Conditions	4
4 Test Requirement	5
4.1 Assessment Result	5



3 General Information

3.1 Details of E.U.T.

Power supply:	Charge:USB-C DC5V Rated power:10W Battery:7.4V/3000mAh
BLE	
Frequency Range:	2402MHz to 2480MHz
Bluetooth Version:	V5.0
Modulation Type:	GFSK
Number of Channels:	40
Antenna Type:	PCB Antenna
Antenna Gain:	0dBi
BT	
Frequency Range:	2402MHz to 2480MHz
Bluetooth Version:	V5.0
Modulation Type:	GFSK, $\pi/4$ DQPSK,8DPSK
Number of Channels:	79
Channel Spacing:	1MHz
Antenna Type:	PCB Antenna
Antenna Gain:	0dBi
Sample No.:	BTEK241216075A01-1-1/1
Model(s) Difference Statement	☐ Singel Model.
	☒ Multi-Models:EG10PRO, EG10 Only the model EG10PRO was tested. According to the declaration from the applicant, the electrical circuit design, layout, components used, internal wiring and functions of other models are identical for the above models, with only difference on Model No

3.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
/	/	/	/

3.3 Test Location

All tests were performed at:
Shenzhen BANTEK Testing Co., Ltd.,
A5&A6, Building B1&B2, No.45 Gangtou Road, Bogang Community, Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518103
Tel:0755-2334 4200 Fax: 0755-2334 4200
FCC Registration Number: 264293
Designation Number: CN1356
No tests were sub-contracted.

3.4 Deviation from Standards

None

3.5 Abnormalities from Standard Conditions

None



4 Test Requirement

KDB447498 D01 General RF Exposure Guidance v06, Clause 4.3.1(b)

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$

Where

-f(GHz) is the RF channel transmit frequency in GHz

-Power and distance are rounded to the nearest mW and mm before calculation

-The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

4.1 Assessment Result

☒ Passed ☐ Not Applicable

Type	Frequency (MHz)	Conducted Power (dBm)	Maximum Tune-up (dBm)	Calculating data	Limit	Result
BLE	2402	2.08	2.5	0.55	3.0	Pass
BT-3DH5	2402	5.83	6	1.23	3.0	Pass

Note: The exposure evaluation safety distance is 5mm.

- End of the Report -

