

FCC RF Exposure

EUT Description: WIRELESS VERTICAL MOUSE

Model No.: xlx-800

Series Model: N/A

FCC ID: 2BMVN-XLX-800

Equipment type: Portable Device

1. Test Procedure

According to KDB 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}$$

where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation. The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6GHz.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

2. Test Result of RF Exposure Evaluation

2.4G

$EIRP = E_{\text{Meas}} + 20 \log(d_{\text{meas}}) - 104.7$

EIRP is the equivalent isotropically radiated power,

E_{Meas} in dBm is the field strength of the emission at the measurement distance, in dB uV/m

d_{meas} is the measurement distance, in m

Field strength(dBuV/m)	EIRP(dBm)	(mW)	Frequency(MHz)	Min. distance(mm)	Calc. thresholds	limit
95.41	0.21	1.050	2408	5	0.3258	3.0
93.94	-1.26	0.748	2440	5	0.2336	3.0
96.75	1.55	1.428	2474	5	0.4497	3.0

Conclusion: No SAR required