



Shenzhen GUOREN Certification Technology Service Co., Ltd.

101#, Building K & Building T, The Second Industrial Zone, Jiazitang Community,  
Fenghuang Street, Guangming District, Shenzhen, China

## FCC PART 15 SUBPART C TEST REPORT

### FCC PART 15.247

Report Reference No.....: GRCTR250202016-01

FCC ID.....: 2BN2Y-5V2835

Compiled by

( position+printed name+signature)..: Testing Engineer Jimmy Wang

Supervised by

( position+printed name+signature)..: Project Engineer Kelley Zhang

Approved by

( position+printed name+signature)..: Manager Sam Wang

Date of issue.....: Mar. 04, 2025

Testing Laboratory Name.....: Shenzhen GUOREN Certification Technology Service Co., Ltd.

Address.....: 101#, Building K & Building T, The Second Industrial Zone, Jiazitang Community, Fenghuang Street, Guangming District, Shenzhen, China

Applicant's name.....: Shenzhen Tongjie E-commerce Co., Ltd

Address.....: A701, Niulanqian Building, Minzhi Avenue, Xinniu Community, Minzhi Street Longhua District, Shenzhen

Test specification.....:

Standard.....: FCC Part 15.247

**Shenzhen GUOREN Certification Technology Service Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen GUOREN Certification Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen GUOREN Certification Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description.....: LED Strip Controller

Trade Mark.....: Acosh Neon

Manufacturer.....: Shenzhenhaiyang Photoelectric

Model/Type reference.....: 5V-2835-60

Listed Models .....: 5050-24V-60,5V-5050-30,12V-5050-30,12V-5050-60,12V-2835-60,24V-5050-30,24V-5050-60,5V-3528-30,5V-3528-60,12V-3528-30,12V-3528-60,24V-3528-30,24V-3528-60,TJDZ8051-SHUANGS,TJDZ8051-DUOS,TJDZ8051-HUANC,TJDZ8051-YINY,TJDZ8051-DANS,TJDZ8051-JIANB-DUOS,TJDZ8051-JIANB-HUANC,TJDZ8051-JIANB-YINY,TJDZ8051-JIANB-DANS,TJDZ8051-JIANB-SHUANGS,TJDZ1341-D,TJDZ1341-S,TJDZ1341-Y,TJDZ1341-H,TJDZ1341-R,TJDZ1341-C,TJDZ1341-M,TJDZ1341-H

Firmware Version.....: V1.0

Hardware Version.....: V1.0

Modulation .....: GFSK

Frequency.....: From 2402MHz to 2480MHz

Ratings.....: DC 5V From External Circuit

Result.....: PASS

TEST REPORT

Equipment under Test : LED Strip Controller

Model /Type : 5V-2835-60

Listed Models : 5050-24V-60,5V-5050-30,12V-5050-30,12V-5050-60,12V-2835-60,24V-5050-30,24V-5050-60,5V-3528-30,5V-3528-60,12V-3528-30,12V-3528-60,24V-3528-30,24V-3528-60,TJDZ8051-SHUANGS, TJDZ8051-DUOS,TJDZ8051-HUANC,TJDZ8051-YINY,TJDZ8051-DANS,TJDZ8051-JIANB-DUOS,TJDZ8051-JIANB-HUANC, TJDZ8051-JIANB-YINY,TJDZ8051-JIANB-DANS,TJDZ8051-JIANB-SHUANGS,TJDZ1341-D,TJDZ1341-S,TJDZ1341-Y,TJDZ1341-H,TJDZ1341-R,TJDZ1341-C,TJDZ1341-M,TJDZ1341-H

**Applicant** : **Shenzhen Tongjie E-commerce Co., Ltd**

Address : A701, Niulanqian Building, Minzhi Avenue, Xinniu Community, Minzhi Street LonghuaDistrict, Shenzhen

**Manufacturer** : **Shenzhenhaiyang Photoelectric**

Address : Second Lane,Zhuanchang New Village,Shiyan Street,Baoan

|              |      |
|--------------|------|
| Test Result: | PASS |
|--------------|------|

The test report merely corresponds to the test sample.  
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## Contents

|                                                               |           |
|---------------------------------------------------------------|-----------|
| <b>1 TEST STANDARDS .....</b>                                 | <b>4</b>  |
| <b>2 SUMMARY .....</b>                                        | <b>5</b>  |
| 2.1 General Remarks .....                                     | 5         |
| 2.2 Product Description .....                                 | 5         |
| 2.3 Equipment Under Test .....                                | 5         |
| 2.4 Short description of the Equipment under Test (EUT) ..... | 5         |
| 2.5 EUT operation mode .....                                  | 6         |
| 2.6 Block Diagram of Test Setup .....                         | 6         |
| 2.7 Related Submittal(s) / Grant (s) .....                    | 6         |
| 2.8 Modifications .....                                       | 6         |
| <b>3 TEST ENVIRONMENT .....</b>                               | <b>7</b>  |
| 3.1 Address of the test laboratory .....                      | 7         |
| 3.2 Test Facility .....                                       | 7         |
| 3.3 Environmental conditions .....                            | 7         |
| 3.4 Summary of measurement results .....                      | 8         |
| 3.5 Statement of the measurement uncertainty .....            | 8         |
| 3.6 Equipments Used during the Test .....                     | 9         |
| <b>4 TEST CONDITIONS AND RESULTS .....</b>                    | <b>10</b> |
| 4.1 AC Power Conducted Emission .....                         | 10        |
| 4.2 Radiated Emissions and Band Edge .....                    | 13        |
| 4.3 Maximum Peak Output Power .....                           | 19        |
| 4.4 Power Spectral Density .....                              | 20        |
| 4.5 6dB Bandwidth .....                                       | 22        |
| 4.6 Out-of-band Emissions .....                               | 24        |
| 4.7 Antenna Requirement .....                                 | 28        |
| <b>5 TEST SETUP PHOTOS OF THE EUT .....</b>                   | <b>29</b> |
| <b>6 PHOTOS OF THE EUT .....</b>                              | <b>30</b> |

## **1 TEST STANDARDS**

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10-2020](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB558074 D01 V05r02](#): Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247

## 2 SUMMARY

### 2.1 General Remarks

|                                |   |               |
|--------------------------------|---|---------------|
| Date of receipt of test sample | : | Feb. 18, 2025 |
| Testing commenced on           | : | Feb. 18, 2025 |
| Testing concluded on           | : | Mar. 04, 2025 |

### 2.2 Product Description

|                                                                                                                                                                                                                                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Name:                                                                                                                                                                                                                                         | LED Strip Controller                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Model/Type reference:                                                                                                                                                                                                                                 | 5V-2835-60                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Listed Models:                                                                                                                                                                                                                                        | 5050-24V-60,5V-5050-30,12V-5050-30,12V-5050-60,12V-2835-60,24V-5050-30,24V-5050-60,5V-3528-30,5V-3528-60,12V-3528-30,12V-3528-60,24V-3528-30,24V-3528-60,TJDZ8051-SHUANGS, TJDZ8051-DUOS,TJDZ8051-HUANC, TJDZ8051-YINY,TJDZ8051-DANS,TJDZ8051-JIANB-DUOS,TJDZ8051-JIANB-HUANC, TJDZ8051-JIANB-YINY,TJDZ8051-JIANB-DANS,TJDZ8051-JIANB-SHUANGS,TJDZ1341-D,TJDZ1341-S,TJDZ1341-Y,TJDZ1341-H,TJDZ1341-R,TJDZ1341-C,TJDZ1341-M,TJDZ1341-H |
| Power supply:                                                                                                                                                                                                                                         | DC 5V From External Circuit                                                                                                                                                                                                                                                                                                                                                                                                           |
| Testing sample ID:                                                                                                                                                                                                                                    | GRCTR250202016-1# (Engineer sample),<br>GRCTR250202016-2# (Normal sample)                                                                                                                                                                                                                                                                                                                                                             |
| <b>Bluetooth</b>                                                                                                                                                                                                                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Supported type:                                                                                                                                                                                                                                       | Bluetooth low Energy                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Modulation:                                                                                                                                                                                                                                           | GFSK                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Operation frequency:                                                                                                                                                                                                                                  | 2402MHz to 2480MHz                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Channel number:                                                                                                                                                                                                                                       | 40                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Channel separation:                                                                                                                                                                                                                                   | 2 MHz                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Antenna type:                                                                                                                                                                                                                                         | PCB antenna                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Antenna gain*(Supplied by the customer):                                                                                                                                                                                                              | 0.43 dBi                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Remark:*When the information provided by the customer was used to calculate test results, if the information provided by the customer is not accurate, shenzhen GUOREN Certification Technology Service Co., Ltd. does not assume any responsibility. |                                                                                                                                                                                                                                                                                                                                                                                                                                       |

### 2.3 Equipment Under Test

#### Power supply system utilised

|                      |   |                                                                   |                                   |
|----------------------|---|-------------------------------------------------------------------|-----------------------------------|
| Power supply voltage | : | <input type="radio"/> 230V / 50 Hz                                | <input type="radio"/> 120V / 60Hz |
|                      |   | <input type="radio"/> 12 V DC                                     | <input type="radio"/> 24 V DC     |
|                      |   | <input checked="" type="radio"/> Other (specified in blank below) |                                   |

DC 5 V From External Circuit

### 2.4 Short description of the Equipment under Test (EUT)

This is a LED Strip Controller.  
For more details, refer to the user's manual of the EUT.


## 2.5 EUT operation mode

The Applicant provides communication tools software(SecureCRT) to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing .There are 40 channels provided to the EUT and Channel 00/19/39 were selected to test.

### Operation Frequency:

| Channel   | Frequency (MHz) |
|-----------|-----------------|
| <b>00</b> | <b>2402</b>     |
| 01        | 2404            |
| 02        | 2406            |
| :         | :               |
| <b>19</b> | <b>2440</b>     |
| :         | :               |
| 37        | 2476            |
| 38        | 2478            |
| <b>39</b> | <b>2480</b>     |

## 2.6 Block Diagram of Test Setup



## 2.7 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for the device filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

## 2.8 Modifications

No modifications were implemented to meet testing criteria.

### **3 TEST ENVIRONMENT**

#### **3.1 Address of the test laboratory**

**Shenzhen GUOREN Certification Technology Service Co., Ltd.**

101#, Building K & Building T, The Second Industrial Zone, Jiazitang Community, Fenghuang Street, Guangming District, Shenzhen, China

#### **3.2 Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

**FCC-Registration No.: 920798    Designation Number: CN1304**

Shenzhen GUOREN Certification Technology Service Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

**A2LA-Lab Cert. No.: 6202.01**

Shenzhen GUOREN Certification Technology Service Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

**ISED#: 27264    CAB identifier: CN0115**

Shenzhen GUOREN Certification Technology Service Co., Ltd. has been listed by Innovation, Science and Economic Development Canada to perform electromagnetic emission measurement.

**CNAS-Lab Code: L15631**

Shenzhen GUOREN Certification Technology Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories for the Competence of Testing and Calibration Laboratories.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.

#### **3.3 Environmental conditions**

During the measurement the environmental conditions were within the listed ranges:

|                    |              |
|--------------------|--------------|
| Normal Temperature | 15-35 °C     |
| Relative Humidity  | 30-60 %      |
| Air Pressure       | 950-1050mbar |

### 3.4 Summary of measurement results

| Test Specification clause | Test case                                    | Test Mode | Test Channel                                                                                                                            | Recorded In Report |                                                                                                                                         | Test result |
|---------------------------|----------------------------------------------|-----------|-----------------------------------------------------------------------------------------------------------------------------------------|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------|-------------|
| §15.247(e)                | Power spectral density                       | GFSK      | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | GFSK               | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | complies    |
| §15.247(a)(2)             | Spectrum bandwidth<br>– 6 dB bandwidth       | GFSK      | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | GFSK               | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | complies    |
| §15.247(b)(3)             | Maximum output<br>Peak power                 | GFSK      | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | GFSK               | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | complies    |
| §15.247(d)                | Band edge compliance conducted               | GFSK      | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Highest                                               | GFSK               | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Highest                                               | complies    |
| §15.205                   | Band edge compliance radiated                | GFSK      | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Highest                                               | GFSK               | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Highest                                               | complies    |
| §15.247(d)                | TX spurious emissions conducted              | GFSK      | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | GFSK               | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | complies    |
| §15.247(d)                | TX spurious emissions radiated               | GFSK      | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | GFSK               | <input checked="" type="checkbox"/> Lowest<br><input checked="" type="checkbox"/> Middle<br><input checked="" type="checkbox"/> Highest | complies    |
| §15.209(a)                | TX spurious Emissions radiated<br>Below 1GHz | GFSK      | -/-                                                                                                                                     | GFSK               | -/-                                                                                                                                     | complies    |
| §15.107(a)<br>§15.207     | Conducted Emissions<br>< 30 MHz              | GFSK      | -/-                                                                                                                                     | GFSK               | -/-                                                                                                                                     | complies    |

Remark:

1. The measurement uncertainty is not included in the test result.
2. We tested all test mode and recorded worst case in report.
3. N/A means “not applicable”.

### 3.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01” Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1” and TR-100028-02 “Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 “ and is documented in the Shenzhen GUOREN Certification Technology Service Co., Ltd.quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GUOREN Certification Technology Service Co., Ltd.:

| Test                   | Range       | Measurement Uncertainty | Notes |
|------------------------|-------------|-------------------------|-------|
| Radiated Emission      | 30~1000MHz  | 4.06 dB                 | (1)   |
| Radiated Emission      | 1~18GHz     | 5.14 dB                 | (1)   |
| Radiated Emission      | 18-40GHz    | 5.38 dB                 | (1)   |
| Conducted Disturbance  | 0.15~30MHz  | 2.14 dB                 | (1)   |
| Max output power       | 30MHz~18GHz | 0.54 dB                 | (1)   |
| Power spectral density | /           | 0.56 dB                 | (1)   |
| Spectrum bandwidth     | /           | 1.2%                    | (1)   |

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.


### 3.6 Equipments Used during the Test

| Test Equipment             | Manufacturer           | Model No.   | Equipment No. | Calibration Date | Calibration Due Date |
|----------------------------|------------------------|-------------|---------------|------------------|----------------------|
| LISN                       | R&S                    | ENV216      | GRCTEE009     | 2024/09/19       | 2025/09/18           |
| LISN                       | R&S                    | ENV216      | GRCTEE010     | 2024/09/19       | 2025/09/18           |
| EMI Test Receiver          | R&S                    | ESPI        | GRCTEE017     | 2024/09/19       | 2025/09/18           |
| EMI Test Receiver          | R&S                    | ESCI        | GRCTEE008     | 2024/09/19       | 2025/09/18           |
| Spectrum Analyzer          | Agilent                | N9020A      | GRCTEE002     | 2024/09/19       | 2025/09/18           |
| Spectrum Analyzer          | R&S                    | FSP         | GRCTEE003     | 2024/09/20       | 2025/09/19           |
| Vector Signal generator    | Agilent                | N5181A      | GRCTEE007     | 2024/09/19       | 2025/09/18           |
| Analog Signal Generator    | R&S                    | SML03       | GRCTEE006     | 2024/09/19       | 2025/09/18           |
| Climate Chamber            | QIYA                   | LCD-9530    | GRCTES016     | 2024/09/19       | 2025/09/18           |
| Ultra-Broadband Antenna    | Schwarzbeck            | VULB9163    | GRCTEE018     | 2023/09/28       | 2026/09/27           |
| Horn Antenna               | Schwarzbeck            | BBHA 9120D  | GRCTEE019     | 2023/09/28       | 2026/09/27           |
| Loop Antenna               | Zhinan                 | ZN30900C    | GRCTEE020     | 2023/10/15       | 2026/10/14           |
| Horn Antenna               | Beijing Hangwei Dayang | OBH100400   | GRCTEE049     | 2023/09/28       | 2026/09/27           |
| Amplifier                  | Schwarzbeck            | BBV 9745    | GRCTEE021     | 2024/09/19       | 2025/09/18           |
| Amplifier                  | Taiwan chengyi         | EMC051845B  | GRCTEE022     | 2024/09/19       | 2025/09/18           |
| Temperature/Humidity Meter | Huaguan                | HG-308      | GRCTES037     | 2024/09/19       | 2025/09/18           |
| Directional coupler        | NARDA                  | 4226-10     | GRCTEE004     | 2024/09/19       | 2025/09/18           |
| High-Pass Filter           | XingBo                 | XBLBQ-GTA18 | GRCTEE053     | 2024/09/19       | 2025/09/18           |
| High-Pass Filter           | XingBo                 | XBLBQ-GTA27 | GRCTEE054     | 2024/09/19       | 2025/09/18           |
| Automated filter bank      | Tonscend               | JS0806-F    | GRCTEE055     | 2024/09/19       | 2025/09/18           |
| Power Sensor               | Agilent                | U2021XA     | GRCTEE070     | 2024/09/19       | 2025/09/18           |
| Cable                      | Times                  | Cable-CE    | GRCTEE086     | 2024/09/19       | 2025/09/18           |
| Cable                      | Times                  | Cable-RE-1  | GRCTEE087     | 2024/09/19       | 2025/09/18           |
| Cable                      | Times                  | Cable-RE-2  | GRCTEE088     | 2024/09/19       | 2025/09/18           |
| EMI Test Software          | ROHDE & SCHWARZ        | ESK1-V1.71  | GRCTEE060     | N/A              | N/A                  |
| EMI Test Software          | Fera                   | EZ-EMC      | GRCTEE061     | N/A              | N/A                  |

## 4 TEST CONDITIONS AND RESULTS

### 4.1 AC Power Conducted Emission

#### TEST CONFIGURATION



#### TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2020.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2020
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2020
- 4 The EUT received power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

#### AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following:

| Frequency range (MHz) | Limit (dBuV) |           |
|-----------------------|--------------|-----------|
|                       | Quasi-peak   | Average   |
| 0.15-0.5              | 66 to 56*    | 56 to 46* |
| 0.5-5                 | 56           | 46        |
| 5-30                  | 60           | 50        |

\* Decreases with the logarithm of the frequency.

#### TEST RESULTS

Remark:


1. GFSK was tested at Low, Middle, and High channel and recorded worst mode at Middle channel:
2. Both 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz power supply have been tested, only the worst result of 120 VAC, 60 Hz was reported as below:

Power supply:

DC 5V from Adapter  
AC 120V/60Hz

Polarization

L

**MEASUREMENT RESULT: "GRC250224004\_fin"**

2/24/2025 4:02PM

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.346000         | 31.30         | 9.5          | 59            | 27.8         | QP       | L1   | GND |
| 0.574000         | 36.50         | 9.6          | 56            | 19.5         | QP       | L1   | GND |
| 1.398000         | 36.00         | 10.0         | 56            | 20.0         | QP       | L1   | GND |
| 2.806000         | 31.00         | 10.0         | 56            | 25.0         | QP       | L1   | GND |
| 6.362000         | 27.00         | 10.0         | 60            | 33.0         | QP       | L1   | GND |
| 13.414000        | 22.10         | 10.0         | 60            | 37.9         | QP       | L1   | GND |

**MEASUREMENT RESULT: "GRC250224004\_fin2"**

2/24/2025 4:02PM


| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.646000         | 31.70         | 9.6          | 46            | 14.3         | AV       | L1   | GND |
| 1.066000         | 27.60         | 10.0         | 46            | 18.4         | AV       | L1   | GND |
| 2.710000         | 24.10         | 10.0         | 46            | 21.9         | AV       | L1   | GND |
| 9.198000         | 20.40         | 10.0         | 50            | 29.6         | AV       | L1   | GND |
| 13.398000        | 21.60         | 10.0         | 50            | 28.4         | AV       | L1   | GND |
| 25.398000        | 17.50         | 10.2         | 50            | 32.5         | AV       | L1   | GND |

Note:1).Level (dBμV)= Reading (dBμV)+ Transducer (dB)

2). Transducer (dB)=insertion loss of LISN (dB) + Cable loss (dB)

3). Margin(dB) = Limit (dBμV) - Level (dBμV)

|               |                                    |              |   |
|---------------|------------------------------------|--------------|---|
| Power supply: | DC 5V from Adapter<br>AC 120V/60Hz | Polarization | N |
|---------------|------------------------------------|--------------|---|



MEASUREMENT RESULT: "GRC250224003\_fin"

2/24/2025 3:59PM

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.294000         | 28.00         | 9.5          | 60            | 32.4         | QP       | N    | GND |
| 0.642000         | 32.50         | 9.6          | 56            | 23.5         | QP       | N    | GND |
| 1.410000         | 25.10         | 10.0         | 56            | 30.9         | QP       | N    | GND |
| 4.226000         | 26.20         | 9.9          | 56            | 29.8         | QP       | N    | GND |
| 8.474000         | 25.40         | 10.0         | 60            | 34.6         | QP       | N    | GND |
| 22.602000        | 34.70         | 10.2         | 60            | 25.3         | QP       | N    | GND |

MEASUREMENT RESULT: "GRC250224003\_fin2"

2/24/2025 3:59PM


| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.346000         | 20.30         | 9.5          | 49            | 28.8         | AV       | N    | GND |
| 0.646000         | 26.60         | 9.6          | 46            | 19.4         | AV       | N    | GND |
| 1.366000         | 19.80         | 10.0         | 46            | 26.2         | AV       | N    | GND |
| 2.806000         | 19.40         | 10.0         | 46            | 26.6         | AV       | N    | GND |
| 10.606000        | 16.10         | 10.0         | 50            | 33.9         | AV       | N    | GND |
| 22.598000        | 21.30         | 10.2         | 50            | 28.7         | AV       | N    | GND |

- Note:1).Level (dBμV)= Reading (dBμV)+ Transducer (dB)  
2). Transducer (dB)=insertion loss of LISN (dB) + Cable loss (dB)  
3). Margin(dB) = Limit (dBμV) - Level (dBμV)


## 4.2 Radiated Emissions and Band Edge

### TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



**TEST PROCEDURE**

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz, the EUT was placed on a turn table which is 1.5m above ground plane when testing frequency range 1GHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

| Test Frequency range | Test Antenna Type          | Test Distance |
|----------------------|----------------------------|---------------|
| 9KHz-30MHz           | Active Loop Antenna        | 3             |
| 30MHz-1GHz           | Ultra-Broadband Antenna    | 3             |
| 1GHz-18GHz           | Double Ridged Horn Antenna | 3             |
| 18GHz-40GHz          | Horn Antenna               | 1             |

7. Setting test receiver/spectrum as following table states:

| Test Frequency range | Test Receiver/Spectrum Setting                                                                            | Detector |
|----------------------|-----------------------------------------------------------------------------------------------------------|----------|
| 9KHz-150KHz          | RBW=200Hz/VBW=3KHz, Sweep time=Auto                                                                       | QP       |
| 150KHz-30MHz         | RBW=9KHz/VBW=100KHz, Sweep time=Auto                                                                      | QP       |
| 30MHz-1GHz           | RBW=120KHz/VBW=1000KHz, Sweep time=Auto                                                                   | QP       |
| 1GHz-40GHz           | Peak Value: RBW=1MHz/VBW=3MHz,<br>Sweep time=Auto<br>Average Value: RBW=1MHz/VBW=10Hz,<br>Sweep time=Auto | Peak     |

**Field Strength Calculation**

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

|                           |                                            |
|---------------------------|--------------------------------------------|
| Where FS = Field Strength | CL = Cable Attenuation Factor (Cable Loss) |
| RA = Reading Amplitude    | AG = Amplifier Gain                        |
| AF = Antenna Factor       |                                            |

$$\text{Transd} = \text{AF} + \text{CL} - \text{AG}$$

**RADIATION LIMIT**

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power.

The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.

| Frequency (MHz) | Distance (Meters) | Radiated (dBµV/m)                            | Radiated (µV/m)       |
|-----------------|-------------------|----------------------------------------------|-----------------------|
| 0.009-0.49      | 3                 | $20\log(2400/F(\text{KHz})) + 40\log(300/3)$ | $2400/F(\text{KHz})$  |
| 0.49-1.705      | 3                 | $20\log(24000/F(\text{KHz})) + 40\log(30/3)$ | $24000/F(\text{KHz})$ |
| 1.705-30        | 3                 | $20\log(30) + 40\log(30/3)$                  | 30                    |
| 30-88           | 3                 | 40.0                                         | 100                   |
| 88-216          | 3                 | 43.5                                         | 150                   |
| 216-960         | 3                 | 46.0                                         | 200                   |
| Above 960       | 3                 | 54.0                                         | 500                   |


**TEST RESULTS**

Remark:

1. This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
2. GFSK was tested at Low, Middle, and High channel and recorded worst mode at Middle channel below 1GHz. GFSK was tested and recorded worst mode above 1GHz.
3. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.

**For 30MHz-1GHz**

Horizontal



Site LAB

Limit: FCC Part15 RE-Class B\_30-1000MHz

EUT: LED Strip Controller

M/N: 5V-2835-60

Mode: GFSK CH 19

Note: N/A

Polarization: **Horizontal**

Power: AC120V/60Hz

Distance: 3m

Temperature: 18.1(C)

Humidity: 47 %

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Azimuth (deg.) | P/F | Remark |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-------------|----------------|-----|--------|
| 1   | 47.1599         | 36.35          | -17.51        | 18.84          | 40.00          | -21.16      | peak     | 100         | 322            | P   |        |
| 2   | 68.3908         | 43.05          | -20.31        | 22.74          | 40.00          | -17.26      | peak     | 100         | 306            | P   |        |
| 3   | 149.4857        | 45.07          | -21.64        | 23.43          | 43.50          | -20.07      | peak     | 100         | 70             | P   |        |
| 4   | 176.2686        | 45.57          | -20.94        | 24.63          | 43.50          | -18.87      | peak     | 100         | 263            | P   |        |
| 5   | 281.0075        | 41.18          | -17.47        | 23.71          | 46.00          | -22.29      | peak     | 100         | 263            | P   |        |
| 6 * | 390.7226        | 50.52          | -15.86        | 34.66          | 46.00          | -11.34      | peak     | 100         | 96             | P   |        |


Note:1).Level (dBuV/m)= Reading (dBuV)+ Factor (dB/m)

2). Factor(dB/m)=Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)

3). Margin(dB) = Level (dBuV/m) - Limit (dBuV/m)

## Vertical

## Radiated Emission Measurement



Site LAB

Limit: FCC Part15 RE-Class B\_30-1000MHz

EUT: LED Strip Controller

M/N: 5V-2835-60

Mode: GFSK CH 19

Note: N/A

Polarization: **Vertical**

Power: AC120V/60Hz

Distance: 3m

Temperature: 19.1(C)

Humidity: 47 %

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector | Height (cm) | Azimuth (deg.) | P/F | Remark |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|-------------|----------------|-----|--------|
| 1 * | 32.4609         | 57.47          | -19.75        | 37.72          | 40.00          | -2.28       | QP       | 100         | 235            | P   |        |
| 2 ! | 49.4117         | 52.50          | -17.46        | 35.04          | 40.00          | -4.96       | QP       | 116         | 271            | P   |        |
| 3 ! | 70.5977         | 57.21          | -20.65        | 36.56          | 40.00          | -3.44       | QP       | 156         | 173            | P   |        |
| 4   | 154.2785        | 48.12          | -21.89        | 26.23          | 43.50          | -17.27      | peak     | 100         | 122            | P   |        |
| 5   | 281.0074        | 40.12          | -17.47        | 22.65          | 46.00          | -23.35      | peak     | 100         | 324            | P   |        |
| 6   | 396.2412        | 54.26          | -15.76        | 38.50          | 46.00          | -7.50       | peak     | 100         | 100            | P   |        |

Note:1).Level (dBuV/m)= Reading (dBuV)+ Factor (dB/m)

2). Factor(dB/m)=Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)

3). Margin(dB) = Level (dBuV/m) - Limit (dBuV/m)

For 1GHz to 25GHz

**GFSK (above 1GHz)**

| Frequency(MHz): |                         |    | 2402           |             | Polarity:        |                       | HORIZONTAL        |                    |                          |
|-----------------|-------------------------|----|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) |    | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4804.00         | 52.97                   | PK | 74             | 21.03       | 74.13            | 28.42                 | 5.14              | 54.72              | -21.16                   |
| 4804.00         | 40.50                   | AV | 54             | 13.50       | 61.66            | 28.42                 | 5.14              | 54.72              | -21.16                   |
| 7206.00         | 49.41                   | PK | 74             | 24.59       | 63.83            | 34.15                 | 6.46              | 55.03              | -14.42                   |
| 7206.00         | 39.29                   | AV | 54             | 14.71       | 53.71            | 34.15                 | 6.46              | 55.03              | -14.42                   |

| Frequency(MHz): |                         |    | 2402           |             | Polarity:        |                       | VERTICAL          |                    |                          |
|-----------------|-------------------------|----|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) |    | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4804.00         | 52.82                   | PK | 74             | 21.18       | 73.98            | 28.42                 | 5.14              | 54.72              | -21.16                   |
| 4804.00         | 41.63                   | AV | 54             | 12.37       | 62.79            | 28.42                 | 5.14              | 54.72              | -21.16                   |
| 7206.00         | 50.14                   | PK | 74             | 23.86       | 64.56            | 34.15                 | 6.46              | 55.03              | -14.42                   |
| 7206.00         | 39.65                   | AV | 54             | 14.35       | 54.07            | 34.15                 | 6.46              | 55.03              | -14.42                   |

| Frequency(MHz): |                         |    | 2440           |             | Polarity:        |                       | HORIZONTAL        |                    |                          |
|-----------------|-------------------------|----|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) |    | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4880.00         | 54.01                   | PK | 74             | 19.99       | 74.32            | 28.73                 | 5.32              | 54.36              | -20.31                   |
| 4880.00         | 41.83                   | AV | 54             | 12.17       | 62.14            | 28.73                 | 5.32              | 54.36              | -20.31                   |
| 7320.00         | 49.37                   | PK | 74             | 24.63       | 63.03            | 34.38                 | 6.81              | 54.85              | -13.66                   |
| 7320.00         | 38.90                   | AV | 54             | 15.10       | 52.56            | 34.38                 | 6.81              | 54.85              | -13.66                   |

| Frequency(MHz): |                         |    | 2440           |             | Polarity:        |                       | VERTICAL          |                    |                          |
|-----------------|-------------------------|----|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) |    | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4880.00         | 52.90                   | PK | 74             | 21.10       | 73.21            | 28.73                 | 5.32              | 54.36              | -20.31                   |
| 4880.00         | 40.37                   | AV | 54             | 13.63       | 60.68            | 28.73                 | 5.32              | 54.36              | -20.31                   |
| 7320.00         | 50.69                   | PK | 74             | 23.31       | 64.35            | 34.38                 | 6.81              | 54.85              | -13.66                   |
| 7320.00         | 37.88                   | AV | 54             | 16.12       | 51.54            | 34.38                 | 6.81              | 54.85              | -13.66                   |

| Frequency(MHz): |                         |    | 2480           |             | Polarity:        |                       | HORIZONTAL        |                    |                          |
|-----------------|-------------------------|----|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) |    | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4960.00         | 53.46                   | PK | 74             | 20.54       | 72.99            | 29.52                 | 5.63              | 54.68              | -19.53                   |
| 4960.00         | 43.02                   | AV | 54             | 10.98       | 62.55            | 29.52                 | 5.63              | 54.68              | -19.53                   |
| 7440.00         | 52.18                   | PK | 74             | 21.82       | 65.38            | 34.49                 | 7.23              | 54.92              | -13.2                    |
| 7440.00         | 40.22                   | AV | 54             | 13.78       | 53.42            | 34.49                 | 7.23              | 54.92              | -13.2                    |

| Frequency(MHz): |                         |    | 2480           |             | Polarity:        |                       | VERTICAL          |                    |                          |
|-----------------|-------------------------|----|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) |    | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 4960.00         | 54.53                   | PK | 74             | 19.47       | 74.06            | 29.52                 | 5.63              | 54.68              | -19.53                   |
| 4960.00         | 42.46                   | AV | 54             | 11.54       | 61.99            | 29.52                 | 5.63              | 54.68              | -19.53                   |
| 7440.00         | 51.68                   | PK | 74             | 22.32       | 64.88            | 34.49                 | 7.23              | 54.92              | -13.2                    |
| 7440.00         | 39.03                   | AV | 54             | 14.97       | 52.23            | 34.49                 | 7.23              | 54.92              | -13.2                    |

## REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier
3. Margin value = Limit value - Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.

**Results of Band Edges Test (Radiated)****GFSK**

| Frequency(MHz): |                         |    | 2402           |             | Polarity:        |                       | HORIZONTAL        |                    |                          |
|-----------------|-------------------------|----|----------------|-------------|------------------|-----------------------|-------------------|--------------------|--------------------------|
| Frequency (MHz) | Emission Level (dBuV/m) |    | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 2390.00         | 56.82                   | PK | 74             | 17.18       | 81.54            | 25.72                 | 4.32              | 54.76              | -24.72                   |
| 2390.00         | 40.57                   | AV | 54             | 13.43       | 65.29            | 25.72                 | 4.32              | 54.76              | -24.72                   |
| 2400.00         | 56.71                   | PK | 74             | 17.29       | 81.14            | 25.73                 | 4.33              | 54.75              | -24.26                   |
| 2400.00         | 41.56                   | AV | 54             | 12.44       | 65.99            | 25.73                 | 4.33              | 54.75              | -24.26                   |
| Frequency(MHz): |                         |    | 2402           |             | Polarity:        |                       | VERTICAL          |                    |                          |
| Frequency (MHz) | Emission Level (dBuV/m) |    | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 2390.00         | 57.13                   | PK | 74             | 16.87       | 81.85            | 25.72                 | 4.32              | 54.76              | -24.72                   |
| 2390.00         | 41.92                   | AV | 54             | 12.08       | 66.64            | 25.72                 | 4.32              | 54.76              | -24.72                   |
| 2400.00         | 57.63                   | PK | 74             | 16.37       | 82.06            | 25.73                 | 4.33              | 54.75              | -24.26                   |
| 2400.00         | 40.54                   | AV | 54             | 13.46       | 64.97            | 25.73                 | 4.33              | 54.75              | -24.26                   |
| Frequency(MHz): |                         |    | 2480           |             | Polarity:        |                       | HORIZONTAL        |                    |                          |
| Frequency (MHz) | Emission Level (dBuV/m) |    | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 2483.50         | 57.43                   | PK | 74             | 16.57       | 82.00            | 25.78                 | 4.48              | 54.83              | -24.57                   |
| 2483.50         | 40.94                   | AV | 54             | 13.06       | 65.51            | 25.78                 | 4.48              | 54.83              | -24.57                   |
| Frequency(MHz): |                         |    | 2480           |             | Polarity:        |                       | VERTICAL          |                    |                          |
| Frequency (MHz) | Emission Level (dBuV/m) |    | Limit (dBuV/m) | Margin (dB) | Raw Value (dBuV) | Antenna Factor (dB/m) | Cable Factor (dB) | Pre-amplifier (dB) | Correction Factor (dB/m) |
| 2483.50         | 57.77                   | PK | 74             | 16.23       | 82.34            | 25.78                 | 4.48              | 54.83              | -24.57                   |
| 2483.50         | 41.34                   | AV | 54             | 12.66       | 65.91            | 25.78                 | 4.48              | 54.83              | -24.57                   |

## REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier
3. Margin value = Limit value - Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.

### 4.3 Maximum Peak Output Power


#### Limit

The Maximum Peak Output Power Measurement is 30dBm.

#### Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power sensor.

#### Test Configuration



#### Test Results

| Type | Channel | Output power (dBm) | Limit (dBm) | Result |
|------|---------|--------------------|-------------|--------|
| GFSK | 00      | -2.29              | 30.00       | Pass   |
|      | 19      | -1.32              |             |        |
|      | 39      | -1.57              |             |        |

Note: 1.The test results including the cable lose.

#### 4.4 Power Spectral Density

##### Limit

The resulting peak PSD level shall not be greater than 8 dBm/3KHz.

##### Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW  $\geq 3$  kHz.
3. Set the VBW  $\geq 3 \times$  RBW.
4. Set the span to 1.5 times the DTS channel bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
11. The resulting peak PSD level shall not be greater than 8 dBm/3KHz.

##### Test Configuration



##### Test Results

| Type | Channel | Power Spectral Density (dBm/3KHz) | Limit (dBm/3KHz) | Result |
|------|---------|-----------------------------------|------------------|--------|
| GFSK | 00      | -17.72                            | 8.00             | Pass   |
|      | 19      | -16.64                            |                  |        |
|      | 39      | -16.85                            |                  |        |

Test plot as follows:

GFSK



CH00



CH19



CH39

## 4.5 6dB Bandwidth


### Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz

### Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 300 KHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

### Test Configuration




### Test Results

| Type | Channel | 6dB Bandwidth (MHz) | Limit (KHz) | Result |
|------|---------|---------------------|-------------|--------|
| GFSK | 00      | 0.704               | ≥500        | Pass   |
|      | 19      | 0.756               |             |        |
|      | 39      | 0.676               |             |        |

Test plot as follows:


GFSK



CH00



CH19



CH39

## 4.6 Out-of-band Emissions

### Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

### Test Procedure

Connect the transmitter output to spectrum analyzer using a low loss RF cable, and set the spectrum analyzer to RBW=100 kHz, VBW= 300 kHz, peak detector, and max hold. Measurements utilizing these settings are made of the in-band reference level, band edge and out-of-band emissions.

### Test Configuration



### Test Results

Remark: The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and band edge measurement data.

Test plot as follows:

GFSK(CH00)





GFSK (CH19)





reference

reference



30MHz-1G

30MHz-1G




1G-25G

1G-25G


GFSK (CH39)



reference




30MHz-1G




1G-25G

Band-edge Measurements for RF Conducted Emissions:

GFSK



Left bandedge



Right bandedge

## 4.7 Antenna Requirement

### Standard Applicable

**For intentional device, according to FCC 47 CFR Section 15.203:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

**FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1) (I):**



(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

### Antenna Connected Construction



The maximum gain of antenna was 0.43 dBi.




Remark: The antenna gain is provided by the customer, if the data provided by the customer is not accurate, Shenzhen GUOREN Certification Technology Service Co., Ltd. does not assume any responsibility.



## 5 Test Setup Photos of the EUT



## 6 Photos of the EUT







\*\*\*\*\* End of Report \*\*\*\*\*