

Maximum Permissible Exposure Report

1 PRODUCT INFORMATION

EUT	: Cyber Light
Model Number	: Cyber Light
Model Declaration	: N/A
Test Model	: Cyber Light
Power Supply	: Input: DC 12V 3A from type-C or DC 11.1V from battery
Hardware version	: N/A
Software version	: N/A

2 EVALUATION METHOD

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3 LIMIT

3.1 Refer evaluation method

ANSI C95.1-1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

FCC CFR 47 part1 1.1310: Radiofrequency radiation exposure limits.

FCC CFR 47 part2 2.1091: Radiofrequency radiation exposure evaluation: mobile devices

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

4 MPE CALCULATION METHOD

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5 ANTENNA INFORMATION

Antenna Gain and type refer to Antenna specification

6 CONDUCTED POWER

5G Band

3.1.1 Power

Mode	TX Type	Frequency (MHz)	Maximum Average Conducted Output Power (dBm)		Verdict
			ANT1	Limit	
802.11a	SISO	5180	12.68	<=30	Pass
		5200	12.51	<=30	Pass
		5240	13.22	<=30	Pass
		5260	11.91	<=23.98	Pass
		5300	12.82	<=23.98	Pass
		5320	13.97	<=23.98	Pass
		5500	12.46	<=23.98	Pass
		5580	12.51	<=23.98	Pass
		5700	14.19	<=23.98	Pass
		5745	12.65	<=30	Pass
		5785	12.84	<=30	Pass
		5825	14.07	<=30	Pass
		5180	12.96	<=30	Pass
		5200	13.74	<=30	Pass
802.11n (HT20)	SISO	5240	13.40	<=30	Pass
		5260	13.51	<=23.98	Pass
		5300	13.86	<=23.98	Pass
		5320	13.82	<=23.98	Pass
		5500	13.46	<=23.98	Pass
		5580	13.53	<=23.98	Pass
		5700	14.06	<=23.98	Pass
		5745	13.77	<=30	Pass
		5785	13.92	<=30	Pass
		5825	13.92	<=30	Pass
		5190	13.31	<=30	Pass
		5230	13.83	<=30	Pass
		5270	13.77	<=23.98	Pass
		5310	14.07	<=23.98	Pass
802.11n (HT40)	SISO	5510	13.48	<=23.98	Pass
		5550	13.58	<=23.98	Pass
		5670	13.81	<=23.98	Pass
		5755	13.78	<=30	Pass
		5795	13.97	<=30	Pass
		5180	12.97	<=30	Pass
		5200	12.52	<=30	Pass
		5240	13.47	<=30	Pass
		5260	13.48	<=23.98	Pass
		5300	12.64	<=23.98	Pass
802.11ac (VHT20)	SISO	5320	13.83	<=23.98	Pass
		5500	13.49	<=23.98	Pass
		5580	12.35	<=23.98	Pass
		5700	14.03	<=23.98	Pass
		5745	13.78	<=30	Pass
		5785	12.66	<=30	Pass
		5825	13.88	<=30	Pass
		5190	12.87	<=30	Pass
		5230	13.88	<=30	Pass
		5270	13.72	<=23.98	Pass
		5310	14.01	<=23.98	Pass
		5510	13.32	<=23.98	Pass
802.11ac (VHT40)	SISO	5550	12.42	<=23.98	Pass
		5670	13.88	<=23.98	Pass

		5755	13.67	<=30	Pass
		5795	14.07	<=30	Pass
802.11ac (VHT80)	SISO	5210	12.82	<=30	Pass
		5290	12.70	<=23.98	Pass
		5530	13.39	<=23.98	Pass
		5610	13.78	<=23.98	Pass
		5775	12.79	<=30	Pass
		Note1: Antenna Gain: Ant1: 3.30dBi; Ant2: 4.60dBi;			

7 MANUFACTURING TOLERANCE

Maximum conduction power

Test Mode	Channel	Frequency (MHz)	Measured Peak Output Power (dBm)
5G_802.11a	140	5700	14.19

Manufacturing tolerance

802.11a	
Channel	Channel 140
Target (dBm)	14.19
Tolerance \pm (dB)	1.0

Measurement Results

7.1 Standalone MPE

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

ANT	Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
		dBm	mW				
ANT1	IEEE 802.11a	15.19	33.03	3.3	2.13	0.014	1.0000
ANT2	IEEE 802.11a	15.19	33.03	4.6	2.88	0.019	1.0000

Remark:

1. Output power including tune-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer;

8 CONCLUSION

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----