

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: 2BN52MINIV2

EUT Specification

| | |
|-----------------------------------|--|
| Frequency band (Operating) | <input checked="" type="checkbox"/> BT: 2.402GHz ~ 2.480GHz <input checked="" type="checkbox"/> 4G LTE-FDD: Band 2(1850MHz -1910MHz, 1930MHz -1990MHz) |
| Device category | <input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) |
| Exposure classification | <input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²) |
| Antenna diversity | <input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity |
| Max. output power | BLE: -8.43 dBm 4G LTE-FDD Band 2: dBm |
| Antenna gain (Max) | BT: 3.26 dBi LTE Band 2: 2.59 dBi |
| Evaluation applied | <input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation |

Limits for Maximum Permissible Exposure(MPE)

| Frequency Range(MHz) | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density(mW/cm ²) | Average Time |
|--|------------------------------|------------------------------|------------------------------------|--------------|
| (A) Limits for Occupational/Control Exposures | | | | |
| 0.3-3.0 | 614 | 1.63 | *(100) | 6 |
| 3.0-30 | 1842/F | 4.89/F | *(900/F ²) | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | / | / | F/300 | 6 |
| 1500-100000 | / | / | 5 | 6 |
| (B) Limits for General Population/Uncontrol Exposures | | | | |
| 0.3-1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34-30 | 824/F | 2.19/F | *(180/f ²) | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | / | / | F/1500 | 30 |

| | | | | |
|---|---|---|-----|----|
| 1500-100000 | / | / | 1.0 | 30 |
| F= frequency in MHz | | | | |
| * =Plane-wave equivalent power density | | | | |
| RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz: 614V/m, 1.63A/m). | | | | |

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm^2 , P_{out} = output power to antenna in mW

G = gain of antenna in linear scale, $\pi = 3.1416$

R = distance between observation point and center of the radiator in $\text{cm} = 20\text{cm}$

P_d the limit of MPE, 1mW/cm^2 . If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

For multiple RF sources: Multiple RF sources are exempt if:

in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation

$$\sum_{k=1}^c \frac{\text{Evaluated}_k}{\text{Exposure Limit}_k} \leq 1$$

Evaluated_k : the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

Exposure Limit_k : either the general population/uncontrolled maximum permissible exposure (MPE) or specific Absorption rate (SAR) limit for each fixed, mobile, or portable RF source k .

Measurement Result

| Operation Mode | Frequency (MHz) | Max Measured Power (dBm) | Tune up tolerance (dBm) | Max tune up conducted power (dBm) | Output Peak power (mW) | Ant. Gain (dBi) | Ant. Gain (numeric) | Power Density at R = 20cm (mW/cm2) | Power density Limits (mW/cm2) | conclusion |
|------------------------|-----------------|--------------------------|-------------------------|-----------------------------------|------------------------|-----------------|---------------------|------------------------------------|-------------------------------|------------|
| 2.4GHz BLE 1Mbps | 2440 | -8.43 | -8±1 | -7 | 0.200 | 3.26 | 2.118 | 0.000084 | 1.00 | PASS |

| Operating Band | Frequency (MHz) | Antenna Gain (dBi) | Max Conducted Average Output Power (dBm) | EIRP(ERP) (dBm) | EIRP(ERP) Limit (dBm) | Power Density at R = 20cm (mW/cm2) | Limit (mW/cm2) | conclusion |
|----------------|-----------------|--------------------|--|-----------------|-----------------------|------------------------------------|----------------|------------|
| LTE Band 2 | 1912.5 | 2.59 | 22.77 | 25.36 | 33.00 | 0.068347 | 1.00 | PASS |

Note:

1. The Product unsupported at the same time to Transmitting. (declared by client)
2. No need to test SAR.

Signature:



Shawn Wen

Date: 2025-2-12