

Test Mode:	TX(5.3G) - 802.11a
------------	--------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5260 MHz)-Above 1G							
Vertical	4434.051	74.87	-20.73	54.14	68.2	-14.06	PK
Vertical	4434.051	59.14	-20.73	38.41	54	-15.59	AV
Vertical	10520.131	63.03	-9.12	53.91	68.2	-14.29	PK
Vertical	10520.131	49.74	-9.12	40.62	54	-13.38	AV
Vertical	15780.042	60.22	-7.77	52.45	74	-21.55	PK
Vertical	15780.042	49.01	-7.77	41.24	54	-12.76	AV
Horizontal	4434.106	72.27	-20.73	51.54	68.2	-16.66	PK
Horizontal	4434.106	59.81	-20.73	39.08	54	-14.92	AV
Horizontal	10520.045	63.44	-9.12	54.32	68.2	-13.88	PK
Horizontal	10520.045	49.52	-9.12	40.40	54	-13.60	AV
Horizontal	15780.059	61.34	-7.77	53.57	74	-20.43	PK
Horizontal	15780.059	49.27	-7.77	41.50	54	-12.50	AV
Middle Channel (5280 MHz)-Above 1G							
Vertical	4592.043	72.79	-20.42	52.37	74	-21.63	PK
Vertical	4592.043	59.05	-20.42	38.63	54	-15.37	AV
Vertical	10560.050	61.50	-9.06	52.44	68.2	-15.76	PK
Vertical	10560.050	49.54	-9.06	40.48	54	-13.52	AV
Vertical	15840.129	62.76	-7.75	55.01	74	-18.99	PK
Vertical	15840.129	49.39	-7.75	41.64	54	-12.36	AV
Horizontal	4592.116	70.10	-20.42	49.69	74	-24.31	PK
Horizontal	4592.116	59.51	-20.42	39.10	54	-14.90	AV
Horizontal	10560.061	62.16	-9.06	53.10	68.2	-15.10	PK
Horizontal	10560.061	49.67	-9.06	40.61	54	-13.39	AV
Horizontal	15840.145	62.00	-7.75	54.25	74	-19.75	PK
Horizontal	15840.145	49.91	-7.75	42.16	54	-11.84	AV
High Channel (5320 MHz)-Above 1G							
Vertical	4739.141	72.35	-20.12	52.23	74	-21.77	PK
Vertical	4739.141	59.98	-20.12	39.86	54	-14.14	AV
Vertical	10640.141	60.17	-8.94	51.23	68.2	-16.97	PK
Vertical	10640.141	49.04	-8.94	40.10	54	-13.90	AV
Vertical	15960.188	64.23	-7.71	56.52	74	-17.48	PK
Vertical	15960.188	49.18	-7.71	41.47	54	-12.53	AV
Horizontal	4739.104	72.11	-20.12	51.99	74	-22.01	PK
Horizontal	4739.104	59.50	-20.12	39.38	54	-14.62	AV
Horizontal	10640.097	64.80	-8.94	55.86	68.2	-12.34	PK
Horizontal	10640.097	49.64	-8.94	40.70	54	-13.30	AV
Horizontal	15960.094	60.79	-7.71	53.08	74	-20.92	PK
Horizontal	15960.094	49.15	-7.71	41.44	54	-12.56	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

The worst case is Antenna A.

Test Mode:	TX(5.3G) - 802.11n-HT20
------------	-------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5260 MHz)-Above 1G							
Vertical	4434.112	74.14	-20.73	53.41	68.2	-14.79	PK
Vertical	4434.112	59.29	-20.73	38.56	54	-15.44	AV
Vertical	10520.099	62.14	-9.12	53.02	68.2	-15.18	PK
Vertical	10520.099	49.18	-9.12	40.06	54	-13.94	AV
Vertical	15780.021	63.93	-7.77	56.16	74	-17.84	PK
Vertical	15780.021	49.44	-7.77	41.67	54	-12.33	AV
Horizontal	4434.056	72.79	-20.73	52.06	68.2	-16.14	PK
Horizontal	4434.056	59.98	-20.73	39.25	54	-14.75	AV
Horizontal	10520.020	60.36	-9.12	51.24	68.2	-16.96	PK
Horizontal	10520.020	49.30	-9.12	40.18	54	-13.82	AV
Horizontal	15780.166	63.78	-7.77	56.01	74	-17.99	PK
Horizontal	15780.166	49.85	-7.77	42.08	54	-11.92	AV
Middle Channel (5280 MHz)-Above 1G							
Vertical	4592.063	74.61	-20.42	54.19	74	-19.81	PK
Vertical	4592.063	59.79	-20.42	39.37	54	-14.63	AV
Vertical	10560.131	60.43	-9.06	51.37	68.2	-16.83	PK
Vertical	10560.131	49.23	-9.06	40.17	54	-13.83	AV
Vertical	15840.144	63.72	-7.75	55.97	74	-18.03	PK
Vertical	15840.144	49.37	-7.75	41.62	54	-12.38	AV
Horizontal	4592.044	71.28	-20.42	50.87	74	-23.13	PK
Horizontal	4592.044	59.31	-20.42	38.89	54	-15.11	AV
Horizontal	10560.151	63.88	-9.06	54.82	68.2	-13.38	PK
Horizontal	10560.151	49.98	-9.06	40.92	54	-13.08	AV
Horizontal	15840.049	60.51	-7.75	52.76	74	-21.24	PK
Horizontal	15840.049	49.70	-7.75	41.95	54	-12.05	AV
High Channel (5320 MHz)-Above 1G							
Vertical	4739.072	72.84	-20.12	52.72	74	-21.28	PK
Vertical	4739.072	59.79	-20.12	39.67	54	-14.33	AV
Vertical	10640.092	63.56	-8.94	54.62	68.2	-13.58	PK
Vertical	10640.092	49.02	-8.94	40.08	54	-13.92	AV
Vertical	15960.073	62.09	-7.71	54.38	74	-19.62	PK
Vertical	15960.073	49.38	-7.71	41.67	54	-12.33	AV
Horizontal	4739.196	72.44	-20.12	52.32	74	-21.68	PK
Horizontal	4739.196	59.79	-20.12	39.67	54	-14.33	AV
Horizontal	10640.135	63.43	-8.94	54.49	68.2	-13.71	PK
Horizontal	10640.135	49.07	-8.94	40.13	54	-13.87	AV
Horizontal	15960.073	60.92	-7.71	53.21	74	-20.79	PK
Horizontal	15960.073	49.13	-7.71	41.42	54	-12.58	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX(5.3G) - 802.11n-HT40
------------	-------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5270 MHz)-Above 1G							
Vertical	4434.065	74.54	-20.73	53.81	68.2	-14.39	PK
Vertical	4434.065	59.55	-20.73	38.82	54	-15.18	AV
Vertical	10540.033	63.16	-9.09	54.07	68.2	-14.13	PK
Vertical	10540.033	49.94	-9.09	40.85	54	-13.15	AV
Vertical	15810.004	60.24	-7.76	52.48	74	-21.52	PK
Vertical	15810.004	49.65	-7.76	41.89	54	-12.11	AV
Horizontal	4434.028	72.30	-20.73	51.57	74	-22.43	PK
Horizontal	4434.028	59.47	-20.73	38.74	54	-15.26	AV
Horizontal	10540.085	62.36	-9.09	53.27	68.2	-14.93	PK
Horizontal	10540.085	49.40	-9.09	40.31	54	-13.69	AV
Horizontal	15810.013	63.38	-7.76	55.62	74	-18.38	PK
Horizontal	15810.013	49.53	-7.76	41.77	54	-12.23	AV
Middle Channel (5310 MHz)-Above 1G							
Vertical	4739.012	74.22	-20.12	54.09	68.2	-14.11	PK
Vertical	4739.012	59.67	-20.12	39.55	54	-14.45	AV
Vertical	10620.106	60.08	-8.97	51.11	68.2	-17.09	PK
Vertical	10620.106	49.32	-8.97	40.35	54	-13.65	AV
Vertical	15930.042	61.54	-7.72	53.82	74	-20.18	PK
Vertical	15930.042	49.35	-7.72	41.63	54	-12.37	AV
Horizontal	4739.023	72.15	-20.12	52.03	68.2	-16.17	PK
Horizontal	4739.023	59.14	-20.12	39.02	54	-14.98	AV
Horizontal	10620.160	64.02	-8.97	55.05	68.2	-13.15	PK
Horizontal	10620.160	49.31	-8.97	40.34	54	-13.66	AV
Horizontal	15930.104	60.69	-7.72	52.97	74	-21.03	PK
Horizontal	15930.104	49.27	-7.72	41.55	54	-12.45	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX(5.3G) - 802.11ac-HT20
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5260 MHz)-Above 1G							
Vertical	4434.118	70.98	-20.73	50.25	68.2	-17.95	PK
Vertical	4434.118	59.87	-20.73	39.13	54	-14.87	AV
Vertical	10520.049	62.06	-9.12	52.94	68.2	-15.26	PK
Vertical	10520.049	49.36	-9.12	40.24	54	-13.76	AV
Vertical	15780.005	60.24	-7.77	52.47	74	-21.53	PK
Vertical	15780.005	49.75	-7.77	41.98	54	-12.02	AV
Horizontal	4434.033	71.04	-20.73	50.31	68.2	-17.89	PK
Horizontal	4434.033	59.59	-20.73	38.86	54	-15.14	AV
Horizontal	10520.163	61.47	-9.12	52.35	68.2	-15.85	PK
Horizontal	10520.163	49.80	-9.12	40.68	54	-13.32	AV
Horizontal	15780.090	63.40	-7.77	55.63	74	-18.37	PK
Horizontal	15780.090	49.35	-7.77	41.58	54	-12.42	AV
Middle Channel (5280 MHz)-Above 1G							
Vertical	4592.036	73.95	-20.42	53.54	74	-20.46	PK
Vertical	4592.036	59.51	-20.42	39.10	54	-14.90	AV
Vertical	10560.114	64.79	-9.06	55.73	68.2	-12.47	PK
Vertical	10560.114	49.37	-9.06	40.31	54	-13.69	AV
Vertical	15840.021	62.64	-7.75	54.89	74	-19.11	PK
Vertical	15840.021	49.93	-7.75	42.18	54	-11.82	AV
Horizontal	4592.071	70.45	-20.42	50.04	74	-23.96	PK
Horizontal	4592.071	59.29	-20.42	38.87	54	-15.13	AV
Horizontal	10560.094	62.65	-9.06	53.59	68.2	-14.61	PK
Horizontal	10560.094	49.52	-9.06	40.46	54	-13.54	AV
Horizontal	15840.091	63.97	-7.75	56.22	74	-17.78	PK
Horizontal	15840.091	49.13	-7.75	41.38	54	-12.62	AV
High Channel (5320 MHz)-Above 1G							
Vertical	4739.025	70.44	-20.12	50.32	74	-23.68	PK
Vertical	4739.025	59.40	-20.12	39.28	54	-14.72	AV
Vertical	10640.050	64.04	-8.94	55.10	68.2	-13.10	PK
Vertical	10640.050	49.65	-8.94	40.71	54	-13.29	AV
Vertical	15960.188	60.46	-7.71	52.75	74	-21.25	PK
Vertical	15960.188	49.40	-7.71	41.69	54	-12.31	AV
Horizontal	4739.056	74.27	-20.12	54.15	74	-19.85	PK
Horizontal	4739.056	59.09	-20.12	38.97	54	-15.03	AV
Horizontal	10640.062	64.95	-8.94	56.01	68.2	-12.19	PK
Horizontal	10640.062	49.84	-8.94	40.90	54	-13.10	AV
Horizontal	15960.189	63.06	-7.71	55.35	74	-18.65	PK
Horizontal	15960.189	49.78	-7.71	42.07	54	-11.93	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX(5.3G) - 802.11ac-HT40
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5270 MHz)-Above 1G							
Vertical	4434.159	72.80	-20.73	52.07	68.2	-16.13	PK
Vertical	4434.159	59.40	-20.73	38.67	54	-15.33	AV
Vertical	10540.141	62.13	-9.09	53.04	68.2	-15.16	PK
Vertical	10540.141	49.43	-9.09	40.34	54	-13.66	AV
Vertical	15810.007	63.44	-7.76	55.68	74	-18.32	PK
Vertical	15810.007	49.62	-7.76	41.86	54	-12.14	AV
Horizontal	4434.186	74.58	-20.73	53.85	74	-20.15	PK
Horizontal	4434.186	59.84	-20.73	39.10	54	-14.90	AV
Horizontal	10540.188	64.70	-9.09	55.61	68.2	-12.59	PK
Horizontal	10540.188	49.52	-9.09	40.43	54	-13.57	AV
Horizontal	15810.113	61.66	-7.76	53.90	74	-20.10	PK
Horizontal	15810.113	49.70	-7.76	41.94	54	-12.06	AV
Middle Channel (5310 MHz)-Above 1G							
Vertical	4739.045	73.50	-20.12	53.38	68.2	-14.82	PK
Vertical	4739.045	59.43	-20.12	39.30	54	-14.70	AV
Vertical	10620.109	62.82	-8.97	53.85	68.2	-14.35	PK
Vertical	10620.109	49.07	-8.97	40.10	54	-13.90	AV
Vertical	15930.151	64.30	-7.72	56.58	74	-17.42	PK
Vertical	15930.151	49.48	-7.72	41.76	54	-12.24	AV
Horizontal	4739.117	74.12	-20.12	54.00	68.2	-14.20	PK
Horizontal	4739.117	59.68	-20.12	39.55	54	-14.45	AV
Horizontal	10620.131	63.97	-8.97	55.00	68.2	-13.20	PK
Horizontal	10620.131	49.66	-8.97	40.69	54	-13.31	AV
Horizontal	15930.018	61.91	-7.72	54.19	74	-19.81	PK
Horizontal	15930.018	49.94	-7.72	42.22	54	-11.78	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX(5.3G) - 802.11ac-HT80
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
(5290 MHz)-Above 1G							
Vertical	4434.104	72.62	-20.73	51.89	68.2	-16.31	PK
Vertical	4434.104	59.57	-20.73	38.83	54	-15.17	AV
Vertical	10580.194	61.00	-9.03	51.97	68.2	-16.23	PK
Vertical	10580.194	49.65	-9.03	40.62	54	-13.38	AV
Vertical	15870.068	63.58	-7.74	55.84	74	-18.16	PK
Vertical	15870.068	49.36	-7.74	41.62	54	-12.38	AV
Horizontal	4434.077	70.12	-20.73	49.39	68.2	-18.81	PK
Horizontal	4434.077	59.17	-20.73	38.44	54	-15.56	AV
Horizontal	10580.174	64.01	-9.03	54.98	68.2	-13.22	PK
Horizontal	10580.174	49.18	-9.03	40.15	54	-13.85	AV
Horizontal	15870.050	63.48	-7.74	55.74	74	-18.26	PK
Horizontal	15870.050	49.94	-7.74	42.20	54	-11.80	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX(5.6G) - 802.11a
------------	--------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5500 MHz)-Above 1G							
Vertical	4434.158	71.20	-20.73	50.47	68.2	-17.73	PK
Vertical	4434.158	59.67	-20.73	38.94	54	-15.06	AV
Vertical	11000.088	62.19	-8.40	53.79	68.2	-14.41	PK
Vertical	11000.088	49.93	-8.40	41.53	54	-12.47	AV
Vertical	16500.089	64.02	-6.09	57.93	74	-16.07	PK
Vertical	16500.089	49.55	-6.09	43.46	54	-10.54	AV
Horizontal	4434.000	70.30	-20.73	49.56	68.2	-18.64	PK
Horizontal	4434.000	59.32	-20.73	38.59	54	-15.41	AV
Horizontal	11000.131	61.07	-8.40	52.67	68.2	-15.53	PK
Horizontal	11000.131	49.60	-8.40	41.20	54	-12.80	AV
Horizontal	16500.154	63.64	-6.09	57.55	74	-16.45	PK
Horizontal	16500.154	49.97	-6.09	43.88	54	-10.12	AV
middle Channel (5580 MHz)-Above 1G							
Vertical	4592.055	74.21	-20.42	53.79	74	-20.21	PK
Vertical	4592.055	59.42	-20.42	39.01	54	-14.99	AV
Vertical	11160.157	63.11	-8.53	54.58	68.2	-13.62	PK
Vertical	11160.157	49.71	-8.53	41.18	54	-12.82	AV
Vertical	16740.104	63.60	-5.31	58.29	74	-15.71	PK
Vertical	16740.104	49.53	-5.31	44.22	54	-9.78	AV
Horizontal	4592.061	70.81	-20.42	50.39	74	-23.61	PK
Horizontal	4592.061	59.03	-20.42	38.62	54	-15.38	AV
Horizontal	11160.067	60.54	-8.53	52.01	68.2	-16.19	PK
Horizontal	11160.067	49.85	-8.53	41.32	54	-12.68	AV
Horizontal	16740.071	61.89	-5.31	56.58	74	-17.42	PK
Horizontal	16740.071	49.32	-5.31	44.01	54	-9.99	AV
High Channel (5700 MHz)-Above 1G							
Vertical	4739.032	74.68	-20.12	54.56	74	-19.44	PK
Vertical	4739.032	59.75	-20.12	39.63	54	-14.37	AV
Vertical	11400.034	63.93	-8.72	55.21	68.2	-12.99	PK
Vertical	11400.034	49.88	-8.72	41.16	54	-12.84	AV
Vertical	17100.064	62.77	-3.92	58.85	74	-15.15	PK
Vertical	17100.064	49.51	-3.92	45.59	54	-8.41	AV
Horizontal	4739.148	71.53	-20.12	51.41	74	-22.59	PK
Horizontal	4739.148	59.87	-20.12	39.75	54	-14.25	AV
Horizontal	11400.085	61.73	-8.72	53.01	68.2	-15.19	PK
Horizontal	11400.085	49.16	-8.72	40.44	54	-13.56	AV
Horizontal	17100.180	60.86	-3.92	56.94	74	-17.06	PK
Horizontal	17100.180	49.54	-3.92	45.62	54	-8.38	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

The worst case is Antenna A.

Test Mode:	TX(5.6G) - 802.11n-HT20
------------	-------------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5500 MHz)-Above 1G							
Vertical	4434.136	71.63	-20.73	50.90	68.2	-17.30	PK
Vertical	4434.136	59.49	-20.73	38.75	54	-15.25	AV
Vertical	11000.198	62.17	-8.40	53.77	68.2	-14.43	PK
Vertical	11000.198	49.96	-8.40	41.56	54	-12.44	AV
Vertical	16500.043	60.99	-6.09	54.90	74	-19.10	PK
Vertical	16500.043	49.95	-6.09	43.86	54	-10.14	AV
Horizontal	4434.026	71.11	-20.73	50.38	68.2	-17.82	PK
Horizontal	4434.026	59.49	-20.73	38.76	54	-15.24	AV
Horizontal	11000.077	61.87	-8.40	53.47	68.2	-14.73	PK
Horizontal	11000.077	49.20	-8.40	40.80	54	-13.20	AV
Horizontal	16500.048	61.75	-6.09	55.66	74	-18.34	PK
Horizontal	16500.048	49.47	-6.09	43.38	54	-10.62	AV
middle Channel (5580 MHz)-Above 1G							
Vertical	4592.111	71.87	-20.42	51.45	74	-22.55	PK
Vertical	4592.111	59.33	-20.42	38.92	54	-15.08	AV
Vertical	11160.041	60.72	-8.53	52.19	68.2	-16.01	PK
Vertical	11160.041	49.14	-8.53	40.61	54	-13.39	AV
Vertical	16740.178	60.89	-5.31	55.58	74	-18.42	PK
Vertical	16740.178	49.55	-5.31	44.24	54	-9.76	AV
Horizontal	4592.067	72.56	-20.42	52.14	74	-21.86	PK
Horizontal	4592.067	59.28	-20.42	38.86	54	-15.14	AV
Horizontal	11160.177	62.66	-8.53	54.13	68.2	-14.07	PK
Horizontal	11160.177	49.02	-8.53	40.49	54	-13.51	AV
Horizontal	16740.077	64.36	-5.31	59.05	74	-14.95	PK
Horizontal	16740.077	49.72	-5.31	44.41	54	-9.59	AV
High Channel (5700 MHz)-Above 1G							
Vertical	4739.196	74.55	-20.12	54.42	74	-19.58	PK
Vertical	4739.196	59.00	-20.12	38.88	54	-15.12	AV
Vertical	11400.030	63.12	-8.72	54.40	68.2	-13.80	PK
Vertical	11400.030	49.03	-8.72	40.31	54	-13.69	AV
Vertical	17100.094	63.64	-3.92	59.72	74	-14.28	PK
Vertical	17100.094	49.90	-3.92	45.98	54	-8.02	AV
Horizontal	4739.141	73.50	-20.12	53.38	74	-20.62	PK
Horizontal	4739.141	59.38	-20.12	39.26	54	-14.74	AV
Horizontal	11400.190	64.47	-8.72	55.75	68.2	-12.45	PK
Horizontal	11400.190	49.14	-8.72	40.42	54	-13.58	AV
Horizontal	17100.062	62.81	-3.92	58.89	74	-15.11	PK
Horizontal	17100.062	49.21	-3.92	45.29	54	-8.71	AV

Note: PK value is lower than the Average value limit, So average didn't record.
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
Emission level (dBuV/m) = 20 log Emission level (uV/m).
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.
Test Mode is MIMO Mode.

Test Mode:	TX(5.6G) - 802.11n-HT40
------------	-------------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5510 MHz)-Above 1G							
Vertical	4434.062	73.75	-20.73	53.02	68.2	-15.18	PK
Vertical	4434.062	59.76	-20.73	39.03	54	-14.97	AV
Vertical	11020.017	61.52	-8.40	53.12	68.2	-15.08	PK
Vertical	11020.017	49.07	-8.40	40.67	54	-13.33	AV
Vertical	16530.199	64.40	-6.09	58.31	74	-15.69	PK
Vertical	16530.199	49.10	-6.09	43.01	54	-10.99	AV
Horizontal	4434.116	74.63	-20.73	53.90	68.2	-14.30	PK
Horizontal	4434.116	59.65	-20.73	38.92	54	-15.08	AV
Horizontal	11020.102	64.46	-8.40	56.06	68.2	-12.14	PK
Horizontal	11020.102	49.21	-8.40	40.81	54	-13.19	AV
Horizontal	16530.164	64.85	-6.09	58.76	74	-15.24	PK
Horizontal	16530.164	49.36	-6.09	43.27	54	-10.73	AV
middle Channel (5550 MHz)-Above 1G							
Vertical	4592.012	70.12	-20.42	49.70	74	-24.30	PK
Vertical	4592.012	59.81	-20.42	39.40	54	-14.60	AV
Vertical	11100.199	61.72	-8.53	53.19	68.2	-15.01	PK
Vertical	11100.199	49.77	-8.53	41.24	54	-12.76	AV
Vertical	16650.070	61.48	-5.31	56.17	74	-17.83	PK
Vertical	16650.070	49.81	-5.31	44.50	54	-9.50	AV
Horizontal	4592.086	73.15	-20.42	52.74	74	-21.26	PK
Horizontal	4592.086	59.40	-20.42	38.98	54	-15.02	AV
Horizontal	11100.070	64.11	-8.53	55.58	68.2	-12.62	PK
Horizontal	11100.070	49.42	-8.53	40.89	54	-13.11	AV
Horizontal	16650.090	62.62	-5.31	57.31	74	-16.69	PK
Horizontal	16650.090	49.20	-5.31	43.89	54	-10.11	AV
High Channel (5670 MHz)-Above 1G							
Vertical	4739.150	71.36	-20.12	51.24	74	-22.76	PK
Vertical	4739.150	59.07	-20.12	38.94	54	-15.06	AV
Vertical	11340.056	63.20	-8.72	54.48	68.2	-13.72	PK
Vertical	11340.056	49.89	-8.72	41.17	54	-12.83	AV
Vertical	17010.089	64.37	-3.92	60.45	74	-13.55	PK
Vertical	17010.089	49.45	-3.92	45.53	54	-8.47	AV
Horizontal	4739.194	74.93	-20.12	54.81	74	-19.19	PK
Horizontal	4739.194	59.40	-20.12	39.28	54	-14.72	AV
Horizontal	11340.092	63.15	-8.72	54.43	68.2	-13.77	PK
Horizontal	11340.092	49.18	-8.72	40.46	54	-13.54	AV
Horizontal	17010.120	64.24	-3.92	60.32	74	-13.68	PK
Horizontal	17010.120	49.84	-3.92	45.92	54	-8.08	AV

Note: PK value is lower than the Average value limit, So average didn't record.
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
Emission level (dBuV/m) = 20 log Emission level (uV/m).
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.
Test Mode is MIMO Mode.

Test Mode:	TX(5.6G) - 802.11ac-HT20
------------	--------------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5500 MHz)-Above 1G							
Vertical	4434.028	71.27	-20.73	50.53	68.2	-17.67	PK
Vertical	4434.028	59.80	-20.73	39.07	54	-14.93	AV
Vertical	11000.082	63.28	-8.40	54.88	68.2	-13.32	PK
Vertical	11000.082	49.58	-8.40	41.18	54	-12.82	AV
Vertical	16500.120	64.33	-6.09	58.24	74	-15.76	PK
Vertical	16500.120	49.59	-6.09	43.50	54	-10.50	AV
Horizontal	4434.113	70.97	-20.73	50.24	68.2	-17.96	PK
Horizontal	4434.113	59.73	-20.73	39.00	54	-15.00	AV
Horizontal	11000.198	60.71	-8.40	52.31	68.2	-15.89	PK
Horizontal	11000.198	49.96	-8.40	41.56	54	-12.44	AV
Horizontal	16500.043	63.98	-6.09	57.89	74	-16.11	PK
Horizontal	16500.043	49.32	-6.09	43.23	54	-10.77	AV
middle Channel (5580 MHz)-Above 1G							
Vertical	4592.194	73.73	-20.42	53.31	74	-20.69	PK
Vertical	4592.194	59.28	-20.42	38.87	54	-15.13	AV
Vertical	11160.163	64.40	-8.53	55.87	68.2	-12.33	PK
Vertical	11160.163	49.85	-8.53	41.32	54	-12.68	AV
Vertical	16740.187	60.23	-5.31	54.92	74	-19.08	PK
Vertical	16740.187	49.73	-5.31	44.42	54	-9.58	AV
Horizontal	4592.009	73.03	-20.42	52.62	74	-21.38	PK
Horizontal	4592.009	59.62	-20.42	39.20	54	-14.80	AV
Horizontal	11160.123	62.95	-8.53	54.42	68.2	-13.78	PK
Horizontal	11160.123	49.46	-8.53	40.93	54	-13.07	AV
Horizontal	16740.137	64.23	-5.31	58.92	74	-15.08	PK
Horizontal	16740.137	50.00	-5.31	44.69	54	-9.31	AV
High Channel (5700 MHz)-Above 1G							
Vertical	4739.023	74.35	-20.12	54.23	74	-19.77	PK
Vertical	4739.023	59.76	-20.12	39.64	54	-14.36	AV
Vertical	11400.104	63.00	-8.72	54.28	68.2	-13.92	PK
Vertical	11400.104	49.46	-8.72	40.74	54	-13.26	AV
Vertical	17100.147	61.01	-3.92	57.09	74	-16.91	PK
Vertical	17100.147	49.68	-3.92	45.76	54	-8.24	AV
Horizontal	4739.029	72.17	-20.12	52.05	74	-21.95	PK
Horizontal	4739.029	59.19	-20.12	39.07	54	-14.93	AV
Horizontal	11400.008	60.04	-8.72	51.32	68.2	-16.88	PK
Horizontal	11400.008	49.45	-8.72	40.73	54	-13.27	AV
Horizontal	17100.193	64.19	-3.92	60.27	74	-13.73	PK
Horizontal	17100.193	49.07	-3.92	45.15	54	-8.85	AV

Note: PK value is lower than the Average value limit, So average didn't record.
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
Emission level (dBuV/m) = 20 log Emission level (uV/m).
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.
Test Mode is MIMO Mode.

Test Mode:	TX(5.6G) - 802.11ac-HT40
------------	--------------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5510 MHz)-Above 1G							
Vertical	4434.047	72.43	-20.73	51.70	68.2	-16.50	PK
Vertical	4434.047	59.09	-20.73	38.36	54	-15.64	AV
Vertical	11020.149	63.42	-8.40	55.02	68.2	-13.18	PK
Vertical	11020.149	49.44	-8.40	41.04	54	-12.96	AV
Vertical	16530.091	62.82	-6.09	56.73	74	-17.27	PK
Vertical	16530.091	49.26	-6.09	43.17	54	-10.83	AV
Horizontal	4434.067	73.22	-20.73	52.49	68.2	-15.71	PK
Horizontal	4434.067	59.40	-20.73	38.67	54	-15.33	AV
Horizontal	11020.185	60.06	-8.40	51.66	68.2	-16.54	PK
Horizontal	11020.185	49.31	-8.40	40.91	54	-13.09	AV
Horizontal	16530.110	62.30	-6.09	56.21	74	-17.79	PK
Horizontal	16530.110	49.60	-6.09	43.51	54	-10.49	AV
middle Channel (5550 MHz)-Above 1G							
Vertical	4592.028	71.54	-20.42	51.12	74	-22.88	PK
Vertical	4592.028	59.47	-20.42	39.05	54	-14.95	AV
Vertical	11100.056	60.77	-8.53	52.24	68.2	-15.96	PK
Vertical	11100.056	49.08	-8.53	40.55	54	-13.45	AV
Vertical	16650.033	62.69	-5.31	57.38	74	-16.62	PK
Vertical	16650.033	49.23	-5.31	43.92	54	-10.08	AV
Horizontal	4592.186	72.64	-20.42	52.22	74	-21.78	PK
Horizontal	4592.186	59.64	-20.42	39.22	54	-14.78	AV
Horizontal	11100.094	64.83	-8.53	56.30	68.2	-11.90	PK
Horizontal	11100.094	49.90	-8.53	41.37	54	-12.63	AV
Horizontal	16650.113	60.05	-5.31	54.74	74	-19.26	PK
Horizontal	16650.113	49.12	-5.31	43.81	54	-10.19	AV
High Channel (5670 MHz)-Above 1G							
Vertical	4739.065	74.77	-20.12	54.65	74	-19.35	PK
Vertical	4739.065	59.00	-20.12	38.88	54	-15.12	AV
Vertical	11340.181	61.81	-8.72	53.09	68.2	-15.11	PK
Vertical	11340.181	49.63	-8.72	40.91	54	-13.09	AV
Vertical	17010.154	63.91	-3.92	59.99	74	-14.01	PK
Vertical	17010.154	49.65	-3.92	45.73	54	-8.27	AV
Horizontal	4739.186	70.77	-20.12	50.65	74	-23.35	PK
Horizontal	4739.186	59.49	-20.12	39.37	54	-14.63	AV
Horizontal	11340.199	63.95	-8.72	55.23	68.2	-12.97	PK
Horizontal	11340.199	49.02	-8.72	40.30	54	-13.70	AV
Horizontal	17010.077	60.99	-3.92	57.07	74	-16.93	PK
Horizontal	17010.077	49.31	-3.92	45.39	54	-8.61	AV

Note: PK value is lower than the Average value limit, So average didn't record.
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
Emission level (dBuV/m) = 20 log Emission level (uV/m).
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.
Test Mode is MIMO Mode.

Test Mode:	TX(5.6G) - 802.11ac-HT80
------------	--------------------------

Polar (H/V)	Fre- quency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Measure- ment (dBuV/m)	Limits (dBuV/m)	Over (dB)	Detector Type
(5530 MHz)-Above 1G							
Vertical	4434.008	70.07	-20.12	49.95	74	-24.05	PK
Vertical	4434.008	59.17	-20.12	39.05	54	-14.95	AV
Vertical	11060.079	61.18	-8.72	52.46	68.2	-15.74	PK
Vertical	11060.079	49.01	-8.72	40.29	54	-13.71	AV
Vertical	16590.052	61.19	-3.92	57.27	74	-16.73	PK
Vertical	16590.052	49.95	-3.92	46.03	54	-7.97	AV
Horizontal	4434.154	74.14	-20.12	54.02	74	-19.98	PK
Horizontal	4434.154	59.50	-20.12	39.38	54	-14.62	AV
Horizontal	11060.093	62.11	-8.72	53.39	68.2	-14.81	PK
Horizontal	11060.093	49.31	-8.72	40.59	54	-13.41	AV
Horizontal	16590.049	62.80	-3.92	58.88	74	-15.12	PK
Horizontal	16590.049	49.73	-3.92	45.81	54	-8.19	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX (5.8G) -- 802.11a
------------	----------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G							
Vertical	4679.002	71.00	-20.24	50.76	74	-23.24	PK
Vertical	4679.002	59.51	-20.24	39.26	54	-14.74	AV
Vertical	11490.195	60.59	-8.79	51.80	68.2	-16.40	PK
Vertical	11490.195	49.86	-8.79	41.07	54	-12.93	AV
Vertical	17235.144	56.55	-3.18	53.37	68.2	-14.83	PK
Vertical	17235.144	44.51	-3.18	41.33	54	-12.67	AV
Horizontal	4679.017	72.98	-20.73	52.25	74	-21.75	PK
Horizontal	4679.017	59.54	-20.73	38.81	54	-15.19	AV
Horizontal	11490.170	63.85	-8.79	55.06	68.2	-13.14	PK
Horizontal	11490.170	49.56	-8.79	40.77	54	-13.23	AV
Horizontal	17235.141	57.98	-3.18	54.80	68.2	-13.40	PK
Horizontal	17235.141	44.75	-3.18	41.57	54	-12.43	AV
Middle Channel (5785 MHz)-Above 1G							
Vertical	4592.007	70.64	-20.42	50.22	74	-23.78	PK
Vertical	4592.007	59.88	-20.42	39.47	54	-14.53	AV
Vertical	11570.127	62.44	-8.86	53.58	68.2	-14.62	PK
Vertical	11570.127	49.94	-8.86	41.08	54	-12.92	AV
Vertical	17355.171	57.30	-2.52	54.78	68.2	-13.42	PK
Vertical	17355.171	44.93	-2.52	42.41	54	-11.59	AV
Horizontal	4592.188	70.65	-20.42	50.23	74	-23.77	PK
Horizontal	4592.188	59.52	-20.42	39.11	54	-14.89	AV
Horizontal	11570.108	63.81	-8.86	54.95	68.2	-13.25	PK
Horizontal	11570.108	49.28	-8.86	40.42	54	-13.58	AV
Horizontal	17355.039	55.27	-2.52	52.75	68.2	-15.45	PK
Horizontal	17355.039	44.47	-2.52	41.95	54	-12.05	AV
High Channel (5825 MHz)-Above 1G							
Vertical	6039.128	72.19	-18.93	53.25	68.2	-14.95	PK
Vertical	6039.128	59.90	-18.93	40.97	54	-13.03	AV
Vertical	11650.100	62.45	-8.92	53.53	74	-20.47	PK
Vertical	11650.100	49.07	-8.92	40.15	54	-13.85	AV
Vertical	17475.009	55.27	-1.86	53.41	68.2	-14.79	PK
Vertical	17475.009	45.00	-1.86	43.14	54	-10.86	AV
Horizontal	6039.119	73.54	-18.93	54.61	68.2	-13.59	PK
Horizontal	6039.119	59.83	-18.93	40.89	54	-13.11	AV
Horizontal	11650.104	62.06	-8.92	53.14	74	-20.86	PK
Horizontal	11650.104	49.61	-8.92	40.69	54	-13.31	AV
Horizontal	17475.075	57.07	-1.86	55.21	68.2	-12.99	PK
Horizontal	17475.075	44.45	-1.86	42.59	54	-11.41	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

The worst case is Antenna A.

Test Mode: TX (5.8G) --802.11n-HT20

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G							
Vertical	4679.196	71.51	-20.24	51.27	74	-22.73	PK
Vertical	4679.196	59.71	-20.24	39.47	54	-14.53	AV
Vertical	11490.156	61.73	-8.79	52.94	68.2	-15.26	PK
Vertical	11490.156	49.47	-8.79	40.68	54	-13.32	AV
Vertical	17235.157	55.79	-3.18	52.61	68.2	-15.59	PK
Vertical	17235.157	44.15	-3.18	40.97	54	-13.03	AV
Horizontal	4679.187	74.19	-20.24	53.94	74	-20.06	PK
Horizontal	4679.187	59.81	-20.24	39.57	54	-14.43	AV
Horizontal	11490.140	64.35	-8.79	55.56	68.2	-12.64	PK
Horizontal	11490.140	49.35	-8.79	40.56	54	-13.44	AV
Horizontal	17235.128	56.89	-3.18	53.71	68.2	-14.49	PK
Horizontal	17235.128	44.45	-3.18	41.27	54	-12.73	AV
Middle Channel (5785 MHz)-Above 1G							
Vertical	4592.110	74.59	-20.42	54.17	74	-19.83	PK
Vertical	4592.110	59.14	-20.42	38.72	54	-15.28	AV
Vertical	11570.156	62.51	-8.86	53.65	68.2	-14.55	PK
Vertical	11570.156	49.73	-8.86	40.87	54	-13.13	AV
Vertical	17355.148	56.27	-2.52	53.75	68.2	-14.45	PK
Vertical	17355.148	44.65	-2.52	42.13	54	-11.87	AV
Horizontal	4592.014	73.17	-20.42	52.75	74	-21.25	PK
Horizontal	4592.014	59.34	-20.42	38.92	54	-15.08	AV
Horizontal	11570.147	61.33	-8.86	52.47	68.2	-15.73	PK
Horizontal	11570.147	49.03	-8.86	40.17	54	-13.83	AV
Horizontal	17355.109	59.46	-2.52	56.94	68.2	-11.26	PK
Horizontal	17355.109	44.48	-2.52	41.96	54	-12.04	AV
High Channel (5825 MHz)-Above 1G							
Vertical	6039.099	71.06	-18.93	52.12	68.2	-16.08	PK
Vertical	6039.099	59.12	-18.93	40.19	54	-13.81	AV
Vertical	11650.068	64.63	-8.92	55.71	74	-18.29	PK
Vertical	11650.068	49.36	-8.92	40.44	54	-13.56	AV
Vertical	17475.104	55.25	-1.86	53.39	68.2	-14.81	PK
Vertical	17475.104	44.52	-1.86	42.66	54	-11.34	AV
Horizontal	6039.158	74.57	-18.93	55.64	68.2	-12.56	PK
Horizontal	6039.158	59.77	-18.93	40.84	54	-13.16	AV
Horizontal	11650.162	62.24	-8.92	53.32	74	-20.68	PK
Horizontal	11650.162	49.58	-8.92	40.66	54	-13.34	AV
Horizontal	17475.123	58.42	-1.86	56.56	68.2	-11.64	PK
Horizontal	17475.123	44.57	-1.86	42.71	54	-11.29	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX (5.8G) -- 802.11n-HT40
------------	---------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5755 MHz)-Above 1G							
Vertical	4679.110	74.10	-20.24	53.86	74	-20.14	PK
Vertical	4679.110	59.06	-20.24	38.82	54	-15.18	AV
Vertical	11510.079	61.05	-8.81	52.24	74	-21.76	PK
Vertical	11510.079	49.32	-8.81	40.51	54	-13.49	AV
Vertical	17265.002	58.93	-3.01	55.92	68.2	-12.28	PK
Vertical	17265.002	45.00	-3.01	41.99	54	-12.01	AV
Horizontal	4679.050	74.82	-20.24	54.58	74	-19.42	PK
Horizontal	4679.050	59.95	-20.24	39.71	54	-14.29	AV
Horizontal	11510.106	61.87	-8.81	53.06	74	-20.94	PK
Horizontal	11510.106	49.28	-8.81	40.47	54	-13.53	AV
Horizontal	17265.120	57.37	-3.01	54.36	68.2	-13.84	PK
Horizontal	17265.120	44.41	-3.01	41.40	54	-12.60	AV
Middle Channel (5795 MHz)-Above 1G							
Vertical	6039.164	72.09	-18.93	53.16	68.2	-15.04	PK
Vertical	6039.164	59.83	-18.93	40.89	54	-13.11	AV
Vertical	11590.059	60.50	-8.87	51.63	74	-22.37	PK
Vertical	11590.059	49.00	-8.87	40.13	54	-13.87	AV
Vertical	17385.137	59.11	-2.35	56.76	68.2	-11.44	PK
Vertical	17385.137	44.68	-2.35	42.33	54	-11.67	AV
Horizontal	6039.037	70.52	-18.93	51.59	68.2	-16.61	PK
Horizontal	6039.037	59.50	-18.93	40.57	54	-13.43	AV
Horizontal	11590.120	64.27	-8.87	55.40	74	-18.60	PK
Horizontal	11590.120	49.60	-8.87	40.73	54	-13.27	AV
Horizontal	17385.104	55.58	-2.35	53.23	68.2	-14.97	PK
Horizontal	17385.104	44.01	-2.35	41.66	54	-12.34	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode: TX (5.8G) --802.11ac-HT20

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G							
Vertical	4679.134	71.04	-20.24	50.80	74	-23.20	PK
Vertical	4679.134	59.11	-20.24	38.87	54	-15.13	AV
Vertical	11490.147	62.98	-8.79	54.19	68.2	-14.01	PK
Vertical	11490.147	49.31	-8.79	40.52	54	-13.48	AV
Vertical	17235.144	56.28	-3.18	53.10	68.2	-15.10	PK
Vertical	17235.144	44.86	-3.18	41.68	54	-12.32	AV
Horizontal	4679.030	73.11	-20.24	52.87	74	-21.13	PK
Horizontal	4679.030	59.84	-20.24	39.60	54	-14.40	AV
Horizontal	11490.072	63.53	-8.79	54.74	68.2	-13.46	PK
Horizontal	11490.072	49.81	-8.79	41.02	54	-12.98	AV
Horizontal	17235.005	59.38	-3.18	56.20	68.2	-12.00	PK
Horizontal	17235.005	44.32	-3.18	41.14	54	-12.86	AV
Middle Channel (5785 MHz)-Above 1G							
Vertical	4592.150	73.86	-20.42	53.44	74	-20.56	PK
Vertical	4592.150	59.22	-20.42	38.80	54	-15.20	AV
Vertical	11570.157	61.78	-8.86	52.92	68.2	-15.28	PK
Vertical	11570.157	49.79	-8.86	40.93	54	-13.07	AV
Vertical	17355.054	58.15	-2.52	55.63	68.2	-12.57	PK
Vertical	17355.054	44.62	-2.52	42.10	54	-11.90	AV
Horizontal	4592.084	72.59	-20.42	52.18	74	-21.82	PK
Horizontal	4592.084	59.62	-20.42	39.21	54	-14.79	AV
Horizontal	11570.016	61.79	-8.86	52.93	68.2	-15.27	PK
Horizontal	11570.016	49.58	-8.86	40.72	54	-13.28	AV
Horizontal	17355.175	55.27	-2.52	52.75	68.2	-15.45	PK
Horizontal	17355.175	44.97	-2.52	42.45	54	-11.55	AV
High Channel (5825 MHz)-Above 1G							
Vertical	6039.171	73.87	-18.93	54.94	68.2	-13.26	PK
Vertical	6039.171	59.73	-18.93	40.80	54	-13.20	AV
Vertical	11650.035	64.00	-8.92	55.08	74	-18.92	PK
Vertical	11650.035	49.12	-8.92	40.20	54	-13.80	AV
Vertical	17475.167	58.90	-1.86	57.04	68.2	-11.16	PK
Vertical	17475.167	44.78	-1.86	42.92	54	-11.08	AV
Horizontal	6039.162	72.26	-18.93	53.33	68.2	-14.87	PK
Horizontal	6039.162	59.58	-18.93	40.65	54	-13.35	AV
Horizontal	11650.084	60.24	-8.92	51.32	74	-22.68	PK
Horizontal	11650.084	49.78	-8.92	40.86	54	-13.14	AV
Horizontal	17475.050	57.08	-1.86	55.22	68.2	-12.98	PK
Horizontal	17475.050	44.38	-1.86	42.52	54	-11.48	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX (5.8G) -- 802.11ac-HT40
------------	----------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5755 MHz)-Above 1G							
Vertical	4679.012	72.67	-20.24	52.43	74	-21.57	PK
Vertical	4679.012	59.14	-20.24	38.89	54	-15.11	AV
Vertical	11510.058	64.87	-8.81	56.06	74	-17.94	PK
Vertical	11510.058	49.59	-8.81	40.78	54	-13.22	AV
Vertical	17265.003	57.95	-3.01	54.94	68.2	-13.26	PK
Vertical	17265.003	44.95	-3.01	41.94	54	-12.06	AV
Horizontal	4679.078	74.86	-20.24	54.62	74	-19.38	PK
Horizontal	4679.078	59.21	-20.24	38.97	54	-15.03	AV
Horizontal	11510.154	62.18	-8.81	53.37	74	-20.63	PK
Horizontal	11510.154	49.96	-8.81	41.15	54	-12.85	AV
Horizontal	17265.149	56.50	-3.01	53.49	68.2	-14.71	PK
Horizontal	17265.149	44.44	-3.01	41.43	54	-12.57	AV
Middle Channel (5795 MHz)-Above 1G							
Vertical	6039.067	73.78	-18.93	54.85	68.2	-13.35	PK
Vertical	6039.067	59.73	-18.93	40.80	54	-13.20	AV
Vertical	11590.023	60.99	-8.87	52.12	74	-21.88	PK
Vertical	11590.023	49.23	-8.87	40.36	54	-13.64	AV
Vertical	17385.121	58.77	-2.35	56.42	68.2	-11.78	PK
Vertical	17385.121	44.23	-2.35	41.88	54	-12.12	AV
Horizontal	6039.196	71.47	-18.93	52.54	68.2	-15.66	PK
Horizontal	6039.196	59.97	-18.93	41.04	54	-12.96	AV
Horizontal	11590.060	62.93	-8.87	54.06	74	-19.94	PK
Horizontal	11590.060	49.87	-8.87	41.00	54	-13.00	AV
Horizontal	17385.094	57.07	-2.35	54.72	68.2	-13.48	PK
Horizontal	17385.094	44.68	-2.35	42.33	54	-11.67	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX (5.8G) -- 802.11ac-HT80
------------	----------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
(5775 MHz)-Above 1G							
Vertical	4679.051	71.61	-20.24	51.37	74	-22.63	PK
Vertical	4679.051	59.34	-20.24	39.10	54	-14.90	AV
Vertical	11550.085	62.29	-8.84	53.45	74	-20.55	PK
Vertical	11550.085	49.83	-8.84	40.99	54	-13.01	AV
Vertical	17325.191	57.24	-2.68	54.56	68.2	-13.64	PK
Vertical	17325.191	44.75	-2.68	42.07	54	-11.93	AV
Horizontal	4679.176	72.32	-20.24	52.08	74	-21.92	PK
Horizontal	4679.176	59.09	-20.24	38.85	54	-15.15	AV
Horizontal	11550.191	63.86	-8.84	55.02	74	-18.98	PK
Horizontal	11550.191	49.30	-8.84	40.46	54	-13.54	AV
Horizontal	17325.009	58.60	-2.68	55.92	68.2	-12.28	PK
Horizontal	17325.009	44.66	-2.68	41.98	54	-12.02	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Antenna 3
Between 1GHz – 40GHz

Test Mode:	TX(5.1G) - 802.11a
------------	--------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G							
Vertical	4434.103	73.48	-20.73	52.75	68.2	-15.45	PK
Vertical	4434.103	59.53	-20.73	38.80	54	-15.20	AV
Vertical	10360.185	64.17	-9.36	54.81	68.2	-13.39	PK
Vertical	10360.185	49.13	-9.36	39.77	54	-14.23	AV
Vertical	15540.070	64.73	-7.84	56.89	74	-17.11	PK
Vertical	15540.070	49.93	-7.84	42.09	54	-11.91	AV
Horizontal	4434.082	72.00	-20.73	51.27	68.2	-16.93	PK
Horizontal	4434.082	59.73	-20.73	39.00	54	-15.00	AV
Horizontal	10360.168	62.37	-9.36	53.01	68.2	-15.19	PK
Horizontal	10360.168	49.06	-9.36	39.70	54	-14.30	AV
Horizontal	15540.178	64.25	-7.84	56.41	74	-17.59	PK
Horizontal	15540.178	49.28	-7.84	41.44	54	-12.56	AV
Middle Channel (5200 MHz)-Above 1G							
Vertical	4592.135	70.86	-20.42	50.45	74	-23.55	PK
Vertical	4592.135	59.55	-20.42	39.14	54	-14.86	AV
Vertical	10400.048	60.75	-9.30	51.45	68.2	-16.75	PK
Vertical	10400.048	49.99	-9.30	40.69	54	-13.31	AV
Vertical	15600.190	60.24	-7.82	52.42	74	-21.58	PK
Vertical	15600.190	49.68	-7.82	41.86	54	-12.14	AV
Horizontal	4592.021	71.11	-20.42	50.69	74	-23.31	PK
Horizontal	4592.021	59.16	-20.42	38.74	54	-15.26	AV
Horizontal	10400.032	61.48	-9.30	52.18	68.2	-16.02	PK
Horizontal	10400.032	49.82	-9.30	40.52	54	-13.48	AV
Horizontal	15600.004	64.57	-7.82	56.75	74	-17.25	PK
Horizontal	15600.004	49.74	-7.82	41.92	54	-12.08	AV
High Channel (5240 MHz)-Above 1G							
Vertical	4739.072	71.68	-20.12	51.55	74	-22.45	PK
Vertical	4739.072	59.91	-20.12	39.79	54	-14.21	AV
Vertical	10480.080	60.91	-9.18	51.73	68.2	-16.47	PK
Vertical	10480.080	49.25	-9.18	40.07	54	-13.93	AV
Vertical	15720.149	64.71	-7.78	56.93	74	-17.07	PK
Vertical	15720.149	49.87	-7.78	42.09	54	-11.91	AV
Horizontal	4739.142	75.00	-20.12	54.88	74	-19.12	PK
Horizontal	4739.142	59.86	-20.12	39.74	54	-14.26	AV
Horizontal	10480.019	61.07	-9.18	51.89	68.2	-16.31	PK
Horizontal	10480.019	49.39	-9.18	40.21	54	-13.79	AV
Horizontal	15720.000	64.48	-7.78	56.70	74	-17.30	PK
Horizontal	15720.000	49.34	-7.78	41.56	54	-12.44	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

The worst case is Antenna A.

Test Mode:	TX(5.1G) - 802.11n-HT20
------------	-------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G							
Vertical	4434.036	70.45	-20.73	49.71	68.2	-18.49	PK
Vertical	4434.036	59.87	-20.73	39.14	54	-14.86	AV
Vertical	10360.128	62.14	-9.36	52.78	68.2	-15.42	PK
Vertical	10360.128	49.86	-9.36	40.50	54	-13.50	AV
Vertical	15540.192	64.49	-7.84	56.65	74	-17.35	PK
Vertical	15540.192	49.94	-7.84	42.10	54	-11.90	AV
Horizontal	4434.005	70.53	-20.73	49.80	68.2	-18.40	PK
Horizontal	4434.005	59.42	-20.73	38.69	54	-15.31	AV
Horizontal	10360.136	60.24	-9.36	50.88	68.2	-17.32	PK
Horizontal	10360.136	49.86	-9.36	40.50	54	-13.50	AV
Horizontal	15540.100	61.78	-7.84	53.94	74	-20.06	PK
Horizontal	15540.100	49.74	-7.84	41.90	54	-12.10	AV
Middle Channel (5200 MHz)-Above 1G							
Vertical	4592.045	72.88	-20.42	52.46	74	-21.54	PK
Vertical	4592.045	59.07	-20.42	38.65	54	-15.35	AV
Vertical	10400.191	64.65	-9.30	55.35	68.2	-12.85	PK
Vertical	10400.191	49.12	-9.30	39.82	54	-14.18	AV
Vertical	15600.191	61.83	-7.82	54.01	74	-19.99	PK
Vertical	15600.191	49.27	-7.82	41.45	54	-12.55	AV
Horizontal	4592.094	70.16	-20.42	49.74	74	-24.26	PK
Horizontal	4592.094	59.12	-20.42	38.70	54	-15.30	AV
Horizontal	10400.071	62.76	-9.30	53.46	68.2	-14.74	PK
Horizontal	10400.071	49.48	-9.30	40.18	54	-13.82	AV
Horizontal	15600.165	60.34	-7.82	52.52	74	-21.48	PK
Horizontal	15600.165	49.07	-7.82	41.25	54	-12.75	AV
High Channel (5240 MHz)-Above 1G							
Vertical	4739.131	70.22	-20.12	50.09	74	-23.91	PK
Vertical	4739.131	59.72	-20.12	39.59	54	-14.41	AV
Vertical	10480.126	61.92	-9.18	52.74	68.2	-15.46	PK
Vertical	10480.126	49.75	-9.18	40.57	54	-13.43	AV
Vertical	15720.106	63.69	-7.78	55.91	74	-18.09	PK
Vertical	15720.106	49.18	-7.78	41.40	54	-12.60	AV
Horizontal	4739.040	71.28	-20.12	51.16	74	-22.84	PK
Horizontal	4739.040	59.04	-20.12	38.92	54	-15.08	AV
Horizontal	10480.150	63.34	-9.18	54.16	68.2	-14.04	PK
Horizontal	10480.150	49.80	-9.18	40.62	54	-13.38	AV
Horizontal	15720.166	61.89	-7.78	54.11	74	-19.89	PK
Horizontal	15720.166	49.94	-7.78	42.16	54	-11.84	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX(5.1G) - 802.11n-HT40
------------	-------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5190 MHz)-Above 1G							
Vertical	4434.074	74.34	-20.73	53.61	68.2	-14.59	PK
Vertical	4434.074	59.99	-20.73	39.26	54	-14.74	AV
Vertical	10380.058	61.10	-9.33	51.77	68.2	-16.43	PK
Vertical	10380.058	49.77	-9.33	40.44	54	-13.56	AV
Vertical	15570.120	60.43	-7.83	52.60	74	-21.40	PK
Vertical	15570.120	49.64	-7.83	41.81	54	-12.19	AV
Horizontal	4434.128	72.45	-20.73	51.72	74	-22.28	PK
Horizontal	4434.128	59.29	-20.73	38.55	54	-15.45	AV
Horizontal	10380.083	64.56	-9.33	55.23	68.2	-12.97	PK
Horizontal	10380.083	49.80	-9.33	40.47	54	-13.53	AV
Horizontal	15570.013	64.84	-7.83	57.01	74	-16.99	PK
Horizontal	15570.013	49.23	-7.83	41.40	54	-12.60	AV
Middle Channel (5230 MHz)-Above 1G							
Vertical	4739.045	73.35	-20.12	53.22	68.2	-14.98	PK
Vertical	4739.045	59.04	-20.12	38.92	54	-15.08	AV
Vertical	10460.052	64.49	-9.21	55.28	68.2	-12.92	PK
Vertical	10460.052	49.24	-9.21	40.03	54	-13.97	AV
Vertical	15690.119	63.71	-7.79	55.92	74	-18.08	PK
Vertical	15690.119	49.05	-7.79	41.26	54	-12.74	AV
Horizontal	4739.143	73.16	-20.12	53.04	68.2	-15.16	PK
Horizontal	4739.143	59.28	-20.12	39.16	54	-14.84	AV
Horizontal	10460.012	61.33	-9.21	52.12	68.2	-16.08	PK
Horizontal	10460.012	49.85	-9.21	40.64	54	-13.36	AV
Horizontal	15690.045	63.21	-7.79	55.42	74	-18.58	PK
Horizontal	15690.045	49.16	-7.79	41.37	54	-12.63	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX(5.1G) - 802.11ac-HT20
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G							
Vertical	4434.169	70.49	-20.73	49.76	68.2	-18.44	PK
Vertical	4434.169	59.88	-20.73	39.15	54	-14.85	AV
Vertical	10360.070	61.43	-9.36	52.07	68.2	-16.13	PK
Vertical	10360.070	49.89	-9.36	40.53	54	-13.47	AV
Vertical	15540.079	60.89	-7.84	53.05	74	-20.95	PK
Vertical	15540.079	49.72	-7.84	41.88	54	-12.12	AV
Horizontal	4434.015	70.93	-20.73	50.20	68.2	-18.00	PK
Horizontal	4434.015	59.56	-20.73	38.83	54	-15.17	AV
Horizontal	10360.005	64.05	-9.36	54.69	68.2	-13.51	PK
Horizontal	10360.005	49.79	-9.36	40.43	54	-13.57	AV
Horizontal	15540.126	64.71	-7.84	56.87	74	-17.13	PK
Horizontal	15540.126	49.27	-7.84	41.43	54	-12.57	AV
Middle Channel (5200 MHz)-Above 1G							
Vertical	4592.118	70.98	-20.42	50.56	74	-23.44	PK
Vertical	4592.118	59.26	-20.42	38.85	54	-15.15	AV
Vertical	10400.195	61.48	-9.30	52.18	68.2	-16.02	PK
Vertical	10400.195	49.20	-9.30	39.90	54	-14.10	AV
Vertical	15600.092	62.67	-7.82	54.85	74	-19.15	PK
Vertical	15600.092	49.75	-7.82	41.93	54	-12.07	AV
Horizontal	4592.131	74.65	-20.42	54.23	74	-19.77	PK
Horizontal	4592.131	59.70	-20.42	39.29	54	-14.71	AV
Horizontal	10400.046	64.42	-9.30	55.12	68.2	-13.08	PK
Horizontal	10400.046	49.24	-9.30	39.94	54	-14.06	AV
Horizontal	15600.188	62.17	-7.82	54.35	74	-19.65	PK
Horizontal	15600.188	49.96	-7.82	42.14	54	-11.86	AV
High Channel (5240 MHz)-Above 1G							
Vertical	4739.169	72.17	-20.12	52.05	74	-21.95	PK
Vertical	4739.169	59.63	-20.12	39.51	54	-14.49	AV
Vertical	10480.001	64.55	-9.18	55.37	68.2	-12.83	PK
Vertical	10480.001	49.14	-9.18	39.96	54	-14.04	AV
Vertical	15720.151	61.82	-7.78	54.04	74	-19.96	PK
Vertical	15720.151	49.70	-7.78	41.92	54	-12.08	AV
Horizontal	4739.044	73.30	-20.12	53.18	74	-20.82	PK
Horizontal	4739.044	59.31	-20.12	39.19	54	-14.81	AV
Horizontal	10480.093	62.49	-9.18	53.31	68.2	-14.89	PK
Horizontal	10480.093	49.06	-9.18	39.88	54	-14.12	AV
Horizontal	15720.087	62.58	-7.78	54.80	74	-19.20	PK
Horizontal	15720.087	49.20	-7.78	41.42	54	-12.58	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX(5.1G) - 802.11ac-HT40
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5190 MHz)-Above 1G							
Vertical	4434.127	71.95	-20.73	51.22	68.2	-16.98	PK
Vertical	4434.127	59.54	-20.73	38.81	54	-15.19	AV
Vertical	10380.189	60.16	-9.33	50.83	68.2	-17.37	PK
Vertical	10380.189	49.72	-9.33	40.39	54	-13.61	AV
Vertical	15570.188	64.62	-7.83	56.79	74	-17.21	PK
Vertical	15570.188	49.57	-7.83	41.74	54	-12.26	AV
Horizontal	4434.093	74.95	-20.73	54.22	74	-19.78	PK
Horizontal	4434.093	59.83	-20.73	39.10	54	-14.90	AV
Horizontal	10380.160	64.99	-9.33	55.66	68.2	-12.54	PK
Horizontal	10380.160	49.23	-9.33	39.90	54	-14.10	AV
Horizontal	15570.189	60.08	-7.83	52.25	74	-21.75	PK
Horizontal	15570.189	49.41	-7.83	41.58	54	-12.42	AV
Middle Channel (5230 MHz)-Above 1G							
Vertical	4739.112	72.39	-20.12	52.27	68.2	-15.93	PK
Vertical	4739.112	59.31	-20.12	39.19	54	-14.81	AV
Vertical	10460.135	63.31	-9.21	54.10	68.2	-14.10	PK
Vertical	10460.135	49.62	-9.21	40.41	54	-13.59	AV
Vertical	15690.101	60.73	-7.79	52.94	74	-21.06	PK
Vertical	15690.101	49.19	-7.79	41.40	54	-12.60	AV
Horizontal	4739.012	73.60	-20.12	53.48	68.2	-14.72	PK
Horizontal	4739.012	59.68	-20.12	39.55	54	-14.45	AV
Horizontal	10460.174	62.52	-9.21	53.31	68.2	-14.89	PK
Horizontal	10460.174	49.11	-9.21	39.90	54	-14.10	AV
Horizontal	15690.149	63.31	-7.79	55.52	74	-18.48	PK
Horizontal	15690.149	49.87	-7.79	42.08	54	-11.92	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX(5.1G) - 802.11ac-HT80
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
(5210 MHz)-Above 1G							
Vertical	4434.099	72.16	-20.73	51.42	68.2	-16.78	PK
Vertical	4434.099	59.48	-20.73	38.74	54	-15.26	AV
Vertical	10420.043	64.82	-9.27	55.55	68.2	-12.65	PK
Vertical	10420.043	49.64	-9.27	40.37	54	-13.63	AV
Vertical	15630.168	63.81	-7.81	56.00	74	-18.00	PK
Vertical	15630.168	49.31	-7.81	41.50	54	-12.50	AV
Horizontal	4434.191	70.07	-20.73	49.34	68.2	-18.86	PK
Horizontal	4434.191	59.07	-20.73	38.34	54	-15.66	AV
Horizontal	10420.073	41.80	9.27	51.07	68.2	-17.13	PK
Horizontal	10420.073	29.29	9.27	38.56	54	-15.44	AV
Horizontal	15630.046	62.71	-7.81	54.90	74	-19.10	PK
Horizontal	15630.046	49.74	-7.81	41.93	54	-12.07	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX(5.3G) - 802.11a
------------	--------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5260 MHz)-Above 1G							
Vertical	4434.150	70.46	-20.73	49.73	68.2	-18.47	PK
Vertical	4434.150	59.83	-20.73	39.10	54	-14.90	AV
Vertical	10520.074	64.62	-9.12	55.50	68.2	-12.70	PK
Vertical	10520.074	49.95	-9.12	40.83	54	-13.17	AV
Vertical	15780.158	64.13	-7.77	56.36	74	-17.64	PK
Vertical	15780.158	49.95	-7.77	42.18	54	-11.82	AV
Horizontal	4434.087	74.36	-20.73	53.63	68.2	-14.57	PK
Horizontal	4434.087	59.66	-20.73	38.93	54	-15.07	AV
Horizontal	10520.073	60.38	-9.12	51.26	68.2	-16.94	PK
Horizontal	10520.073	49.73	-9.12	40.61	54	-13.39	AV
Horizontal	15780.005	62.00	-7.77	54.23	74	-19.77	PK
Horizontal	15780.005	49.00	-7.77	41.23	54	-12.77	AV
Middle Channel (5280 MHz)-Above 1G							
Vertical	4592.081	71.66	-20.42	51.24	74	-22.76	PK
Vertical	4592.081	59.89	-20.42	39.48	54	-14.52	AV
Vertical	10560.194	61.33	-9.06	52.27	68.2	-15.93	PK
Vertical	10560.194	49.37	-9.06	40.31	54	-13.69	AV
Vertical	15840.158	64.56	-7.75	56.81	74	-17.19	PK
Vertical	15840.158	49.43	-7.75	41.68	54	-12.32	AV
Horizontal	4592.162	73.83	-20.42	53.41	74	-20.59	PK
Horizontal	4592.162	59.47	-20.42	39.06	54	-14.94	AV
Horizontal	10560.197	64.06	-9.06	55.00	68.2	-13.20	PK
Horizontal	10560.197	49.31	-9.06	40.25	54	-13.75	AV
Horizontal	15840.104	60.06	-7.75	52.31	74	-21.69	PK
Horizontal	15840.104	49.99	-7.75	42.24	54	-11.76	AV
High Channel (5320 MHz)-Above 1G							
Vertical	4739.172	71.05	-20.12	50.93	74	-23.07	PK
Vertical	4739.172	59.54	-20.12	39.42	54	-14.58	AV
Vertical	10640.020	64.43	-8.94	55.49	68.2	-12.71	PK
Vertical	10640.020	49.16	-8.94	40.22	54	-13.78	AV
Vertical	15960.102	62.29	-7.71	54.58	74	-19.42	PK
Vertical	15960.102	49.32	-7.71	41.61	54	-12.39	AV
Horizontal	4739.134	73.84	-20.12	53.72	74	-20.28	PK
Horizontal	4739.134	59.63	-20.12	39.50	54	-14.50	AV
Horizontal	10640.133	62.61	-8.94	53.67	68.2	-14.53	PK
Horizontal	10640.133	49.32	-8.94	40.38	54	-13.62	AV
Horizontal	15960.031	61.32	-7.71	53.61	74	-20.39	PK
Horizontal	15960.031	49.65	-7.71	41.94	54	-12.06	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

The worst case is Antenna A.

Test Mode:	TX(5.3G) - 802.11n-HT20
------------	-------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5260 MHz)-Above 1G							
Vertical	4434.113	73.57	-20.73	52.84	68.2	-15.36	PK
Vertical	4434.113	59.74	-20.73	39.01	54	-14.99	AV
Vertical	10520.057	62.40	-9.12	53.28	68.2	-14.92	PK
Vertical	10520.057	49.13	-9.12	40.01	54	-13.99	AV
Vertical	15780.092	63.66	-7.77	55.89	74	-18.11	PK
Vertical	15780.092	49.52	-7.77	41.75	54	-12.25	AV
Horizontal	4434.071	71.34	-20.73	50.61	68.2	-17.59	PK
Horizontal	4434.071	59.83	-20.73	39.10	54	-14.90	AV
Horizontal	10520.194	62.97	-9.12	53.85	68.2	-14.35	PK
Horizontal	10520.194	49.06	-9.12	39.94	54	-14.06	AV
Horizontal	15780.126	61.70	-7.77	53.93	74	-20.07	PK
Horizontal	15780.126	49.60	-7.77	41.83	54	-12.17	AV
Middle Channel (5280 MHz)-Above 1G							
Vertical	4592.128	72.67	-20.42	52.26	74	-21.74	PK
Vertical	4592.128	59.13	-20.42	38.72	54	-15.28	AV
Vertical	10560.000	64.70	-9.06	55.64	68.2	-12.56	PK
Vertical	10560.000	49.04	-9.06	39.98	54	-14.02	AV
Vertical	15840.159	64.08	-7.75	56.33	74	-17.67	PK
Vertical	15840.159	49.15	-7.75	41.40	54	-12.60	AV
Horizontal	4592.169	74.33	-20.42	53.91	74	-20.09	PK
Horizontal	4592.169	59.19	-20.42	38.78	54	-15.22	AV
Horizontal	10560.009	60.66	-9.06	51.60	68.2	-16.60	PK
Horizontal	10560.009	49.14	-9.06	40.08	54	-13.92	AV
Horizontal	15840.056	63.49	-7.75	55.74	74	-18.26	PK
Horizontal	15840.056	49.17	-7.75	41.42	54	-12.58	AV
High Channel (5320 MHz)-Above 1G							
Vertical	4739.111	74.42	-20.12	54.30	74	-19.70	PK
Vertical	4739.111	59.43	-20.12	39.31	54	-14.69	AV
Vertical	10640.169	61.66	-8.94	52.72	68.2	-15.48	PK
Vertical	10640.169	49.88	-8.94	40.94	54	-13.06	AV
Vertical	15960.088	63.79	-7.71	56.08	74	-17.92	PK
Vertical	15960.088	49.64	-7.71	41.93	54	-12.07	AV
Horizontal	4739.087	70.52	-20.12	50.40	74	-23.60	PK
Horizontal	4739.087	59.65	-20.12	39.53	54	-14.47	AV
Horizontal	10640.018	61.09	-8.94	52.15	68.2	-16.05	PK
Horizontal	10640.018	49.32	-8.94	40.38	54	-13.62	AV
Horizontal	15960.077	61.25	-7.71	53.54	74	-20.46	PK
Horizontal	15960.077	49.04	-7.71	41.33	54	-12.67	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX(5.3G) - 802.11n-HT40
------------	-------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5270 MHz)-Above 1G							
Vertical	4434.024	70.01	-20.73	49.27	68.2	-18.93	PK
Vertical	4434.024	59.37	-20.73	38.64	54	-15.36	AV
Vertical	10540.169	62.10	-9.09	53.01	68.2	-15.19	PK
Vertical	10540.169	49.90	-9.09	40.81	54	-13.19	AV
Vertical	15810.030	62.32	-7.76	54.56	74	-19.44	PK
Vertical	15810.030	49.16	-7.76	41.40	54	-12.60	AV
Horizontal	4434.113	72.20	-20.73	51.47	74	-22.53	PK
Horizontal	4434.113	59.68	-20.73	38.94	54	-15.06	AV
Horizontal	10540.170	62.62	-9.09	53.53	68.2	-14.67	PK
Horizontal	10540.170	49.41	-9.09	40.32	54	-13.68	AV
Horizontal	15810.176	60.91	-7.76	53.15	74	-20.85	PK
Horizontal	15810.176	49.79	-7.76	42.03	54	-11.97	AV
Middle Channel (5310 MHz)-Above 1G							
Vertical	4739.180	71.48	-20.12	51.36	68.2	-16.84	PK
Vertical	4739.180	59.62	-20.12	39.50	54	-14.50	AV
Vertical	10620.194	64.21	-8.97	55.24	68.2	-12.96	PK
Vertical	10620.194	49.54	-8.97	40.57	54	-13.43	AV
Vertical	15930.060	61.40	-7.72	53.68	74	-20.32	PK
Vertical	15930.060	49.53	-7.72	41.81	54	-12.19	AV
Horizontal	4739.118	73.34	-20.12	53.22	68.2	-14.98	PK
Horizontal	4739.118	59.34	-20.12	39.22	54	-14.78	AV
Horizontal	10620.144	62.41	-8.97	53.44	68.2	-14.76	PK
Horizontal	10620.144	49.30	-8.97	40.33	54	-13.67	AV
Horizontal	15930.002	60.41	-7.72	52.69	74	-21.31	PK
Horizontal	15930.002	49.27	-7.72	41.55	54	-12.45	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX(5.3G) - 802.11ac-HT20
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5260 MHz)-Above 1G							
Vertical	4434.000	71.66	-20.73	50.92	68.2	-17.28	PK
Vertical	4434.000	59.31	-20.73	38.57	54	-15.43	AV
Vertical	10520.032	60.52	-9.12	51.40	68.2	-16.80	PK
Vertical	10520.032	49.75	-9.12	40.63	54	-13.37	AV
Vertical	15780.043	61.40	-7.77	53.63	74	-20.37	PK
Vertical	15780.043	49.43	-7.77	41.66	54	-12.34	AV
Horizontal	4434.084	71.34	-20.73	50.61	68.2	-17.59	PK
Horizontal	4434.084	59.22	-20.73	38.49	54	-15.51	AV
Horizontal	10520.051	64.05	-9.12	54.93	68.2	-13.27	PK
Horizontal	10520.051	49.65	-9.12	40.53	54	-13.47	AV
Horizontal	15780.117	61.77	-7.77	54.00	74	-20.00	PK
Horizontal	15780.117	49.44	-7.77	41.67	54	-12.33	AV
Middle Channel (5280 MHz)-Above 1G							
Vertical	4592.181	74.71	-20.42	54.30	74	-19.70	PK
Vertical	4592.181	59.72	-20.42	39.30	54	-14.70	AV
Vertical	10560.156	60.46	-9.06	51.40	68.2	-16.80	PK
Vertical	10560.156	49.06	-9.06	40.00	54	-14.00	AV
Vertical	15840.026	61.48	-7.75	53.73	74	-20.27	PK
Vertical	15840.026	49.92	-7.75	42.17	54	-11.83	AV
Horizontal	4592.124	70.33	-20.42	49.92	74	-24.08	PK
Horizontal	4592.124	59.17	-20.42	38.76	54	-15.24	AV
Horizontal	10560.011	60.55	-9.06	51.49	68.2	-16.71	PK
Horizontal	10560.011	49.58	-9.06	40.52	54	-13.48	AV
Horizontal	15840.013	61.10	-7.75	53.35	74	-20.65	PK
Horizontal	15840.013	49.81	-7.75	42.06	54	-11.94	AV
High Channel (5320 MHz)-Above 1G							
Vertical	4739.052	72.25	-20.12	52.13	74	-21.87	PK
Vertical	4739.052	59.84	-20.12	39.72	54	-14.28	AV
Vertical	10640.124	63.75	-8.94	54.81	68.2	-13.39	PK
Vertical	10640.124	49.01	-8.94	40.07	54	-13.93	AV
Vertical	15960.040	63.63	-7.71	55.92	74	-18.08	PK
Vertical	15960.040	49.50	-7.71	41.79	54	-12.21	AV
Horizontal	4739.027	74.76	-20.12	54.64	74	-19.36	PK
Horizontal	4739.027	59.77	-20.12	39.65	54	-14.35	AV
Horizontal	10640.170	60.05	-8.94	51.11	68.2	-17.09	PK
Horizontal	10640.170	49.05	-8.94	40.11	54	-13.89	AV
Horizontal	15960.135	62.39	-7.71	54.68	74	-19.32	PK
Horizontal	15960.135	49.67	-7.71	41.96	54	-12.04	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX(5.3G) - 802.11ac-HT40
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5270 MHz)-Above 1G							
Vertical	4434.125	72.57	-20.73	51.83	68.2	-16.37	PK
Vertical	4434.125	59.13	-20.73	38.40	54	-15.60	AV
Vertical	10540.105	64.17	-9.09	55.08	68.2	-13.12	PK
Vertical	10540.105	49.07	-9.09	39.98	54	-14.02	AV
Vertical	15810.115	60.11	-7.76	52.35	74	-21.65	PK
Vertical	15810.115	49.38	-7.76	41.62	54	-12.38	AV
Horizontal	4434.177	70.55	-20.73	49.82	74	-24.18	PK
Horizontal	4434.177	59.56	-20.73	38.83	54	-15.17	AV
Horizontal	10540.063	61.62	-9.09	52.53	68.2	-15.67	PK
Horizontal	10540.063	49.25	-9.09	40.16	54	-13.84	AV
Horizontal	15810.139	64.08	-7.76	56.32	74	-17.68	PK
Horizontal	15810.139	49.91	-7.76	42.15	54	-11.85	AV
Middle Channel (5310 MHz)-Above 1G							
Vertical	4739.199	71.34	-20.12	51.22	68.2	-16.98	PK
Vertical	4739.199	59.30	-20.12	39.17	54	-14.83	AV
Vertical	10620.171	60.39	-8.97	51.42	68.2	-16.78	PK
Vertical	10620.171	49.20	-8.97	40.23	54	-13.77	AV
Vertical	15930.038	62.88	-7.72	55.16	74	-18.84	PK
Vertical	15930.038	49.18	-7.72	41.46	54	-12.54	AV
Horizontal	4739.054	74.20	-20.12	54.07	68.2	-14.13	PK
Horizontal	4739.054	59.04	-20.12	38.92	54	-15.08	AV
Horizontal	10620.156	62.35	-8.97	53.38	68.2	-14.82	PK
Horizontal	10620.156	49.08	-8.97	40.11	54	-13.89	AV
Horizontal	15930.122	60.59	-7.72	52.87	74	-21.13	PK
Horizontal	15930.122	49.48	-7.72	41.76	54	-12.24	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX(5.3G) - 802.11ac-HT80
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
(5290 MHz)-Above 1G							
Vertical	4434.118	73.14	-20.73	52.40	68.2	-15.80	PK
Vertical	4434.118	59.15	-20.73	38.42	54	-15.58	AV
Vertical	10580.160	62.34	-9.03	53.31	68.2	-14.89	PK
Vertical	10580.160	49.82	-9.03	40.79	54	-13.21	AV
Vertical	15870.017	62.66	-7.74	54.92	74	-19.08	PK
Vertical	15870.017	49.79	-7.74	42.05	54	-11.95	AV
Horizontal	4434.036	73.14	-20.73	52.41	68.2	-15.79	PK
Horizontal	4434.036	59.05	-20.73	38.32	54	-15.68	AV
Horizontal	10580.043	64.32	-9.03	55.29	68.2	-12.91	PK
Horizontal	10580.043	49.88	-9.03	40.85	54	-13.15	AV
Horizontal	15870.100	61.88	-7.74	54.14	74	-19.86	PK
Horizontal	15870.100	49.53	-7.74	41.79	54	-12.21	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX(5.6G) - 802.11a
------------	--------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5500 MHz)-Above 1G							
Vertical	4434.180	74.36	-20.73	53.63	68.2	-14.57	PK
Vertical	4434.180	59.64	-20.73	38.91	54	-15.09	AV
Vertical	11000.050	62.67	-8.40	54.27	68.2	-13.93	PK
Vertical	11000.050	49.80	-8.40	41.40	54	-12.60	AV
Vertical	16500.132	62.34	-6.09	56.25	74	-17.75	PK
Vertical	16500.132	49.42	-6.09	43.33	54	-10.67	AV
Horizontal	4434.140	74.86	-20.73	54.13	68.2	-14.07	PK
Horizontal	4434.140	59.34	-20.73	38.60	54	-15.40	AV
Horizontal	11000.148	60.59	-8.40	52.19	68.2	-16.01	PK
Horizontal	11000.148	49.31	-8.40	40.91	54	-13.09	AV
Horizontal	16500.092	63.41	-6.09	57.32	74	-16.68	PK
Horizontal	16500.092	49.68	-6.09	43.59	54	-10.41	AV
middle Channel (5580 MHz)-Above 1G							
Vertical	4592.174	71.56	-20.42	51.14	74	-22.86	PK
Vertical	4592.174	59.07	-20.42	38.65	54	-15.35	AV
Vertical	11160.028	63.14	-8.53	54.61	68.2	-13.59	PK
Vertical	11160.028	49.67	-8.53	41.14	54	-12.86	AV
Vertical	16740.055	62.81	-5.31	57.50	74	-16.50	PK
Vertical	16740.055	49.99	-5.31	44.68	54	-9.32	AV
Horizontal	4592.062	70.81	-20.42	50.39	74	-23.61	PK
Horizontal	4592.062	59.25	-20.42	38.83	54	-15.17	AV
Horizontal	11160.192	61.95	-8.53	53.42	68.2	-14.78	PK
Horizontal	11160.192	49.61	-8.53	41.08	54	-12.92	AV
Horizontal	16740.034	63.73	-5.31	58.42	74	-15.58	PK
Horizontal	16740.034	49.44	-5.31	44.13	54	-9.87	AV
High Channel (5700 MHz)-Above 1G							
Vertical	4739.139	71.56	-20.12	51.44	74	-22.56	PK
Vertical	4739.139	59.48	-20.12	39.36	54	-14.64	AV
Vertical	11400.061	64.37	-8.72	55.65	68.2	-12.55	PK
Vertical	11400.061	49.05	-8.72	40.33	54	-13.67	AV
Vertical	17100.044	61.57	-3.92	57.65	74	-16.35	PK
Vertical	17100.044	49.89	-3.92	45.97	54	-8.03	AV
Horizontal	4739.083	72.97	-20.12	52.85	74	-21.15	PK
Horizontal	4739.083	59.86	-20.12	39.74	54	-14.26	AV
Horizontal	11400.098	64.24	-8.72	55.52	68.2	-12.68	PK
Horizontal	11400.098	49.36	-8.72	40.64	54	-13.36	AV
Horizontal	17100.055	60.96	-3.92	57.04	74	-16.96	PK
Horizontal	17100.055	49.88	-3.92	45.96	54	-8.04	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

The worst case is Antenna A.

Test Mode:	TX(5.6G) - 802.11n-HT20
------------	-------------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5500 MHz)-Above 1G							
Vertical	4434.106	73.84	-20.73	53.11	68.2	-15.09	PK
Vertical	4434.106	59.75	-20.73	39.02	54	-14.98	AV
Vertical	11000.038	62.19	-8.40	53.79	68.2	-14.41	PK
Vertical	11000.038	49.08	-8.40	40.68	54	-13.32	AV
Vertical	16500.138	61.36	-6.09	55.27	74	-18.73	PK
Vertical	16500.138	49.72	-6.09	43.63	54	-10.37	AV
Horizontal	4434.197	73.14	-20.73	52.41	68.2	-15.79	PK
Horizontal	4434.197	59.79	-20.73	39.06	54	-14.94	AV
Horizontal	11000.191	61.19	-8.40	52.79	68.2	-15.41	PK
Horizontal	11000.191	49.77	-8.40	41.37	54	-12.63	AV
Horizontal	16500.019	61.60	-6.09	55.51	74	-18.49	PK
Horizontal	16500.019	49.49	-6.09	43.40	54	-10.60	AV
middle Channel (5580 MHz)-Above 1G							
Vertical	4592.003	71.07	-20.42	50.66	74	-23.34	PK
Vertical	4592.003	59.72	-20.42	39.31	54	-14.69	AV
Vertical	11160.140	63.28	-8.53	54.75	68.2	-13.45	PK
Vertical	11160.140	49.43	-8.53	40.90	54	-13.10	AV
Vertical	16740.019	64.27	-5.31	58.96	74	-15.04	PK
Vertical	16740.019	49.94	-5.31	44.63	54	-9.37	AV
Horizontal	4592.180	71.67	-20.42	51.25	74	-22.75	PK
Horizontal	4592.180	59.49	-20.42	39.08	54	-14.92	AV
Horizontal	11160.134	63.23	-8.53	54.70	68.2	-13.50	PK
Horizontal	11160.134	49.50	-8.53	40.97	54	-13.03	AV
Horizontal	16740.169	62.94	-5.31	57.63	74	-16.37	PK
Horizontal	16740.169	49.20	-5.31	43.89	54	-10.11	AV
High Channel (5700 MHz)-Above 1G							
Vertical	4739.184	73.76	-20.12	53.63	74	-20.37	PK
Vertical	4739.184	59.62	-20.12	39.50	54	-14.50	AV
Vertical	11400.136	64.44	-8.72	55.72	68.2	-12.48	PK
Vertical	11400.136	49.40	-8.72	40.68	54	-13.32	AV
Vertical	17100.009	63.33	-3.92	59.41	74	-14.59	PK
Vertical	17100.009	49.46	-3.92	45.54	54	-8.46	AV
Horizontal	4739.071	73.10	-20.12	52.97	74	-21.03	PK
Horizontal	4739.071	59.49	-20.12	39.37	54	-14.63	AV
Horizontal	11400.103	60.79	-8.72	52.07	68.2	-16.13	PK
Horizontal	11400.103	49.16	-8.72	40.44	54	-13.56	AV
Horizontal	17100.084	63.52	-3.92	59.60	74	-14.40	PK
Horizontal	17100.084	49.75	-3.92	45.83	54	-8.17	AV

Note: PK value is lower than the Average value limit, So average didn't record.
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
Emission level (dBuV/m) = 20 log Emission level (uV/m).
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.
Test Mode is MIMO Mode.

Test Mode:	TX(5.6G) - 802.11n-HT40
------------	-------------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5510 MHz)-Above 1G							
Vertical	4434.083	71.63	-20.12	51.51	74	-22.49	PK
Vertical	4434.083	59.47	-20.12	39.35	54	-14.65	AV
Vertical	11020.112	63.32	-8.72	54.60	68.2	-13.60	PK
Vertical	11020.112	49.06	-8.72	40.34	54	-13.66	AV
Vertical	16530.034	63.23	-3.92	59.31	74	-14.69	PK
Vertical	16530.034	49.86	-3.92	45.94	54	-8.06	AV
Horizontal	4434.074	73.19	-20.12	53.07	74	-20.93	PK
Horizontal	4434.074	59.74	-20.12	39.62	54	-14.38	AV
Horizontal	11020.027	60.79	-8.72	52.07	68.2	-16.13	PK
Horizontal	11020.027	49.54	-8.72	40.82	54	-13.18	AV
Horizontal	16530.196	61.57	-3.92	57.65	74	-16.35	PK
Horizontal	16530.196	49.91	-3.92	45.99	54	-8.01	AV
middle Channel (5550 MHz)-Above 1G							
Vertical	4592.170	72.56	-20.42	52.15	74	-21.85	PK
Vertical	4592.170	59.99	-20.42	39.57	54	-14.43	AV
Vertical	11100.118	63.58	-8.53	55.05	68.2	-13.15	PK
Vertical	11100.118	49.69	-8.53	41.16	54	-12.84	AV
Vertical	16650.034	61.01	-5.31	55.70	74	-18.30	PK
Vertical	16650.034	49.04	-5.31	43.73	54	-10.27	AV
Horizontal	4592.061	71.84	-20.42	51.43	74	-22.57	PK
Horizontal	4592.061	59.54	-20.42	39.12	54	-14.88	AV
Horizontal	11100.170	62.38	-8.53	53.85	68.2	-14.35	PK
Horizontal	11100.170	49.29	-8.53	40.76	54	-13.24	AV
Horizontal	16650.151	64.50	-5.31	59.19	74	-14.81	PK
Horizontal	16650.151	49.86	-5.31	44.55	54	-9.45	AV
High Channel (5670 MHz)-Above 1G							
Vertical	4739.034	74.04	-20.73	53.31	68.2	-14.89	PK
Vertical	4739.034	59.59	-20.73	38.85	54	-15.15	AV
Vertical	11340.054	60.29	-8.40	51.89	68.2	-16.31	PK
Vertical	11340.054	49.66	-8.40	41.26	54	-12.74	AV
Vertical	17010.083	64.23	-6.09	58.14	74	-15.86	PK
Vertical	17010.083	49.36	-6.09	43.27	54	-10.73	AV
Horizontal	4739.025	73.17	-20.73	52.43	68.2	-15.77	PK
Horizontal	4739.025	59.74	-20.73	39.01	54	-14.99	AV
Horizontal	11340.086	62.83	-8.40	54.43	68.2	-13.77	PK
Horizontal	11340.086	49.42	-8.40	41.02	54	-12.98	AV
Horizontal	17010.041	61.83	-6.09	55.74	74	-18.26	PK
Horizontal	17010.041	49.43	-6.09	43.34	54	-10.66	AV

Note: PK value is lower than the Average value limit, So average didn't record.
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
Emission level (dBuV/m) = 20 log Emission level (uV/m).
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.
Test Mode is MIMO Mode.

Test Mode:	TX(5.6G) - 802.11ac-HT20
------------	--------------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5500 MHz)-Above 1G							
Vertical	4434.064	70.84	-20.73	50.11	68.2	-18.09	PK
Vertical	4434.064	59.69	-20.73	38.96	54	-15.04	AV
Vertical	11000.133	61.16	-8.40	52.76	68.2	-15.44	PK
Vertical	11000.133	49.32	-8.40	40.92	54	-13.08	AV
Vertical	16500.046	61.45	-6.09	55.36	74	-18.64	PK
Vertical	16500.046	49.74	-6.09	43.65	54	-10.35	AV
Horizontal	4434.058	74.92	-20.73	54.18	68.2	-14.02	PK
Horizontal	4434.058	59.10	-20.73	38.36	54	-15.64	AV
Horizontal	11000.090	62.32	-8.40	53.92	68.2	-14.28	PK
Horizontal	11000.090	49.25	-8.40	40.85	54	-13.15	AV
Horizontal	16500.175	62.72	-6.09	56.63	74	-17.37	PK
Horizontal	16500.175	49.35	-6.09	43.26	54	-10.74	AV
middle Channel (5580 MHz)-Above 1G							
Vertical	4592.002	72.59	-20.42	52.17	74	-21.83	PK
Vertical	4592.002	59.07	-20.42	38.65	54	-15.35	AV
Vertical	11160.035	64.64	-8.53	56.11	68.2	-12.09	PK
Vertical	11160.035	49.74	-8.53	41.21	54	-12.79	AV
Vertical	16740.042	61.59	-5.31	56.28	74	-17.72	PK
Vertical	16740.042	49.95	-5.31	44.64	54	-9.36	AV
Horizontal	4592.145	74.39	-20.42	53.97	74	-20.03	PK
Horizontal	4592.145	59.85	-20.42	39.43	54	-14.57	AV
Horizontal	11160.149	63.79	-8.53	55.26	68.2	-12.94	PK
Horizontal	11160.149	49.72	-8.53	41.19	54	-12.81	AV
Horizontal	16740.197	64.92	-5.31	59.61	74	-14.39	PK
Horizontal	16740.197	49.48	-5.31	44.17	54	-9.83	AV
High Channel (5700 MHz)-Above 1G							
Vertical	4739.036	74.87	-20.12	54.74	74	-19.26	PK
Vertical	4739.036	59.33	-20.12	39.21	54	-14.79	AV
Vertical	11400.179	60.08	-8.72	51.36	68.2	-16.84	PK
Vertical	11400.179	49.98	-8.72	41.26	54	-12.74	AV
Vertical	17100.116	60.45	-3.92	56.53	74	-17.47	PK
Vertical	17100.116	49.09	-3.92	45.17	54	-8.83	AV
Horizontal	4739.025	70.69	-20.12	50.57	74	-23.43	PK
Horizontal	4739.025	59.89	-20.12	39.77	54	-14.23	AV
Horizontal	11400.031	62.50	-8.72	53.78	68.2	-14.42	PK
Horizontal	11400.031	49.72	-8.72	41.00	54	-13.00	AV
Horizontal	17100.129	61.31	-3.92	57.39	74	-16.61	PK
Horizontal	17100.129	49.85	-3.92	45.93	54	-8.07	AV

Note: PK value is lower than the Average value limit, So average didn't record.
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
Emission level (dBuV/m) = 20 log Emission level (uV/m).
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.
Test Mode is MIMO Mode.

Test Mode:	TX(5.6G) - 802.11ac-HT40
------------	--------------------------

Polar	Fre- quency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5510 MHz)-Above 1G							
Vertical	4434.180	71.68	-20.73	50.95	68.2	-17.25	PK
Vertical	4434.180	59.80	-20.73	39.07	54	-14.93	AV
Vertical	11020.096	61.35	-8.40	52.95	68.2	-15.25	PK
Vertical	11020.096	49.66	-8.40	41.26	54	-12.74	AV
Vertical	16530.084	61.64	-6.09	55.55	74	-18.45	PK
Vertical	16530.084	49.23	-6.09	43.14	54	-10.86	AV
Horizontal	4434.168	70.23	-20.73	49.50	68.2	-18.70	PK
Horizontal	4434.168	59.02	-20.73	38.29	54	-15.71	AV
Horizontal	11020.054	62.39	-8.40	53.99	68.2	-14.21	PK
Horizontal	11020.054	49.42	-8.40	41.02	54	-12.98	AV
Horizontal	16530.049	64.66	-6.09	58.57	74	-15.43	PK
Horizontal	16530.049	49.84	-6.09	43.75	54	-10.25	AV
middle Channel (5550 MHz)-Above 1G							
Vertical	4592.166	74.42	-20.42	54.01	74	-19.99	PK
Vertical	4592.166	59.17	-20.42	38.75	54	-15.25	AV
Vertical	11100.197	64.98	-8.53	56.45	68.2	-11.75	PK
Vertical	11100.197	49.30	-8.53	40.77	54	-13.23	AV
Vertical	16650.025	60.77	-5.31	55.46	74	-18.54	PK
Vertical	16650.025	49.86	-5.31	44.55	54	-9.45	AV
Horizontal	4592.146	72.27	-20.42	51.85	74	-22.15	PK
Horizontal	4592.146	59.88	-20.42	39.47	54	-14.53	AV
Horizontal	11100.134	62.91	-8.53	54.38	68.2	-13.82	PK
Horizontal	11100.134	49.04	-8.53	40.51	54	-13.49	AV
Horizontal	16650.055	60.92	-5.31	55.61	74	-18.39	PK
Horizontal	16650.055	49.07	-5.31	43.76	54	-10.24	AV
High Channel (5670 MHz)-Above 1G							
Vertical	4739.183	72.78	-20.12	52.66	74	-21.34	PK
Vertical	4739.183	59.07	-20.12	38.94	54	-15.06	AV
Vertical	11340.082	63.57	-8.72	54.85	68.2	-13.35	PK
Vertical	11340.082	49.40	-8.72	40.68	54	-13.32	AV
Vertical	17010.095	61.03	-3.92	57.11	74	-16.89	PK
Vertical	17010.095	49.52	-3.92	45.60	54	-8.40	AV
Horizontal	4739.157	70.41	-20.12	50.29	74	-23.71	PK
Horizontal	4739.157	59.88	-20.12	39.76	54	-14.24	AV
Horizontal	11340.175	60.51	-8.72	51.79	68.2	-16.41	PK
Horizontal	11340.175	49.49	-8.72	40.77	54	-13.23	AV
Horizontal	17010.200	61.05	-3.92	57.13	74	-16.87	PK
Horizontal	17010.200	49.94	-3.92	46.02	54	-7.98	AV

Note: PK value is lower than the Average value limit, So average didn't record.
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
Emission level (dBuV/m) = 20 log Emission level (uV/m).
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.
Test Mode is MIMO Mode.

Test Mode:	TX(5.6G) - 802.11ac-HT80
------------	--------------------------

Polar (H/V)	Fre- quency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Measure- ment (dBuV/m)	Limits (dBuV/m)	Over (dB)	Detector Type
(5530 MHz)-Above 1G							
Vertical	4434.193	73.74	-20.12	53.62	74	-20.38	PK
Vertical	4434.193	59.05	-20.12	38.93	54	-15.07	AV
Vertical	11060.165	64.26	-8.72	55.54	68.2	-12.66	PK
Vertical	11060.165	49.69	-8.72	40.97	54	-13.03	AV
Vertical	16590.116	64.05	-3.92	60.13	74	-13.87	PK
Vertical	16590.116	49.67	-3.92	45.75	54	-8.25	AV
Horizontal	4434.114	71.99	-20.12	51.86	74	-22.14	PK
Horizontal	4434.114	59.66	-20.12	39.54	54	-14.46	AV
Horizontal	11060.111	63.20	-8.72	54.48	68.2	-13.72	PK
Horizontal	11060.111	49.00	-8.72	40.28	54	-13.72	AV
Horizontal	16590.124	64.55	-3.92	60.63	74	-13.37	PK
Horizontal	16590.124	50.00	-3.92	46.08	54	-7.92	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX (5.8G) -- 802.11a
------------	----------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G							
Vertical	4679.108	70.66	-20.24	50.42	74	-23.58	PK
Vertical	4679.108	59.19	-20.24	38.95	54	-15.05	AV
Vertical	11490.174	61.94	-8.79	53.15	68.2	-15.05	PK
Vertical	11490.174	49.39	-8.79	40.60	54	-13.40	AV
Vertical	17235.197	57.80	-3.18	54.62	68.2	-13.58	PK
Vertical	17235.197	44.83	-3.18	41.65	54	-12.35	AV
Horizontal	4679.078	71.24	-20.73	50.51	74	-23.49	PK
Horizontal	4679.078	59.73	-20.73	39.00	54	-15.00	AV
Horizontal	11490.120	60.37	-8.79	51.58	68.2	-16.62	PK
Horizontal	11490.120	49.93	-8.79	41.14	54	-12.86	AV
Horizontal	17235.076	57.26	-3.18	54.08	68.2	-14.12	PK
Horizontal	17235.076	44.85	-3.18	41.67	54	-12.33	AV
Middle Channel (5785 MHz)-Above 1G							
Vertical	4592.061	73.65	-20.42	53.23	74	-20.77	PK
Vertical	4592.061	59.39	-20.42	38.97	54	-15.03	AV
Vertical	11570.007	64.32	-8.86	55.46	68.2	-12.74	PK
Vertical	11570.007	49.57	-8.86	40.71	54	-13.29	AV
Vertical	17355.042	57.83	-2.52	55.31	68.2	-12.89	PK
Vertical	17355.042	44.88	-2.52	42.36	54	-11.64	AV
Horizontal	4592.096	71.01	-20.42	50.60	74	-23.40	PK
Horizontal	4592.096	59.66	-20.42	39.25	54	-14.75	AV
Horizontal	11570.156	60.49	-8.86	51.63	68.2	-16.57	PK
Horizontal	11570.156	49.97	-8.86	41.11	54	-12.89	AV
Horizontal	17355.170	59.46	-2.52	56.94	68.2	-11.26	PK
Horizontal	17355.170	44.26	-2.52	41.74	54	-12.26	AV
High Channel (5825 MHz)-Above 1G							
Vertical	6039.149	73.74	-18.93	54.81	68.2	-13.39	PK
Vertical	6039.149	59.45	-18.93	40.52	54	-13.48	AV
Vertical	11650.067	62.64	-8.92	53.72	74	-20.28	PK
Vertical	11650.067	49.82	-8.92	40.90	54	-13.10	AV
Vertical	17475.147	57.79	-1.86	55.93	68.2	-12.27	PK
Vertical	17475.147	44.34	-1.86	42.48	54	-11.52	AV
Horizontal	6039.148	73.79	-18.93	54.86	68.2	-13.34	PK
Horizontal	6039.148	59.85	-18.93	40.92	54	-13.08	AV
Horizontal	11650.156	62.21	-8.92	53.29	74	-20.71	PK
Horizontal	11650.156	49.41	-8.92	40.49	54	-13.51	AV
Horizontal	17475.044	56.88	-1.86	55.02	68.2	-13.18	PK
Horizontal	17475.044	44.82	-1.86	42.96	54	-11.04	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

The worst case is Antenna A.

Test Mode: TX (5.8G) --802.11n-HT20

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G							
Vertical	4679.123	74.75	-20.24	54.51	74	-19.49	PK
Vertical	4679.123	59.26	-20.24	39.02	54	-14.98	AV
Vertical	11490.034	63.17	-8.79	54.38	68.2	-13.82	PK
Vertical	11490.034	49.29	-8.79	40.50	54	-13.50	AV
Vertical	17235.196	56.92	-3.18	53.74	68.2	-14.46	PK
Vertical	17235.196	44.97	-3.18	41.79	54	-12.21	AV
Horizontal	4679.008	74.72	-20.24	54.48	74	-19.52	PK
Horizontal	4679.008	59.83	-20.24	39.58	54	-14.42	AV
Horizontal	11490.045	60.63	-8.79	51.84	68.2	-16.36	PK
Horizontal	11490.045	49.77	-8.79	40.98	54	-13.02	AV
Horizontal	17235.017	58.74	-3.18	55.56	68.2	-12.64	PK
Horizontal	17235.017	44.73	-3.18	41.55	54	-12.45	AV
Middle Channel (5785 MHz)-Above 1G							
Vertical	4592.050	73.46	-20.42	53.05	74	-20.95	PK
Vertical	4592.050	59.14	-20.42	38.72	54	-15.28	AV
Vertical	11570.067	64.47	-8.86	55.61	68.2	-12.59	PK
Vertical	11570.067	49.89	-8.86	41.03	54	-12.97	AV
Vertical	17355.194	57.06	-2.52	54.54	68.2	-13.66	PK
Vertical	17355.194	44.23	-2.52	41.71	54	-12.29	AV
Horizontal	4592.166	73.98	-20.42	53.57	74	-20.43	PK
Horizontal	4592.166	59.01	-20.42	38.59	54	-15.41	AV
Horizontal	11570.130	63.84	-8.86	54.98	68.2	-13.22	PK
Horizontal	11570.130	49.51	-8.86	40.65	54	-13.35	AV
Horizontal	17355.016	58.87	-2.52	56.35	68.2	-11.85	PK
Horizontal	17355.016	44.65	-2.52	42.13	54	-11.87	AV
High Channel (5825 MHz)-Above 1G							
Vertical	6039.081	70.20	-18.93	51.27	68.2	-16.93	PK
Vertical	6039.081	59.18	-18.93	40.25	54	-13.75	AV
Vertical	11650.166	60.58	-8.92	51.66	74	-22.34	PK
Vertical	11650.166	49.81	-8.92	40.89	54	-13.11	AV
Vertical	17475.023	57.56	-1.86	55.70	68.2	-12.50	PK
Vertical	17475.023	44.16	-1.86	42.30	54	-11.70	AV
Horizontal	6039.168	74.68	-18.93	55.75	68.2	-12.45	PK
Horizontal	6039.168	59.22	-18.93	40.28	54	-13.72	AV
Horizontal	11650.006	60.72	-8.92	51.80	74	-22.20	PK
Horizontal	11650.006	49.20	-8.92	40.28	54	-13.72	AV
Horizontal	17475.147	55.92	-1.86	54.06	68.2	-14.14	PK
Horizontal	17475.147	44.85	-1.86	42.99	54	-11.01	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX (5.8G) -- 802.11n-HT40
------------	---------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5755 MHz)-Above 1G							
Vertical	4679.186	74.95	-20.24	54.71	74	-19.29	PK
Vertical	4679.186	59.59	-20.24	39.35	54	-14.65	AV
Vertical	11510.056	61.83	-8.81	53.02	74	-20.98	PK
Vertical	11510.056	49.44	-8.81	40.63	54	-13.37	AV
Vertical	17265.051	59.43	-3.01	56.42	68.2	-11.78	PK
Vertical	17265.051	44.05	-3.01	41.04	54	-12.96	AV
Horizontal	4679.093	70.31	-20.24	50.07	74	-23.93	PK
Horizontal	4679.093	59.13	-20.24	38.88	54	-15.12	AV
Horizontal	11510.044	60.68	-8.81	51.87	74	-22.13	PK
Horizontal	11510.044	49.84	-8.81	41.03	54	-12.97	AV
Horizontal	17265.028	56.82	-3.01	53.81	68.2	-14.39	PK
Horizontal	17265.028	44.32	-3.01	41.31	54	-12.69	AV
Middle Channel (5795 MHz)-Above 1G							
Vertical	6039.122	72.96	-18.93	54.02	68.2	-14.18	PK
Vertical	6039.122	59.90	-18.93	40.97	54	-13.03	AV
Vertical	11590.141	63.57	-8.87	54.70	74	-19.30	PK
Vertical	11590.141	49.07	-8.87	40.20	54	-13.80	AV
Vertical	17385.189	57.98	-2.35	55.63	68.2	-12.57	PK
Vertical	17385.189	44.09	-2.35	41.74	54	-12.26	AV
Horizontal	6039.084	70.97	-18.93	52.04	68.2	-16.16	PK
Horizontal	6039.084	59.65	-18.93	40.72	54	-13.28	AV
Horizontal	11590.116	63.19	-8.87	54.32	74	-19.68	PK
Horizontal	11590.116	49.57	-8.87	40.70	54	-13.30	AV
Horizontal	17385.051	57.51	-2.35	55.16	68.2	-13.04	PK
Horizontal	17385.051	44.66	-2.35	42.31	54	-11.69	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode: TX (5.8G) --802.11ac-HT20

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G							
Vertical	4679.071	74.59	-20.24	54.35	74	-19.65	PK
Vertical	4679.071	59.36	-20.24	39.12	54	-14.88	AV
Vertical	11490.132	61.73	-8.79	52.94	68.2	-15.26	PK
Vertical	11490.132	49.59	-8.79	40.80	54	-13.20	AV
Vertical	17235.055	56.39	-3.18	53.21	68.2	-14.99	PK
Vertical	17235.055	44.66	-3.18	41.48	54	-12.52	AV
Horizontal	4679.081	72.93	-20.24	52.69	74	-21.31	PK
Horizontal	4679.081	59.96	-20.24	39.72	54	-14.28	AV
Horizontal	11490.029	63.30	-8.79	54.51	68.2	-13.69	PK
Horizontal	11490.029	49.75	-8.79	40.96	54	-13.04	AV
Horizontal	17235.171	55.12	-3.18	51.94	68.2	-16.26	PK
Horizontal	17235.171	44.07	-3.18	40.89	54	-13.11	AV
Middle Channel (5785 MHz)-Above 1G							
Vertical	4592.003	72.25	-20.42	51.84	74	-22.16	PK
Vertical	4592.003	59.26	-20.42	38.85	54	-15.15	AV
Vertical	11570.118	63.16	-8.86	54.30	68.2	-13.90	PK
Vertical	11570.118	49.94	-8.86	41.08	54	-12.92	AV
Vertical	17355.079	59.78	-2.52	57.26	68.2	-10.94	PK
Vertical	17355.079	44.53	-2.52	42.01	54	-11.99	AV
Horizontal	4592.049	72.65	-20.42	52.24	74	-21.76	PK
Horizontal	4592.049	59.76	-20.42	39.34	54	-14.66	AV
Horizontal	11570.044	61.38	-8.86	52.52	68.2	-15.68	PK
Horizontal	11570.044	49.11	-8.86	40.25	54	-13.75	AV
Horizontal	17355.101	55.59	-2.52	53.07	68.2	-15.13	PK
Horizontal	17355.101	44.55	-2.52	42.03	54	-11.97	AV
High Channel (5825 MHz)-Above 1G							
Vertical	6039.019	70.93	-18.93	52.00	68.2	-16.20	PK
Vertical	6039.019	59.36	-18.93	40.43	54	-13.57	AV
Vertical	11650.094	62.14	-8.92	53.22	74	-20.78	PK
Vertical	11650.094	49.16	-8.92	40.24	54	-13.76	AV
Vertical	17475.178	59.77	-1.86	57.91	68.2	-10.29	PK
Vertical	17475.178	44.89	-1.86	43.03	54	-10.97	AV
Horizontal	6039.123	72.98	-18.93	54.05	68.2	-14.15	PK
Horizontal	6039.123	59.10	-18.93	40.17	54	-13.83	AV
Horizontal	11650.192	61.86	-8.92	52.94	74	-21.06	PK
Horizontal	11650.192	49.78	-8.92	40.86	54	-13.14	AV
Horizontal	17475.067	59.48	-1.86	57.62	68.2	-10.58	PK
Horizontal	17475.067	44.48	-1.86	42.62	54	-11.38	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX (5.8G) -- 802.11ac-HT40
------------	----------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5755 MHz)-Above 1G							
Vertical	4679.033	70.58	-20.24	50.34	74	-23.66	PK
Vertical	4679.033	59.81	-20.24	39.57	54	-14.43	AV
Vertical	11510.167	63.69	-8.81	54.88	74	-19.12	PK
Vertical	11510.167	49.89	-8.81	41.08	54	-12.92	AV
Vertical	17265.176	55.02	-3.01	52.01	68.2	-16.19	PK
Vertical	17265.176	44.65	-3.01	41.64	54	-12.36	AV
Horizontal	4679.139	73.63	-20.24	53.39	74	-20.61	PK
Horizontal	4679.139	59.94	-20.24	39.70	54	-14.30	AV
Horizontal	11510.154	64.66	-8.81	55.85	74	-18.15	PK
Horizontal	11510.154	49.77	-8.81	40.96	54	-13.04	AV
Horizontal	17265.114	59.52	-3.01	56.51	68.2	-11.69	PK
Horizontal	17265.114	44.44	-3.01	41.43	54	-12.57	AV
Middle Channel (5795 MHz)-Above 1G							
Vertical	6039.174	74.91	-18.93	55.97	68.2	-12.23	PK
Vertical	6039.174	59.19	-18.93	40.26	54	-13.74	AV
Vertical	11590.111	63.50	-8.87	54.63	74	-19.37	PK
Vertical	11590.111	49.09	-8.87	40.22	54	-13.78	AV
Vertical	17385.157	55.13	-2.35	52.78	68.2	-15.42	PK
Vertical	17385.157	44.56	-2.35	42.21	54	-11.79	AV
Horizontal	6039.184	70.23	-18.93	51.30	68.2	-16.90	PK
Horizontal	6039.184	59.10	-18.93	40.17	54	-13.83	AV
Horizontal	11590.086	63.70	-8.87	54.83	74	-19.17	PK
Horizontal	11590.086	49.41	-8.87	40.54	54	-13.46	AV
Horizontal	17385.005	55.69	-2.35	53.34	68.2	-14.86	PK
Horizontal	17385.005	44.54	-2.35	42.19	54	-11.81	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX (5.8G) -- 802.11ac-HT80
------------	----------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
(5775 MHz)-Above 1G							
Vertical	4679.128	72.34	-20.24	52.10	74	-21.90	PK
Vertical	4679.128	59.79	-20.24	39.55	54	-14.45	AV
Vertical	11550.196	63.30	-8.84	54.46	74	-19.54	PK
Vertical	11550.196	49.04	-8.84	40.20	54	-13.80	AV
Vertical	17325.072	57.42	-2.68	54.74	68.2	-13.46	PK
Vertical	17325.072	44.12	-2.68	41.44	54	-12.56	AV
Horizontal	4679.173	71.59	-20.24	51.35	74	-22.65	PK
Horizontal	4679.173	59.84	-20.24	39.60	54	-14.40	AV
Horizontal	11550.077	61.15	-8.84	52.31	74	-21.69	PK
Horizontal	11550.077	49.21	-8.84	40.37	54	-13.63	AV
Horizontal	17325.154	59.16	-2.68	56.48	68.2	-11.72	PK
Horizontal	17325.154	44.85	-2.68	42.17	54	-11.83	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Antenna 4
Between 1GHz – 40GHz

Test Mode:	TX(5.1G) - 802.11a
------------	--------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G							
Vertical	4434.151	72.15	-20.73	51.42	68.2	-16.78	PK
Vertical	4434.151	59.24	-20.73	38.51	54	-15.49	AV
Vertical	10360.161	61.70	-9.36	52.34	68.2	-15.86	PK
Vertical	10360.161	49.45	-9.36	40.09	54	-13.91	AV
Vertical	15540.017	62.06	-7.84	54.22	74	-19.78	PK
Vertical	15540.017	49.58	-7.84	41.74	54	-12.26	AV
Horizontal	4434.165	72.37	-20.73	51.64	68.2	-16.56	PK
Horizontal	4434.165	59.74	-20.73	39.01	54	-14.99	AV
Horizontal	10360.124	61.99	-9.36	52.63	68.2	-15.57	PK
Horizontal	10360.124	49.42	-9.36	40.06	54	-13.94	AV
Horizontal	15540.197	62.50	-7.84	54.66	74	-19.34	PK
Horizontal	15540.197	49.28	-7.84	41.44	54	-12.56	AV
Middle Channel (5200 MHz)-Above 1G							
Vertical	4592.171	73.77	-20.42	53.35	74	-20.65	PK
Vertical	4592.171	59.27	-20.42	38.85	54	-15.15	AV
Vertical	10400.012	63.97	-9.30	54.67	68.2	-13.53	PK
Vertical	10400.012	49.74	-9.30	40.44	54	-13.56	AV
Vertical	15600.168	63.40	-7.82	55.58	74	-18.42	PK
Vertical	15600.168	49.86	-7.82	42.04	54	-11.96	AV
Horizontal	4592.100	72.54	-20.42	52.12	74	-21.88	PK
Horizontal	4592.100	59.04	-20.42	38.62	54	-15.38	AV
Horizontal	10400.166	61.31	-9.30	52.01	68.2	-16.19	PK
Horizontal	10400.166	49.45	-9.30	40.15	54	-13.85	AV
Horizontal	15600.101	63.52	-7.82	55.70	74	-18.30	PK
Horizontal	15600.101	49.21	-7.82	41.39	54	-12.61	AV
High Channel (5240 MHz)-Above 1G							
Vertical	4739.181	73.97	-20.12	53.85	74	-20.15	PK
Vertical	4739.181	59.11	-20.12	38.99	54	-15.01	AV
Vertical	10480.101	64.38	-9.18	55.20	68.2	-13.00	PK
Vertical	10480.101	49.73	-9.18	40.55	54	-13.45	AV
Vertical	15720.002	64.80	-7.78	57.02	74	-16.98	PK
Vertical	15720.002	49.34	-7.78	41.56	54	-12.44	AV
Horizontal	4739.089	70.81	-20.12	50.69	74	-23.31	PK
Horizontal	4739.089	59.58	-20.12	39.46	54	-14.54	AV
Horizontal	10480.176	63.15	-9.18	53.97	68.2	-14.23	PK
Horizontal	10480.176	49.68	-9.18	40.50	54	-13.50	AV
Horizontal	15720.037	64.88	-7.78	57.10	74	-16.90	PK
Horizontal	15720.037	49.57	-7.78	41.79	54	-12.21	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

The worst case is Antenna A.

Test Mode:	TX(5.1G) - 802.11n-HT20
------------	-------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G							
Vertical	4434.082	74.80	-20.73	54.07	68.2	-14.13	PK
Vertical	4434.082	59.97	-20.73	39.23	54	-14.77	AV
Vertical	10360.199	64.50	-9.36	55.14	68.2	-13.06	PK
Vertical	10360.199	49.20	-9.36	39.84	54	-14.16	AV
Vertical	15540.170	63.19	-7.84	55.35	74	-18.65	PK
Vertical	15540.170	49.11	-7.84	41.27	54	-12.73	AV
Horizontal	4434.108	72.20	-20.73	51.46	68.2	-16.74	PK
Horizontal	4434.108	59.14	-20.73	38.41	54	-15.59	AV
Horizontal	10360.160	61.31	-9.36	51.95	68.2	-16.25	PK
Horizontal	10360.160	49.13	-9.36	39.77	54	-14.23	AV
Horizontal	15540.075	62.76	-7.84	54.92	74	-19.08	PK
Horizontal	15540.075	49.41	-7.84	41.57	54	-12.43	AV
Middle Channel (5200 MHz)-Above 1G							
Vertical	4592.117	74.89	-20.42	54.47	74	-19.53	PK
Vertical	4592.117	59.82	-20.42	39.40	54	-14.60	AV
Vertical	10400.006	62.22	-9.30	52.92	68.2	-15.28	PK
Vertical	10400.006	49.71	-9.30	40.41	54	-13.59	AV
Vertical	15600.178	61.28	-7.82	53.46	74	-20.54	PK
Vertical	15600.178	49.18	-7.82	41.36	54	-12.64	AV
Horizontal	4592.190	73.49	-20.42	53.07	74	-20.93	PK
Horizontal	4592.190	59.15	-20.42	38.74	54	-15.26	AV
Horizontal	10400.193	63.48	-9.30	54.18	68.2	-14.02	PK
Horizontal	10400.193	49.23	-9.30	39.93	54	-14.07	AV
Horizontal	15600.083	64.92	-7.82	57.10	74	-16.90	PK
Horizontal	15600.083	49.40	-7.82	41.58	54	-12.42	AV
High Channel (5240 MHz)-Above 1G							
Vertical	4739.084	74.52	-20.12	54.39	74	-19.61	PK
Vertical	4739.084	59.23	-20.12	39.11	54	-14.89	AV
Vertical	10480.027	62.97	-9.18	53.79	68.2	-14.41	PK
Vertical	10480.027	49.77	-9.18	40.59	54	-13.41	AV
Vertical	15720.077	60.70	-7.78	52.92	74	-21.08	PK
Vertical	15720.077	49.95	-7.78	42.17	54	-11.83	AV
Horizontal	4739.156	72.81	-20.12	52.69	74	-21.31	PK
Horizontal	4739.156	59.32	-20.12	39.20	54	-14.80	AV
Horizontal	10480.178	62.57	-9.18	53.39	68.2	-14.81	PK
Horizontal	10480.178	49.41	-9.18	40.23	54	-13.77	AV
Horizontal	15720.066	60.90	-7.78	53.12	74	-20.88	PK
Horizontal	15720.066	49.41	-7.78	41.63	54	-12.37	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX(5.1G) - 802.11n-HT40
------------	-------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5190 MHz)-Above 1G							
Vertical	4434.045	73.67	-20.73	52.94	68.2	-15.26	PK
Vertical	4434.045	59.06	-20.73	38.33	54	-15.67	AV
Vertical	10380.189	62.74	-9.33	53.41	68.2	-14.79	PK
Vertical	10380.189	49.12	-9.33	39.79	54	-14.21	AV
Vertical	15570.018	61.60	-7.83	53.77	74	-20.23	PK
Vertical	15570.018	49.82	-7.83	41.99	54	-12.01	AV
Horizontal	4434.193	71.61	-20.73	50.88	74	-23.12	PK
Horizontal	4434.193	59.29	-20.73	38.56	54	-15.44	AV
Horizontal	10380.162	60.17	-9.33	50.84	68.2	-17.36	PK
Horizontal	10380.162	49.12	-9.33	39.79	54	-14.21	AV
Horizontal	15570.020	62.76	-7.83	54.93	74	-19.07	PK
Horizontal	15570.020	49.70	-7.83	41.87	54	-12.13	AV
Middle Channel (5230 MHz)-Above 1G							
Vertical	4739.178	73.83	-20.12	53.71	68.2	-14.49	PK
Vertical	4739.178	59.64	-20.12	39.52	54	-14.48	AV
Vertical	10460.175	62.25	-9.21	53.04	68.2	-15.16	PK
Vertical	10460.175	49.98	-9.21	40.77	54	-13.23	AV
Vertical	15690.005	64.01	-7.79	56.22	74	-17.78	PK
Vertical	15690.005	49.12	-7.79	41.33	54	-12.67	AV
Horizontal	4739.030	70.91	-20.12	50.79	68.2	-17.41	PK
Horizontal	4739.030	59.27	-20.12	39.14	54	-14.86	AV
Horizontal	10460.166	61.91	-9.21	52.70	68.2	-15.50	PK
Horizontal	10460.166	49.90	-9.21	40.69	54	-13.31	AV
Horizontal	15690.125	61.12	-7.79	53.33	74	-20.67	PK
Horizontal	15690.125	49.18	-7.79	41.39	54	-12.61	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX(5.1G) - 802.11ac-HT20
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G							
Vertical	4434.046	72.66	-20.73	51.93	68.2	-16.27	PK
Vertical	4434.046	59.10	-20.73	38.37	54	-15.63	AV
Vertical	10360.044	64.10	-9.36	54.74	68.2	-13.46	PK
Vertical	10360.044	49.99	-9.36	40.63	54	-13.37	AV
Vertical	15540.178	60.71	-7.84	52.87	74	-21.13	PK
Vertical	15540.178	49.66	-7.84	41.82	54	-12.18	AV
Horizontal	4434.186	70.30	-20.73	49.57	68.2	-18.63	PK
Horizontal	4434.186	59.14	-20.73	38.41	54	-15.59	AV
Horizontal	10360.045	62.73	-9.36	53.37	68.2	-14.83	PK
Horizontal	10360.045	49.25	-9.36	39.89	54	-14.11	AV
Horizontal	15540.169	63.00	-7.84	55.16	74	-18.84	PK
Horizontal	15540.169	49.89	-7.84	42.05	54	-11.95	AV
Middle Channel (5200 MHz)-Above 1G							
Vertical	4592.194	70.61	-20.42	50.19	74	-23.81	PK
Vertical	4592.194	59.63	-20.42	39.22	54	-14.78	AV
Vertical	10400.048	61.85	-9.30	52.55	68.2	-15.65	PK
Vertical	10400.048	49.83	-9.30	40.53	54	-13.47	AV
Vertical	15600.045	62.95	-7.82	55.13	74	-18.87	PK
Vertical	15600.045	49.51	-7.82	41.69	54	-12.31	AV
Horizontal	4592.137	70.30	-20.42	49.89	74	-24.11	PK
Horizontal	4592.137	59.04	-20.42	38.62	54	-15.38	AV
Horizontal	10400.141	64.11	-9.30	54.81	68.2	-13.39	PK
Horizontal	10400.141	49.69	-9.30	40.39	54	-13.61	AV
Horizontal	15600.037	64.66	-7.82	56.84	74	-17.16	PK
Horizontal	15600.037	49.93	-7.82	42.11	54	-11.89	AV
High Channel (5240 MHz)-Above 1G							
Vertical	4739.009	71.62	-20.12	51.50	74	-22.50	PK
Vertical	4739.009	59.64	-20.12	39.52	54	-14.48	AV
Vertical	10480.113	62.13	-9.18	52.95	68.2	-15.25	PK
Vertical	10480.113	49.45	-9.18	40.27	54	-13.73	AV
Vertical	15720.155	62.37	-7.78	54.59	74	-19.41	PK
Vertical	15720.155	49.03	-7.78	41.25	54	-12.75	AV
Horizontal	4739.186	70.23	-20.12	50.11	74	-23.89	PK
Horizontal	4739.186	59.85	-20.12	39.73	54	-14.27	AV
Horizontal	10480.075	63.25	-9.18	54.07	68.2	-14.13	PK
Horizontal	10480.075	49.64	-9.18	40.46	54	-13.54	AV
Horizontal	15720.093	61.48	-7.78	53.70	74	-20.30	PK
Horizontal	15720.093	49.74	-7.78	41.96	54	-12.04	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX(5.1G) - 802.11ac-HT40
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5190 MHz)-Above 1G							
Vertical	4434.171	71.75	-20.73	51.02	68.2	-17.18	PK
Vertical	4434.171	59.57	-20.73	38.84	54	-15.16	AV
Vertical	10380.029	63.23	-9.33	53.90	68.2	-14.30	PK
Vertical	10380.029	49.61	-9.33	40.28	54	-13.72	AV
Vertical	15570.078	60.33	-7.83	52.50	74	-21.50	PK
Vertical	15570.078	49.91	-7.83	42.08	54	-11.92	AV
Horizontal	4434.188	73.92	-20.73	53.19	74	-20.81	PK
Horizontal	4434.188	59.57	-20.73	38.84	54	-15.16	AV
Horizontal	10380.126	61.44	-9.33	52.11	68.2	-16.09	PK
Horizontal	10380.126	49.89	-9.33	40.56	54	-13.44	AV
Horizontal	15570.154	61.13	-7.83	53.30	74	-20.70	PK
Horizontal	15570.154	49.44	-7.83	41.61	54	-12.39	AV
Middle Channel (5230 MHz)-Above 1G							
Vertical	4739.066	70.77	-20.12	50.65	68.2	-17.55	PK
Vertical	4739.066	59.14	-20.12	39.02	54	-14.98	AV
Vertical	10460.021	61.05	-9.21	51.84	68.2	-16.36	PK
Vertical	10460.021	49.26	-9.21	40.05	54	-13.95	AV
Vertical	15690.027	61.27	-7.79	53.48	74	-20.52	PK
Vertical	15690.027	49.29	-7.79	41.50	54	-12.50	AV
Horizontal	4739.002	72.60	-20.12	52.48	68.2	-15.72	PK
Horizontal	4739.002	59.55	-20.12	39.43	54	-14.57	AV
Horizontal	10460.102	60.72	-9.21	51.51	68.2	-16.69	PK
Horizontal	10460.102	49.38	-9.21	40.17	54	-13.83	AV
Horizontal	15690.084	63.64	-7.79	55.85	74	-18.15	PK
Horizontal	15690.084	49.03	-7.79	41.24	54	-12.76	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX(5.1G) - 802.11ac-HT80
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
(5210 MHz)-Above 1G							
Vertical	4434.013	71.89	-20.73	51.15	68.2	-17.05	PK
Vertical	4434.013	59.18	-20.73	38.45	54	-15.55	AV
Vertical	10420.025	62.29	-9.27	53.02	68.2	-15.18	PK
Vertical	10420.025	49.18	-9.27	39.91	54	-14.09	AV
Vertical	15630.020	63.98	-7.81	56.17	74	-17.83	PK
Vertical	15630.020	49.54	-7.81	41.73	54	-12.27	AV
Horizontal	4434.115	73.52	-20.73	52.79	68.2	-15.41	PK
Horizontal	4434.115	59.28	-20.73	38.55	54	-15.45	AV
Horizontal	10420.049	40.07	9.27	49.34	68.2	-18.86	PK
Horizontal	10420.049	29.75	9.27	39.02	54	-14.98	AV
Horizontal	15630.176	64.03	-7.81	56.22	74	-17.78	PK
Horizontal	15630.176	49.66	-7.81	41.85	54	-12.15	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX(5.3G) - 802.11a
------------	--------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5260 MHz)-Above 1G							
Vertical	4434.121	72.41	-20.73	51.67	68.2	-16.53	PK
Vertical	4434.121	59.06	-20.73	38.33	54	-15.67	AV
Vertical	10520.117	64.09	-9.12	54.97	68.2	-13.23	PK
Vertical	10520.117	49.56	-9.12	40.44	54	-13.56	AV
Vertical	15780.013	62.41	-7.77	54.64	74	-19.36	PK
Vertical	15780.013	49.01	-7.77	41.24	54	-12.76	AV
Horizontal	4434.095	74.55	-20.73	53.82	68.2	-14.38	PK
Horizontal	4434.095	59.16	-20.73	38.43	54	-15.57	AV
Horizontal	10520.092	60.09	-9.12	50.97	68.2	-17.23	PK
Horizontal	10520.092	49.80	-9.12	40.68	54	-13.32	AV
Horizontal	15780.132	64.67	-7.77	56.90	74	-17.10	PK
Horizontal	15780.132	49.65	-7.77	41.88	54	-12.12	AV
Middle Channel (5280 MHz)-Above 1G							
Vertical	4592.115	72.02	-20.42	51.60	74	-22.40	PK
Vertical	4592.115	59.03	-20.42	38.61	54	-15.39	AV
Vertical	10560.155	64.71	-9.06	55.65	68.2	-12.55	PK
Vertical	10560.155	49.06	-9.06	40.00	54	-14.00	AV
Vertical	15840.001	62.21	-7.75	54.46	74	-19.54	PK
Vertical	15840.001	49.55	-7.75	41.80	54	-12.20	AV
Horizontal	4592.104	74.07	-20.42	53.66	74	-20.34	PK
Horizontal	4592.104	59.80	-20.42	39.38	54	-14.62	AV
Horizontal	10560.015	62.90	-9.06	53.84	68.2	-14.36	PK
Horizontal	10560.015	49.49	-9.06	40.43	54	-13.57	AV
Horizontal	15840.170	60.89	-7.75	53.14	74	-20.86	PK
Horizontal	15840.170	49.31	-7.75	41.56	54	-12.44	AV
High Channel (5320 MHz)-Above 1G							
Vertical	4739.172	71.36	-20.12	51.24	74	-22.76	PK
Vertical	4739.172	59.33	-20.12	39.20	54	-14.80	AV
Vertical	10640.197	61.34	-8.94	52.40	68.2	-15.80	PK
Vertical	10640.197	49.86	-8.94	40.92	54	-13.08	AV
Vertical	15960.051	61.31	-7.71	53.60	74	-20.40	PK
Vertical	15960.051	49.92	-7.71	42.21	54	-11.79	AV
Horizontal	4739.159	70.50	-20.12	50.38	74	-23.62	PK
Horizontal	4739.159	60.00	-20.12	39.88	54	-14.12	AV
Horizontal	10640.008	60.79	-8.94	51.85	68.2	-16.35	PK
Horizontal	10640.008	49.86	-8.94	40.92	54	-13.08	AV
Horizontal	15960.199	61.49	-7.71	53.78	74	-20.22	PK
Horizontal	15960.199	49.19	-7.71	41.48	54	-12.52	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

The worst case is Antenna A.

Test Mode:	TX(5.3G) - 802.11n-HT20
------------	-------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5260 MHz)-Above 1G							
Vertical	4434.087	74.95	-20.73	54.22	68.2	-13.98	PK
Vertical	4434.087	59.05	-20.73	38.32	54	-15.68	AV
Vertical	10520.192	60.41	-9.12	51.29	68.2	-16.91	PK
Vertical	10520.192	49.30	-9.12	40.18	54	-13.82	AV
Vertical	15780.004	63.32	-7.77	55.55	74	-18.45	PK
Vertical	15780.004	49.99	-7.77	42.22	54	-11.78	AV
Horizontal	4434.017	70.35	-20.73	49.62	68.2	-18.58	PK
Horizontal	4434.017	59.30	-20.73	38.57	54	-15.43	AV
Horizontal	10520.012	62.44	-9.12	53.32	68.2	-14.88	PK
Horizontal	10520.012	49.82	-9.12	40.70	54	-13.30	AV
Horizontal	15780.054	62.71	-7.77	54.94	74	-19.06	PK
Horizontal	15780.054	49.35	-7.77	41.58	54	-12.42	AV
Middle Channel (5280 MHz)-Above 1G							
Vertical	4592.122	71.95	-20.42	51.54	74	-22.46	PK
Vertical	4592.122	59.41	-20.42	38.99	54	-15.01	AV
Vertical	10560.009	60.40	-9.06	51.34	68.2	-16.86	PK
Vertical	10560.009	49.15	-9.06	40.09	54	-13.91	AV
Vertical	15840.182	63.92	-7.75	56.17	74	-17.83	PK
Vertical	15840.182	49.55	-7.75	41.80	54	-12.20	AV
Horizontal	4592.164	70.52	-20.42	50.11	74	-23.89	PK
Horizontal	4592.164	59.92	-20.42	39.50	54	-14.50	AV
Horizontal	10560.186	63.74	-9.06	54.68	68.2	-13.52	PK
Horizontal	10560.186	49.51	-9.06	40.45	54	-13.55	AV
Horizontal	15840.028	63.23	-7.75	55.48	74	-18.52	PK
Horizontal	15840.028	49.28	-7.75	41.53	54	-12.47	AV
High Channel (5320 MHz)-Above 1G							
Vertical	4739.174	73.27	-20.12	53.15	74	-20.85	PK
Vertical	4739.174	59.93	-20.12	39.81	54	-14.19	AV
Vertical	10640.180	64.56	-8.94	55.62	68.2	-12.58	PK
Vertical	10640.180	49.68	-8.94	40.74	54	-13.26	AV
Vertical	15960.167	64.05	-7.71	56.34	74	-17.66	PK
Vertical	15960.167	49.31	-7.71	41.60	54	-12.40	AV
Horizontal	4739.067	70.23	-20.12	50.11	74	-23.89	PK
Horizontal	4739.067	59.33	-20.12	39.21	54	-14.79	AV
Horizontal	10640.157	63.25	-8.94	54.31	68.2	-13.89	PK
Horizontal	10640.157	49.18	-8.94	40.24	54	-13.76	AV
Horizontal	15960.095	61.92	-7.71	54.21	74	-19.79	PK
Horizontal	15960.095	49.24	-7.71	41.53	54	-12.47	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX(5.3G) - 802.11n-HT40
------------	-------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5270 MHz)-Above 1G							
Vertical	4434.112	74.88	-20.73	54.15	68.2	-14.05	PK
Vertical	4434.112	59.22	-20.73	38.49	54	-15.51	AV
Vertical	10540.005	64.95	-9.09	55.86	68.2	-12.34	PK
Vertical	10540.005	49.59	-9.09	40.50	54	-13.50	AV
Vertical	15810.143	64.75	-7.76	56.99	74	-17.01	PK
Vertical	15810.143	49.48	-7.76	41.72	54	-12.28	AV
Horizontal	4434.004	72.40	-20.73	51.67	74	-22.33	PK
Horizontal	4434.004	59.23	-20.73	38.49	54	-15.51	AV
Horizontal	10540.001	62.88	-9.09	53.79	68.2	-14.41	PK
Horizontal	10540.001	49.64	-9.09	40.55	54	-13.45	AV
Horizontal	15810.179	62.83	-7.76	55.07	74	-18.93	PK
Horizontal	15810.179	49.99	-7.76	42.23	54	-11.77	AV
Middle Channel (5310 MHz)-Above 1G							
Vertical	4739.066	74.64	-20.12	54.52	68.2	-13.68	PK
Vertical	4739.066	59.35	-20.12	39.22	54	-14.78	AV
Vertical	10620.110	64.75	-8.97	55.78	68.2	-12.42	PK
Vertical	10620.110	49.04	-8.97	40.07	54	-13.93	AV
Vertical	15930.029	61.90	-7.72	54.18	74	-19.82	PK
Vertical	15930.029	49.52	-7.72	41.80	54	-12.20	AV
Horizontal	4739.044	71.37	-20.12	51.24	68.2	-16.96	PK
Horizontal	4739.044	59.86	-20.12	39.74	54	-14.26	AV
Horizontal	10620.024	62.02	-8.97	53.05	68.2	-15.15	PK
Horizontal	10620.024	49.56	-8.97	40.59	54	-13.41	AV
Horizontal	15930.095	63.37	-7.72	55.65	74	-18.35	PK
Horizontal	15930.095	49.53	-7.72	41.81	54	-12.19	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX(5.3G) - 802.11ac-HT20
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5260 MHz)-Above 1G							
Vertical	4434.049	74.37	-20.73	53.64	68.2	-14.56	PK
Vertical	4434.049	59.56	-20.73	38.83	54	-15.17	AV
Vertical	10520.184	63.91	-9.12	54.79	68.2	-13.41	PK
Vertical	10520.184	49.75	-9.12	40.63	54	-13.37	AV
Vertical	15780.043	63.61	-7.77	55.84	74	-18.16	PK
Vertical	15780.043	49.92	-7.77	42.15	54	-11.85	AV
Horizontal	4434.140	73.47	-20.73	52.74	68.2	-15.46	PK
Horizontal	4434.140	59.66	-20.73	38.93	54	-15.07	AV
Horizontal	10520.047	62.54	-9.12	53.42	68.2	-14.78	PK
Horizontal	10520.047	49.96	-9.12	40.84	54	-13.16	AV
Horizontal	15780.016	62.66	-7.77	54.89	74	-19.11	PK
Horizontal	15780.016	49.93	-7.77	42.16	54	-11.84	AV
Middle Channel (5280 MHz)-Above 1G							
Vertical	4592.014	73.75	-20.42	53.34	74	-20.66	PK
Vertical	4592.014	59.97	-20.42	39.56	54	-14.44	AV
Vertical	10560.040	63.94	-9.06	54.88	68.2	-13.32	PK
Vertical	10560.040	49.70	-9.06	40.64	54	-13.36	AV
Vertical	15840.094	61.66	-7.75	53.91	74	-20.09	PK
Vertical	15840.094	49.22	-7.75	41.47	54	-12.53	AV
Horizontal	4592.154	71.88	-20.42	51.47	74	-22.53	PK
Horizontal	4592.154	59.34	-20.42	38.92	54	-15.08	AV
Horizontal	10560.160	62.51	-9.06	53.45	68.2	-14.75	PK
Horizontal	10560.160	49.81	-9.06	40.75	54	-13.25	AV
Horizontal	15840.119	60.39	-7.75	52.64	74	-21.36	PK
Horizontal	15840.119	49.44	-7.75	41.69	54	-12.31	AV
High Channel (5320 MHz)-Above 1G							
Vertical	4739.078	72.90	-20.12	52.78	74	-21.22	PK
Vertical	4739.078	59.62	-20.12	39.50	54	-14.50	AV
Vertical	10640.053	62.39	-8.94	53.45	68.2	-14.75	PK
Vertical	10640.053	49.53	-8.94	40.59	54	-13.41	AV
Vertical	15960.039	60.07	-7.71	52.36	74	-21.64	PK
Vertical	15960.039	49.91	-7.71	42.20	54	-11.80	AV
Horizontal	4739.049	71.56	-20.12	51.44	74	-22.56	PK
Horizontal	4739.049	59.12	-20.12	39.00	54	-15.00	AV
Horizontal	10640.091	60.52	-8.94	51.58	68.2	-16.62	PK
Horizontal	10640.091	49.97	-8.94	41.03	54	-12.97	AV
Horizontal	15960.044	63.80	-7.71	56.09	74	-17.91	PK
Horizontal	15960.044	49.57	-7.71	41.86	54	-12.14	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.

Test Mode:	TX(5.3G) - 802.11ac-HT40
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5270 MHz)-Above 1G							
Vertical	4434.003	72.92	-20.73	52.18	68.2	-16.02	PK
Vertical	4434.003	59.28	-20.73	38.54	54	-15.46	AV
Vertical	10540.118	63.56	-9.09	54.47	68.2	-13.73	PK
Vertical	10540.118	49.64	-9.09	40.55	54	-13.45	AV
Vertical	15810.100	60.72	-7.76	52.96	74	-21.04	PK
Vertical	15810.100	49.40	-7.76	41.64	54	-12.36	AV
Horizontal	4434.114	74.25	-20.73	53.52	74	-20.48	PK
Horizontal	4434.114	59.04	-20.73	38.31	54	-15.69	AV
Horizontal	10540.044	64.51	-9.09	55.42	68.2	-12.78	PK
Horizontal	10540.044	49.80	-9.09	40.71	54	-13.29	AV
Horizontal	15810.099	62.35	-7.76	54.59	74	-19.41	PK
Horizontal	15810.099	49.69	-7.76	41.93	54	-12.07	AV
Middle Channel (5310 MHz)-Above 1G							
Vertical	4739.145	72.78	-20.12	52.66	68.2	-15.54	PK
Vertical	4739.145	59.65	-20.12	39.53	54	-14.47	AV
Vertical	10620.122	62.23	-8.97	53.26	68.2	-14.94	PK
Vertical	10620.122	49.49	-8.97	40.52	54	-13.48	AV
Vertical	15930.104	64.51	-7.72	56.79	74	-17.21	PK
Vertical	15930.104	49.40	-7.72	41.68	54	-12.32	AV
Horizontal	4739.073	71.97	-20.12	51.85	68.2	-16.35	PK
Horizontal	4739.073	59.23	-20.12	39.11	54	-14.89	AV
Horizontal	10620.160	61.67	-8.97	52.70	68.2	-15.50	PK
Horizontal	10620.160	49.04	-8.97	40.07	54	-13.93	AV
Horizontal	15930.169	61.43	-7.72	53.71	74	-20.29	PK
Horizontal	15930.169	49.58	-7.72	41.86	54	-12.14	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode is MIMO Mode.