



FCC §15.247 (i), §2.1091 – RF Exposure

FCC ID: 2BN5S-2503S

Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: *f* is frequency in MHz

* = Power density limit is applicable at frequencies greater than 100 MHz

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: *f* = frequency in MHz

* = Plane-wave equivalent power density

MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=0.2m

TEST RESULTS

Main Power: 84.56dB μ V/m=84.56-95.2=-10.64dBm

30MHz-1G:-10.64+4.7=-5.94dBm

	Tune up Produce power	Maximum peak output power (dBm)	Output power to antenna (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm ²)	Limit (mW/ cm ²)	Result
915	-6±1	-5	0.32	1.48 (1.7dBi)	0.000094	0.61	Pass

	Tune up Produce power	Maximum peak output power (dBm)	Output power to antenna (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm ²)	Limit (mW/ cm ²)	Result
WIFI 2.4G	11±1	12	15.85	1.71 (2.32dBi)	0.005394	1	Pass
WIFI 5.1G	12±1	13	19.95	2.03 (3.07dBi)	0.008059	1	Pass
WIFI 5.3G	13±1	14	25.12	2.03 (3.07dBi)	0.010148	1	Pass
WIFI 5.6G	15±1	16	39.81	2.03 (3.07dBi)	0.016082	1	Pass
WIFI 5.8G	12±1	13	19.95	2.03 (3.07dBi)	0.008059	1	Pass



The report only evaluated the antenna values of the maximum antenna gain.

Simultaneous transmitting evaluation:

WIFI and 915

Mode	Power Density (S) (mW/ cm ²)	Simultaneous transmitting (mW/ cm ²)	Limit (mW/ cm ²)
2.4G WIFI	0.005394	0.02157	1
5G WIFI	0.016082		
915	0.000094		

Simultaneous transmitting=0.005394/1+0.016082/1+0.000094/0.61=0.021630098

For the max result : 0.021630098 \leq 1.0, compliance with FCC's RF Exposure