

TEST REPORT

Product Name : ROBOTIC POOL CLEANER
Model Number : SK03, Pleco SK02
FCC ID : 2BN5V-SK03

Prepared for : Nanjing Toua Robot Technology Co.,Ltd
Address : F11, Building 1, Chuangzhi Park, 99#Wan 'an North
Road,Jiangning District, Nanjing,Jiangsu, China

Prepared by : EMTEK (SHENZHEN) CO., LTD.
Address : Building 69, Majialong Industry Zone, Nanshan District,
Shenzhen, Guangdong, China

TEL:(0755) 26954280
FAX:(0755) 26954282

Report Number : ENS2506110027W00204R
Date of sample receipt : Mar 03, 2025
Date(s) of Tests : Mar 03, 2025 to Jun 12, 2025
Date of issue : Jun 13, 2025

Table of Contents

1. TEST RESULT CERTIFICATION	3
2. EUT SPECIFICATION	5
3. TEST REQUIREMENT:	6
RF EXPOSURE EVALUATION	6
4. MEASUREMENT RESULT	7



1. TEST RESULT CERTIFICATION

Applicant : Nanjing Toua Robot Technology Co.,Ltd
 Address : F11, Building 1, Chuangzhi Park, 99#Wan 'an North Road,Jiangning District, Nanjing,Jiangsu, China
 Manufacturer : Nanjing Toua Robot Technology Co.,Ltd
 Address : F11, Building 1, Chuangzhi Park, 99#Wan 'an North Road,Jiangning District, Nanjing,Jiangsu, China
 Factory : Anhui Toua Robot Co.,Ltd.
 Address : Building 4#, No.29, Runzhou Road, Danyang Town, Bowang District, Maanshan, Anhui Province, P.R.China
 EUT : ROBOTIC POOL CLEANER
 Model Name : SK03, Pleco SK02
 Trademark : N/A

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 15.247(i), § 2.1091	PASS

The above equipment was tested by EMTEK (SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 15.247(i), § 2.1091.

The test results of this report relate only to the tested sample identified in this report

Date of Test : Mar 03, 2025 to Jun 12, 2025

Prepared by : 
Una Yu /Editor

Reviewer : 
Joe Xia/Supervisor

Approve & Authorized Signer : 
Lisa Wang/Manager



Modified History

Version	Report No.	Revision Date	Summary
	ENS2506110027W00204R	/	Original Report



2. EUT Specification

Characteristics	Description
Product:	ROBOTIC POOL CLEANER
Model Number:	SK03, Pleco SK02 (Note: These models are the same, except for the model numbers;SK03 was selected for full test.)
Sample:	2#
Device Type:	BT/BLE 2.4G WIFI
Data Rate:	802.11b 802.11g 802.11n(20MHz channel bandwidth) 802.11n(40MHz channel bandwidth) 1Mbps for GFSK modulation 2Mbps for $\pi/4$ -DQPSK modulation 3Mbps for 8DPSK modulation 1Mbps for GFSK modulation
Modulation:	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n; GFSK, $\pi/4$ -DQPSK, 8DPSK
Operating Frequency Range(s) :	2412-2462MHz for 802.11b/g/n(HT20); 2422-2452MHz for 802.11n(HT40); 2402-2480MHz
Number of Channels:	11 channels for 802.11b/g/n(HT20); 7 Channels for 802.11n(HT40); BT: 79 channels BLE:40 channels
Transmit Power Max:	BT:-4.10 dBm(0.000389 W) BLE:-6.57 dBm(0.000220 W) 2.4G WIFI:13.26 dBm(0.021184 W)
Antenna Type:	FPC Antenna
Antenna Gain:	2.33 dBi
Power supply:	DC 5.0V from USB DC 3.65V built-in battery
Evaluation applied:	☒ MPE Evaluation ☐ SAR Evaluation

3. Test Requirement:

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} =output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π =3.1416

R =20, distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Antenna gain:
2.4G: 2.33 dBi

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain		(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	(dBi)	Numeric		
2412	11B	13.26	13±1	14	25.119	2.33	1.71	0.0085	1
2437		10.46	10±1	11	12.589	2.33	1.71	0.0043	1
2462		10.76	11±1	12	15.849	2.33	1.71	0.0054	1
2412	11G	11.53	11±1	12	15.849	2.33	1.71	0.0054	1
2437		8.53	8±1	9	7.943	2.33	1.71	0.0027	1
2462		8.22	8±1	9	7.943	2.33	1.71	0.0027	1
2412	11N20SISO	11.38	11±1	12	15.849	2.33	1.71	0.0054	1
2437		8.33	8±1	9	7.943	2.33	1.71	0.0027	1
2462		8	8±1	9	7.943	2.33	1.71	0.0027	1
2422	11N40SISO	9.69	9±1	10	10.000	2.33	1.71	0.0034	1
2437		7.79	7±1	8	6.310	2.33	1.71	0.0021	1
2452		7.47	7±1	8	6.310	2.33	1.71	0.0021	1

Antenna gain:
BT/BLE: 2.33 dBi

B7/DLE: 2.55 dB

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain		(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	(dBi)	Numeric		
2402	GFSK	-6.2	-6±1	-5	0.316	2.33	1.71	0.0001	1
2441		-8.45	-8±1	-7	0.200	2.33	1.71	0.0001	1
2480		-8.89	-8±1	-7	0.200	2.33	1.71	0.0001	1
2402	π/4-DQPSK	-4.39	-4±1	-3	0.501	2.33	1.71	0.0002	1
2441		-6.74	-6±1	-5	0.316	2.33	1.71	0.0001	1
2480		-7.4	-7±1	-6	0.251	2.33	1.71	0.0001	1
2402	8-DPSK	-4.1	-4±1	-3	0.501	2.33	1.71	0.0002	1
2441		-6.53	-6±1	-5	0.316	2.33	1.71	0.0001	1
2480		-7.01	-7±1	-6	0.251	2.33	1.71	0.0001	1
2402	GFSK (1M)	-6.57	-6±1	-5	0.316	2.33	1.71	0.0001	1
2440		-8.61	-8±1	-7	0.200	2.33	1.71	0.0001	1
2480		-9.19	-9±1	-8	0.158	2.33	1.71	0.0001	1

According to KDB 447498, no stand-alone required for WIFI antenna, and no simultaneous SAR measurement is required.

*** End of Report ***