



TEST REPORT

Application No.: DNT2502200186R1242-01627

Applicant: SHANTOU CITY CHENGHAI DISTRICT LIANXIA YILE PLASTIC TOY FACTORY

Address of Applicant: Huaidong Industrial Zone, Lianxia Town, Chenghai District, Shantou City, Guangdong Province, China

EUT Description: Toys series

Model No.: YL-111

FCC ID: 2BN69-YL-111

Power Supply
Remote control: DC 3V by AA Battery
Car: Input: DC 5V; DC 3.7V From Battery

Trade Mark: /
47 CFR FCC Part 2, Subpart J

Standards: 47 CFR Part 15, Subpart C
ANSI C63.10: 2013

Date of Receipt: 2025/02/21

Date of Test: 2025/02/22 to 2025/03/05

Date of Issue: 2025/03/20

Test Result: **PASS**

Prepared By: Wayne Lin (Testing Engineer)

Reviewed By: Pencils Chen (Project Engineer)

Approved By: Heise Shen (Manager)



Note: If there is any objection to the results in this report, please submit a written inquiry to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp, and is issued by the company in accordance with the requirements of the "Conditions of Issuance of Test Reports" printed in the attached page. Unless otherwise stated, the results presented in this report only apply to the samples tested this time. Partial reproduction of this report is not allowed unless approved by the company in writing.

Dongguan DN Testing Co., Ltd.

Add: No. 1, West Fourth Street, Xingfa South Road, Wusha Community, Chang 'an Town, Dongguan City, Guangdong P.R.China

Web: www.dn-testing.com

Tel: +86-769-88087383

E-mail: service@dn-testing.com



Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V2.0	/	Mar.20, 2025	Valid	Original Report



1 Test Summary

Test Item	Standard Section	Test Result
Antenna Requirement	15.203	PASS
20dB Occupied Bandwidth	15.215	PASS
Duty Cycle	N/A	PASS
Field Strength	15.249(a)	PASS
Radiated Spurious Emissions And Band Edge	15.205, 15.209, 15.249(a)(c)(d)(e), 15.35(b)	PASS
AC Power Line Conducted Emissions	15.207	N/A



Contents

1 Test Summary	3
2 General Information	5
2.1 Test Location	5
2.2 General Description of EUT	6
2.3 Power Setting of Test Software	9
2.4 Test Environment and Mode	9
2.5 Channel List	9
2.6 Description of Support Units	9
2.7 Test Facility	10
2.8 Measurement Uncertainty (95% confidence levels, k=2)	10
2.9 Equipment List	11
2.10 Assistant equipment used for test	12
3 Test results and Measurement Data	13
3.1 Antenna requirements	13
3.2 20dB Occupied Bandwidth	14
3.3 Duty Cycle	17
3.4 Field Strength of Fundamental	18
3.5 Radiated Spurious Emissions	24
3.6 AC Power Line Conducted Emissions	33



2 General Information

2.1 Test Location

Company:	Dongguan DN Testing Co., Ltd
Address:	No. 1, West Fourth Street, South Xinfu Road, Wusha Liwu, Chang 'an Town, Dongguan City, Guangdong P.R.China
Test engineer:	Wayne Lin



2.2 General Description of EUT

Manufacturer:	SHANTOU CITY CHENGHAI DISTRICT LIANXIA YILE PLASTIC TOY FACTORY
Address of Manufacturer:	Huaidong Industrial Zone, Lianxia Town, Chenghai District, Shantou City, Guangdong Province, China
EUT Description:	Toys series
Test Model No.:	YL-111
Additional Model(s):	58216,58218,58400,58401,58607,58608,58609,58611,58612,58615,58616,58617,58618, 58620, 58621,58622,58623,58624,58625,58626,58627, 58628,58629,58631,58632,58633,58634,58635,58636,58639,58641,58642,58643,58644,58645,58646,58647,58648,58649,58650,58651,58652, 58653,58654,58655,58656,58657,58658,58659,58660,58661,58662,58663,58664,58665,58666,58667,58668,58669,58670,58671,58672,58673,58674,58675,58676,58677,58678,58679,58680,58681,58682,58683,58684,58685,58686,58687,58688,58689,58690,58691,58692,58693, 58694,58695,58696,58697,58698,58699,58700,58701,58702,58703,58704,58705,58706,58707,58708,58709,58710,58711,58712,58713,58714,58715,58716,58717,58718,58719,58720,58721,58722,58723,58724,58725,58726,58727,58728,58729,58730,58731,58732,58733,58734,58735, 58736,58737,58738,58739,58740,58741,58742,58743,58744,58745,58746,58747,58748,58749,58750,58751,58752,58753,58754,58755,58756,58757,58758,58759,58760,58761,58762,58763,58764,58765,58766,58767,58768,58769,58770,58771,58772,58773,58774,58775,58776,58777, 58778,58779,58780,58781,58782,58783,58784,58620A,58630A,58631A, 58644A,YL-01,YL-02,YL-03, YL-06,YL-07,YL-08,YL-09,YL-09A,YL-10, YL-10A,YL-10TY,YL-11,YL-11A,YL-12,YL-12A,YL-13,YL-13A,YL-14, YL-14A,YL-15,YL-15A,YL-16,YL-16A,YL-17,YL-17A,YL-18,YL-18A,YL-19, YL-19A,YL-20,YL-20A,YL-21,YL-21A, YL-22,YL-22A,YL-23,YL-23A,YL-24,YL-24A,YL-25,YL-25A,YL-26,YL-27,YL-28,YL-29,YL-30,YL-30A,YL-31, YL-31A,YL-32,YL-32A,YL-33,YL-34,YL-34S,YL-35,YL-35S,YL-36,YL-36S,YL-37,YL-37S,YL-38,YL-38S,YL-39, YL-40,YL-42,YL-43,YL-44,YL-45,YL-46,YL-47,YL-48,YL-49,YL-50,YL-51,YL-52,YL-53,YL-54,YL-55,YL-56,YL-57, YL-58,YL-59,YL-60,YL-61,YL-62,YL-63,YL-64,YL-65,YL-66,YL-67,YL-68,YL-69,YL-70,YL-71,YL-72,YL-73,YL-74, YL-74-1,YL-75,YL-75-1,YL-76,YL-76-1,YL-77,YL-77-1,YL-78,YL-78-1,YL-79,YL-79-1,YL-80,YL-80-1,YL-80-2, YL-80-3,YL-80-4,YL-46-0,YL-46-1,YL-47-0,YL-47-1,YL-48-0,YL-48-1,YL-81,YL-81-1,YL-82,YL-82-1,YL-83, YL-83-1,YL-84,YL-84-1, YL-85,YL-85-1,YL-86,YL-86-1,YL-87,YL-87-1,YL-88,YL-88-1,YL-89,YL-89-1,YL-90, YL-90-1,YL-91,YL-91-1,YL-92,YL-92-1,YL-93,YL-93-1,YL-

Dongguan DN Testing Co., Ltd.



	94,YL-94-1,YL-95,YL-95-1,YL-96,YL-96-1,YL-97, YL-97-1,YL-98,YL-98-1,YL-99,YL-99-1,YL-100,YL-100-1,YL-101,YL-101-1,YL-102,YL-102-1,YL-103,YL-103-1, YL-104,YL-104-1,YL-105,YL-105-1,YL-106,YL-106-1,YL-107,YL-107-1,YL-108,YL-108-1,YL-109,YL-109-1, YL-110,YL-110-1,YL-111,YL-111-1,YL-112,YL-112-1,YL-113,YL-113-1,YL-114,YL-114-1,YL-115,YL-115-1, YL-116,YL-116-1,YL-117,YL-117-1,YL-118,YL-118-1,YL-119,YL-119-1,YL-120,YL-120-1,YL-121,YL-121-1, YL-122,YL-122-1,YL-123,YL-123-1,YL-124,YL-124-1,YL-125,YL-125-1,YL-126,YL-126-1,YL-127,YL-127-1, YL-128,YL-128-1,YL-129,YL-129-1,YL-130,YL-130-1,YL-131,YL-131-1,YL-132,YL-132-1,YL-133,YL-133-1, YL-134,YL-134-1,YL-135,YL-135-1,YL-136,YL-136-1,YL-137,YL-137-1,YL-138,YL-138-1,YL-139,YL-139-1, YL-140,YL-140-1,YL-141,YL-141-1,YL-142,YL-142-1,YL-143,YL-143-1,YL-144,YL-144-1,YL-145,YL-145-1, YL-146,YL-146-1,YL-147,YL-147-1,YL-148,YL-148-1,YL-149,YL-149-1,YL-150,YL-150-1,YL-151,YL-151-1, YL-152,YL-152-1,YL-153,YL-153-1,YL-154,YL-154-1,YL-155,YL-155-1,YL-156,YL-156-1,YL-157,YL-157-1, YL-158,YL-158-1,YL-159,YL-159-1,YL-160,YL-160-1,YL-161,YL-161-1,YL-162,YL-162-1,YL-163,YL-163-1, YL-164,YL-164-1,YL-165,YL-165-1,YL-166,YL-166-1,YL-167,YL-167-1,YL-168,YL-168-1,YL-169,YL-169-1, YL-170,YL-170-1,YL-171,YL-171-1,YL-172,YL-172-1,YL-173,YL-173-1,YL-174,YL-174-1,YL-175,YL-175-1, YL-176,YL-176-1,YL-177,YL-177-1,YL-178,YL-178-1,YL-179,YL-179-1,YL-180,YL-180-1,YL-181,YL-181-1, YL-182,YL-182-1,YL-183,YL-183-1,YL-184,YL-184-1,YL-185,YL-185-1,YL-186,YL-186-1,YL-187,YL-187-1, YL-188,YL-188-1,YL-189,YL-189-1,YL-190,YL-190-1,YL-191,YL-191-1,YL-192,YL-192-1,YL-193,YL-193-1, YL-194,YL-194-1,YL-195,YL-195-1,YL-196,YL-196-1,YL-197,YL-197-1,YL-198,YL-198-1,YL-199,YL-199-1, YL-200,YL-200-1,YL-201,YL-201-1,YL-202,YL-202-1,YL-203,YL-203-1,YL-204,YL-204-1,YL-205,YL-205-1, YL-206,YL-206-1,YL-207,YL-207-1,YL-208,YL-208-1,YL-209,YL-209-1,YL-210,YL-210-1.
Power Supply	Remote control: DC 3V by AA Battery Car:Input:DC 5V; DC 3.7V From Battery
Chip Type:	RF2020A
Serial number:	PR2502200186R1242
Trade Mark:	/
Hardware Version:	V1.0
Software Version:	V1.0
Operation Frequency:	2405MHz-2475MHz
Type of Modulation:	GFSK
Sample Type:	Prototype production



Antenna Type:	Copper Antenna
Antenna Ports	☒ Ant 1, ☐ Ant 2, ☐ Ant 3
Antenna Gain*:	☒ Provided by applicant
	0dBi
RF Cable*:	☒ Provided by applicant
	0.5dB(0.6~1GHz); 0.8dB(1.4~2GHz); 1.0dB(2.1~2.7GHz); 1.5dB(3~4GHz); 1.8dB(4.4~6GHz);

Remark:

*All models are just color differences, motherboard, PCB circuit board, chip, electronic components, appearance is all the same.

*Since the above data and/or information is provided by the applicant relevant results or conclusions of this report are only made for these data and/or information, DNT is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.

*The remote control only TX, the car only RX.



2.3 Power Setting of Test Software

Software Name	N/A		
Frequency(MHz)	2405	2445	2475
Setting	Default	Default	Default

2.4 Test Environment and Mode

Operating Environment:	
Temperature:	20~25.0 °C
Humidity:	45~56 % RH
Atmospheric Pressure:	101.0~101.30 KPa
Test mode:	
Transmitting mode:	Keep the EUT in transmitting mode with all kind of modulation and all kind of data rate.

2.5 Channel List

Operation Frequency of each channel					
Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2405	11	2428	21	2471
2	2407	12	2435	22	2472
3	2408	13	2445	23	2473
4	2410	14	2451	24	2474
5	2411	15	2452	25	2475
6	2414	16	2453		
7	2418	17	2454		
8	2422	18	2462		
9	2425	19	2469		
10	2427	20	2470		

2.6 Description of Support Units

The EUT has been tested independent unit.



2.7 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

Lab A:

• **FCC, USA**

Designation Number: CN1348

• **A2LA (Certificate No. 7050.01)**

DONGGUAN DN TESTING CO., LTD.

• **Innovation, Science and Economic Development Canada**

DONGGUAN DN TESTING CO., LTD. EMC Laboratory has been recognized by ISED as an accredited testing laboratory. CAB identifier is CN0149.

IC#: 30755.

2.8 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Total RF power, conducted	$\pm 0.41\text{dB}$
2	RF power density, conducted	$\pm 1.96\text{dB}$

No.	Item	Measurement Uncertainty
1	Conduction Emission	$\pm 3.0\text{dB}$ (150kHz to 30MHz)
2	Radiated Emission	$\pm 4.8\text{dB}$ (Below 1GHz)
		$\pm 4.8\text{dB}$ (1GHz to 6GHz)
		$\pm 4.5\text{dB}$ (6GHz to 18GHz)
		$\pm 5.02\text{dB}$ (Above 18GHz)



2.9 Equipment List

For Connect EUT Antenna Terminal Test					
Description	Manufacturer	Model	Serial Number	Cal date	Due date
Signal Generator	Keysight	N5181A-6G	MY48180415	2024-10-23	2025-10-22
Signal Generator	Keysight	N5182B	MY57300617	2024-10-23	2025-10-22
Power supply	Keysight	E3640A	ZB2022656	2024-10-23	2025-10-22
Spectrum Analyzer	Aglient	N9010A	MY52221458	2024-10-23	2025-10-22
BT/WIFI Test Software	Tonscend	JS1120 V3.1.83	NA	NA	NA
RF Control Unit	Tonscend	JS0806-2	22F8060581	NA	NA
temperature and humidity box	SCOTEK	SCD-C40-80PRO	6866682020008	2024-10-23	2025-10-22

Test Equipment for Conducted Emission					
Description	Manufacturer	Model	Serial Number	Cal Date	Due Date
Receiver	R&S	ESCI3	101152	2024-10-23	2025-10-22
LISN	R&S	ENV216	102874	2024-10-23	2025-10-22
ISN	R&S	ENY81-CA6	1309.8590.03	2024-10-23	2025-10-22

Test Equipment for Radiated Emission(below 1000MHz)					
Description	Manufacturer	Model	Serial Number	Cal Date	Due Date
Receiver	R&S	ESR7	102497	2024-10-23	2025-10-22
Test Software	ETS-LINDGREN	TiLE-FULL	NA	NA	NA
RF Cable	ETS-LINDGREN	RFC-NMS-100- NMS-350-IN	NA	2024-10-23	2025-10-22
Log periodic antenna	ETS-LINDGREN	VULB 9168	01475	2022-11-28	2025-11-27
Pre-amplifier	Schwarzbeck	BBV9743B	00423	2024-10-23	2025-10-22
Single ring magnetic field ring antenna	ETS-LINDGREN	6502	6502	2024-10-23	2025-10-22



Test Equipment for Radiated Emission(Above 1000MHz)					
Description	Manufacturer	Model	Serial Number	Cal Date	Due Date
Frequency analyser	Keysight	N9010A	MY52221458	2024-10-23	2025-10-22
RF Cable	ETS-LINDGREN	RFC-NMS-100- NMS-350-IN	NA	2024-10-23	2025-10-22
Horn Antenna	ETS-LINDGREN	3117	00252567	2022-11-28	2025-11-27
Double ridged waveguide antenna	ETS-LINDGREN	3116C	00251780	2022-11-28	2025-11-27
Test Software	ETS-LINDGREN	TILE-FULL	NA	NA	NA
Pre-amplifier	ETS-LINDGREN	3117-PA	252567	2024-10-23	2025-10-22
Pre-amplifier	ETS-LINDGREN	3116C-PA	251780	2024-10-23	2025-10-22

2.10 Assistant equipment used for test

Code	Equipment	Manufacturer	Model No.	Equipment No.
1	/			




3 Test results and Measurement Data

3.1 Antenna requirements

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.	
The antenna is welded on the main PCB and no consideration of replacement. The best case gain of the antenna is 0dBi.	



3.2 20dB Occupied Bandwidth



Test Requirement:	47 CFR Part 15C Section 15.215
Test Method:	ANSI C63.10:2013 Section 7.8.7
Test Setup:	
Instruments Used:	Refer to section 2.9 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the worst case
Limit:	no wider than 0.25% of the center frequency
Test Results:	Pass


Test Data:

Test Frequency (MHz)	20dB Bandwidth (MHz)	Result
2405	1.151	Pass
2445	1.205	Pass
2475	1.180	Pass



Test Graphs








3.3 Duty Cycle

Limit :N/A




The average correction factor is computed by analyzing the on time less than or equal to 100ms over one complete pulse train. Analysis of the remote transmitter on time in one complete pulse train, therefore the average value of fundamental frequency is: Average = Peak value + 20log (Duty cycle), where the duty factor is calculated from following formula:

$20\log (\text{Duty cycle}) = 20\log (0.27/12.06) = -33\text{dB}$

Please refer to below plots for more details.



3.4 Field Strength of Fundamental

Test Requirement:	47 CFR Part 15C Section 15.249(a)		
Test Method:	ANSI C63.10 :2020 Section 11.12		
Test Setup:			
Test Instruments:	Refer to section 2.9 for details		
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates		
Final Test Mode:	Through Pre-scan, find the worst case		
Limit:	Fundamental frequency		Field strength of fundamental@3m (microvolts/meter)
	902-928MHz		50
	2400-2483.5MHz		50
	5725-5875MHz		50
	24.0-24.25		250
	The EUT fundamental frequency is in 2400-2483.5MHz,So the Average Limit& Peak Limit is show in below table:		
	Fundamental frequency	Field strength of fundamental@3m (dBμV/m)	
	Average Limit	Peak Limit	
2400-2483.5MHz	94	114	
Note:	1. Average Limit (dBμV/m)=20×log[1000×Field Strength (mV/m)].		
	2. Peak Limit (dBμV/m)= Average Limit (dBμV/m)+20dB		
Test Configuration:	RBW: ≥OBW VBW: 3XRBW Start frequency: 2400MHz Stop frequency: 2483.5MHz Sweep Time: Auto Detector: PEAK/AVG		



	Trace Mode: Max Hold
Test Procedure:	a. the EUT was placed on the top of a rotating table 1 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case. r. Repeat above procedures until all frequencies measured was complete.
Test Results:	Pass




Test Data

Frequency (MHz)	20log (Duty cycle) (dB)	Peak Level (dBμV/m)	Average Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector Type	Polarity
2405	-33	95.94	62.94	94	31.06	AVG	H
2405	-33	87.22	54.22	94	39.78	AVG	V
2445	-33	95.78	62.78	94	31.22	AVG	H
2445	-33	86.05	53.05	94	40.95	AVG	V
2475	-33	94.01	61.01	94	32.99	AVG	H
2475	-33	89.02	56.02	94	37.98	AVG	V




2405MHz

Horizontal:



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dB μ V/m]	Margin [dB]	Height [cm]	Angle [°]	Remark
1	2405.13	96.65	-0.71	95.94	114.00	18.06	150	44	PK

Vertical:




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dB μ V/m]	Margin [dB]	Height [cm]	Angle [°]	Remark
1	2405.54	87.93	-0.71	87.22	114.00	26.78	150	225	PK




2445MHz

Horizontal:



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dB μ V/m]	Margin [dB]	Height [cm]	Angle [°]	Remark
1	2445.72	96.24	-0.46	95.78	114.00	18.22	150	48	PK

Vertical:




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dB μ V/m]	Margin [dB]	Height [cm]	Angle [°]	Remark
1	2445.14	86.51	-0.46	86.05	114.00	27.95	150	190	PK




2475MHz

Horizontal:



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dB μ V/m]	Margin [dB]	Height [cm]	Angle [°]	Remark
1	2475.83	94.34	-0.33	94.01	114.00	19.99	150	31	PK

Vertical:



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dB μ V/m]	Margin [dB]	Height [cm]	Angle [°]	Remark
1	2475.32	89.35	-0.33	89.02	114.00	24.98	150	182	PK

Note

1. The Measurement (Result Level) is calculated by Reading Level adding the Correct Factor(maybe including LISN Factor and the Cable Factor etc.), The basic equation is as follows:
Result Level= Reading Level + Correct Factor(including Ant.Factor ,Cable Factor etc.)
2. Average Level=Peak Level + 20log(Duty cycle)



3.5 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.249(a) 47 CFR Part 15C Section 15.209 47 CFR Part 15C Section 15.205				
Test Method:	ANSI C63.10 :2020 Section 11.12				
Test Site:	Measurement Distance: 3m or 10m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak
Limit:	Above 1GHz	Peak	1MHz	3MHz	Peak
	15.209 Radiated emission limits				
	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	Remark: Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.				
	The limits on the field strength of the spurious emissions in the below table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in §15.209, whichever limit permits a higher field strength.				



Fundamental frequency	Field strength of harmonics@3m (microvolts/meter)
902-928MHz	500
2400-2483.5MHz	500
5725-5875MHz	500
24.0-24.25	2500

The EUT fundamental frequency is 2400-2483.5MHz, So the Average Limit & Peak Limit is show in below table:

Fundamental frequency (MHz)	Field strength of spurious emission@3m (dBμV/m)	
	Average Limit	Peak Limit
2400-2483.5	54	74

Note:

1. Average Limit (dBμV/m) = $20 \times \log[1000 \times \text{Field Strength (mV/m)}]$.

2. Peak Limit (dBμV/m) = Average Limit (dBμV/m) + 20dB

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:

- h. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- i. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation
- j. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- k. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- l. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- m. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- n. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- o. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- p. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case.
- q. Repeat above procedures until all frequencies measured was complete.

Exploratory Test Mode:


Transmitting with all kind of modulations, data rates. Transmitting mode.



Final Test Mode:	Pretest the EUT at Transmitting mode. Through Pre-scan, find the worst case.
Instruments Used:	Refer to section 2.9 for details
Test Results:	Pass


Test data**For 30-1000MHz TX**

Vertical:



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark
1	47.84	28.27	-8.07	20.20	40.00	19.80	100	267	QP
2	79.83	29.76	-12.50	17.26	40.00	22.74	100	0	QP
3	150.12	28.84	-7.88	20.96	43.50	22.54	100	360	QP
4	244.92	30.00	-9.03	20.97	46.00	25.03	100	102	QP
5	444.23	30.25	-2.96	27.29	46.00	18.71	100	8	QP
6	857.02	32.01	4.56	36.57	46.00	9.43	100	299	QP

Horizontal:




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark
1	41.77	28.61	-8.54	20.07	40.00	19.93	100	278	QP
2	67.60	29.18	-9.70	19.48	40.00	20.52	100	360	QP
3	126.06	29.56	-9.78	19.78	43.50	23.72	100	313	QP
4	256.16	29.75	-8.76	20.99	46.00	25.01	100	46	QP
5	465.11	29.89	-2.43	27.46	46.00	18.54	100	36	QP
6	803.19	31.71	4.37	36.08	46.00	9.92	100	352	QP



For above 1GHz TX


2405MHz

Horizontal:



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark
1	4810.59	58.37	-4.61	53.76	74.00	20.24	150	66	PK
2	7215.21	45.24	-1.74	43.50	74.00	30.50	150	234	PK
3	9620.58	44.09	0.94	45.03	74.00	28.97	150	136	PK
4	4811.34	54.72	-4.61	50.11	54.00	3.89	150	66	AV
5	7215.21	35.82	-1.74	34.08	54.00	19.92	150	164	AV
6	9620.58	34.99	0.94	35.93	54.00	18.07	150	164	AV


Vertical:



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark
1	4811.34	59.13	-4.61	54.52	74.00	19.48	150	174	PK
2	7215.21	45.46	-1.74	43.72	74.00	30.28	150	286	PK
3	9620.58	42.91	0.94	43.85	74.00	30.15	150	147	PK
4	4812.09	53.96	-4.61	49.35	54.00	4.65	150	216	AV
5	7215.21	36.21	-1.74	34.47	54.00	19.53	150	62	AV
6	9620.58	34.64	0.94	35.58	54.00	18.42	150	342	AV


**2445MHz**

Horizontal:



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark
1	4891.59	63.05	-4.72	58.33	74.00	15.67	150	117	PK
2	7336.72	55.35	-1.46	53.89	74.00	20.11	150	160	PK
3	9780.34	43.62	1.73	45.35	74.00	28.65	150	103	PK
4	4892.34	50.25	-4.72	45.53	54.00	8.47	150	117	AV
5	7338.22	48.60	-1.44	47.16	54.00	6.84	150	160	AV
6	9780.34	34.53	1.73	36.26	54.00	17.74	150	302	AV

Vertical:




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark
1	4890.09	58.62	-4.72	53.90	74.00	20.10	150	357	PK
2	7337.47	52.63	-1.46	51.17	74.00	22.83	150	274	PK
3	9780.34	44.78	1.73	46.51	74.00	27.49	150	19	PK
4	4891.59	52.24	-4.72	47.52	54.00	6.48	150	357	AV
5	7336.72	51.06	-1.46	49.60	54.00	4.40	150	0	AV
6	9780.34	34.70	1.73	36.43	54.00	17.57	150	103	AV




2475MHz

Horizontal:



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark
1	4951.60	60.69	-4.85	55.84	74.00	18.16	150	230	PK
2	7425.97	57.98	-1.32	56.66	74.00	17.34	150	176	PK
3	9900.35	43.23	2.20	45.43	74.00	28.57	150	94	PK
4	4952.35	56.27	-4.85	51.42	54.00	2.58	150	230	AV
5	7427.47	51.65	-1.33	50.32	54.00	3.68	150	176	AV
6	9900.35	35.56	2.20	37.76	54.00	16.24	150	274	AV

Vertical:




NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark
1	4951.60	62.12	-4.85	57.27	74.00	16.73	150	356	PK
2	7426.72	54.63	-1.33	53.30	74.00	20.70	150	204	PK
3	9900.35	44.33	2.20	46.53	74.00	27.47	150	149	PK
4	4951.60	56.62	-4.85	51.77	54.00	2.23	150	176	AV
5	7427.47	48.33	-1.33	47.00	54.00	7.00	150	204	AV
6	9900.35	34.93	2.20	37.13	54.00	16.87	150	11	AV




2405MHz

Horizontal:



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark
1	2386.34	56.56	-0.81	55.75	74.00	18.25	150	34	PK
2	2390.01	48.71	-0.80	47.91	74.00	26.09	150	112	PK
3	2386.72	39.95	-0.81	39.14	54.00	14.86	150	272	AV
4	2390.01	39.58	-0.80	38.78	54.00	15.22	150	24	AV


Vertical:



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark
1	2388.25	50.44	-0.80	49.64	74.00	24.36	150	89	PK
2	2390.01	49.01	-0.80	48.21	74.00	25.79	150	335	PK
3	2387.92	40.08	-0.80	39.28	54.00	14.72	150	132	AV
4	2390.01	39.49	-0.80	38.69	54.00	15.31	150	325	AV


**2475MHz**

Horizontal:



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark
1	2483.50	48.76	-0.29	48.47	74.00	25.53	150	182	PK
2	2484.73	59.47	-0.27	59.20	74.00	14.80	150	313	PK
3	2483.50	39.04	-0.29	38.75	54.00	15.25	150	36	AV
4	2484.45	39.93	-0.28	39.65	54.00	14.35	150	36	AV

Vertical:



NO.	Freq. [MHz]	Reading Level [dBμV]	Correct Factor [dB/m]	Result Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark
1	2483.50	48.68	-0.29	48.39	74.00	25.61	150	128	PK
2	2484.55	55.52	-0.28	55.24	74.00	18.76	150	214	PK
3	2483.50	39.18	-0.29	38.89	54.00	15.11	150	246	AV
4	2484.84	39.95	-0.27	39.68	54.00	14.32	150	140	AV

Note:

1. The Measurement (Result Level) is calculated by Reading Level adding the Correct Factor(maybe including Ant.Factor and the Cable Factor etc.), The basic equation is as follows:

Measurement Level= Reading Level + Correct Factor(including LISN Factor ,Cable Factor etc.)

2. The amplitude of 9KHz to 30MHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.





	Charge + Transmitting mode.
Final Test Mode:	Through Pre-scan, find the 6.5Mbps of rate of 802.11n(HT20) at lowest channel is the worst case. Charge + Transmitting mode. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 2.9 for details
Test Results:	N/a

---END REPORT---