


TEST REPORT

FCC ID.	2BN8F-CAMR50-4G
Test Report No.	TCT250618E014
Date of issue	Jun. 26, 2025
Testing laboratory	SHENZHEN TONGCE TESTING LAB
Testing location/ address:	2101 & 2201, Zhenchang Factory Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China
Applicant's name	NUMLAKE TECH LIMITED
Address	UNIT 1505, 15/F WORKINGPORT COMMERCIAL BUILDING 3 HAU FOK STREET TSIM SHA TSUI HONG KONG, China
Manufacturer's name	NUMLAKE TECH LIMITED
Address	UNIT 1505, 15/F WORKINGPORT COMMERCIAL BUILDING 3 HAU FOK STREET TSIM SHA TSUI HONG KONG, China
Standard(s)	FCC CFR Title 47 Part 1.1307
Product Name	4G 1080p Battery Camera with Solar Panel
Trade Mark	N/A
Model/Type reference	R50-4G, R10-4G, R20-4G, R30-4G, R60-4G, R70-4G, R80-4G, R90-4G
Rating(s)	Rechargeable Li-ion Battery DC 3.7V
Date of receipt of test item	Jun. 18, 2025
Date (s) of performance of test	Jun. 18, 2025 ~ Jun. 26, 2025
Tested by (+signature)	Aaron MO
Check by (+signature)	Beryl ZHAO
Approved by (+signature) :	Tomsin



General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

Table of Contents

1. General Product Information	3
1.1. EUT description	3
1.2. Model(s) list.....	3
2. General Information.....	4
2.1. Test environment and mode.....	4
2.2. Description of Support Units.....	4
3. Facilities and Accreditations	5
3.1. Facilities	5
3.2. Location	5
4. Test Results and Measurement Data	6

1. General Product Information

1.1. EUT description

Product Name.....	4G 1080p Battery Camera with Solar Panel
Model/Type reference.....	R50-4G
Sample Number.....	TCT250618E013-0101
Operation Frequency	LTE Band 2: TX: 1850 MHz ~ 1910 MHz RX: 1930 MHz ~ 1990 MHz LTE Band 4: TX: 1710 MHz ~ 1755 MHz RX: 2110 MHz ~ 2155 MHz LTE Band 5: TX: 824 MHz ~ 849 MHz RX: 869 MHz ~ 894 MHz LTE Band 12: TX: 699 MHz ~ 716 MHz RX: 729 MHz ~ 746 MHz LTE Band 13: TX: 777 MHz ~ 787 MHz RX: 746 MHz ~ 756 MHz LTE Band 66: TX: 1710 MHz ~ 1780 MHz RX: 2110 MHz ~ 2180 MHz
Modulation Type.....	QPSK, 16-QAM
Antenna Type.....	External Antenna
Antenna Gain.....	LTE Band 2: 0.78dBi LTE Band 4: 1.67dBi LTE Band 5: 2.11dBi LTE Band 12: 0.93dBi LTE Band 13: 2.11dBi LTE Band 66: 1.67dBi
Rating(s).....	Rechargeable Li-ion Battery DC 3.7V

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. Model(s) list

No.	Model No.	Tested with
1	R50-4G	<input checked="" type="checkbox"/>
Other models	R10-4G, R20-4G, R30-4G, R60-4G, R70-4G, R80-4G, R90-4G	<input type="checkbox"/>

Note: R50-4G is tested model, other models are derivative models. The models are identical in circuit and PCB layout, only different on the model names and color. So the test data of R50-4G can represent the remaining models.

2. General Information

2.1. Test environment and mode

Item	Normal condition	
Temperature	+25°C	
Voltage	DC 3.7V	
Humidity	56%	
Atmospheric Pressure:	1008 mbar	
Test Mode:		
Engineering mode:	Keep the EUT in continuous transmitting by select channel	

2.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 20dB Occupied Bandwidth, Carrier Frequencies Separation, Hopping Channel Number, Dwell Time, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

3. Facilities and Accreditations

3.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- A2LA-No.: 4320.01

SHENZHEN TONGCE TESTING LAB

The testing lab has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories.

3.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339

4. Test Results and Measurement Data

According to §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Remark: 1)

- For LTE Band 2:** The maximum output power for antenna is 24.19dBm (262.42mW) at 1860MHz, 0.78dBi antenna gain (with 1.20 numeric antenna gain.)
- For LTE Band 4:** The maximum output power for antenna is 24.82dBm (303.39mW) at 1754.3MHz, 1.67dBi antenna gain (with 1.47 numeric antenna gain.)
- For LTE Band 5:** The maximum output power for antenna is 23.52dBm (224.91mW) at 844MHz, 2.11dBi antenna gain (with 1.63 numeric antenna gain.)
- For LTE Band 12:** The maximum output power for antenna is 22.74dBm (187.93mW) at 711MHz, 0.93dBi antenna gain (with 1.24 numeric antenna gain.)
- For LTE Band 13:** The maximum output power for antenna is 23.19dBm (208.45mW) at 782MHz, 2.11dBi antenna gain (with 1.63 numeric antenna gain.)
- For LTE Band 66:** The maximum output power for antenna is 24.93dBm (311.17mW) at 1745MHz, 1.67dBi antenna gain (with 1.47 numeric antenna gain.)

- 2) For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20cm, even if the calculation indicate that the MPE distance would be lesser.

Calculation:

Given $E = \frac{\sqrt{30*P*G}}{d}$ & $S = \frac{E^2}{3770}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Substituting the MPE safe distance using $d=20\text{cm}$ into above equation.

Yields: $S=0.000199*P*G$

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=frequency in MHz
*=Plane-wave equivalent power density
RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

LTE:

Mode	Power(mW)	numeric antenna gain	Power density (mW/cm ²)	Limit (mW/cm ²)	Result
LTE Band 2	262.42	1.20	0.06267	1	Pass
LTE Band 4	303.39	1.47	0.08875	1	
LTE Band 5	224.91	1.63	0.07295	0.562667	
LTE Band 12	187.93	1.24	0.04637	0.474000	
LTE Band 13	208.45	1.63	0.06762	0.521333	
LTE Band 66	311.17	1.47	0.09103	1	

*******END OF REPORT*******