

# TEST REPORT

<b>FCC ID.</b> .....	2BN8F-VDT52
<b>Test Report No.</b> .....	TCT250822E034
<b>Date of issue</b> .....	Aug. 27, 2025
<b>Testing laboratory</b> .....	SHENZHEN TONGCE TESTING LAB
<b>Testing location/ address:</b>	2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China
<b>Applicant's name</b> .....	NUMLAKE TECH LIMITED
<b>Address</b> .....	UNIT 1505, 15/F WORKINGPORT COMMERCIAL BUILDING 3 HAU FOK STREET TSIM SHA TSUI HONG KONG, China
<b>Manufacturer's name</b> .....	NUMLAKE TECH LIMITED
<b>Address</b> .....	UNIT 1505, 15/F WORKINGPORT COMMERCIAL BUILDING 3 HAU FOK STREET TSIM SHA TSUI HONG KONG, China
<b>Standard(s)</b> .....	FCC CFR Title 47 Part 1.1307
<b>Product Name</b> .....	Doorbell Camera
<b>Trade Mark</b> .....	N/A
<b>Model/Type reference</b> .....	T52, M20, M50, M51, M52, P20, P50, P51, P52, T20, T50, T51
<b>Rating(s)</b> .....	Rechargeable Li-ion Battery DC 3.7V
<b>Date of receipt of test item</b> .....	Aug. 22, 2025
<b>Date (s) of performance of test</b> .....	Aug. 22, 2025 ~ Aug. 27, 2025
<b>Tested by (+signature)</b> .....	Ronaldo LUO
<b>Check by (+signature)</b> .....	Beryl ZHAO
<b>Approved by (+signature)</b> :	Tomsin



#### General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

## Table of Contents

<b>1. General Product Information .....</b>	<b>3</b>
1.1. EUT description .....	3
1.2. Model(s) list.....	3
<b>2. General Information.....</b>	<b>4</b>
2.1. Test environment and mode.....	4
2.2. Description of Support Units.....	4
<b>3. Facilities and Accreditations .....</b>	<b>5</b>
3.1. Facilities .....	5
3.2. Location .....	5
<b>4. Limit .....</b>	<b>6</b>
<b>5. Test Results and Measurement Data .....</b>	<b>7</b>

## 1. General Product Information

### 1.1. EUT description

<b>Product Name</b> .....	Doorbell Camera
<b>Model/Type reference</b> .....	T52
<b>Sample Number</b> .....	TCT250822E025-0101
<b>Operation Frequency</b> .....	For BLE: 2402MHz~2480MHz For WIFI: 2412MHz~2462MHz (802.11b/802.11g/802.11n(HT20))
<b>Modulation Type</b> .....	For BLE: GFSK For WIFI: 802.11b: Direct Sequence Spread Spectrum (DSSS) 802.11g/802.11n: Orthogonal Frequency Division Multiplexing (OFDM)
<b>Antenna Type</b> .....	Internal Antenna
<b>Antenna Gain</b> .....	2.99dBi
<b>Rating(s)</b> .....	Rechargeable Li-ion Battery DC 3.7V

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

### 1.2. Model(s) list

No.	Model No.	Tested with
1	T52	<input checked="" type="checkbox"/>
Other models	M20, M50, M51, M52, P20, P50, P51, P52, T20, T50, T51	<input type="checkbox"/>

Note: T52 is tested model, other models are derivative models. The models are identical in circuit and PCB layout, only different on the model names. So the test data of T52 can represent the remaining models.

## 2. General Information

### 2.1. Test environment and mode

Item	Normal condition
Temperature	+25°C
Voltage	DC 3.7V
Humidity	56%
Atmospheric Pressure:	1008 mbar
<b>Test Mode:</b>	
Transmitting Mode:	Keep the EUT in continuous transmitting by select channel

### 2.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

#### Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 20dB Occupied Bandwidth, Carrier Frequencies Separation, Hopping Channel Number, Dwell Time, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

### 3. Facilities and Accreditations

#### 3.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098  
SHENZHEN TONGCE TESTING LAB  
Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- A2LA-No.: 4320.01  
SHENZHEN TONGCE TESTING LAB

The testing lab has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories.

#### 3.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict,

Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339

#### 4. Limit

According to §1.1310, the limit is as follow,

TABLE 1 TO § 1.1310(e)(1)—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE  
(MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(i) LIMITS FOR OCCUPATIONAL/CONTROLLED EXPOSURE				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
(ii) LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

*f = frequency in MHz. \* = Plane-wave equivalent power density.*

## 5. Test Results and Measurement Data

According to §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Remark: 1) **For BLE:** The maximum output power for antenna is 3.33dBm (2.15mW) at 2440MHz, 2.99dBi antenna gain (with 1.99 numeric antenna gain.)  
**For WIFI:** The maximum output power for antenna is 13.26dBm (21.18mW) at 2437MHz, 2.99dBi antenna gain (with 1.99 numeric antenna gain.)

2) For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20cm, even if the calculation indicate that the MPE distance would be lesser.

### Calculation

$$\text{Given } E = \sqrt{\frac{30 \times P \times G}{d}} \quad \& \quad S = \frac{E^2}{3770}$$

Where  
*E* = Field Strength in Volts / meter  
*P* = Power in Watts  
*G* = Numeric antenna gain  
*d* = Distance in meters  
*S* = Power Density in milliwatts / square centimeter

Substituting the MPE safe distance using *d*=20cm into above equation.  
Yields:  $S=0.000199*P*G$

Mode	Power (dBm)	Power (mW)	numeric antenna gain	Power density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
<b>BLE</b>	3.33	2.15	1.99	0.000851	1.00	PASS
<b>WIFI</b>	13.26	21.18	1.99	0.008387	1.00	

\*\*\*\*\*END OF REPORT\*\*\*\*\*