



FCC TEST REPORT

FCC ID: 2BN93-HS-X32PRO

On Behalf of

huashiweiye(shenzhen)kejiyouxiangongsi

Portable TV / Portable Touch Screen TV

Model No.: HS-X32 PRO, Other see model list

Prepared for : huashiweiye(shenzhen)kejiyouxiangongsi
901, Building B, Guancheng Low Carbon Industrial Park,
Address : Shangcun Community, Gongming Street, Guangming District,
Shenzhen

Prepared By : Shenzhen Alpha Product Testing Co., Ltd.
Address : Building i, No.2, Lixin Road, Fuyong Street, Bao'an District,
518103, Shenzhen, Guangdong, China

Report Number : A2503070-C01-R04
Date of Receipt : March 11, 2025
Date of Test : March 11, 2025 – April 1, 2025
Date of Report : April 5, 2025
Version Number : V0
Result **Pass**

TABLE OF CONTENTS

	Description	Page
1	TEST SUMMARY	5
1.1	MEASUREMENT UNCERTAINTY.....	5
2	GENERAL INFORMATION	6
2.1	GENERAL DESCRIPTION OF EUT	6
2.2	TEST MODE	7
2.3	TEST FACILITY	7
2.4	DESCRIPTION OF SUPPORT UNITS	7
2.5	DEVIATION FROM STANDARDS.....	7
2.6	ABNORMALITIES FROM STANDARD CONDITIONS.....	7
2.7	OTHER INFORMATION REQUESTED BY THE CUSTOMER	7
2.8	ADDITIONAL INSTRUCTIONS	7
3	TEST INSTRUMENTS LIST	8
4	TEST RESULTS AND MEASUREMENT DATA.....	9
4.1	ANTENNA REQUIREMENT:	9
4.2	CONDUCTED EMISSIONS	10
4.3	EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH.....	13
4.4	PEAK TRANSMIT POWER	74
4.5	POWER SPECTRAL DENSITY.....	77
4.6	BAND EDGE.....	110
4.7	RADIATED EMISSION	130
5	MODEL LIST	135

TEST REPORT DECLARATION

Applicant : huashiweiye(shenzhen)kejijouxiangongsi
Address : 901, Building B, Guancheng Low Carbon Industrial Park, Shangcun Community,
Gongming Street, Guangming District, Shenzhen
Manufacturer : huashiweiye(shenzhen)kejijouxiangongsi
Address : 901, Building B, Guancheng Low Carbon Industrial Park, Shangcun Community,
Gongming Street, Guangming District, Shenzhen
EUT Description : Portable TV / Portable Touch Screen TV
(A) Model No. : HS-X32 PRO, Other see model list
(B) Trademark : HshWeiy

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart E

ANSI C63.4:2014, ANSI C63.10:2013

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits both conducted and radiated emissions. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....:

Yannis Wen
Project Engineer



Approved by (name + signature).....:

Jack Xu
Project Manager



Date of issue.....:

April 5, 2025

Revision History

Revision	Issue Date	Revisions	Revised By
V0	April 5, 2025	Initial released Issue	Yannis Wen

1 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	Section 15.203 Section 7.1.4	PASS
AC Power Line Conducted Emission	Section 15.207 Section 7.2.4 ANSI C63.10	PASS
Peak Transmit Power	Section 15.407(a)	PASS
Power Spectral Density	Section 15.407(a)	PASS
Undesirable Emission	Section 15.407(b)	PASS
26dB/6dB&99% Bandwidth	Section 15.407	PASS
Radiated Emission	Section 15.407(b)&15.209 Section 5.5 ANSI C63.10	PASS
Band Edge	15.205, ANSI C63.10	PASS

Remark:

1. Pass: The EUT complies with the essential requirements in the standard.
2. N/A is an abbreviation for Not Applicable.
3. Frequency Stability: The manufacturer stated in the user's manual.
4. The conclusion of this test report is judged by actual test data without considering measurement uncertainty.

1.1 Measurement Uncertainty

Item	Uncertainty
Uncertainty for Power point Conducted Emissions Test	1.63dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	3.5dB
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.74dB(Polarize: V)
	3.76dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	3.77dB(Polarize: V)
	3.80dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (18GHz to 40GHz)	4.31 dB(Polarize: V)
	4.30 dB(Polarize: H)
Uncertainty for radio frequency	5.06×10^{-8} GHz
Uncertainty for conducted RF Power	0.40dB
Uncertainty for temperature	0.2°C
Uncertainty for humidity	1%
Uncertainty for DC and low frequency voltages	0.06%

2 General Information

2.1 General Description of EUT

EUT Name	: Portable TV / Portable Touch Screen TV
Model No.	: HS-X32 PRO, Other see model list
DIFF.	: There is no difference except for sales regions and channels. All tests are made with the HS-X32 PRO model.
Power supply	: DC 12V from DC port or DC from the storage battery
Radio Technology	: 5G WIFI
Operation Frequency	: 802.11a/n(HT20)/ac(VHT20): 5180~5240MHz; 5260-5320MHz; 5500-5700MHz; 5745~5825MHz 802.11n(HT40)/ac(VHT40): 5190~5230MHz; 5270-5310MHz; 5510-5670MHz; 5755~5795MHz 802.11ac(VHT80): 5210MHz, 5290MHz, 5530MHz, 5775MHz
Channel separation	: 20MHz for 802.11a/ 802.11ac(VHT20)/ 802.11n(HT20) 40MHz for 802.11ac(VHT40)/ 802.11n(HT40) 80MHz for 802.11ac(VHT80)
Modulation technology:	: IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Type	: Internal antenna, max gain 3.59dBi (Antenna information is provided by applicant.)
Software version	: V1.0
Hardware version	: V1.0
Intend use environment	: Residential, commercial and light industrial environment

2.2 Test mode

Transmitting mode Keep the EUT in transmitting with modulation.
EUT was test with 99% duty cycle at its maximum power control level.

Remark: 1. During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.

2.3 Test Facility

Shenzhen Alpha Product Testing Co., Ltd
Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103, Shenzhen, Guangdong, China

2.4 Description of Support Units

Accessories : N/A
Manufacturer : N/A
Model : N/A
Ratings : N/A

2.5 Deviation from Standards

None.

2.6 Abnormalities from Standard Conditions

None.

2.7 Other Information Requested by the Customer

None.

2.8 Additional instructions

Software (Used for test) from client

Channel	Power level
Lowest	Default
Middle	Default
Highest	Default

3 Test Instruments list

Equipment	Manufacture	Model No.	Firmware version	Serial No.	Last cal.	Cal Interval
9*6*6 anechoic chamber	CHENYU	9*6*6	/	N/A	2025.03.09	4Year
4*4*3 Shielded room	CHENYU	4*4*3	/	N/A	2025.03.09	4Year
Spectrum analyzer	ROHDE&SCHWARZ	FSV40-N	2.3	102137	2024.08.08	1Year
Spectrum analyzer	Agilent	N9020A	A.14.16	MY499100060	2024.08.08	1Year
Receiver	ROHDE&SCHWARZ	ESR	2.28 SP1	1316.3003K03-102082-Wa	2024.08.08	1Year
Receiver	R&S	ESCI	4.42 SP1	101165	2024.08.08	1Year
Bilog Antenna	Schwarzbeck	VULB 9168	/	VULB 9168#627	2023.08.28	2Year
Horn Antenna	SCHWARZBECK	BBHA 9120 D	/	2106	2023.08.19	2Year
Loop Antenna	SCHWARZBECK	FMZB 1519B	/	00128	2023.08.19	2Year
RF Cable	Resenberger	Cable 1	/	RE1	2024.08.08	1Year
RF Cable	Resenberger	Cable 2	/	RE2	2024.08.08	1Year
RF Cable	Resenberger	Cable 3	/	CE1	2024.08.08	1Year
Pre-amplifier	HP	HP8347A	/	2834A00455	2024.08.08	1Year
Pre-amplifier	Agilent	8449B	/	3008A02664	2024.08.08	1Year
L.I.S.N.#1	Schwarzbeck	NSLK8126	/	8126-466	2024.08.08	1Year
L.I.S.N.#2	ROHDE&SCHWARZ	ENV216	/	101043	2024.08.08	1Year
Horn Antenna	SCHWARZBECK	BBHA 9170	/	00946	2023.08.19	2Year
Preamplifier	SKET	LNPA_1840-50	/	SK2018101801	2024.08.08	1 Year
Power Meter	Agilent	E9300A	/	MY41496628	2024.08.08	1 Year
Power Sensor	DARE	RPR3006W	/	15100041SNO91	2024.08.08	1 Year
Temp. & Humid. Chamber	Teelong	TL-HW408S	/	TL-20191205-01	2024.07.15	1 Year
Electronic Thermo-Hygrometer	S.H.Qixiang	HTC-1	/	N/A	2024.08.11	1 Year
Switching Mode Power Supply	JUNKE	JK12010S	/	20140927-6	2024.08.08	1 Year
Adjustable attenuator	MWRFTest	N/A	/	N/A	N/A	N/A
10dB Attenuator	Mini-Circuits	DC-6G	/	N/A	N/A	N/A


Software Information			
Test Item	Software Name	Manufacturer	Version
RE	EZ-EMC	EZ	Alpha-3A1
CE	EZ-EMC	EZ	Alpha-3A1
RF-CE	MTS 8310	MW	V2.0.0.0

4 Test results and Measurement Data

4.1 Antenna requirement:

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
E.U.T Antenna:	
The antenna is internal antenna. The best case gain of the antenna is 3.59dBi, for 5180~5240MHz; 5260-5320MHz; 5500-5700MHz; 5745~5825MHz	


4.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207		
Test Method:	ANSI C63.10:2013		
Test Frequency Range:	150KHz to 30MHz		
Class Severity:	Class B		
Class B			
Receiver setup:	RBW=9KHz, VBW=30KHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
	* Decreases with the logarithm of the frequency.		
Test procedure	The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). The provide a 50ohm/50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs). Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.		
Test setup:	 Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m		
Test Instruments:	Refer to section 5.10 for details		
Test mode:	Refer to section 5.3 for details		
Test results:	Pass		

Measurement Data

An initial pre-scan was performed on the line and neutral lines with peak detector. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Line:




*:Maximum data x:Over limit !:over margin

(Reference Only)

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable


Neutral:



*:Maximum data x:Over limit !:over margin (Reference Only)

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

4.3 Emission Bandwidth and 99% Occupied Bandwidth

Test Requirement:	FCC Part15 E Section 15.407
Test Method:	KDB 789033 D02 General UNII Test Procedures New Rules v02r01
Limit:	>500kHz for 6 dB bandwidth
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer, shown with a grid and a green trace, is connected to an E.U.T. (Equipment Under Test) box by a red cable. Both the Spectrum Analyzer and the E.U.T. are positioned on a Non-Conducted Table, which is supported by two vertical legs. Below the table is a Ground Reference Plane, represented by a thick gray bar.
Test procedure:	According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Test Instruments:	Refer to section 5.10 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass


Measurement Data:

Band 1 (5150-5250 MHz):

-26dB Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	-26 dB Bandwidth (MHz)
NVNT	a	5180	Ant1	22.35
NVNT	a	5200	Ant1	22.14
NVNT	a	5240	Ant1	23.13
NVNT	ac20	5180	Ant1	23.4
NVNT	ac20	5200	Ant1	23.94
NVNT	ac20	5240	Ant1	23.1
NVNT	ac40	5190	Ant1	40.38
NVNT	ac40	5230	Ant1	41.16
NVNT	ac80	5210	Ant1	85.92
NVNT	n20	5180	Ant1	22.65
NVNT	n20	5200	Ant1	23.46
NVNT	n20	5240	Ant1	24.09
NVNT	n40	5190	Ant1	40.26
NVNT	n40	5230	Ant1	41.34

-26dB Bandwidth NVNT a 5180MHz Ant1




Date: 28.MAR.2025 11:08:53


-26dB Bandwidth NVNT a 5200MHz Ant1




-26dB Bandwidth NVNT a 5240MHz Ant1




-26dB Bandwidth NVNT ac20 5180MHz Ant1




-26dB Bandwidth NVNT ac20 5200MHz Ant1




-26dB Bandwidth NVNT ac20 5240MHz Ant1




-26dB Bandwidth NVNT ac40 5190MHz Ant1




-26dB Bandwidth NVNT ac40 5230MHz Ant1




-26dB Bandwidth NVNT ac80 5210MHz Ant1




-26dB Bandwidth NVNT n20 5180MHz Ant1




-26dB Bandwidth NVNT n20 5200MHz Ant1




-26dB Bandwidth NVNT n20 5240MHz Ant1



-26dB Bandwidth NVNT n40 5190MHz Ant1




-26dB Bandwidth NVNT n40 5230MHz Ant1



Occupied Channel Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	a	5180	Ant1	16.573
NVNT	a	5200	Ant1	16.513
NVNT	a	5240	Ant1	16.573
NVNT	ac20	5180	Ant1	17.742
NVNT	ac20	5200	Ant1	17.772
NVNT	ac20	5240	Ant1	17.682
NVNT	ac40	5190	Ant1	36.324
NVNT	ac40	5230	Ant1	36.324
NVNT	ac80	5210	Ant1	75.764
NVNT	n20	5180	Ant1	17.712
NVNT	n20	5200	Ant1	17.712
NVNT	n20	5240	Ant1	17.892
NVNT	n40	5190	Ant1	36.324
NVNT	n40	5230	Ant1	36.683

OBW NVNT a 5180MHz Ant1




Date: 28.MAR.2025 11:08:45

OBW NVNT a 5200MHz Ant1




Date: 28.MAR.2025 11:17:10

OBW NVNT a 5240MHz Ant1




Date: 28.MAR.2025 11:20:00

OBW NVNT ac20 5180MHz Ant1




Date: 28.MAR.2025 11:31:44


OBW NVNT ac20 5200MHz Ant1




OBW NVNT ac20 5240MHz Ant1




OBW NVNT ac40 5190MHz Ant1




OBW NVNT ac40 5230MHz Ant1




OBW NVNT ac80 5210MHz Ant1




OBW NVNT n20 5180MHz Ant1




OBW NVNT n20 5200MHz Ant1



OBW NVNT n20 5240MHz Ant1




OBW NVNT n40 5190MHz Ant1



Date: 28.MAR.2025 14:11:56


OBW NVNT n40 5230MHz Ant1



Date: 28.MAR.2025 14:27:36


Band 2 (5250-5350 MHz):**-26dB Bandwidth**

Condition	Mode	Frequency (MHz)	Antenna	-26 dB Bandwidth (MHz)
NVNT	a	5260	Ant1	22.53
NVNT	a	5280	Ant1	21.09
NVNT	a	5320	Ant1	23.7
NVNT	ac20	5260	Ant1	22.26
NVNT	ac20	5280	Ant1	24.24
NVNT	ac20	5320	Ant1	25.23
NVNT	ac40	5270	Ant1	40.98
NVNT	ac40	5310	Ant1	41.34
NVNT	ac80	5290	Ant1	82.56
NVNT	n20	5260	Ant1	24.15
NVNT	n20	5280	Ant1	23.25
NVNT	n20	5320	Ant1	22.5
NVNT	n40	5270	Ant1	41.22
NVNT	n40	5310	Ant1	40.32


-26dB Bandwidth NVNT a 5260MHz Ant1

Date: 28.MAR.2025 15:44:54


-26dB Bandwidth NVNT a 5280MHz Ant1




-26dB Bandwidth NVNT a 5320MHz Ant1




-26dB Bandwidth NVNT ac20 5260MHz Ant1




-26dB Bandwidth NVNT ac20 5280MHz Ant1




-26dB Bandwidth NVNT ac20 5320MHz Ant1




-26dB Bandwidth NVNT ac40 5270MHz Ant1




-26dB Bandwidth NVNT ac40 5310MHz Ant1




-26dB Bandwidth NVNT ac80 5290MHz Ant1




-26dB Bandwidth NVNT n20 5260MHz Ant1




-26dB Bandwidth NVNT n20 5280MHz Ant1




-26dB Bandwidth NVNT n20 5320MHz Ant1



-26dB Bandwidth NVNT n40 5270MHz Ant1



-26dB Bandwidth NVNT n40 5310MHz Ant1




Date: 28.MAR.2025 16:24:28

Occupied Channel Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	a	5260	Ant1	16.603
NVNT	a	5280	Ant1	16.484
NVNT	a	5320	Ant1	16.603
NVNT	ac20	5260	Ant1	17.862
NVNT	ac20	5280	Ant1	17.892
NVNT	ac20	5320	Ant1	17.802
NVNT	ac40	5270	Ant1	36.444
NVNT	ac40	5310	Ant1	36.324
NVNT	ac80	5290	Ant1	75.884
NVNT	n20	5260	Ant1	17.892
NVNT	n20	5280	Ant1	17.832
NVNT	n20	5320	Ant1	17.802
NVNT	n40	5270	Ant1	36.683
NVNT	n40	5310	Ant1	36.503

OBW NVNT a 5260MHz Ant1




Date: 28.MAR.2025 15:44:46

OBW NVNT a 5280MHz Ant1




Date: 28.MAR.2025 15:48:16


OBW NVNT a 5320MHz Ant1




OBW NVNT ac20 5260MHz Ant1




OBW NVNT ac20 5280MHz Ant1




OBW NVNT ac20 5320MHz Ant1




OBW NVNT ac40 5270MHz Ant1




OBW NVNT ac40 5310MHz Ant1




OBW NVNT ac80 5290MHz Ant1



OBW NVNT n20 5260MHz Ant1




OBW NVNT n20 5280MHz Ant1




Date: 28.MAR.2025 15:59:53

OBW NVNT n20 5320MHz Ant1




Date: 28.MAR.2025 16:02:36

OBW NVNT n40 5270MHz Ant1




OBW NVNT n40 5310MHz Ant1




Band 3 (5470-5725 MHz):**-26dB Bandwidth**

Condition	Mode	Frequency (MHz)	Antenna	-26 dB Bandwidth (MHz)
NVNT	a	5500	Ant1	22.02
NVNT	a	5580	Ant1	23.19
NVNT	a	5700	Ant1	23.28
NVNT	ac20	5500	Ant1	23.82
NVNT	ac20	5580	Ant1	23.85
NVNT	ac20	5700	Ant1	23.1
NVNT	ac40	5510	Ant1	40.92
NVNT	ac40	5670	Ant1	40.56
NVNT	ac80	5530	Ant1	81.72
NVNT	n20	5500	Ant1	23.58
NVNT	n20	5580	Ant1	22.74
NVNT	n20	5700	Ant1	23.67
NVNT	n40	5510	Ant1	40.44
NVNT	n40	5670	Ant1	41.52

-26dB Bandwidth NVNT a 5500MHz Ant1


Date: 28.MAR.2025 17:10:10

-26dB Bandwidth NVNT a 5580MHz Ant1




Date: 28.MAR.2025 17:29:43

-26dB Bandwidth NVNT a 5700MHz Ant1




Date: 28.MAR.2025 17:32:54


-26dB Bandwidth NVNT ac20 5500MHz Ant1




-26dB Bandwidth NVNT ac20 5580MHz Ant1




-26dB Bandwidth NVNT ac20 5700MHz Ant1




-26dB Bandwidth NVNT ac40 5510MHz Ant1



-26dB Bandwidth NVNT ac40 5670MHz Ant1




Date: 29.MAR.2025 10:05:54


-26dB Bandwidth NVNT ac80 5530MHz Ant1

Date: 29.MAR.2025 10:30:06


-26dB Bandwidth NVNT n20 5500MHz Ant1




-26dB Bandwidth NVNT n20 5580MHz Ant1



-26dB Bandwidth NVNT n20 5700MHz Ant1



-26dB Bandwidth NVNT n40 5510MHz Ant1



-26dB Bandwidth NVNT n40 5670MHz Ant1