


# TEST REPORT

Applicant:	ning bo ming wo jin chu kou you xian gong si.		
Address:	Room 8-11-1, No. 402 Yiyuan Road, Panhu Street, Yinzhou District, Ningbo City, Zhejiang, China		
Manufacturer:	Ningbo Changdian Electric Appliance Manufacturing Co., Ltd.		
Address:	No. 168, Ningxi Industrial Park, Chalu Town, Ninghai County, Ningbo City, Zhejiang Province, China		
Factory:	Ningbo Changdian Electric Appliance Manufacturing Co., Ltd.		
Address:	No. 168, Ningxi Industrial Park, Chalu Town, Ninghai County, Ningbo City, Zhejiang Province, China		
E.U.T.:	Multi-function Emergency Radio		
Model Number:	KK-228WB, 228, 229, WY03, WY04, WY05, WY06, WY07, WY08, WY326, WY328, WY338, WY368, WY398		
Trade mark:	 WARSUN		
FCC ID:	2BNN2-KK228WB		
Date of Receipt:	2025-1-16	Date of Test:	2025-1-16 to 2025-2-10
Test Specification:	FCC 47 CFR Part 15, Subpart C		
Test Result:	The equipment under test was found to be compliance with the requirements of the standards applied.		
Prepared by:	Approved & Authorized Signer:		
 Jerry Hu/ Engineer	 Frank Shen/ Manager		
Date: 2025-2-6	Issue Date: 2025-2-18		
This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Dongguan Lepont Service Co., Ltd.			

## TABLE OF CONTENTS

<b>1. GENERAL PRODUCT INFORMATION .....</b>	<b>4</b>
1.1. PRODUCT FUNCTION .....	4
1.2. EUT TECHNICAL DESCRIPTION .....	4
1.3. INDEPENDENT OPERATION MODES .....	5
1.4. TEST SOFTWARE .....	6
1.5. GENERAL CONDITION .....	6
1.6. SUPPORT EQUIPMENT .....	6
<b>2. TEST STANDARDS AND SITES .....</b>	<b>7</b>
2.1. DESCRIPTION OF STANDARDS AND RESULTS .....	7
2.2. LIST OF TEST AND MEASUREMENT INSTRUMENTS .....	8
2.3. MEASUREMENT UNCERTAINTY .....	9
2.4. TEST FACILITY .....	9
<b>3. SETUP OF EQUIPMENT UNDER TEST .....</b>	<b>10</b>
3.1. RADIO FREQUENCY TEST SETUP 1 .....	10
3.2. RADIO FREQUENCY TEST SETUP 2 .....	10
3.3. CONDUCTED EMISSION TEST SETUP .....	12
3.4. BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM .....	12
<b>4. TEST RESULTS AND MEASUREMENT DATA .....</b>	<b>13</b>
4.1. 20DB BANDWIDTH .....	13
4.2. CARRIER FREQUENCY SEPARATION .....	20
4.3. NUMBER OF HOPPING FREQUENCIES .....	23
4.4. AVERAGE TIME OF OCCUPANCY (DWELL TIME) .....	26
4.5. MAXIMUM PEAK CONDUCTED OUTPUT POWER .....	30
4.6. CONDUCTED SPURIOUS EMISSION AND BAND EDGE .....	37
4.7. RADIATED SPURIOUS EMISSION .....	59
4.8. CONDUCTED EMISSION TEST .....	70
4.9. ANTENNA APPLICATION .....	73

## Revision History of This Test Report

## 1. GENERAL PRODUCT INFORMATION

### 1.1. PRODUCT FUNCTION

Refer to Technical Construction Form and User Manual.

### 1.2. EUT TECHNICAL DESCRIPTION

Product Name:	Multi-function Emergency Radio
Model No.:	KK-228WB, 228, 229, WY03, WY04, WY05, WY06, WY07, WY08, WY326, WY328, WY338, WY368, WY398
Test Model No.:	KK-228WB
Difference:	All models have the same PCB, schematics, only the model name is different
Serial No.:	N/A
Test sample(s) ID:	LP25010043C01-S001
Sample(s) Status	Engineer sample
Hardware:	V 1.0
Software:	V 1.0
Operation Frequency:	2402MHz-2480MHz
Channel numbers:	79
Channel separation:	1MHz
Modulation type:	GFSK, $\pi/4$ -DQPSK,8DPSK
Antenna Type:	PCB Antenna
Antenna gain:	-0.58dBi
Power supply:	<input checked="" type="checkbox"/> DC 5V form USB <input checked="" type="checkbox"/> DC 3.7V form battery

### 1.3. INDEPENDENT OPERATION MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps for GFSK modulation; 2Mbps for pi/4-DQPSK modulation; 3Mbps for 8DPSK modulation) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	39	2441	...	...
1	2403	40	2442	76	2478
2	2404	41	2443	77	2479
...	...	...	...	78	2480

Note:  $fc = 2402\text{MHz} + (k-1) \times 1\text{MHz}$  k=1 to 79

Test Frequency and channel

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	39	2441	78	2480

#### 1.4. TEST SOFTWARE

Software	Description
BT_Tool.exe	Set the COM Port Test Tool to set the corresponding Test conditions

#### 1.5. GENERAL CONDITION

	Temperature	Humidity
Ambient Condition:	21.1°C	40.3%RH

#### 1.6. SUPPORT EQUIPMENT

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Laptop computer	Lenovo	Xiaoxin Pro IA5HR	PF490VB0

#### Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

## 2. TEST STANDARDS AND SITES

### 2.1. DESCRIPTION OF STANDARDS AND RESULTS

The EUT have been tested according to the applicable standards as referenced below.

FCC Part Clause	Test Parameter	Verdict	Remark
15.247(a)(1)	20 dB Bandwidth	PASS	
15.247(a)(1)	Carrier Frequency Separation	PASS	
15.247(a)(1)	Number of Hopping Frequencies	PASS	
15.247(a)(1)	Average Time of Occupancy (Dwell Time)	PASS	
15.247(b)(1)	Maximum Peak Conducted Output Power	PASS	
15.247(d)	Conducted Spurious Emissions	PASS	
15.247(d) 15.209	Radiated Spurious Emissions	PASS	
15.207	Conducted Emission	PASS	
15.203	Antenna Application	PASS	
15.247 (a) (1)/g/h	Frequency Hopping System	PASS	

NOTE1: N/A (Not Applicable)

NOTE2: According to FCC KDB 558074 D01 15.247 Meas Guidance v05r02, the report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits.

## 2.2. LIST OF TEST AND MEASUREMENT INSTRUMENTS

For conducted emission at the mains terminals test(Shielded Room 1)							
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval	Lab No.	Remark
EMI Test Receiver	Rohde & Schwarz	ESHS30	8290501003	Dec. 23, 2024	1 Year	LEP-E002	<input checked="" type="checkbox"/>
Artificial Mains Network	Baluelec	LSN016	BL0411220501 21	Nov. 01, 2024	1 Year	LEP-E067	<input checked="" type="checkbox"/>
Shielded Room 1	MR	MR-L05	LEP-E053	Nov. 17, 2022	3 Year	LEP-E053	<input checked="" type="checkbox"/>
Test software	EZ-EMC	Fala	LEPONT-03A2	N/A	N/A	N/A	<input checked="" type="checkbox"/>
For radiated(9K-30M) emission test(966 Chamber 1)							
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval	Lab No.	Remark
EMI Test Receiver	Rohde & Schwarz	ESR 3	101849	Dec. 23, 2024	1 Year	LEP-E006	<input checked="" type="checkbox"/>
Active Loop Antenna	Schwarzbeck	FMZB 1519C	00008	Feb. 02, 2024	3 Year	LEP-E068	<input checked="" type="checkbox"/>
966 Chamber 1	MR	MR-L02	LEP-E051	Nov. 17, 2022	3 Year	LEP-E051	<input checked="" type="checkbox"/>
Test software	EZ-EMC	Fala	EMEC-3A1	N/A	N/A	N/A	<input checked="" type="checkbox"/>
For radiated(30M-1G) emission test(966 Chamber 1)							
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval	Lab No.	Remark
EMI Test Receiver	Rohde & Schwarz	ESR 3	101849	Dec. 23, 2024	1 Year	LEP-E006	<input checked="" type="checkbox"/>
TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	743	Nov. 20, 2022	3 Year	LEP-E005	<input checked="" type="checkbox"/>
Signal Amplifier	HP	8447D	1726A01222	Jan. 07, 2025	1 Year	LEP-E007	<input type="checkbox"/>
6dB Attenuator	RswTech	5W 6dB	LEP-E084	Jan. 07, 2025	1 Year	LEP-E084	<input type="checkbox"/>
966 Chamber 1	MR	MR-L02	LEP-E051	Nov. 17, 2022	3 Year	LEP-E051	<input checked="" type="checkbox"/>
Test software	EZ-EMC	Fala	EMEC-3A1	N/A	N/A	N/A	<input checked="" type="checkbox"/>
For radiated(1-18G) emission test(966 Chamber 1)							
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval	Lab No.	Remark
Spectrum analyzer	Rohde & Schwarz	FSV40	101412	Jan. 24, 2024	1 Year	LEP-E076	<input checked="" type="checkbox"/>
Spectrum analyzer	Agilent	N9020A	MY49100060	Jan. 07, 2025	1 Year	LEP-E020	<input checked="" type="checkbox"/>
Horn antenna	Schwarzbeck	BBHA 9120D	01875	Nov. 20, 2022	3 Year	LEP-E024	<input checked="" type="checkbox"/>
Preamplifier	Schwarzbeck	BBN 9718B	00010	Jan. 07, 2025	1 Year	LEP-E025	<input checked="" type="checkbox"/>
966 Chamber 1	MR	MR-L02	LEP-E051	Nov. 17, 2022	3 Year	LEP-E051	<input checked="" type="checkbox"/>
Test software	EZ-EMC	Fala	EMEC-3A1	N/A	N/A	N/A	<input checked="" type="checkbox"/>
For radiated(18-40G) emission test(966 Chamber 1)							
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval	Lab No.	Remark
Spectrum analyzer	Rohde & Schwarz	FSV40	101412	Jan. 07, 2025	1 Year	LEP-E076	<input checked="" type="checkbox"/>
Horn antenna+Preamplifier	COM-POWER	AH840	10100020	Sep. 05, 2022	3 Year	LEP-E075	<input checked="" type="checkbox"/>
966 Chamber 1	MR	MR-L02	LEP-E051	Nov. 17, 2022	3 Year	LEP-E051	<input checked="" type="checkbox"/>
Test software	EZ-EMC	Fala	EMEC-3A1	N/A	N/A	N/A	<input checked="" type="checkbox"/>
For RF test							
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval	Lab No.	Remark
Spectrum analyzer	Rohde & Schwarz	FSV40	101412	Jan. 07, 2025	1 Year	LEP-E076	<input checked="" type="checkbox"/>
Spectrum analyzer	Agilent	N9020A	MY49100060	Jan. 07, 2025	1 Year	LEP-E020	<input checked="" type="checkbox"/>
Vector source	Agilent	N5182A	MY47420382	Jan. 07, 2025	1 Year	LEP-E021	<input checked="" type="checkbox"/>
Analog signal source	Agilent	N5171B	MY51350292	Jan. 07, 2025	1 Year	LEP-E022	<input checked="" type="checkbox"/>
All instrument	Rohde & Schwarz	CMW 500	1201.002K50	Jan. 07, 2025	1 Year	LEP-E019	<input checked="" type="checkbox"/>
High and low temperature chamber	Math-mart	MT-1202-40	LEP-E041	Jan. 07, 2025	1 Year	LEP-E041	<input checked="" type="checkbox"/>
control unit	Tonscend	JS0806-2	10165	Jan. 07, 2025	1 Year	LEP-E034	<input checked="" type="checkbox"/>
Testing software	Tonscend	JSTS1120-3	Ver 2.6.77.0518	N/A	N/A	N/A	<input checked="" type="checkbox"/>

### 2.3. MEASUREMENT UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0\%$
Conducted Emissions Test	$\pm 3.08\text{dB}$
Radiated Emission Test	$\pm 4.60\text{dB}$
Power Density	$\pm 0.9\%$
Occupied Bandwidth Test	$\pm 2.3\%$
Band Edge Test	$\pm 1.2\%$
Antenna Port Emission	$\pm 3\text{dB}$
Temperature	$\pm 3.2\%$
Humidity	$\pm 2.5\%$
Measurement Uncertainty for a level of Confidence of 95%	

### 2.4. TEST FACILITY

EMC Lab. : The Laboratory has been assessed and proved to be in compliance with CNAS/CL01

The Certificate Registration Number is L10100.

The Laboratory has been assessed and proved to be in compliance with A2LA

The Certificate Registration Number is 6901.01

FCC Designation No.: CN1351

Test Firm Registration No.: 397428

ISED CAB identifier: CN0151

Test Firm Registration No.: 20133


Test Location : Dongguan Lepont Testing Service Co., Ltd.

Address : Room 102, Building 11, No.7, Houjie Science And Technology Avenue, Houjie, Dongguan, Guangdong, China

### 3. SETUP OF EQUIPMENT UNDER TEST

#### 3.1. RADIO FREQUENCY TEST SETUP 1

The component's antenna port(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



#### 3.2. RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 32.

Below 30MHz:

The EUT is placed on a turntable 0.8meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.


Above 30MHz:

The EUT is placed on a turntable 0.8meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


Above 1GHz:

(Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.)  
 The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


##### (a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




### 3.3. CONDUCTED EMISSION TEST SETUP


The mains cable of the EUT (Perfect Share Mini) must be connected to LISN. The LISN shall be placed 0.8m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.8m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



### 3.4. BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM



## 4. TEST RESULTS AND MEASUREMENT DATA

### 4.1. 20DB BANDWIDTH

#### 4.1.1. Applicable Standard

According to FCC Part 15.247(a)(1) and KDB 558074 D01 15.247 Meas Guidance v05r02

#### 4.1.2. Conformance Limit

No limit requirement.

#### 4.1.3. Test Configuration

Test according to clause 3.1 radio frequency test setup 1

#### 4.1.4. Test Procedure

The EUT was operating in Bluetooth mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 30 kHz.

Set the video bandwidth (VBW) =100 kHz.

Set Span= approximately 2 to 3 times the 20 dB bandwidth

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

Measure and record the results in the test report.

**Test Results:**

TestMode	Antenna	Freq(MHz)	20dB EBW[MHz]	FL[MHz]	FH[MHz]	Limit[MHz]
DH5	Ant1	2402	0.954	2401.577	2402.531	N/A
		2441	0.951	2440.577	2441.528	N/A
		2480	0.948	2479.574	2480.522	N/A
2DH5	Ant1	2402	1.347	2401.364	2402.711	N/A
		2441	1.323	2440.373	2441.696	N/A
		2480	1.356	2479.361	2480.717	N/A
3DH5	Ant1	2402	1.329	2401.367	2402.696	N/A
		2441	1.287	2440.400	2441.687	N/A
		2480	1.275	2479.406	2480.681	N/A

## Test Graphs











## 4.2. CARRIER FREQUENCY SEPARATION

### 4.2.1. Applicable Standard

According to FCC Part 15.247(a)(1) and KDB 558074 D01 15.247 Meas Guidance v05r02

### 4.2.2. Conformance Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively, frequency hopping systems operating in the 2400 – 2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

### 4.2.3. Test Configuration

Test according to clause 3.1 radio frequency test setup 1

### 4.2.4. Test Procedure

■ According to FCC Part15.247(a)(1)

The EUT must have its hopping function enabled.

Settings:

Set the RBW =300kHz.

Set VBW =300kHz.

Set the span = wide enough to capture the peaks of two adjacent channels

Set Sweep time = auto couple.

Set Detector = peak. Set Trace mode = max hold.

Allow the trace to stabilize. Use the marker-delta function to determine the separation

between the peaks of the adjacent channels. The limit is specified in one of the

Sub paragraphs of this Section. Submit this plot.

## Test Results:

TestMode	Antenna	Freq(MHz)	Result[MHz]	Limit[MHz]	Verdict
DH5	Ant1	Hop	1.322	≥0.954	PASS
2DH5	Ant1	Hop	1.008	≥0.904	PASS
3DH5	Ant1	Hop	1.178	≥0.886	PASS

## Test Graphs





### 4.3. NUMBER OF HOPPING FREQUENCIES

#### 4.3.1. Applicable Standard

According to FCC Part 15.247(a)(1) and KDB 558074 D01 15.247 Meas Guidance v05r02

#### 4.3.2. Conformance Limit

Frequency hopping systems operating in the 2400-2483.5MHz band shall use at least 15 channels.

#### 4.3.3. Test Configuration

Test according to clause 3.1 radio frequency test setup 1

#### 4.3.4. Test Procedure

- According to FCC Part15.247(a)(1)(iii)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation (2400-2483.5MHz)

RBW  $\geq$  300KHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold


Allow the trace to stabilize. It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies.

#### Test Results:

TestMode	Antenna	Freq(MHz)	Result[Num]	Limit[Num]	Verdict
DH5	Ant1	Hop	79	$\geq 15$	PASS
2DH5	Ant1	Hop	79	$\geq 15$	PASS
3DH5	Ant1	Hop	79	$\geq 15$	PASS

## Test Graphs





## 4.4. AVERAGE TIME OF OCCUPANCY (DWELL TIME)

### 4.4.1. Applicable Standard

According to FCC Part 15.247(a)(1) and KDB 558074 D01 15.247 Meas Guidance v05r02

### 4.4.2. Conformance Limit

For frequency hopping systems operating in the 2400-2483.5MHz band, the average time of occupancy on any channel shall not be greater than 0.4s within a period of 0.4s multiplied by the number of hopping channels employed.

### 4.4.3. Test Configuration

Test according to clause 3.1 radio frequency test setup 1

### 4.4.4. Test Procedure

- According to FCC Part15.247(a)(1)(iii)

The EUT must have its hopping function enabled.

Settings:

Span = zero span, centered on a hopping channel

RBW = 1 MHz

VBW  $\geq$  RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak


Trace = max hold



If possible, use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section.

## Test Results:


TestMode	Antenna	Freq(MHz)	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH5	Ant1	Hop	2.915	50	0.146	≤0.4	PASS
2DH5	Ant1	Hop	2.921	100	0.292	≤0.4	PASS
3DH5	Ant1	Hop	2.923	70	0.205	≤0.4	PASS


## Test Graphs





3DH5\_Ant1\_Hop





## 4.5. MAXIMUM PEAK CONDUCTED OUTPUT POWER

### 4.5.1. Applicable Standard

According to FCC Part 15.247(b)(1) and KDB 558074 D01 15.247 Meas Guidance v05r02

### 4.5.2. Conformance Limit

The max For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

### 4.5.3. Test Configuration

Test according to clause 4.5.4 radio frequency test setup 1

### 4.5.4. Test Procedure

- According to FCC Part15.247(b)(1)

As an alternative to a peak power measurement, compliance with the limit can be based on a measurement of the maximum conducted output power.

Use the following spectrum analyzer settings:

Set Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

Set RBW > the 20 dB bandwidth of the emission being measured

Set VBW  $\geq$  RBW

Set Sweep = auto

Set Detector function = peak


Set Trace = max hold


Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission to determine the peak amplitude level.

**Test Results**

Test Mode	Antenna	Freq(MHz)	Conducted Peak Power[dBm]	Conducted Limit[dBm]	Verdict
DH5	Ant1	2402	6.86	≤30	PASS
		2441	6.96	≤30	PASS
		2480	6.97	≤30	PASS
2DH5	Ant1	2402	7.02	≤20.97	PASS
		2441	7.24	≤20.97	PASS
		2480	7.21	≤20.97	PASS
3DH5	Ant1	2402	7.58	≤20.97	PASS
		2441	7.64	≤20.97	PASS
		2480	7.71	≤20.97	PASS

## Test Graphs







2DH5\_Ant1\_2480



3DH5\_Ant1\_2402



3DH5\_Ant1\_2441



3DH5\_Ant1\_2480



## 4.6. CONDUCTED SUPRIOS EMISSION AND BAND EDGE

### 4.6.1. Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 D01 15.247 Meas Guidance v05r02

### 4.6.2. Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted, provided the transmitter demonstrates compliance with the peak conducted power limits.

### 4.6.3. Test Configuration

Test according to clause 3.1 radio frequency test setup 1

### 4.6.4. Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

#### ■ Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DSS channel center frequency.

Set Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel.

Set the RBW = 100 kHz. Set the VBW  $\geq 3 \times$  RBW.

Set Detector = peak. Set Sweep time = auto couple.

Set Trace mode = max hold. Allow trace to fully stabilize.

Use the peak marker function to determine the maximum Maximum conducted level.

Note that the channel found to contain the maximum conducted level can be used to establish the reference level.

#### ■ Band-edge Compliance of RF Conducted Emissions

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the emission operating on the channel closest to the band-edge, as well as any modulation products which fall outside of the authorized band of operation

Set RBW  $\geq 1\%$  of the span=100kHz Set VBW  $\geq$  RBW

Set Sweep = auto Set Detector function = peak Set Trace = max hold

Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. The marker-delta value now displayed must comply with the limit specified in this Section.

Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize.

Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit.

#### ■ Conducted Spurious RF Conducted Emission

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic.(30MHz to 26.5GHz). Set RBW = 100 kHz Set VBW  $\geq$  RBW


Set Sweep = auto Set Detector function = peak Set Trace = max hold


Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this Section.


**Test Results:**


TestMode	Antenna	ChName	Freq(MHz)	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	Low	2402	5.97	-49.55	≤-14.03	PASS
		High	2480	6.10	-49.08	≤-13.9	PASS
		Low	Hop_2402	6.00	-49.35	≤-14	PASS
		High	Hop_2480	6.27	-48.4	≤-13.73	PASS
2DH5	Ant1	Low	2402	3.80	-49.47	≤-16.2	PASS
		High	2480	6.02	-49.34	≤-13.98	PASS
		Low	Hop_2402	4.69	-49.39	≤-15.31	PASS
		High	Hop_2480	6.31	-48.69	≤-13.69	PASS
3DH5	Ant1	Low	2402	5.75	-47.75	≤-14.25	PASS
		High	2480	5.84	-47.98	≤-14.16	PASS
		Low	Hop_2402	3.93	-47.9	≤-16.08	PASS
		High	Hop_2480	6.23	-48.95	≤-13.78	PASS


## Test Graphs





















DH5\_Ant1\_2441\_0~Reference





DH5\_Ant1\_2441\_30~1000






























## 4.7. RADIATED SPURIOUS EMISSION

### 4.7.1. Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 D01 15.247 Meas Guidance v05r02

### 4.7.2. Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength ( $\mu$ V/m)	Field Strength ( $\text{dB}\mu$ V/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log ( $\mu$ V/m)	300
0.490-1.705	24000/F(KHz)	20 log ( $\mu$ V/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

### 4.7.3. Test Configuration

Test according to clause 3.2 radio frequency test setup 2

#### 4.7.4. Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

For Above 1GHz:

The EUT was placed on a turn table which is 1.5m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 1GHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 30MHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 9kHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 150KHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 200Hz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from  $20\log(\text{dwell time}/100 \text{ ms})$ , in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

## ■ Spurious Emission below 30MHz (9KHz to 30MHz)

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type	Ant. Pol.
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)		H/V
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance} / \text{test distance})(\text{dB})$ ;

Limit line=Specific limits(dBuV) + distance extrapolation factor

## ■ Spurious Emission Above 1GHz (1GHz to 25GHz)

Bluetooth (GFSK,  $\pi/4$ -DQPSK, 8DPSK) mode have been tested, and the worst result(8DPSK) was report as below:

Test mode:		8DPSK		Frequency:		Channel 0: 2402MHz	
Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type	Ant. Pol.
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)		H/V
4808	46.35	-1.01	45.34	74	-28.66	peak	V
4825	34.47	-1.02	33.45	54	-20.55	AVG	V
7001	40.64	5.77	46.41	74	-27.59	peak	V
7103	30.22	5.72	35.94	54	-18.06	AVG	V
9364	40.66	7.43	48.09	74	-25.91	peak	V
9500	29.75	7.51	37.26	54	-16.74	AVG	V
4808	48.75	-1.01	47.74	74	-26.26	peak	H
4825	35.52	-1.02	34.5	54	-19.5	AVG	H
7120	40.14	5.72	45.86	74	-28.14	peak	H
7103	30.15	5.72	35.87	54	-18.13	AVG	H
9466	40.12	7.49	47.61	74	-26.39	peak	H
9500	29.55	7.51	37.06	54	-16.94	AVG	H

Test mode:		8DPSK		Frequency:		Channel 39: 2441MHz	
Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type	Ant. Pol.
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)		H/V
4876	45.1	-1.01	44.09	74	-29.91	peak	V
4893	32.81	-1	31.81	54	-22.19	AVG	V
7120	40.61	5.72	46.33	74	-27.67	peak	V
7103	30.15	5.72	35.87	54	-18.13	AVG	V
9330	40.04	7.41	47.45	74	-26.55	peak	V
9381	29.37	7.45	36.82	54	-17.18	AVG	V
4876	44.86	-1.01	43.85	74	-30.15	peak	H
4893	33.25	-1	32.25	54	-21.75	AVG	H
7154	39.71	5.71	45.42	74	-28.58	peak	H
7103	29.98	5.72	35.7	54	-18.3	AVG	H
9364	39.9	7.43	47.33	74	-26.67	peak	H
9500	29.74	7.51	37.25	54	-16.75	AVG	H


Test mode:		8DPSK		Frequency:		Channel 78: 2480MHz	
Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type	Ant. Pol.
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)		H/V
4961	46.58	-1	45.58	74	-28.42	peak	V
4978	33.7	-1.01	32.69	54	-21.31	AVG	V
7103	40.3	5.72	46.02	74	-27.98	peak	V
7086	30.17	5.73	35.9	54	-18.1	AVG	V
9381	39.98	7.45	47.43	74	-26.57	peak	V
9381	29.4	7.45	36.85	54	-17.15	AVG	V
4961	43.59	-1	42.59	74	-31.41	peak	H
4978	31.25	-1.01	30.24	54	-23.76	AVG	H
7086	40.49	5.73	46.22	74	-27.78	peak	H
7103	30.16	5.72	35.88	54	-18.12	AVG	H
9415	40.44	7.46	47.9	74	-26.1	peak	H
9483	29.49	7.51	37	54	-17	AVG	H

**Note:** (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).


(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

(3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2300-2390MHz and 2483.5-2500MHz  
Bluetooth (GFSK,  $\pi/4$ -DQPSK, 8DPSK, Hopping) mode have been tested, and the worst result(8DPSK)  
was report as below:




Test Mode:	8DPSK	2402MHz	Test Channel	Lowest
Temperature:	22.7°C		Phase:	Horizontal
Relative Humidity:	47%		Pressure:	101.8KPa




No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	2310.000	-5.12	39.46	34.34	74.00	-39.66	peak		
2	2310.010	-5.12	30.08	24.96	54.00	-29.04	AVG		
3	2390.000	-4.83	39.72	34.89	74.00	-39.11	peak		
4	2390.090	-4.83	30.39	25.56	54.00	-28.44	AVG	*	

Test Mode:	8DPSK	2480MHz	Test Channel	Highest
Temperature:	22.7°C		Phase:	Vertical
Relative Humidity:	47%		Pressure:	101.8KPa



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	2483.500	-4.46	46.83	42.37	74.00	-31.63	peak		
2	2483.530	-4.46	30.62	26.16	54.00	-27.84	AVG	*	
3	2500.000	-4.41	40.13	35.72	74.00	-38.28	peak		
4	2500.000	-4.41	29.40	24.99	54.00	-29.01	AVG		

Test Mode:	8DPSK	2480MHz	Test Channel	Highest
Temperature:	22.7°C		Phase:	Horizontal
Relative Humidity:	47%		Pressure:	101.8KPa




No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	2483.500	-4.46	52.44	47.98	74.00	-26.02	peak		
2	2483.500	-4.46	32.53	28.07	54.00	-25.93	AVG	*	
3	2500.000	-4.41	39.67	35.26	74.00	-38.74	peak		
4	2500.000	-4.41	29.63	25.22	54.00	-28.78	AVG		

**Note:** (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).  
 (2) Emission Level= Reading Level+Correct Factor.  
 (3) Correct Factor= Ant\_F + Cab\_L - Preamp  
 (4) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission below 1GHz (30MHz to 1GHz)


Bluetooth (GFSK,  $\pi/4$ -DQPSK, 8DPSK, Hopping) mode have been tested, and the worst result(8DPSK) was report as below:

Test Mode:	8DPSK	2402MHz	Test Voltage:	DC 3.7V
Temperature:	22.7 °C		Phase:	Vertical
Relative Humidity:	47%		Pressure:	101.8KPa



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	71.8319	8.44	15.30	23.74	40.00	-16.26	QP		
2	119.8555	9.31	23.32	32.63	43.50	-10.87	QP		
3	143.8294	6.93	24.80	31.73	43.50	-11.77	QP		
4	167.8241	8.47	25.08	33.55	43.50	-9.95	QP	*	
5	216.0238	10.94	21.48	32.42	46.00	-13.58	QP		
6	744.8659	20.30	14.17	34.47	46.00	-11.53	QP		

Test Mode:	8DPSK	2402MHz	Test Voltage:	DC 3.7V
Temperature:	24.2°C		Phase:	Horizontal
Relative Humidity:	42%		Pressure:	101.4KPa



No.	Frequency (MHz)	Factor (dBuV/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	MK.	Remark
1	71.8319	8.44	16.67	25.11	40.00	-14.89	QP		
2	107.8876	10.09	17.65	27.74	43.50	-15.76	QP		
3	143.8294	6.93	26.21	33.14	43.50	-10.36	QP		
4	167.8241	8.47	25.66	34.13	43.50	-9.37	QP	*	
5	216.0238	10.94	21.93	32.87	46.00	-13.13	QP		
6	744.8659	20.30	14.97	35.27	46.00	-10.73	QP		

## 4.8. CONDUCTED EMISSION TEST

### 4.8.1. Applicable Standard

According to FCC Part 15.207(a)

### 4.8.2. Conformance Limit

Conducted Emission Limit		
Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies  
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

Remark: Test results were obtained from the following equation:

Measurement (dB $\mu$ V) = LISN Factor (dB) + Cable Loss (dB) + Reading (dB $\mu$ V)

Margin (dB) = Measurement (dB $\mu$ V) - Limit (dB $\mu$ V)

### 4.8.3. Test Configuration

Test according to clause 3.3 conducted emission test setup


### 4.8.4. Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.  
Repeat above procedures until all frequency measured were complete.


**Test Results :PASS**

Test Mode:	Charging	Test Voltage:	AC 120V/60Hz
Temperature:	23.2 °C	Phase:	L1
Relative Humidity:	37%	Pressure:	101.2KPa



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1703	10.30	25.06	35.36	64.95	-29.59	QP	P	
2	0.1703	10.30	18.35	28.65	54.95	-26.30	AVG	P	
3	0.2973	10.34	23.70	34.04	60.32	-26.28	QP	P	
4	0.2973	10.34	21.24	31.58	50.32	-18.74	AVG	P	
5	0.3690	10.36	23.90	34.26	58.52	-24.26	QP	P	
6	0.3690	10.36	21.24	31.60	48.52	-16.92	AVG	P	
7	0.4192	10.38	23.69	34.07	57.46	-23.39	QP	P	
8	0.4192	10.38	23.65	34.03	47.46	-13.43	AVG	P	
9	0.6392	10.45	21.89	32.34	56.00	-23.66	QP	P	
10	0.6392	10.45	18.51	28.96	46.00	-17.04	AVG	P	
11	1.3744	10.57	19.41	29.98	56.00	-26.02	QP	P	
12	1.3744	10.57	14.90	25.47	46.00	-20.53	AVG	P	

Test Mode:	Charging	Test Voltage:	AC 120V/60Hz
Temperature:	23.2°C	Phase:	N
Relative Humidity:	37%	Pressure:	101.2KPa



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1703	10.35	25.47	35.82	64.95	-29.13	QP	P	
2	0.1703	10.35	17.77	28.12	54.95	-26.83	AVG	P	
3	0.2705	10.37	23.88	34.25	61.10	-26.85	QP	P	
4	0.2705	10.37	20.70	31.07	51.10	-20.03	AVG	P	
5	0.3690	10.40	23.32	33.72	58.52	-24.80	QP	P	
6	0.3690	10.40	20.30	30.70	48.52	-17.82	AVG	P	
7	0.4160	10.41	23.62	34.03	57.53	-23.50	QP	P	
8	0.4160	10.41	23.28	33.69	47.53	-13.84	AVG	P	
9	0.6391	10.46	21.10	31.56	56.00	-24.44	QP	P	
10	0.6391	10.46	17.13	27.59	46.00	-18.41	AVG	P	
11	1.4415	10.56	20.04	30.60	56.00	-25.40	QP	P	
12	1.4415	10.56	15.99	26.55	46.00	-19.45	AVG	P	

## 4.9. ANTENNA APPLICATION

### 4.9.1. Antenna Requirement

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### 4.9.2. Result

PASS.

The EUT has 1 antenna: PCB Antenna for BT with classic mode, the gain is -0.58dBi;

- Antenna use a permanently attached antenna which is not replaceable.
- Not using a standard antenna jack or electrical connector for antenna replacement
- The antenna has to be professionally installed (please provide method of installation)

Note: which in accordance to section 15.203, please refer to the internal photos.

----- END OF REPORT -----